

National Aeronautics and Space Administration

ACCESSION NUMBER RANGES

Accession numbers cited in this Supplement fall within the following ranges.

STAR (N-10000 Series) N79-17794 - N79-19987

IAA (A-10000 Series) A79-24525 - A79-28388

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by Informatics Information Systems Company.

AERONAUTICAL ENGINEERING

A Continuing Bibliography

Supplement 110

Á selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in May 1979 in

- Scientific and Technical Aerospace Reports (STAR)
- International Aerospace Abstracts (IAA)

This Supplement is available from the National Technical Information Service (NTIS), Springfield, Virginia 22161, at the price code E02 (\$4.75 domestic, **\$9** 50 foreign)

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering. The first issue of this bibliography was published in September 1970 and the first supplement in January 1971. Since that time, monthly supplements have been issued.

This supplement to Aeronautical Engineering -- A Continuing Bibliography (NASA SP-7037) lists 504 reports, journal articles, and other documents originally announced in May 1979 in Scientific and Technical Aerospace Reports (STAR) or in International Aerospace Abstracts (IAA)

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied in most cases by an abstract. The listing of the entries is arranged in two major sections, IAA Entries and STAR Entries, in that order The citations, and abstracts when available, are reproduced exactly as they appeared originally in IAA and STAR, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances

Three indexes -- subject, personal author, and contract number -- are included An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A79-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc. (AIAA), as follows. Paper copies of accessions are available at \$6.00 per document up to a maximum of 20 pages. The charge for each additional page is \$0.25. Microfiche (1) of documents announced in IAA are available at the rate of \$2.50 per microfiche on demand, and at the rate of \$1.10 per microfiche for standing orders for all IAA microfiche. The price for the IAA microfiche by category is available at the rate of \$1.25 per microfiche plus a \$1.00 service charge per category per issue. Microfiche of all the current AIAA Meeting Papers are available on a standing order basis at the rate of \$1.35 per microfiche.

Minimum air-mail postage to foreign countries is \$1.00 and all foreign orders are shipped on payment of pro-forma invoices

All inquiries and requests should be addressed to AIAA Technical Information Service. Please refer to the accession number when requesting publications

STAR ENTRIES (N79-10000 Series)

One or more sources from which a document announced in *STAR* is available to the public is ordinarily given on the last line of the citation. The most commonly indicated sources and their acronyms or abbreviations are listed below. If the publication is available from a source other than those listed the publisher and his address will be displayed on the availability line or in combination with the corporate source line.

Avail NTIS Sold by the National Technical Information Service Prices for hard copy (HC) and microfiche (MF) are indicated by a price code followed by the letters HC or MF in the STAR citation. Current values for the price codes are given in the tables on page VIII

Documents on microfiche are designated by a pound sign (#) following the accession number. The pound sign is used without regard to the source or quality of the microfiche

Initially distributed microfiche under the NTIS SRIM (Selected Research in Microfiche) is available at greatly reduced unit prices. For this service and for information concerning subscription to NASA printed reports, consult the NTIS Subscription Section, Springfield, Va. 22161.

NOTE ON ORDERING DOCUMENTS When ordering NASA publications (those followed by the * symbol), use the N accession number NASA patent applications (only the specifications are offered) should be ordered by the US-Patent-Appl-SN number Non-NASA publications (no asterisk) should be ordered by the AD, PB, or other *report* number shown on the last line of the citation, not by the N accession number. It is also advisable to cite the title and other bibliographic identification.

Avail SOD (or GPO) Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The current price and order number are given following the availability line. (NTIS will fill microfiche requests, at the standard \$3.00 price, for those documents identified by a # symbol.)

⁽¹⁾ A microfiche is a transparent sheet of film 105 by 148 mm in size containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 26.1 reduction)

- Avail NASA Public Document Rooms Documents so indicated may be examined at or purchased from the National Aeronautics and Space Administration, Public Documents Room (Room 126), 600 Independence Ave., S.W., Washington, D.C. 20546, or public document rooms located at each of the NASA research centers, the NASA Space Technology Laboratories, and the NASA Pasadena Office at the Jet Propulsion Laboratory
- Avail DOE Depository Libraries Organizations in U.S. cities and abroad that maintain collections of Department of Energy reports, usually in microfiche form, are listed in *Energy Research Abstracts*. Services available from the DOE and its depositories are described in a booklet, *DOE Technical Information Center Its Functions and Services* (TID-4660), which may be obtained without charge from the DOE Technical Information Center.
- Avail Univ Microfilms Documents so indicated are dissertations selected from *Dissertation Abstracts* and are sold by University Microfilms as xerographic copy (HC) and microfilm All requests should cite the author and the Order Number as they appear in the citation
- Avail USGS Originals of many reports from the U.S. Geological Survey, which may contain color illustrations, or otherwise may not have the quality of illustrations preserved in the microfiche or facsimile reproduction, may be examined by the public at the libraries of the USGS field offices whose addresses are listed in this introduction. The libraries may be queried concerning the availability of specific documents and the possible utilization of local copying services, such as color reproduction.
- Avail HMSO Publications of Her Majesty's Stationery Office are sold in the U.S. by Pendragon House, Inc. (PHI), Redwood City, California. The U.S. price (including a service and mailing charge) is given, or a conversion table may be obtained from PHI.
- Avail BLL (formerly NLL) British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England Photocopies available from this organization at the price shown (If none is given, inquiry should be addressed to the BLL)
- Avail Fachinformationszentrum Karlsruhe Sold by the Fachinformationszentrum Energie, Physik, Mathematik GMBH Eggenstein Leopoldshafen, Federal Republic of Germany, at the price shown in deutschmarks (DM)
- Avail Issuing Activity, or Corporate Author, or no indication of availability. Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.
- Avail U.S. Patent and Trademark Office. Sold by Commissioner of Patents and Trademarks, U.S. Patent and Trademark Office, at the standard price of 50 cents each, postage free
- Other availabilities If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the STAR Entries and IAA Entries sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA A listing of public collections of NASA documents is included on the inside back cover

SUBSCRIPTION AVAILABILITY

This publication is available on subscription from the National Technical Information Service (NTIS) The annual subscription rate for the monthly supplements is \$45.00 domestic, \$75.00 foreign. All questions relating to the subscriptions should be referred to NTIS, Attn. Subscriptions, 5285 Port Royal Road, Springfield Virginia 22161.

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics and Astronautics Technical Information Service 750 Third Ave New York, N.Y. 10017

British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England

Commissioner of Patents and Trademarks U.S. Patent and Trademark Office Washington, D.C. 20231

Department of Energy Technical Information Center P O Box 62 Oak Ridge, Tennessee 37830

ESA-Information Retrieval Service ESRIN Via Galileo Galilei 00044 Frascati (Rome) Italy

Her Majesty's Stationery Office P O Box 569, S E 1 London, England

NASA Scientific and Technical Information Facility P O Box 8757 B W I Airport, Maryland 21240

National Aeronautics and Space
Administration
Scientific and Technical Information
Branch (NST-41)
Washington, D.C. 20546

National Technical Information Service 5285 Port Royal Road Springfield, Virginia 22161 Pendragon House, Inc 899 Broadway Avenue Redwood City, California 94063

Superintendent of Documents U.S. Government Printing Office Washington, D.C. 20402

University Microfilms
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

University Microfilms, Ltd Tylers Green London, England

U S Geological Survey 1033 General Services Administration Building Washington, D C 20242

U S Geological Survey 601 E Cedar Avenue Flagstaff, Arizona 86002

U S Geological Survey 345 Middlefield Road Menlo Park, California 94025

U S Geological Survey Bldg 25, Denver Federal Center Denver, Colorado 80225

Fachinformationszentrum Energie, Physik, Mathematik GMBH 7514 Eggenstein Leopoldshafen Federal Republic of Germany

NTIS PRICE SCHEDULES

Schedule A

STANDARD PAPER COPY PRICE SCHEDULE

(Effective October 1 1977)

Price	Page Range	North American	Foreign
Code		Price	Price
A01	Microfiche	\$ 300	\$ 450
A02	001-025	4 00	8 00
A03	026-050	4 50	9 00
A04	051-075	5 2 5	10 50
A05	076 100	6 00	12 00
A06	101 125	6 50	13 00
A07	126 150	7 25	14 50
A08	151 175	800	16 00
A09	176 200	900	18 00
A10	201 225	´ 9 25	18 50
A11	228 250	9 50	19 00
211	220 230	2 30	1500
A12	251 275	10 75	21 50
A13	276 300	11 00	22 00
A14	301 325	11 75	23 50
A15	326-350	12 00	24 00
A16	351 375	12 50	25 00
A17	376 400	13 00	26 00
A18	401 425	13 25	26 50
A19	426-450	14 00	28 00
A20	451-475	14 50	29 00
A21	476 500	15 00	30 00
A22	501-525	15 25	30 50
A23	526-550	15 50	31 00
A24	551 575	16 25	32 50
A25	576 600	16 50	33 00
A99	601 up	1/	- 2/

- / Add \$2.50 for each additional 100 page increment from 601 pages up
- 2/ Add \$5.00 for each additional 100 page increment from 601 pages up

Schedule E

EXCEPTION PRICE SCHEDULE

Paper Copy & Microfiche


Price	North American	Foreign	
Code	Price	Price	
E01	\$ 325	\$ 650	
E02	4 75	9 50	
E03	6 25	12 50	
E04	7 50	15 00	
E05	9 00	18 00 ~	
E06	10 50	21 00	
E07	12 50	. 25 00	
E08	15 00	30 00	
E09	17 50	35 00	
E10	20 00	40 00	
E11	22 50	45 00	
E12	25 00	50 00	
E13	28 00	56 00	
E14	31 00	62 00	
E15	34 00	68 00	
E16	37 00	74 00	
E17	40 00	80 00	
E18	45 00	90 00	
E19	50 00	100 00	
E20	60 00	120 00	
E99 Write for quote			
N01	28 00	40 00	

TABLE OF CONTENTS

TYPICAL	CITATION	AND	ABSTRACT	FROM	STAR
Contract Numb	oer Index				C-1
Subject Index .					A-1
STAR Entries .	• • • • • • • • • • • • • • • • • • • •				285
IAA Entries					247

NASA SPONSORED DOCUMENT-AVAILABLE ON MICROFICHE N79-10024*# Northrop Corp Hawthorne Calif Aircraft -**NASA ACCESSION** NUMBER -Group STUDY OF AERODYNAMIC TECHNOLOGY FOR VSTOL CORPORATE FIGHTER/ATTACK AIRCRAFT HORIZONTAL ATTITUDE SOURCE **CONCEPT** Final Report S H Brown May 1978 242 p refs Sponsored in part by TITLE the David Taylor Naval Ship Research and Development Center PUBLICATION Bethesda Md (Contract NAS2-9771) DATE AUTHOR -(NASA-CR 152130 NOR78-54) NTIS -Avail HC A11/MF A01 CSCL O1A → A horizontal attitude VSTOL (HAVSTOL) supersonic fighter AVAILABILITY CONTRACT attack aircraft powered by RALS turbofan propulsion system is SOURCE analyzed Reaction control for subaerodynamic flight is obtained OR GRANT in pitch and yaw from the RALS and roll from wingtip jets powered by bleed air from the RALS duct. Emphasis is placed REPORT COSATI on the development of aerodynamic characteristics and the NUMBERS identification of aerodynamic uncertainties. A wind tunnel program CODE is shown to resolve some of the uncertainties. Aerodynamic data developed are static characteristics about all axes control effectiveness drag propulsion induced effects and reaction control characteristics

TYPICAL CITATION AND ABSTRACT FROM IAA



AERONAUTICAL ENGINEERING

A Continuing Bibliography (Suppl. 110)

JUNE 1979

IAA ENTRIES

A79-24715 # Modeling the X-band radar augmentation system of a high altitude supersonic target W L Ko and R Mittra (Illinois, University, Urbana, III) In Antenna Applications Symposium, Urbana, III , September 20-22, 1978, Proceedings

Urbana, III , University of Illinois, 1978 25 p Grant No DAAG29-77-G-0111

The objective of the HAST (high altitude supersonic target) radar augmentation system is to simulate real target variation in radar cross section (RCS) as a function of aspect angle. In the present paper, detailed information is given on the individual radiation pattern modeling of the transmitting antenna system. The procedure used to combine these individual patterns, taking into account the proper phase of each antenna, is outlined. The simulated RCS is obtained by properly combining the data measured with the augmentation system off and the data generated from the analytical model. A comparison of the measured RCS with augmentation system on and the simulated RCS shows that the analytical model of the augmentation system can accurately describe the aspect angle and the power level of the dominant radar returns from the scattering centers.

A79-24716 # RCS reduction of installed aircraft antennas M S Sohel (General Dynamics Corp., Fort Worth, Tex.) In Antenna Applications Symposium, Urbana, III., September 20-22, 1978, Proceedings Urbana, III., University of Illinois, 1978 12 p 8 refs

Techniques to predict and reduce radar cross-section of installed aircraft antennas are examined. Their ranges of applications and limitations are outlined. Only the classical theory predicts accurate RCS results and then only for simple shapes. RCS varies widely due to aspect angles, polarizations and frequencies. Assigning a single number for RCS of an antenna can be inaccurate at the desired aspect angle, polarization and frequency. An equation to model the RCS of installed aircraft antennas is given. Experimental results are needed to validate theoretical predictions. (Author)

A79-24718 # An IFF antenna with superior sidelobe and backlobe suppression characteristics C W Westerman (Ford Aerospace and Communications Corp., Aeronutronic Div., Newport Beach, Calif.) In Antenna Applications Symposium, Urbana, III., September 20-22, 1978, Proceedings Urbana, III., University of Illinois, 1978 15 p Grant No DAAH01-76-C-0583

When the sum beam sidelobes or backlobes of an IFF (identification friend or foe) antenna exceed the difference beam sidelobes or backlobes, punch-through is said to exist which causes interrogation in undesired directions. Current IFF antennas using balanced array geometry typically suffer from backlobe punch-through because the difference pattern null is present both in the front and rear of the antenna. This paper describes an 8-element stripline slot array with unsymmetrical array geometry which overcomes the backlobe punch-

through problem Performance data are presented for the antenna which was developed as part of the IFF subsystem for use in the Chaparral Air Defense Weapon System

B J

A79-24721 # Aircraft antenna pattern measurements using near field techniques J D Osborn (Martin Marietta Aerospace, Denver, Colo) In Antenna Applications Symposium, Urbana, III , September 20 22, 1978, Proceedings Urbana, III , University of Illinois, 1978 30 p 5 refs Contract No F33615-77-C 1070

Far field antenna patterns on operational aircraft are computed from near field measurements taken with a portable scanning system Measurement criteria are presented in conjunction with results from the Apollo Range Instrumentation Aircraft (A/RIA) antenna Param eters measured included patterns, gain, boresight alignment and radome effects. Since the A/RIA antenna is larger than the maximum scan capability of 5 feet, techniques for effectively increasing the scan length are considered. (Author)

A79 24726 # A proposed integrated ECM system using the constant index lens antenna E M Turner In Antenna Applications Symposium, Urbana, III , September 20 22, 1978, Proceedings

Urbana, III, University of Illinois, 1978 15 p

It is demonstrated how the outstanding properties of the constant index lens can be used to design an integrated ECM or communications system which will have superior capability and flexibility and be light-weight, low-cost and readily installable on high performance aircraft. The technique minimizes the incompatibilities of broadbandness versus low noise, omnidirectional coverage versus high gain, and large bandwidths versus selectivity. Instantaneous readouts of frequency and angle of arrival are provided.

A79-24771 * A shock capturing application of the finite element method C H Cooke (Old Dominion University, Norfolk, Va) and D K Blanchard (NASA, Langley Research Center, High Speed Aerodynamics Div, Hampton, Va) International Journal for Numerical Methods in Engineering, vol 14, no 2, 1979, p 271-286 Grant No NsG-1098

The paper is concerned with the development of finite element algorithms for the solution of viscous compressible flow problems with possible embedded shocks and recirculation regions. As a first step, the calculation in Cartesian coordinates of uniform flow on a rectangular region which encounters an embedded oblique shock with known turning angle is considered. A code is developed which is then used for computation of the boattail plume simulator problem in cylindrical coordinates. Oblique shock calculations are performed and the results are compared with a known finite difference solution.

A79-24800 The future of surveillance systems in civil aviation (L'avenir des systemes de surveillance dans l'aviation civile) G Lefevre (Direction Generale de l'Aviation Civile, Service Technique de la Navigation Aerienne, Paris, France) Navigation (Paris), vol. 27, Jan. 1979, p. 44-52. In French

The future of the current SSR (secondary surveillance radar) system for civil aviation has been put into question. The present paper reviews the limitations of SSR and discusses three surveillance philosophies which may come to replace SSR, the monopulse tech nique and the stochastic response secondary surveillance radar, the Discrete Address Beacon System and the Beacon Collision Avoidance System, and multifunction integrated systems.

A79-24827 Engine technology for production turbofan engines B Walsh Aviation Engineering and Maintenance, vol 3, Feb 1979, p 28-31

Technologies sponsored by NASA for the improvement of the JT8D and JT9D turbofan engines used on commercial transports are discussed. The four concepts in progress for the JT8D engine are (1) the development of an abradable trenched HP compressor blade resulting in a tighter blade clearance and an increase in the compressor's efficiency, (2) the modification of the turbine blade, (3) the replacement of the single pass blade with a two-pass root discharge blade with lower cooling air flow, and (4) the introduction of an advanced composite, the Kevlar PMR. The concepts in progress for the JT9D are the design of a 3.8 aspect ratio fan blade for modifying aerodynamic airfoil, modification of first and second stage outer air seal supports, and coating of vane platforms and seal with Zirconia/NiCoCrAlY spray. The new technologies are expected to provide fuel savings ranging from 0.8% to 1.5%.

A79-24829 Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ (Etude numérique d'écoulements instationnaires de fluide visqueux incompressible autour de corps profilés par une méthode combinée d'ordre O/h2/ et O/h4/) O Daube and T P Loc (Paris XI, Universite, Orsay, Essonne, France) Journal de Mecanique, vol 17, no 5, 1978, p 651-678 16 refs In French

A study of unsteady separated flows around bodies using the numerical solution of the Navier Stokes equations is presented. The method is based on a combination of two finite difference schemes, one of second order accuracy, the other of fourth order accuracy. Results obtained for unsteady flow around a circular cylinder are successfully compared with experimental data and with other numerical or semianalytical results. The evolution of Von Karman vortices behind elliptic bodies is analyzed. The time dependent flow structure is compared with experimental visualizations. The evolution of the flow behind an elliptic cylinder for two different initial conditions is studied. (Author)

A79-24958 Reliability growth on B-52 FLIR system J C Evans and S I Legreid (Hughes Aircraft Co , Culver City, Calif) In Reliability growth management, testing, and modeling, Proceedings of the Seminar, Washington, D C , February 27, 28, 1978

 $$\operatorname{\textsc{Mt}}$ Prospect, III , Institute of Environmental Sciences, 1978, p. 18 22

The paper describes the application of a reliability screening and control program to an item of avionic equipment and the resultant reliability growth of that equipment. The equipment, a 8-52 forward looking IR (FLIR) sensor, was developed to provide IR imagery to the 8-52 electrooptical viewing system. Reliability data taken during the engineering development phase and on the first 100 production units are summarized. It is shown that application of this reliability screening approach proves to be an extremely successful and cost-effective means for accelerating equipment reliability growths, as predicted. The FLIR system passed a 1100-hr production reliability demonstration test with only six relevant failures against ten allowed. Operational experience is equally impressive since the system exceeded required MTBF very early in its operational life.

S D

A79-24965 Reliability growth planning to achieve RIW/GMTBF requirements for an airborne radar J B Hovis and D O Fieni (Westinghouse Electric Corp., Baltimore, Md.) In Reliability growth management, testing, and modeling, Proceedings of the Seminar, Washington, D C, February 27, 28, 1978

 $$\operatorname{\textsc{Mt}}$ Prospect, III , Institute of Environmental Sciences, 1978, p. 61-64. 6 refs

A reliability engineering approach to meet reliability improvement warranty (RIW) requirements for the airborne fire control radar relies on a comprehensive design and test-analyze-and-fix (TAAF) program. The starting point of the test program is a direct

result of the effectiveness of the various reliability tools such as a failure mode and effects analysis (FMEA) and design checklist. The final payoff is seen in the life-cycle costs reflected by the field MTBF. The current field MTBF exceeds the predicted values derived from an inherent MIL-HDBK-2178 prediction. The guaranteed MTBF (GMTBF) imposed on the transmitter is not yet in effect. However, the reliability growth performance of the unit seems to indicate that the specified value will be met.

A79-25065 # The influence of geometric asymmetry on the flow downstream of row of jets discharging normally into a free stream D Crabb and J H Whitelaw (Imperial College of Science and Technology, London, England) ASME, Transactions, Journal of Heat Transfer, vol. 101, Feb. 1979, p. 183-185

Wind tunnel measurements are presented which comprise values of mean velocity and the mass concentration of a tracer in the flow downstream of a row of jets issuing normally into a free stream. The geometric configuration and velocity ratio are directly relevant to the combustion chamber of a gas turbine, and the results are obtained to quantify the influence of asymmetry in the hole arrangement on the downstream mean-flow properties. The measurements are obtained with four locations of the central pipe, corresponding to zero eccentricity and to eccentricities of 0.5, 0.25 and 0.1 diameter, the precision of location of the central pipe is better than 0.005 diameter. The results suggest that the asymmetries observed in the exit plane of gas turbine combustors are, at least in part, due to asymmetries in the location of the plunged primary and dilution holes.

A79-25131 Near-field analysis of helicopter rotating blades modulation interference M K Moaveni and M Mohseni (Pahlavi University, Shiraz, Iran) IEEE Transactions on Aerospace and Electronic Systems, vol. AES-15, Jan. 1979, p. 47-57, 10 refs

A near-field analysis is carried out to obtain the level of modulation interference due to rotating blades in a helicopter-borne pulse. Doppler radar system. The interference power spectra are calculated for different values of antenna depression angle and helicopter (radar) speed at a constant helicopter altitude of 300 m. Numerical results for the case of 1 kW radiated power show that blade interference level is about 5 to 8 dBW/Hz less than that of the direct ground clutter in the clutter region. It extends, however, into the clutter-free region which may cause false alarms and degradation of the radar performance. (Author)

A79-25139 Radar system design for track-while-scan R J Evans (Melbourne, University, Melbourne, Australia), C R Hewett (Royal Australian Air Force, Australian Embassy, Washington, D C), and F Barker (Plessey Radar, Ltd , Weybridge, Surrey, England) IEEE Transactions on Aerospace and Electronic Systems, vol AES-15, Jan 1979, p 125-133 5 refs

The problem of selecting search radar system parameters to achieve desired track-while-scan performance is investigated at a fundamental theoretical level. The vehicle being tracked is modeled as an object traveling at a random velocity along a random highway. The radar is modeled as a noisy sampler which occasionally drops samples. The best achievable tracking performance in a least-squares error sense of this vehicle/sampler combination is analyzed in general and for a variety of specific situations. (Author)

A79-25247 # Characteristic aerodynamic coefficients at high Reynolds numbers (Charakterystyczne wspołczynniki aerodynamiczne przy duzych liczbach Reynoldsa) J Staszek (Instytut Lotnictwa, Warsaw, Poland) Technika Lotnicza i Astronautyczna, vol 34, Jan 1979, p 25-28 6 refs In Polish

Recent wind tunnel tests and flight tests have confirmed the radical changes in the aerodynamic coefficients at high Reynolds numbers, especially in the transonic region Problems in extrapolating test results to higher Reynolds numbers are exemplified PTH

A79-25248 # Introduction of electron beam welding in aircraft production (Wdrazanie spawania wiazka elektronow do produkcji lotniczej) H Zatyka (Instytut Lotnictwa, Warsaw, Poland) Technika Lotnicza i Astronautyczna, vol 34, Jan 1979, p 29-33 15 refs. In Polish

The results of initial attempts to develop applications of electron beam welding in aircraft production are discussed. Examples of electron beam welds performed on various aircraft parts are shown, and some test methods are described. Types of future experiments and weld studies to be carried out before full establishment of electron beam welding in the aircraft industry are identified.

A79-25249 # Causes for the deterioration of splined connections in aircraft engines during service (Przyczyny uszkodzenia polaczen wielowypustowych w silnikach lotniczych w czasie ich eksploatacji) M Stukonis (Instytut Techniczny Wojsk Lotniczych, Warsaw, Poland) Technika Lotnicza i Astronautyczna, vol 34, Jan 1979, p 34-37 5 refs in Polish

The in-service deterioration characteristics of splined connections for torque transmission in aircraft engines are investigated. Data on the wear of the splines of torsion shafts in the gear box as a function of service time are studied. It is found that conditions favorable to intense wear of the splines often exist at the contact surfaces in the presence of friction corrosion under the dominating influence of metal tacking or oxidation, depending on the load conditions, type of contact, and lubrication conditions.

A79-25296 Overestimates of entrainment from wetting of aircraft temperature sensors in cloud A J Heymsfield, J E Dye, and C J Biter (National Center for Atmospheric Research, Boulder, Colo) Journal of Applied Meteorology, vol 18, Jan 1979, p 92-95 8 refs NSF-sponsored research

Temperature measurements from aircraft, taken with a reverse flow and Rosemount probe, were compared in a penetration through a cloud to determine the effect of sensor wetting on the deduced entrainment. The temperature measured using the Rosemount probe was depressed relative to that measured with the reverse flow probe, leading to an underestimate of the equivalent potential temperature and an overestimate of the deduced entrainment. These results were used to identify possible errors in recent entrainment studies that used temperature as an indicator entrainment. (Author)

A79-25313 Recent advances in indirect lightning effects research L C Walko, K J Maxwell, J G Schneider, and A V Serrano (Technology/Scientific Services, Inc., Dayton, Ohio) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga, June 20-22, 1978, Proceedings New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p 128-136 13 refs

Advances in lightning effects research are reported that include both test procedures and advances in data acquisition and analysis Advances in streamering tests, with which probable lightning reattachment points can be known more precisely, were made possible by the use of Tesla coils generating longer-duration high-voltage pulses that can sustain streamering on scaled down models of aircraft and full scale aircraft components. A new improved lightning test simulation configuration has been developed, in which the return leads are situated farther from the fuselage and at the approximate height of the fuselage centerline. Greater symmetry achieved in this way tends to minimize the influence of the return path. Instead of an oscilloscope, the data acquisition system includes a signal processing system consisting of transient digitizer, minicomputer, CRT display, and graphic terminal. A new frequency domain analysis approach is outlined.

A79-25317 Lightning protection with segmented diverters J A Plumer (Lightning Technologies, Inc., Pittsfield, Mass.) and L

C Hoots (Brunswick Corp., Marion, Va.) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga., June 20-22, 1978, Proceedings. New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 196-203. 13 refs. Research supported by the Lockheed-Georgia Co., General Dynamics Corp., Brunswick Corp., General Electric Co., Douglas Aircraft Co., Lightning Technologies, Inc., and NOAA

One way of protecting radomes or other dielectric structures from lightning is through the use of segmented diverter strips. These segmented strips provide many small air gaps that ionize and spark when an intense electric field is applied along the strip, as when a lightning leader approaches. The diverter guides an external streamer to meet the leader before the internal streamer can puncture the radome wall. Some tests were carried out to obtain data for lightning protection design with segmented diverters. The goals were to compare the amount of voltage needed to flash over a segmented strip as compared with that needed to flash over an equal length of unprotected dielectric wall, to determine the effect of voltage rate of rise on strip breakdown voltage, and to determine optimal segmented diverter spacings. These tests are described and their results are discussed.

A79-25319 The impact of the total lightning environment on aircraft flight control systems D W Clifford (McDonnell Aircraft Co, St Louis, Mo) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga, June 20-22, 1978, Proceedings New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 211-217, 12 refs

The extremely high peak currents (up to 200,000 A) associated with lightning, and rapidly changing magnetic fields appear to pose the most significant threat to aircraft electronic systems. However, recently reported flight data, together with new information from laboratory tests, indicate that other aspects of the lightning flash, in particular electric field changes and radiated RF, may pose as much of a threat as the peak currents to modern well designed systems. In the present paper, a 'total lightning threat scenario' is proposed that identifies the specific aspects of a lightning strike, which may affect avionics design and performance.

A79-25321 EMP coupling to a composite aircraft R A Perala, K M Lee, and R B Cook (Mission Research Corp., Albuquerque, N Mex.) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga., June 20.22, 1978, Proceedings

New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p 233-237 7 refs Contract No F33615-77-C 5169

The present paper deals with external and internal coupling two important factors in the exposure of an aircraft to a nuclear electromagnetic pulse (EMP). For an aircraft of advanced design, large portions of whose skin are made of a graphite epoxy composite material, numerical results are obtained for induced surface charges and currents (external coupling) and for skin-diffusion induced currents and voltages on typical cable runs inside the aircraft (internal coupling). It is shown that the hazard that may arise to aircraft electronics due to energy diffusion through a composite skin can be effectively eliminated by applying an aluminum flame spray coating to the skin.

A79-25322 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP R F Hess (Sperry Flight Systems, Phoenix, Ariz) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga , June 20-22, 1978, Proceedings New York, Institute of Electrical and Electronics Engineers, Inc , 1978, p 238-242

When an aircraft encounters lightning, the resulting electromagnetic pulse (EMP) field produces subsystem wiring transients which contain several components. A portion of the external EM environ-

ment associated with lightning penetrates to the aircraft interior and couples to the wiring which interconnects subsystem equipment. An investigation is conducted regarding the influence of the time constants of the excitation waveform on the waveform of the induced transients. It is found that even for the simple circuit configuration of a thin wire suspended in space, the induced response to EMP contains several components.

A79-25323 FAA remote terminal system frequency assignment model C Cram (FAA, Systems Research and Development Service, Washington, D C) and T Hensler (U S Department of Defense, Electromagnetic Compatibility Analysis Center, Annapolis, Md) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga, June 20 22, 1978, Proceedings

New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 278-281 U.S. Department of Transportation Contract No FA76WAI-612, Contract No F19628-78-C-0006 AF Project 649E

A system of interactive analysis models was developed for the Federal Aviation Administration (FAA) to provide automated, quick response capabilities for use by FAA frequency managers in solving frequency management problems. This paper describes the frequency assignment model that was developed as part of the FAA's interactive system. The model is used to make VHF (118-135 MHz) Air Traffic Control (ATC) frequency assignments. The criteria used by the model, the operation of the model, and examples of the model's use are discussed in this paper.

A79-25326 # Validation of IEMCAP using the B 52 F K Gardner and S A Davidson (USAF, Aeronautical Systems Div , Wright-Patterson AFB, Ohio) In International Symposium on Electromagnetic Compatibility, Atlanta, Ga , June 20-22, 1978, Proceedings New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 307-309

This study assessed the effectiveness of the Intrasystem Electromagnetic Compatibility Analysis Program (IEMCAP) in predicting antenna-coupled interference problems. The B 52 aircraft is used in the case study. The study concludes that IEMCAP does correctly predict a high percentage of actual interference problems. (Author)

A79-25350 * Thermal response of composite panels D A Kourtides, W J Gilwee, Jr, and J A Parker (NASA, Ames Research Center, Moffett Field, Calif) Polymer Engineering and Science, vol 19, no 3, Feb 1979, p 226-231 10 refs

The thermochemical and flammability characteristics of laminating resins and composites currently in use and others being considered for use as aircraft interior panels are described. The properties studied included (1) limiting oxygen index of the composite constituents, (2) fire containment capability of the composite, (3) smoke evolution from the composite, (4) thermogravimetric analysis, (5) composition of the volatile products of thermal degradation, and (6) relative toxicity of the volatile products of pyrolysis. The performance of high-temperature laminating resins such as modified phenolics, polyimides and bismalerimides is compared with the performance of epoxies. The relationship of increased fire safety with the use of polymers with high anaerobic char yield is shown. Processing parameters of the state-of-the art epoxy resin and the advanced resin composites are detailed.

(Author)

A79-25368 # Objectives related to an enhancement of the effectivity of MALEV I (Aufgaben zur Erhohung der Effektivität der MALEV I) E Vilmos (Ungarische Fluggesellschaft MALEV, Budapest, Hungary) Technisch-okonomische Information der zivilen Luftfahrt, vol. 14, no. 5, 1978, p. 234-244. In German

The effectivity is obtained as the ratio of expenditure and result On the basis of an extension in the definition of effectivity, it is possible to relate an increase in effectivity to improved management leading to a better utilization of the given production factors. An enhancement of the effectivity of the operation of an airline must be compatible with an increase in flight safety. The reported investiga-

tion is particularly concerned with the obtained level of capacity utilization in the case of airliners. Attention is given to developments regarding the yearly flight hours, the factors which have an effect on an extensive utilization, problems related to a suitable time interval selection for the study, the characteristics of the route network of the airline, the dependence of airline operation on the season, the characteristics of the employed aircraft types, the direct advantages of an increase in the extensive utilization of the transport capacity, and the conditions for an increase in specific flight-operational performance at MALEV.

A79-25369 # Selective calling procedure in air traffic (Selektivrufverfahren im Luftverkehr) G Westphal (Gesellschaft für Internationalen Flugverkehr mbH, Berlin, East Germany) Technischokonomische Information der zivilen Luftfahrt, vol. 14, no. 5, 1978, p. 245-251. In German

The safety of air traffic requires the continuous guidance of aircraft by the air traffic control organization. It is, therefore, necessary that the given communication channel is monitored without interruption on board of the aircraft Such monitoring activities, which involve also listening to calls between ATC and other aircraft, impose a great deal of psychic stress on the cockpit personnel Approaches for relieving the crew of a great part of this stress are considered. The employment of the Selective Calling System (SELCAL) makes it possible that the cockpit personnel has to give attention only to calls directed to their aircraft Calls intended for an individual aircraft are recognized by means of a code used in the calling procedure. The SELCAL device on board of the aircraft monitors the calling frequency and alerts the crew only when calls intended for their own aircraft are received. A description is presented of the design of SELCAL units located on board of the aircraft and on the ground

A79-25370 # Control of the location of the center of gravity of loaded aircraft (Kontrolle der Schwerpunktlage beladener Flugzeuge) B Glockner (Gesellschaft für Internationalen Flugverkehr mbH, Berlin, East Germany) Technisch-okonomische Information der zivilen Luftfahrt, vol 14, no 5, 1978, p 254-256 In German

One of the most basic requirements regarding flight safety is related to the correct location of the center of gravity of an aircraft Aircraft stability and controllability are directly affected by this location. The optimization of center of gravity location as a function of flight altitude, flight Mach number, and flight weight can also have a favorable effect on flight economy by reducing the air resistance to a minimum value on the basis of small stabilizer setting angles. A description is presented of a suitable approach for the determination of the center of gravity location of an aircraft. The aircraft IL-62 is used as an example to illustrate the procedure for implementing the considered approach.

A79-25371 # Statistics of disturbances and maintenance according to conditions at Interflug III - Technical requirements concerning the program for the processing of disturbance data by means of electronic data processing (Storstatistik und Zustandswartung bei der Interflug III - Technische Forderungen an das Programm zur Bearbeitung von Daten über Storungen mittels EDV) J. Liess (Gesellschaft für Internationalen Flügverkehr mbH, Berlin, East Germany) Technisch-okonomische Information der zivilen Luftfahrt, vol. 14, no. 5, 1978, p. 260-272. In German

The long-term storage of all data related to the operation of the airline makes it possible to obtain the numerical characteristics for extensive and intensive expansions on the basis of statistical studies and mathematical models. Electronic data processing operations related to aircraft maintenance and repair are considered, taking into account procedures for the acquisition of the necessary data related to aircraft components and the aircraft themselves, data sets on magnetic-storage media, aspects of data coding, the data set for reports of operational disturbances, details regarding the information items to be recorded, the data set containing information regarding

the technical parameters of aircraft components, aspects of data flow procedures, and various data processing programs.

G R

A79-25372 # Aviation obstructions and the particular conditions for construction projects in the vicinity of airports (Luftfahrthindernisse und die besonderen Bedingungen für das Bauen in der Umgebung von Flugplatzen). E Harzbecker (Hauptverwaltung der zivilen Luftfahrt, Berlin, East Germany) Technisch-okonomische Information der zivilen Luftfahrt, vol 14, no 5, 1978, p 273-277 In German

Considerations regarding the safety of air traffic make it necessary to control construction activities in the vicinity of airports and air routes to avoid collision hazards produced by buildings and other structures which represent obstructions to the air traffic. If existing constructions representing such obstructions cannot be removed, special steps must be taken to provide by means of signs and markings to pilots adequate warning of the existence of the flight obstructions. The approaches used in the German Democratic Republic for the demarcation of such obstructions are discussed, taking into account obstruction markings and lighting employed in the case of smokestacks and tall towers. Legal restrictions concerning constructional designs and activities are also considered.

A79-25482 The prediction of fatigue crack growth under flight-by-flight loading D Broek and S H Smith (Battelle Columbus Laboratories, Columbus, Ohio) Engineering Fracture Mechanics, vol 11, no 1, 1978, p 123-141 12 refs Navy-sponsored research

Techniques for dealing with random or quasi-random service-load histories were recently proposed. In this paper, the adequacy of these new techniques for fatigue crack growth under flight-by-flight loading is examined. The load spectrum used is a fighter spectrum in the form of a basic load sequence of 72,000 cycles for 6000 flight hours. The experimental materials considered are Ti-6Al-4V mill-annealed plate and 7075-T73 aluminum alloy plate. Two adjustable retardation models for crack growth analysis are discussed the Wheeler (1972) model and the Willenborg (1971) model. The Wheeler model is preferable for accurate prediction of crack propagation under flight-by-flight loading because it can be adjusted independent of baseline crack growth data, whereas the Willenborg model can be adjusted only by selecting another set of crack growth data. The only satisfactory way to apply a safety factor to crack growth predictions is to apply a factor to fatigue crack growth life.

A79-25484 Four lectures on fatigue crack growth J Schijve (Delft, Technische Hogeschool, Delft, Netherlands) Engineering Fracture Mechanics, vol 11, no 1, 1978, p 167-177, 179-185, 187-221 58 refs

The cited lectures deal with fatigue crack growth and fracture mechanics, fatigue cracks, plasticity effects and crack closure, fatigue crack propagation, prediction and correlation, and fatigue crack growth under variable-amplitude loading. Fatigue life is divided into a crack nucleation period and a crack propagation period, and the similarity approach for correlating fatigue data is introduced. The role of crack closure in fatigue crack growth is analyzed. Two prediction techniques (cycle-by cycle prediction and prediction by correlation) for fatigue crack propagation are described. Stationary and nonstationary types of variable-amplitude loading are specified. The significance of crack closure for understanding crack growth under variable-amplitude loading is emphasized. Illustrative examples are presented throughout the text.

A79-25485 Fundamentals of design I - Whys' and 'where-fores' of wings B R A Burns *Air International*, vol 16, Feb 1979, p 81-85

Wing design is discussed considering the effect of the aspect ratio, sweep, taper, thickness, camber, twist, and high lift devices on its performance. For example at high subsonic speed there is a relationship between wing thickness/chord ratio and sweep allowing for the same design Mach number. 30 deg sweep with 10% t/c and 40 deg sweep with 12% t/c being roughly equivalent. The amount of nose and rear camber depends on the design lift value, with the best characteristics obtainable by leading-edge and trailing edge droop

which is variable with incidence. Minimum drag and maximum lift in subsonic flight is obtainable by deflecting leading edge droop and trailing edge flaps progressively as incidence increases. Future combat planes are expected to combine automatic wing sweep with a more smoothly cambered wing section, making it possible for the aircraft to change its sweep as it accelerates or decelerates and camber its wing with increasing incidence for efficient operation in all flight conditions.

A79-25491 System for the display of extracted radar data on the basis of minicomputer-controlled display devices /DERD-MC/ for an employment in Air Traffic Control (System zur Darstellung extrahierter Radardaten auf der Basis minicomputergesteuerter Sichtgerate /DERD-MC/ fur den Einsatz in der Flugsicherung) B E Schafer (Bundesanstalt fur Flugsicherung, Frankfurt am Main, West Germany) Ortung und Navigation, no 3, 1978, p 395-408 In German

The currently employed system for the display of extracted radar data (DERD-I) represents a first design stage. The four regional ATC centers in West Germany employ identical systems. Essential functions are related to the reception and the processing of digitized radar data, the synthetic representation of the air traffic situation on display devices, the display of additional information, such as maps and tables, and the processing of input data from the controller. A number of disadvantages and restrictions concerning the DERD-I are to be eliminated with the aid of an improved system in which the display device is controlled by minicomputer. Data processing operations are performed in a Central Computer Complex. The improvements provided by the new DERD-MC system are discussed.

A79-25492 Navstar/GPS /Global Positioning System/ and electronic counter measures (Navstar/GPS /Global Positioning System/ und elektronische Stormassnahmen) D Ernst (Bundesamt für Wehrtechnik und Beschaffung, Koblenz, West Germany) Ortung und Navigation, no 3, 1978, p. 409-426 In German

Certain weaknesses of the currently used radio navigation system Tacan are to be overcome with the aid of the satellite navigation system Navstar which is presently being developed in the U.S. These weaknesses include the susceptibility of Tacan against electronic counter measures (ECM). However, even Navstar remains vulnerable to ECM. An investigation is conducted regarding the utilization of Navstar in the presence of ECM, taking into account the most effective approach which can be used by the enemy to disturb the navigational functions. Attention is given to the Navstar transmitter, the basic structure of Navstar receivers, and the functioning of Navstar receivers under the conditions of EMC.

A79-25505 # Analysis of longitudinal natural vibrations of deformable aircraft by the finite-element method Z Dzygadlo and J Blaszczyk Journal of Technical Physics, vol 19, no 2, 1978, p 223 234 9 refs

A finite-element dynamic model is used to analyze the vibration modes and frequencies of a deformable aircraft. Calculations have been carried out for a hypothetical aircraft with constant mass and stiffness parameters along the length of the deformable units. The method is applied to the natural vibrations of a training aircraft. B J

A79-25517 # Dynamics of controlled longitudinal motion of an airplane with a variable-geometry wing Z Dzygadlo and J Maruszkiewicz *Journal of Technical Physics*, vol. 19, no. 3, 1978, p. 371-382, 7 refs

A method for controlling the perturbed longitudinal motion of a variable sweepback aircraft is proposed based on the assumption that the flight speed remains unchanged during the process of sweepback change and static equilibrium conditions are satisfied at the final moment of the sweepback process for a prescribed inclination of the flight trajectory. The motion of the aircraft is analyzed numerically for increasing and decreasing sweepback. The controlled motion of the aircraft is found to be characterized by small perturbations of flight parameters.

A79-25541 # Flight deck alarm systems. E Edwards (Aston, University, Birmingham, England) Aircraft Engineering, vol 51, Feb 1979, p 11-14

Aircraft alarm systems are examined and a detailed checklist for their systematic evaluations is presented. Various taxonomies relating to methods for the classification of alarms are noted, including degree of urgency, nature of event, nature of appropriate action, and sensory modality of alarm. The human factors aspects of individual alarms are reviewed, indicating various problems and their possible solutions. The design of total alarm systems is described in the light of suggestions for improving their efficiency.

A79-25542 # Safety of air transport W Tye (Civil Aviation Authority, London, England) Aircraft Engineering, vol 51, Feb 1979, p 15-20

General issues and human factor questions relating to air safety are discussed. The controllability of and constraints to safety, the balance between safety and cost, responsibility for deciding safety level, public attitude to safety, and the business of achieving high safety are taken into account. Three categories into which the great part of human errors may be grouped are noted. failure to apply the best strategy to the flight, failure to comprehend the situation, and failure to control the aircraft. The causes of errors and their avoidance are considered in the context of matching the flight crew to the aircraft, designing to accomodate error, learning from occurrences, sub-standard airworthiness, the old-aircraft problem, and problems of warning systems. It is concluded that it is preferable to put more effort in the area of warning design, minimizing thus false warnings, even at the expense of reliability of functioning when needed.

A79-25618 # Behavior of elastic systems in separated flow (Povedenie uprugikh sistem pri otryvnom obtekanii) A S Vol'mir, V V Guliaev, and A T Ponomarev Akademiia Nauk SSSR, Doklady, vol 243, Dec 1, 1978, p 886 888 In Russian

A numerical approach is taken to the aeroelastic problem of the aerodynamic loading of a thin airfoil in separated flow. The study is carried out in the context of nonlinear wing theory and takes account of disturbances introduced in the flow by the deformed structure. The numerical model is based on the method of discrete vortices and the thin lifting surface scheme. Total aerodynamic loading is determined with consideration of flow prehistory and deformations of the body. Numerical results show that deformation of the body leads to a significant reduction in its oscillations.

A79-25681 Adaptation of a digital airborne radar for use on the microphysics research aircraft R S Anderson (Meteorology Research, Inc., Altadena, Calif.) and G M Naegele (National Center for Atmospheric Research, Boulder, Colo.) In Conference on Radar Meteorology, 18th, Atlanta, Ga, March 28-31, 1978, Preprints

Boston, Mass., American Meteorological Society, 1978, p 370-375 U.S. Bureau of Reclamation Contract No 14-06-0-7699

A description is presented of a single range gate video integrator and the modifications made to the RDR-130 weather avoidance radar. The modifications are related to the rectification of the cockpit display image to make it more representative and quantita tive in terms of the meteorology, steps taken to allow operation of a single range gate analog video integrator, and the acquisition of a complete digital record of the display image via an onboard computer-weather radar interface. Attention is given to the radar characteristics, the integrator decoder, the memory decoder, the video integrator, circuit details, and aspects of digital image recording.

A79-25689 Design considerations for the NOAA airborne meteorological radar and data system B L Trotter (NOAA, Environment Research Laboratories, Boulder, Colo) In Conference

on Radar Meteorology, 18th, Atlanta, Ga, March 28-31, 1978, Preprints Boston, Mass, American Meteorological Society, 1978, p. 405-408

Experience with the NOAA DC-6 and C130 aircraft had shown at the time of the acquisition of the two new NOAA WP3D aircraft that a definite need existed to develop a weather research radar and data system for the WP3D aircraft. A description is presented of an airborne system that was designed to enhance the capabilities of the WP3D's which were scheduled for multidisciplinary research programs in the atmospheric sciences. Expectations for use of the radar and data system are related to hurricane research, severe storm research, and basic research. The described airborne system is currently operational on both of the NOAA WP3D aircraft. The NOAA C130 aircraft has a nose radar that is identical to the ones installed in the nose of the WP3D's.

A79-25718 * SIFT - Design and analysis of a fault-tolerant computer for aircraft control J H Wensley, L Lamport, J Goldberg, M W Green, K N Levitt, P M Melliar-Smith, R E Shostak, and C B Weinstock (SRI International, Menlo Park, Calif) IEEE, Proceedings, vol 66, Oct 1978, p 1240-1255 12 refs Contract No NAS1-13792

SIFT (Software Implemented Fault Tolerance) is an ultrareliable computer for critical aircraft control applications that achieves fault tolerance by the replication of tasks among processing units. The main processing units are off-the-shelf minicomputers, with standard microcomputers serving as the interface to the I/O system. Fault isolation is achieved by using a specially designed redundant bus system to interconnect the processing units. Error detection and analysis and system reconfiguration are performed by software Iterative tasks are redundantly executed, and the results of each iteration are voted upon before being used. Thus, any single failure in a processing unit or bus can be tolerated with triplication of tasks, and subsequent failures can be tolerated after reconfiguration independent execution by separate processors means that the processors need only be loosely synchronized, and a novel fault-tolerant synchronization method is described. (Author)

A79-25750

Aircraft fire protection and rescue procedures
/2nd edition/ Edited by C E Williams and J W Laughlin Stillwater, Okla, Oklahoma State University, Fire Protection Publications (General Fire Service Training Manuals No 206), 1978 247 p
\$7 00

The manual informs all fire service personnel about problems that may arise should an aircraft disaster occur in their area. Information on all general aircraft related methods of fire attack and rescue procedures is given. In particular, the manual helps firefighters select techniques and procedures applicable to the facilities available to them. Areas of interest include aircraft types, engines and systems, apparatus and equipment, airfield operations, and planning and communications. Also discussed are forcible entry tools, explosive cargo and nuclear weapons, and post-incident operations.

S.D.

A79-25845 # Dynamic data analysis D S Pearson (Rolls-Royce, Ltd , London, England) Transducer Conference, Wembley, Middx , England, June 26-28, 1978, Paper 16 p

The requirements for basic dynamic transducers, objectives in their use, and simple logistics of the engine as well as information elements of a gas turbine development process are introduced Editing techniques are presented by complementary analysis methods through which pre-edited data may be converted selectively into engineering information in a compact and simple form. Four case histories are used to illustrate the techniques, with the first two recording respectively frequency information derived from several strain gauges during uniform engine acceleration of a blade standard known to fail, and comparative 'g' amplitude data from an accessory gear-box having a major accessory mounted at extremes of an acceptable clamp tightness specification. Cases three and four illustrate respectively distribution of stress, and an engine mounted accessory used to control the engine throttle.

A79-25849 # Recording methods for steady state and tran sient signals E N Jones (Rolls-Royce, Ltd., London, England)
Transducer Conference, Wembley, Middx, England, June 26-28, 1978, Paper 15 p

The paper presents data recording techniques in the testing of aircraft engines in transient and steady state regimes (take-off and cruising, and the transition between them). Parameters measured include gas or liquid pressure, gas or metal temperature, fuel flow, static or dynamic strain, vibration, speed, thrust, and sound pressure. The centralized data processing system for high accuracy steady state data, the noncentralized system for wideband processing of steady state data and the transient data processing system are described and diagrams given. The UV film recording system for transient data, and analog FM and direct recording tape recorders for dynamic data are discussed, with digital tape recorders in the minority. It is projected that the role of on-line processing of test data will increase and the use of UV recorders will diminish, although analog recorders will continue to be employed.

A79-25850 # Pressure measurement in air data instrumentation A N Du Feu (Smiths Industries, Ltd., Aviation Div., Cheltenham, England) Transducer Conference, Wembley, Middx., England, June 26 28, 1978, Paper 18 p. 5 refs

The study was concerned with pressure measurements insofar as they affect such key output quantities as altitude, calibrated air speed, and Mach number. Absolute and differential pressures are determined for three ranges of tolerances greater than 0.5 mbar, between 0.5 and 0.2 mbar, and below 0.2 mbar. Using these data, a fully automated pressure test module has been constructed with precise control of dynamic pressure characteristics, the ability to control environmental tests from the software, and the ability to interrupt the program, scan data, and execute additional tests from the keyboard and return to the program.

A79-25853 * # Technology for future air transports J M Klineberg (NASA, Office of Aeronautics and Space Technology, Washington, D C) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C , Feb 6-8, 1979, Paper 79-0529 10 p

The requirements and opportunities for technological development in transport aircraft of the next generation are reviewed, focusing primarily on conventional, subsonic aircraft. Advances in computational aerodynamics and computer-aided design and manufacturing (in numerically controlled processes) are noted as well as improved wind tunnel testing and drag reduction techniques Advances in aeroelasticity prediction have made it possible to use flexible, high-aspect ratio wings without large weight penalties Weight reduction may be achieved by the use of composite aircraft structures and superplastic forming combined with diffusion bonding, however composites require improvement in manufacturing techniques and mechanical properties in order to gain general acceptance Propulsion systems can be improved in engine fuel efficiency, control, durability, environmental compatibility (exhaust and noise emissions), and fuel specifications. In avionics, due to the growth of low-cost, miniaturized packages, opportunities exist in the fields of digital controls, navigation, guidance and communication Applications of new technologies to various aspects of flight safety are also outlined ALW

A79-25856 * # Lean combustion limits of a confined premixed-prevaporized propane jet K L Huck (NASA, Lewis Research Center, Cleveland, Ohio, Martin Marietta Aerospace, Bethesda, Md.) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D.C., Feb. 6-8, 1979, Paper 79-0538 9 p. 10 refs

An experimental study was carried out to determine the effects of jet velocity and confinement on lean premixed-prevaporized propane/air blowout limits. The combustor consisted of a single hole flameholder within a quartz liner. Five flameholder plates and two

quartz liners were used. Lean stability limits were mapped for confined propane jet in cylindrical combustor. Three zones of flame stability were observed depending on the liner and jet Reynolds number and the combustor geometry. At low Reynolds number the combustor was jet stabilized. As the Reynolds number was increased the combustor became either recirculation zone stabilized, or for small recirculation zone step sizes, the combustor was wall stabilized. The factors affecting stability seem to be the Reynolds numbers of the liner and inlet jet along with the flameholder step size. Stability was achieved at both laminar and turbulent conditions.

A79-25859 # Control system time response optimization - A nonlinear programming approach M R Pouliot (General Dynamics Corp, Electronics Div, San Diego, Calif) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C, Feb 6-8, 1979, Paper 79-0540 10 p 13 refs

Typically, the time response of a flight control system is a function of variables such as amplifier gain constants or rate gyro sensitivity settings. In this paper, a formal nonlinear programming procedure for choosing an optimal combination of these control variables is proposed and investigated. To demonstrate this approach to control system analysis, a pitch orientation autopilot for a transport jet aircraft is used as an example. This particular system is dependent upon two control variables. Variation of these two parameters will produce an array of system responses. A performance index is then formulated in terms of transient time response characteristics and minimized via the control variables to obtain the optimum system response. Three parameters are used to define the performance index rise time, damping ratio, and peak overshoot. For the basic system solution, rise time is minimized while inequality constraints are imposed upon both damping ratio and peak overshoot through the use of penalty functions. A family of solutions are then generated, analyzed, and compared to other solutions derived via (Author) classical analysis techniques

A79-25861 * # Characteristics of the wake of a lightly loaded compressor or fan rotor B D Reynolds (Pennsylvania State University, University Park, Pa) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C, Feb 6-8, 1979, Paper 79-0550 17 p 27 refs Contract No NsG-3012

An experimental investigation was carried out to evaluate the properties of the rotor fan or compressor wake in order to understand the structure of the wake. This included a study of profile shape, decay characteristics, effects of rotation, and effects of varying blade loading on the wake. Rotating tri axial hot-wire probe measurements were reported which represent the first systematic data in the near wake region of the rotor wake using this technique It is found that the radial, tangential, and axial components of mean velocities and turbulence intensities decay very rapidly near the rotor blade trailing edge, and that increased blade loading reduces the decay rates of axial and tangential mean velocity defects and radial velocities in the wake. In particular, the presence of an almost constant wake width region for increasing axial distance shows the effects of three-dimensionality on the rotor wake flow Other SD conclusions are also given

A79-25862 # Advances in avionics G W Church (Bendix Corp., Avionics Div., Ft Lauderdale, Fla.) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D.C., Feb. 6-8, 1979, Paper 79-0562 6 p

Advances in avionics are discussed with emphasis on microprocessor technology. The general aviation computer programmer capable of restoring and recalling ten navigational frequencies, the electronic course deviation indicator working through a programmable memory, and the airborne weather radar displaying simultaneously weather and the route to be flown are considered. Developments in integrated circuitry are described particularly noting the progressive reduction in their purchasing price (e.g., circuitry that cost \$10 eighteen years ago is purchasable today for only 30 cents). The introduction of electronic technologies into general aviation is taken into account, including microwave landing system, and flight director system. The challenge to find ways for keeping the pilot in the logic loop despite his being surrounded with electronic logic far exceeding his own capacity is mentioned.

A79-25863 * # A visual investigation of the separation and subsequent transition near the leading edge of airfoils A V Arena (Notre Dame, University, Notre Dame, Ind.) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C, Feb 6-8, 1979, Paper 79-0552 11 p 9 refs Grant No NsG-1419

Subsonic (5 to 30 m/sec) wind tunnels were used to measure pressure distributions at the leading edge and upper surface of airfoil models and to obtain high-speed movie photographs of smokevisualized separation, transition, and reattachment phenomena Points of turbulent shear layer reattachment could be determined by using an oil-mixture coating on the surface Plots of the static pressure coefficient along the chord of several models are presented, and the measured separation, transition, and reattachment points are plotted against the chord Reynolds number V P

A79-25865 # Helicopter rotor radius optimization A M Ahsan (Rosemount, Inc., Eden Prairie, Minn.) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D.C., Feb. 6-8, 1979, Paper 79-0554 9 p. 6 refs

The study focuses on various methods of producing an optimum rotor radius, where the term optimum means reduction of helicopter rotor to the extent that it can perform effectively without losing much of its aerodynamic capabilities. The ideal helicopter envisioned has to carry only two or three persons including the pilot. To understand the basics of helicopter rotors, the study is divided into three parts. The first part deals with the efficiency criteria of a helicopter rotor, namely the figure of merit. The second part considers the aerodynamic characteristics of a helicopter rotor. The third part examines minimum power requirements for an optimum rotor, both for hovering and forward flight regimes. It is shown that by increasing the number of blades the rotor radius can be reduced for a fixed weight and air density, and that taking into account the tip loss factors and nonuniform downwash reduces the optimum rotor size. The results match very closely with helicopter rotors in current use

A79-25866 # General aviation aircraft in the 1990's M S Harned (Cessna Aircraft Co, Wichita, Kan) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C, Feb. 6-8, 1979, Paper 79-0560 9 p

Demands and improvements in the field of general aviation aircraft during the 1990's are discussed Projected increases in affluence are expected to lead to a substantial growth in the personal ownership of aircraft noting the subsequent demands, especially in the safety domain where emphasis is placed in improving the areas of weather prediction, approach speed, pressurization and radar systems, and centerline thrust. The need for fuel efficiency improvements is stressed, noting that by 1990 fuel will probably have more than doubled in price. Composite materials such as the aramid and graphite fibers with epoxy bonds, highly reliable low-cost computers, large scale integration of semiconductors, and lean burning techniques with fuel injection are expected to be widely used in the general aviation aircraft. Models of future general aviation aircraft are presented, including a turbocharged diesel-powered four-place family airplane Centrifugal compressors as well as the pusher propeller concept are taken into account A five-fold increase in general aviation business is predicted for the decade of the 90's AA

A79-25869 # Lifting surface theory for skewed and swept subsonic wings N T Frink American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D.C., Feb 6-8, 1979, Paper 79-0551 11 p 11 refs Grant No DAAG-76-G-0318

A new method is developed for solving the lifting surface equation for thin subsonic wings which can also be interpreted as a vortex lattice method. The downwash equation is transformed into double integrals involving Cauchy-type singularities in the chordwise and spanwise directions. A technique developed by Lan for airfoil theory is used to reduce both integrals to a double summation. This method properly accounts for the leading-edge singularity, Cauchy singularity, and Kutta condition. The solutions generally compared well with other lifting-surface theories, but with much smaller computational times, and the method was found to be more accurate and converge faster than conventional vortex lattice methods. (Author)

A79-25870 * # NASA research on general aviation power plants W L Stewart, R J Weber, E A Willis, and G K Sievers (NASA, Lewis Research Center, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 15th, Washington, D C, Feb 6-8, 1979, Paper 79-0561 10 p 7 refs

Research activities within NASA to support general aviation industry in improving propulsion engines are described. Near-term objectives include improvements of gasoline piston engines to achieve fuel savings and reduce emissions well below EPA levels. To meet the longer term goals, advanced combustion research has been considered as essential in obtaining further improvements in BSFC (break specific fuel consumption). Modifications of an aircraft rotary engine were tested and it was found that by increasing the compression ratio and other refinements the BSFC was improved by 15%. The applicability of available large turbofan engine technology to small engines in order to obtain significant reductions in noise and pollutant emissions is being tested. Studies have been conducted at exploring the possibility of achieving high improvements in cost and performance for turboprop engines of less than 1000 horsepower.

AA

A79-25872 # Slender wing in compressible flow (Tonkoe krylo v szhimaemom potoke) E A Krasil'shchikova Moscow, Izdatel'stvo Nauka, 1978 226 p 91 refs. In Russian

The book deals with the derivation of a mathematical theory of small disturbances generated in a compressible medium by the motion of a slender wing and by acoustic waves interacting with the wing. A general method is proposed for studying the unsteady potential field from arbitrary unsteady motions of the wing. The method is shown to be well suited for calculating flows past wings with supersonic leading edges. In the study of two-dimensional unsteady fields, solutions to boundary value problems are obtained by a method based on the used integral equations in characteristic variables. Quadrature solutions are obtained to two- and three-dimensional problems involving unsteady flows past an isolated wing and past wings interacting with acoustic waves incident on the wing

A79-25875 # Redundant control systems for flight vehicles (Izbytochnye sistemy upravlenija letateľnymi apparatami) A D Epifanov Moscow, Izdateľstvo Mashinostroenie, 1978 146 p 49 refs. In Russian

In this book, the fundamentals of the theory of adaptive control systems are outlined, and vector-matrix equations for redundant systems of advanced digital flight control are derived Attention is given to the adaptation of strapdown redundant sensor inertial navigation systems to a digital computer and the evaluation of failure detection algorithms for such systems VP

A79-25876 Recent General Electric engine development testing for improved service life R C Turnbull (General Electric Co, Evendale, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 780990 22 p 5 refs.

More exact simulation of engine in-service operating conditions by accelerated development test program improvements - T700/F101/F404/CFM56/CF6 - are reviewed for lessons learned towards earlier identification/solution of engine life extension problems Improved design features, improved analysis and test simulation of mission cycles, improved component test techniques and, in general, increased emphasis on demonstrating required minimum service life prior to production are briefly discussed Possible future direction of these efforts is indicated for consideration in General Engine Specification revisions (Author)

A79-25877 The application of a design verification system and accelerated mission testing to gas turbine engine development B J McDonnell (United Technologies Corp., Pratt and Whitney Aircraft Group, West Palm Beach, Fla.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 780991 13 p

Advanced techniques for the design and development of high technology gas turbine engines are discussed, considering the improved design Verification System (DVS) and the Accelerated Mission Test (AMT) concept. The first technique, originally developed by NASA for use in the space programs, provides the designer of a gas turbine engine with feedback data showing the relationship between his predictions and the actuals through two advanced tools the computer analytical prediction systems, and the high technology instrumentation. Sputtered sensor, optical clearance vibration, fiber optics, and engine radiography techniques are employed in the instrumentation device. While the DVS verifies that the basic design is founded on sound assumptions, the AMT exposes the design to the damaging portions of the mission duty cycle to prove by test that the hardware will operate satisfactorily for its predicted life under flight operation conditions. The techniques are being applied to current and advanced engine programs with good success

A79-25878 Planning the development and qualification process for the next generation of high technology aircraft engines S M Hudson and W L McIntire (General Motors Corp., Detroit Diesel Allison Div., Detroit, Mich.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 780992. 14 p. 13 refs

The concurrent requirements to maximize performance and minimize cost and program risk provide a great challenge for the weapon-system planner and the propulsion-system manager. The propulsion-system development process consists of the definition of requirements, the selection of the appropriate technology, the design and fabrication of the configuration, the verification of characteristics, and the resolution of problems identified during the verification phase. The development process must be structured to be consistent with the current procurement policies and be responsive to requirements of timing and funding constraints. This paper addresses the development process for the high-technology aircraft engine in the light of recent military engine experience and the current policies and constraints.

(Author)

A79-25879 Requirements and constraints in the development and qualification of gas turbine engines for the Navy M E Dell (US Naval Air Propulsion Test Center, Trenton, NJ) and M D Mead (US Naval Air Systems Command, Washington, DC) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov 27-30, 1978, Paper 780994 11 p

An improved approach to the development and qualification of aircraft turbine engines has been developed by the Navy. The approach places emphasis on durability testing throughout the engine development program. This testing is intended to assure that structural requirements have been achieved upon the introduction of new engines into service. The approach utilizes three different types of

durability tests each of which is intended to address a separate aspect of the overall durability problem (Author)

A79-25880 * Prop-fan propulsion - Its status and potential J F Dugan, Jr (NASA, Lewis Research Center, Cleveland, Ohio), B S Gatzen, and W M Adamson (United Technologies Corp., Hartford, Conn.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 780995, 22 p. 43 refs.

Studies have established that advanced turboprop (prop-fan) equipped aircraft will reduce fuel consumption by 15 to 30 percent compared to aircraft equipped with high-bypass turbofan engines of equivalent technology A reduction in direct operating costs of approximately 10 percent has been identified for commercial aircraft as well as approximately 20 percent lower gross weight airplane for long endurance military missions. The prop fan propulsion system is being investigated as part of the NASA Aircraft Energy Efficiency program which includes both analytical studies and experimental tests. The experimental work encompasses performance and acoustic wind tunnel tests on several prop-fan models. The prop-fan technology status is reviewed in the major areas of performance, installed effects, cabin noise, blade structure and maintenance cost Also, further activities required to complete the technical validation of prop-fans are described (Author)

A79-25881 * Propeller slipstream wing interactions at Mach no 0 8 D P Bencze, R C Smith (NASA, Ames Research Center, Moffett Field, Calif), H R Welge, and J P Crowder (Douglas Aircraft Co, Long Beach, Calif) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov 27-30, 1978, Paper 780997 11 p 11 refs

Configuration and results of a wind tunnel test of the aerodynamic interactions between propeller slipstream and a supercritical wing at transonic Mach numbers are discussed. The test was conducted over a free-stream Mach number range from 0.7 to 0.84, with the slipstream simulator and the wing-body model installed in the tunnel. The angle of attack and the spanning lift coefficients were varied from 1 to 3 deg and from 0.4 to 0.7 deg respectively, while the slipstream swirl angle was varied from 0 to 11 deg with an upwash on the inboard side of the wing It was found that at a free-stream Mach number of 08 and a lift coefficient of 05, incremental drag results for 7 deg of swirl and a slipstream Mach number of 0.87 indicated a penalty equivalent to a 0.024 loss in propeller efficiency, whereas at 11 deg the drag increment was favorable. Swirl had significant effects on the chordwise pressure distributions of the inboard section of the wing within the slipstream. Neither surface nor wake pressures showed signs of significant flow separation induced by the slipstream

A79-25882 TDS - A preliminary design system for turbines R R Wysong (General Electric Co , Fairfield, Conn) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27-30, 1978, Paper 780999 21 p Contract No F33615-75-C-2073

The Turbine Design System (TDS) is a time sharing computer system developed for preliminary design and performance evaluation of axial flow turbines having up to ten stages TDS is an interactive, modularized system incorporating aerodynamic, heat transfer and structural analyses in a contiguous arrangement Each task-oriented module addresses one major facet of the design process. This paper discusses the overall system philosophy and organization, the input/output data flow, the tasks performed, and the functional utilization of the system. Selected results of a sample case are shown. (Author)

A79-25883 Integrally cast turbine rotor for high volume production L A Junod and J R Arvin (General Motors Corp., Detroit Diesel Allison Div., Detroit, Mich.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781000 9 p.

The goal is to design an integrally cast wheel with blades which can be produced from high volume production tooling. An auto-

mated procedure is described to determine the optimum radial orientation, or 'stacking', of turbine rotor blade sections to give a design which satisfies both high production manufacturing and rotor structural requirements. High production manufacturing requires that the spaces between blades be pulled away from the wheel in a generally radial direction to release the wax replica of the wheel from the tooling. Structural requirements are expressed in terms of bending stress constraints. A pullability index is defined to indicate the amount of interference to be encountered in removing the tooling. This index is optimized with respect to the direction of removal of the tooling. Bending stress requirements are simultaneously satisfied. (Author)

A79-25884 An alternating direction explicit method for computing three-dimensional viscous flow fields in turbomachines L Walitt (Numerical Continuum Mechanics, Inc., Woodland Hills, Calif), C Y Liu (California, University, Los Angeles, Calif), and J L Harp, Jr (Thermo-Mechanical Systems Co., Canoga Park, Calif) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781001 26 p. 21 refs

A numerical method has been developed to solve the steady three dimensional Reynolds-averaged Navier-Stokes equations by successive approximations. The method is applicable to rotors of axial or radial compressors and turbines. Viscous flow fields were calculated in the blading passages of an axial supersonic compressor cascade, a radial impeller and a backswept impeller. Pressure measurements on the cascade blades agreed with corresponding computations. Radial impeller calculations showed suction blade separation, while backswept calculations indicated shroud separation. This paper describes the numerical method in detail, with results presented as numerical examples.

(Author)

A79-25885 * An in-place recalibration technique to extend the temperature capability of capacitance-sensing, rotor-blade-tip-clearance measurement systems. J Barranger (NASA, Lewis Research Center, Cleveland, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781003

It is known that capacitance-sensing, rotor-blade-tip-clearance measurement systems suffer from a strong dependency on probe tip temperature and humidity. A novel in-place recalibration technique partly overcomes this problem through a simple modification of the electronics that permits a scale factor correction. The technique is used to reduce the errors in a commercial system by more than 50 percent up to a temperature of 370 C (700 F). A probe design is proposed to further raise the maximum temperature capability of the measurement system.

A79-25892 Environmental factors affecting the installation and operation of gas turbine engines in agricultural aircraft G M Hogg (Pratt and Whitney Aircraft of Canada, Ltd, Longueuil, Quebec, Canada) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov 27-30, 1978, Paper 781010 17 p 6 refs

The operational and economic environments associated with agricultural aircraft have dictated several changes to basic turbine engine installation procedures. As the ingestion of chemicals can cause rapid distress in the engine hot section, intake systems are proposed. Aircraft missions are analyzed, and the effect of high cycle time on major rotating components explained. In addition, with jet fuel seldom available at remote fields, alternates such as diesel and gasoline - together with their limitations - are dealt with Operational data is reviewed, recent studies and developments outlined, and the future of the gas turbine engine in agricultural aircraft discussed

(Author)

A79-25893 Methanol, ethanol and jet fuel emissions comparison from a small gas turbine J B Pullman (Santa Clara, University, Santa Clara, Calif) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov 27-30, 1978, Paper 781013 23 p 26 refs

A 60 hp gas turbine engine has been easily converted to operate on methanol and ethanol fuels. No unusual fuel system hardware problems were experienced during 15 hours of testing with methanol and one hour of testing with ethanol Our computer model's pre dicted low emissions of NOx and CO for methanol were closely approximated after the installation of an air atomizing fuel nozzle Substantial NOx reductions also resulted from ethanol fuel. Hydrocarbon unburned fuel emissions were increased with methanol and ethanol Agreement is found with five previously reported methanol gas turbine experiments which indicate from 60% to 80% NOx reductions in comparison with distillate-type fuels. Combustor inlet temperature variation is considered as one cause of variability of reported CO emissions with methanol Droplet size effects and increased ignition delay are considered to adversely affect methanol's CO and hydrocarbon emissions Detailed emissions data for NOx. NO, NO2, CO and hydrocarbons are reported for several series of fuel nozzle tests with methanol, ethanol and Jet A fuels

A79-25894 Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle F D Groutage (U S Naval Ocean Systems Center San Diego, Calif) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov 27-30, 1978, Paper 781017 27 p 12 refs

A concept for an advanced defense suppression system using an unmanned (bomb rack launched, 500 lb class air launched) vehicle with cruise/loiter/attack capabilities has been developed. Guidance commands are provided by either a radiation sensor or a flight reference unit depending upon the phase of the trajectory (antiradiation during attack/flight reference during cruise and loiter). Two airframe configurations (mono wing and cruciform) were analyzed for the three phases of the flight trajectory. Overall systems requirements such as speed, weight, thrust levels, maneuverability, cross section and control configurations were formulated. (Author)

A79-25895 Recognition of damage-tolerance in civil airworthiness standards. J E Dougherty (FAA, Washington, D.C.)
Society of Automotive Engineers, Aerospace Meeting, San Diego,
Calif., Nov. 27-30, 1978, Paper 781019. 6 p

Amendments relating to the structural fatigue evaluation re quirements are described. The amendments improve and update the airworthiness standards applicable to the type certification of civil transport category airplanes. They take into account state-of-the-art developments and accumulated service experience. The authority for and origin of the related rules is also briefly traced. The interest in world-wide acceptance of these new standards is noted. (Author)

A79-25896 Damage-tolerance practices applied to transport aircraft structures M Stone (Douglas Aircraft Co., Long Beach, Calif.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781021. 7 p.

Practices in the design and testing of jet transport aircraft structures to comply with damage tolerance regulations are listed, including the acquisition of loading spectra from aircraft mission profiles, the use of multiload path construction, the use of crack stoppers to limit crack growth and the detailing of design. Results are then reported of an investigation of structural analysis programs used in design. Crack propagation and residual stress analytical predictions of crack length and critical loads of a fatigue-cracked wing panel were verified by comparison with test results. Future activities will include the development of a multiple crack analysis program and testing to obtain more complete crack propagation data, in order to enable the establishment of safe inspection periods.

A79-25897 Technology and the new look meet the F/A-18 radar reliability challenge F B Nelson and C F Farrell (Hughes Aircraft Co , Culver City, Calif) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27 30, 1978, Paper 781024 7 p

The Naval Air Systems Command's 'New Look Acquisition Fundamentals' program establishes requirements and incentives for achieving reliability and maintainability in contracted systems, as well as imposing stringent disciplines on design, testing, and manufacturing. The paper discusses the application of the program requirements to the F/A-18 airborne radar system, especially as it relates to the simplifications in system architecture and hardware design necessary for increased reliability and maintainability. The reliability specified for the F/A-18 radar is 106 hours Mean Time Between Failures (MTBF) Microminiaturized digital computers in control and signal processing have contributed to the replacement of dedicated analog circuits by more reliable digital software, and the application of these concepts to the F/A-18 radar is described. The implementation of parts selection and derating, testing and production quality control disciplines is discussed, and the distribution of contract incentives indicated. Thus far, increases in reliability and maintainability have been achieved and prospects are favorable AIW

A79-25899 Effects of fuel properties on soot formation in turbine combustion D W Naegeli and C A Moses (U S Army, Fuels and Lubricants Research Laboratory, San Antonio, Tex.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781026. 11 p. 25 refs. Grant No DAAK70-78-C 0001, Contract No. N00140-77-C-1345

A combustor rig instrumented for measuring flame radiation, exhaust smoke, and gaseous emissions is used to study the sensitivity of combustor performance to the physical and chemical properties of fuels used in turbine combustion. These fuels include petroleum-base jet fuels, JP 5 syncrudes, water-fuel emulsions, and hybrid aromatic/methanol solutions. Examination of the effects of aromatic content, ring carbon content, and hydrogen-to-carbon (H/C) ratio on the flame radiation and exhaust smoke reveals that H/C ratio is the most effective indicator of soot formation. There is no observed effect of viscosity and end point on flame radiation and smoke. It is suggested that the mechanism for soot formation in the turbulent diffusion flame of a turbine combustor is due to gas-phase reactions and essentially independent of molecular structure. Water appears to play an important chemical role in soot reduction, probably as an additional source of hydrogen.

A79-25900 Shale oil - The answer to the jet fuel availability question L C Angello, A V Churchill, C L Delaney, and H R Lander (USAF, Aero Propulsion Laboratory, Wright-Patterson AFB, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov 27-30, 1978, Paper 781027 11 p

The Air Force began in 1974 a program to investigate the possibility of using alternative domestic liquid hydrocarbons, primarily shale oil, as sources for the standard jet fuel, JP-4, in order to ensure adequate fuel availability at an acceptable cost. The paper discusses the results of this program and its future goals. Results of processing studies on alternative hydrocarbon sources from shale oil are presented, it is found that shale oil processing resulted in specification turbine fuel when hydrotreated at 1500 psi, while coal liquids failed to meet specifications even when hydrotreated to 2200 psi. Fuel derived from shale oil was also found to be economically competitive under proper conditions. Results from shale oil-derived fuel combustion studies are presented, showing the effects of hydrogen and nitrogen content on combustor liner temperature, smoke and NOx emission. A projection of future specifications of Air Force aviation fuels is then presented.

A79-25901 Life Cycle Cost in advanced technology engine development F W Tegarden and W W Shoemaker (General Electric Co., Advanced Engineering and Technology Programs Dept., Cincinnati, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781029 13 p.

A computerized Life Cycle Cost (LCC) model to be applied at advanced technology stages of aircraft turbine engine development in order to characterize trade-offs between cost and performance is presented. The model employs parametric relationships between such

factors as cost, performance, weight, life and maintainability and includes considerations of airframes and missions. The data base contains cost, weight and performance data of a supersonic attack aircraft equipped with two advanced technology turbofan engines. Program modules for research, development, testing and evaluation, acquisition, and operation and support cost areas are described and flow charts for each module and for the entire model are presented. The model has been applied to six trade-off studies, treating component, maintenance, and flight time variations, and results are presented in terms of deviations from baseline costs.

A79-25902 Applying design-to-life cycle cost methods during engine advanced development J R Apel and D E Wiltse (Teledyne CAE, Toledo, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov 27-30, 1978, Paper 781030 10 p 6 refs

In order to make better decisions during advanced development of turbine engines, life cycle cost (LCC) methodologies must adequately reflect the impact of engine design decisions on the total system LCC. Two applications of Teledyne CAE's APSICOST Methodology are presented herein. These demonstrate the integrated nature of turbine engine LCC analyses with total aircraft system LCC. It is recommended that a joint airframe/propulsion/government effort be undertaken to standardize methods for reflecting aircraft system LCC impacts in turbine engine advanced development activities. (Author)

A79-25903 Turbine engine cost reduction using Life Cycle Cost techniques C E Curry, R V Earle, and G H Pedersen (General Motors Corp, Detroit Diesel Allison Div, Indianapolis, Ind.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif, Nov. 27-30, 1978, Paper 781031 9 p 8 refs Contract No F33657-77-C 0425

This paper describes the technical approach and development of methodologies used to conduct design trade studies from a Life Cycle Cost standpoint. A discussion of computer program capability is followed by a general discussion of several engine design trade studies. The potential for influencing engine design using a Life Cycle Cost methodology is emphasized. (Author)

A79-25904 Life cycle cost in preliminary engine design J Vernon (United Technologies Corp., Pratt and Whitney Aircraft Group, West Palm Beach, Fla.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781032, 7 p.

The life cycle cost (LCC) effects of the F100-PW 100 engine design life and duty cycle on the F 15 weapon system LCC are analyzed. The analysis reveals that (1) the preliminary design phase presents the first and most profitable opportunity to maximize the cost effectiveness of life-limited engine parts, (2) the weapon system life cycle and engine duty cycle must be accurately determined early in the engine design and continually updated in order to fully benefit from trade studies involving part life, cost, weight, and LCC, (3) the ratio of total engine operating hours to engine flight hours is far greater than generally thought, (4) small weight increases in life-limited parts often provide considerable LCC savings, (5) the trade between engine weight and manufacturing cost is a variable which depends on the actual part life and the engine life cycle, and (6) designing major parts for full engine life pays off in reduced weapon system LCC.

A79-25905 Trade-off studies with an interactive engine/airframe life-cycle-cost model D H Comey, D G Culy, and J E Cassidy (AiResearch Manufacturing Company of Arizona, Phoenix, Ariz., Rockwell International Corp., Pittsburgh, Pa) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781033 10 p

The purpose of this paper is to show the importance of interactive connections between the engine and airframe sections of an A79-25906 V/STOL aircraft engine and mechanical drive component integration S M Hudson and P E Beam, Jr (General Motors Corp , Detroit Diesel Allison Div , Detroit, Mich) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27-30, 1978, Paper 781038 15 p 7 refs

The paper addresses the general propulsion system requirements of V/STOL aircraft as they apply to mechanical drive components. These requirements have been defined in some of the recent and continuing multimission subsonic aircraft design efforts and the studies of high-performance aircraft. The mechanical drive components include gears, bearings, clutches, and shafting that interconnect the engines, lift and propulsion fans, and rotors in various V/STOL aircraft defined in recent system studies. The design and the current state of development of individual mechanical drive components may influence the aircraft design. Gearbox cases and structural requirements are also discussed, with special emphasis on organic composites for weight reduction, noise suppression and corrosion resistance improvement.

A79-25907 Advanced overrunning clutch technology J G Kish (United Technologies Corp., Sikorsky Aircraft Div., Stratford, Conn.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781039 15 p 7 refs Grant No DAAJ02-74-C-0028

This paper summarizes the results of a 3 year research program to advance the state-of-the-art in helicopter free-wheel units (over-running clutches) by permitting operation at 20,000 rpm By designing the free-wheel unit to operate at engine input speed instead of at the speed of the 2nd reduction where it is usually located, the torque, and hence size and weight of the unit, will be reduced High-speed designs, test results, and application of the designs to the UH-60A Black Hawk are presented for spring, sprag, and ramp roller types of overrunning clutches (Author)

A79-25908 Advanced technology applied to the CH-47D drive system S Binder and J C Mack (Boeing Vertol Co , Philadelphia, Pa) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27-30, 1978, Paper 781040 10 p 5 refs

The U.S. Army CH-47D helicopter modernization program incorporates improvements in all major subsystems. The drive train has been redesigned to incorporate evolutionary improvements which will increase reliability, survivability, and maintainability. This paper describes the background experience that led to the selection of VASCO X-2 high hot-hardness gear steel, it also discusses design improvements in the integration of components, in lubrication and diagnostic systems, in overrunning clutches, and in noise reduction New capabilities to predict and measure gear bending stresses and resonant frequencies have been developed and are described as part of a systems design approach.

(Author)

A79-25909 The Lynx transmission and Conformal gearing B A Shotter (Westland Helicopters, Ltd., Yeovil, Somerset, England) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov. 27-30, 1978, Paper 781041 9 p

A description of the Lynx transmission is linked with the basic factors which determined its general form. This gear system is compared with other alternatives and an improved Lynx system is also shown which gives even higher load capacity. Some of the character istics of the output stage Conformal gears are given, together with a description of a few of the development stages through which the gears have passed. (Author)

A79-25915 Use of radio controlled models in the conceptual development of V/STOL aircraft R W Kress (Grumman Aerospace Corp , Business Development Dept , Bethpage, N Y) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27-30, 1978, Paper 781050 15 p

The effectiveness of using radio controlled models in aircraft development programs is examined. The experience reviewed indicates that radio controlled models are statically correct for hover and provide a good indication of aircraft static stability and control. In the case of hover, they are dynamically dissimilar from a rotational point of view, however, in the initial stages of airplane design, most of the key issues pertaining to V/STOL concepts are static rather than dynamic issues. Also, the model response rates are much faster than full scale (roughly a 3 to 1 speedup). If flying with crude equipment proves possible, the chances of operating at full scale are probably excellent. Another important factor is that radio controlled models are inexpensive.

A79-25916 An unstable subsynchronous critical speed solution M Kershisnik (Sundstrand Corp., Rockford, III) and E Harding (General Dynamics Corp., Fort Worth, Tex.) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif., Nov 27-30, 1978, Paper 781055 8 p

The occurrence of shaft failures in the engine start system (ESS) of the F-16 aircraft is discussed, and the solution to the problem is presented. During the test stand testing of a two part high speed. shaft and gearbox of the ESS it was found that the shaft exhibited a first bending synchronous critical speed just below or in the lower portion of the operating speed range of the gearbox, and a reexcitation of the same critical speed at a frequency below the rational speed in the upper portion of the operating speed range. The subsynchronous re-excitation was attributed to the friction generated at the pilot/spline interfaces between the gearbox input shaft and the shaft coupled to it. Since the unstable critical occurs above the first bending critical speed, the input shaft and power takeoff shaft were redesigned to raise the first bending critical to at least 15% above the ESS operating speed range, with the results from such figuration showing an absence of any critical speed response in the operational AA

A79-25917 * Evaluation of the application of some gas chromatographic methods for the determination of properties of synthetic fuels A C Antoine (NASA, Lewis Research Center, Cleveland, Ohio) Society of Automotive Engineers, Aerospace Meeting, San Diego, Calif , Nov 27-30, 1978, Paper 45 p 6 refs

The purpose of the investigation was to evaluate the applicability, to some synthetic fuels, of some gas chromatographic methods now under development for use with petroleum based fuels. Thirtytwo jet and diesel fuel samples which were prepared from oil shale and coal syncrudes were examined. The boiling range distribution of each was determined by gas chromatography, and from that data distillation properties were calculated. The calculated results gave sufficient agreement with the measured values that the equations could be useable in their present form. Bulk fuel properties were calculated for the 16 JP 5 and Diesel No 2 type fuels. The results show that the equations would not give useable results. Capillary column gas chromatography was used to determine the n-alkane content of the eight JP-5 type samples and the results related to the observed freezing points. The results show that the concentrations of the long straight chain molecules in the fuels exert influence on the freezing point but are not the complete controlling factor (Author)

A79-26130 # Aircraft static charging testing J Taillet (ONERA, Châtillon-sous Bagneux, Hauts-de-Seine, France) (Conférence sur la Certification des Avions pour les Dangers dus a la Foudre et a l'Electricité Statique, Châtillon-sous-Bagneux, Hauts-de-Seine, France, Sept 11-13, 1978) ONERA, TP no 1978 110, 1978 11 p 9 refs Research supported by the Direction des Recherches, Etudes et Techniques de l'Air, and Avions Marcel Dassault-Brequet Aviation

Static charge accumulation on aircraft structures can produce three types of discharges sparks between conductors, streamers over insulating surfaces, and coronas at sharp points and edges. All these discharges induce radioelectric noise on navigation/communication equipment, thereby reducing equipment performance and impairing flight safety. The paper outlines the solutions proposed by ONERA to meet the requirements of safe protection. In order to apply the test technique rapidly and efficiently, specific instruments are designed and implemented at ONERA, which will be commercially available in the near future. A general description of their performance is given Finally, a practical application to real aircraft is described in some detail.

A79-26246 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem W S McCormick (Wright State University, Dayton, Ohio) IEEE Transactions on Electromagnetic Compatibility, vol EMC 21, Feb 1979, p 13-19 6 refs

One of the acknowledged lightning threats to aircraft is the induction threat in which a lightning-induced fuselage skin current inductively or capacitively flux couples through small dielectric 'holes' or apertures in the fuselage onto internal avionics cabling. In order to optimize the circuit protection, it is necessary to identify both the nature and location of the flux excitation. Using standard capacitor bank LTA testing, this paper advances a linear systemidentification technique, based on the impulse response, that will define both the nature and location of the dominant excitations. The technique is then successfully applied to the identification of the Yaw Damper Circuit of the USAF F-111.

A79-26354 # Visual simulation devices for flight training simulators (Imitatory vizual'noi obstanovki trenazherov letatel'nykh apparatov) V S Babenko Moscow, Izdatel'stvo Mashinostroenie, 1978 144 p 53 refs. In Russian

The basic theoretical principles behind the visual simulation of flight environments are elaborated. Detailed consideration is then given to the design and operation of three types of visual flight simulation systems systems which use optical memory devices, TV-based simulators, and simulators based on analog or digital image synthesis.

A79-26355 # Aerodynamics of flame jets (Aerodinamika fakela) L A Vulis and L P larin Leningrad, Izdatel'stvo Energiia, 1978 216 p 101 refs In Russian

The work elaborates an aerodynamic theory of turbulent gaseous flame jets and presents new data on the influence of various combustion-regime parameters on flame characteristics. A method for computing the characteristics of turbulent flame jets is outlined and applied to unmixed-gas flames and homogeneous flames. The use of low-frequency oscillations in order to intensify and control the combustion process in turbulent flame jets is examined.

A79-26400 * Elevated-temperature effects on strain gages on the YF-12A wing J M Jenkins, R A Field, and W J Sefic (NASA, Flight Research Center, Edwards, Calif) (Society for Experimental Stress Analysis, Spring Meeting, Wichita, Kan, May 14-18, 1978) Experimental Mechanics, vol 19, Mar 1979, p 81-86 12 refs

A general study is made of the effects of structural heating on calibrated-strain-gage load measurements on the wing of a supersonic airplane. The primary emphasis is on temperature-induced effects as they relate to slope changes and thermal shifts of the applied load/strain relationships. These effects are studied by using the YF-12A airplane, a structural computer model, and subsequent analyses. Such topics as the thermal environment of the structure, the variation of load paths at elevated temperature, the thermal response characteristics of load equations, elevated-temperature load measurement approaches, the thermal calibration of wings, and the correlation of strains are discussed. Ways are suggested to measure loads with calibrated strain gages in the supersonic environment. (Author)

A79-26487 Quasi-natural numerical methods for the computation of inviscid potential or rotational transonic flows J A Essers (Liege, Universite, Liège, Belgium) Applied Mathematical Modelling, vol 3, Feb 1979, p 55-66 21 refs

A new fast time-dependent method for the computation of inviscid potential or rotational transonic flows is described. The method is significantly faster than the classical time-dependent techniques, and is constructed in order to be especially very efficient at transonic and at low speed flow regimes. It is applied to the computation of the transonic flow in a nozzle with small throat radius of curvature. The results compare favourably with those of other computations and with experimental measurements. (Author)

A79-26498 # A simulator study of aircraft ground-run handling in the Fosim Research Simulator - Some results and experiences S Luthander (LUTAB, Bromma, Sweden) In Extending the scope of flight simulation, Proceedings of the Fourth Symposium, London, England, April 19, 1978 Symposium sponsored by the Royal Aeronautical Society London, Royal Aeronautical Society, 1978 13 p

In the study described, an aircraft during ground run is treated as a road vehicle, and two-wheel analysis models with two degrees of freedom (side deviation and yaw angle) are employed. Since the handling qualities during ground run depend on the vehicle's dynamic parameters, the relationship between the dynamic parameters and pilots ratings are studied in the simulation program, using the equations of motion of each of the degrees of freedom, written in a frequency response form. The results of the simulation, concerning response problems and phase problems are plotted and discussed.

A79-26527 F-16 high angle of attack testing P F Oestricher (General Dynamics Corp., St Louis, Mo.) and R C Ettinger (USAF, Flight Test Center, Edwards AFB, Calif.) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27.30, 1978.) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 1-10.

The paper discusses some of the design features of the F 16 that give it some unusual high angle-of-attack handling features. The F-16, in order to avoid large trim drag and maneuvering penalties, is balanced such that the static margin is negative subsonically and only mildly positive in supersonic flight. The deep stall capability is the result of this relaxed longitudinal stability concept. Angle-of-attack and structural limiting provide excellent protection up to reasonable airspeeds for symmetric maneuvers. Full time aileron rudder interconnect enables rapid rolls with flaperon about the velocity vector at all reasonable airspeeds. Pitch-roll coupling susceptibility was countered by the roll-rate limiter. The yaw rate limiter essentially prevents erect spins. The pilot rudder command limiter results in no roll-coupled departures during rudder only or rudder-assisted flaperon rolls.

A79-26529 F-18 status report J E Krings (McDonnell Douglas Corp., St Louis, Mo.) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27-30, 1978.) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 21-25

The F-18 program employs a new concept in which a team of experimental test pilots under a team leader is active throughout the design stages of an airplane. The F-18 design has been dominated by simulation, which has been the key to obtaining effective and efficient design. At each plateau in the simulator design, Navy and Marine personnel were invited to evaluate the design and check that the design was heading in the right direction. One of the many simulators is dedicated primarily to the first flight configuration.

PTH

A79-26530 Flight testing the Kfir Y Peer (Israel Air Force, Tel Aviv. Israel) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif, Sept 27-30, 1978) Society

of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 26-37

The Kfir is the result of replacing the Atar-9C engine of the Mirage with the J-79 engine and incorporating a canard configuration on the Mirage. The autocommand is a 100% authority, electrical, fly-by-wire flight control system operating on the pitch axis of the aircraft alone. It is a closed-loop control augmentation system with pilot stick force as input. During initial testing, pilots found the low-speed flight uncomfortable as it demanded a positive stick push to lower the angle of attack (AOA) instead of natural stick relaxation. The problem was solved by AOA feedback achieved by causing the control stick to trim forward in proportion to the increase in AOA. A reduction in stick force per g without affecting loop stability was also accomplished. Flight testing concentrated on air-to-air tracking. The optimum parameter setting showed a definite advantage of pre-filter lead and the normal acceleration feedback filter.

A79-26531 Small fan-jet engines I E Speer (Garrett Corp , Los Angeles, Calif) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif , Sept 27-30, 1978) Society of Experimental Test Pilots, Technical Review, vol 14, no 2, 1979, p 43-51

The article reviews some of the thinking that went into choosing the cycle and sizing of the TFE731 engine and to evaluate some of the characteristics in light of what is now developing as a second generation of small fan-powered business aircraft. The optimum long range cruise design point of the TFE731 was found to be at 40.000 ft at Mach 0 7 with a bypass ratio between 2 5 1 and 3 5 1. The first application of the TFE371 was for aircraft sized to a CJ610 turbojet, so the fan was sized at a thrust somewhat higher than the jet. At the optimum cruise point the specific fuel consumption is about 68% of that of the jet. The trend in business jets is toward higher altitude envelopes The design point for 40,000 ft extended to 50,000 ft is also relatively optimal, so no major design cycle change appears necessary for second-generation fans. Reynolds number and engine drag effects would seem to dictate medium bypass ratio. The lapse ratio with ambient temperature for a fan may limit performance, although at temperate latitudes no problem should be present at 50,000 ft

A79-26532 The Learjet Longhorn series - The first jets with winglets N A Armstrong (Cincinnati, University, Cincinnati, Ohio) and P T Reynolds (Gates Learjet Corp., Wichita, Kan) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27-30, 1978) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 57-66

The Gates Learjet Model 28 is similar to the Model 25 except for the addition of six-foot wing extensions and the winglets and the removal of the tip tanks Model 29 has the same aerodynamic configuration as Model 28, but has a larger fuselage fuel tank Cruise fuel flow reductions result from several factors (1) the aircraft can operate at higher altitudes due to added wing area, (2) for some payload and range the takeoff weight is lower because less mission fuel is needed, and (3) drag is reduced by removing the tip tanks, increasing the aspect ratio, and adding the winglets Some of the aerodynamic reasons for the effects of the winglets are briefly discussed. An overall stabilizing effect of the winglets at about 6-8 deg sideslip is due to winglet stall.

A79-26533 Airline approach to CAT III J E Ellington (Delta Air Lines, Inc., Atlanta, Ga.) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27-30, 1978.) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 79-109

It is stated that the way to approach CAT III operation is to present it to the line pilot in such a way that he will begin to build confidence that continues to build until he is ready and has a strong desire to execute an approach to the lower visibility minimums. With this in mind, an outline of a CAT III training program is presented. Training starts in the ground school phase, after which the pilot

proceeds to the simulator phase and then to actual aircraft training

A79-26534 * Flying NASA's Terminal Configured Vehicle against the Microwave Landing System L H Person, Jr and K R Yenni (NASA, Langley Research Center, Hampton, Va) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif, Sept 27-30, 1978) Society of Experimental Test Pilots, Technical Review, vol 14, no 2, 1979, p 110-123

A prototype Boeing 737 aircraft has been received for use in the Terminal Configured Vehicle (TCV) Program, the aim of which is to develop technology for advanced airborne systems and flight procedures to improve terminal area operations in the future ATC environment. The paper discusses the TCV aircraft, its integrated digital electronic displays and flight controls, and the means by which the pilot interfaces with the aircraft to fly precise curved descending approaches under MLS guidance.

PTH

A79-26535 Development of the L-1011 Flight Management System D A Moor (Lockheed Aircraft Corp., Burbank, Calif.) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27-30, 1978.) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 124-134

The paper discusses the development of the L 1011 Flight Management System, a fully automatic navigation and performance system coupled to existing L-1011 autopilot and autothrottles. The system provides a means for automatic, precise control of airplane speeds and engine thrust during climb, cruise, and descent. The steps taken to achieve the design goals and their modifications in order to ensure control stability are briefly described. The FLM provides full-time performance management in areas of near neutral speed-thrust stability, reducing crew workload, and offering a large potential for fuel savings.

A79-26536 The continuity factor in aircraft development A M Johnston (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif, Sept 27-30, 1978) Society of Experimental Test Pilots, Technical Review, vol 14, no 2, 1979, p 135-145

Some of the milestones in the development of the jet aircraft are noted. Mention is made of the Bell XP-59 (1945), the Bell L-39 (1945), the rocket-powered XS-1 (1946), the XB-47 and YB-47, the B-52, the 'dash 80', and the 727 and 737. The significant technical advances incorporated by these aircraft are identified. The discussion is oriented to bring to light the 'continuity factor', that is, the sequential application of tested and desirable technologies. PTH

A79-26537 The U-2 story K W Weir (Lockheed Aircraft Corp., Burbank, Calif.) (Society of Experimental Test Pilots, Symposium, 22nd, Beverly Hills, Calif., Sept. 27-30, 1978.) Society of Experimental Test Pilots, Technical Review, vol. 14, no. 2, 1979, p. 186-192

The paper gives an account of the development of the U-2 aircraft for reconnaissance missions. Basically, the U-2 began as an F-104 with high-aspect ratio wings attached and equipped with a nonafterburning P & W J-57 engine. The flight control system is a conventional unboosted system using a yoke rather than a stick. Some of the demanding and delicate operations at high-altitude high-speed flights are briefly described. Modifications of the recent U 2R are mentioned.

A79-26544 * # Turbulence characteristics in the near wake of a compressor rotor blade B Lakshminarayana and B Reynolds (Pennsylvania State University, University Park, Pa) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 17th, New Orleans, La, Jan 15-17, 1979, Paper 79-0280 13 p 13 refs Grant No NsG-3012

This paper is concerned with the turbulence properties in the near wake of a rotating compressor blade. The variation of the axial,

tangential and radial intensities as well as stresses across the wake and its decay characteristics were measured with a triaxial hot wire probe rotating with the rotor downstream of an axial flow compressor. The turbulence intensities decay very rapidly in the near wake region. The radial component of intensity is found to be higher than the tangential and axial components. This is a consequence of the effect of rotation on the turbulence structure. A qualitative analysis is carried out to predict the effect of rotation on the turbulence structure. These are in general agreement with the measured data.

(Author)

A79-26545 * # Unsteady pressures on a NACA 64A010 airfoil - Experimental and theoretical results J A Davis and S L Petrie (Ohio State University, Columbus, Ohio) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 17th, New Orleans, La, Jan 15-17, 1979, Paper 79-0330 11 p 13 refs Grants No AF-AFOSR-76-3021, No NsG 2298

Transonic testing of an NACA 64A010 airfoil at the Ohio State University Aero-Astro Research Laboratory is described, and results of fixed angle of attack and pitch oscillation experiments are discussed. The operating range was Mach 0.20 to 1.07 with available total pressures of 140,000 N/m2 to 620,000 N/m2. The airful model was mounted on roller bearings installed in the solid sidewalls of the tunnel test section. The equipment included transducers to measure unsteady pressures, and static pressure taps obtaining steady-state data The data gathered at Mach 0.8 gave an indication of the influence of the natural shock instability and shock-induced flow separation on the unsteady pressures, with the location of the peak disturbance level shifting forward in the comparison of 0 to 2 deg pitch angle data. The oscillating airfoil data is examined in terms of harmonic content and the in-phase and out-of phase components. It is concluded that the experimental data has good qualitative comparison with methods accounting for shock interaction

A79-26546 * Effect of a chromum-containing fuel additive on hot corrosion C E Lowell and D L Deadmore (NASA, Lewis Research Center, Cleveland, Ohio) Corrosion Science, vol 18, 1978, p 747-749, 751-759, 761-763-8 refs

Four cast superalloys (one cobalt-base and three nickel-base) were tested at 900 C for 100 h in Mach 0.3 combustion gases. 5 ppm of synthetic sea salt were added to the gases in the combustion chamber. Several types of thermal cycle and washing procedures were employed. Similar tests were made with the addition of 300 ppm of a chromium-containing fuel additive. In both sets of tests the extent of hot corrosion was evaluated by specific weight change and metal recession. In general, the chromium additive in the fuel reduced the extent of hot (salt) corrosion but did not eliminate it The percentage reduction of hot corrosion attack was similar for all four alloys. As great a reduction of hot corrosion was achieved by reducing the number of thermal cycles during the test from 100 to 5 or 6 The effect of washing the alloys every ten cycles as opposed to the end of the test was erratic, some alloys were attacked slightly more, others somewhat less A NiCrAlY coating was found to be more effective in reducing hot corrosion than either the fuel additive or the washing schedule

A79-26592 The application of computer aided techniques to project design D Howe (Cranfield Institute of Technology, Cranfield, Beds, England) Aeronautical Journal, vol 83, Jan 1979, p 16-21

The paper discusses the application of computer aided techniques in aircraft design to the project design phase, in which the detailed specifications are interpreted to define the component parts of the system and the aircraft configuration is established. Various aspects of project design are considered and it is noted that the process depends heavily on the availability of large amounts of statistical data and allows for the application of numerical analysis. Possible design areas in which to employ computers are discussed, including weight, drag and stability and control modules and the optimization of multiple dependent parameters. The use of com-

puters is limited by the validity of the initial data, the size of the program and the lack of flexibility in baseline design, however interactive techniques can overcome many of these limitations. Computer programs presently in use in project design include engineering technologies, design analysis and configuration packages, as parts of larger computerized design systems.

A L W

A79-26593 Theoretical lower limits of forebody drag T Morel (GM Research Laboratories, Warren, Mich) Aeronautical Journal, vol. 83, Jan. 1979, p. 23-27. 5 refs

The lower limits to which forebody pressure drag may theoretically be reduced by the elimination of flow separation are considered. The analysis treats a potential incompressible flow about a body which is symmetrical about its centerline and has fore-and-aft symmetry, and is placed in the center of a constant area duct. It is found that for semi-infinite bodies with constant cross-sectional area, the pressure drag coefficient is zero, as demonstrated by Prandtl and Tietjens (1934), while for shorter bodies with variable area the pressure drag coefficient must be less than zero. Approximate integral analysis is used to calculate the pressure drag coefficient for given velocity profiles and results suggest that a proportionality may be expected between the forebody drag and the dimensionless potential flow velocity overshoot at the body surface in the plane of fore-and aft symmetry. These results tend to be supported in a comparison with exact solutions for Rankine bodies ALW

A79-26594 The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A C McIntosh (Cranfield Institute of Technology, Cranfield, Beds, England) and J Pike (Royal Aircraft Establishment, Bedford, England) Aeronautical Journal, vol. 83, Jan. 1979, p. 28-31

In order to improve the flow angle and Mach number distribution in a flexible-plate supersonic wind tunnel, a method has been proposed in which the wind tunnel liner is caused to make small displacements by the movement of the jacks supporting it. Methods employing a single jack movement to measure the Mach number disturbance to the flow caused by the liner displacement have been found to cause extensive rippling to the liner, making it difficult to obtain accurate measurements of the direct effect of the displacement on the flow. The 1-4-1 system of movements of three adjacent jacks, which overcomes these difficulties, is presented. The 1-4-1 system consists of moving the jacks on either side of a central jack through a quarter of the movement executed by the central jack, leading to a situation in which the portion of the liner two jacks removed from the central jack undergoes no deflection. Experiments have shown that the 1-4-1 system causes a lesser Mach disturbance than a single jack movement, thus making the disturbance easier to ALW

A79-26597 * # Laser aircraft A Hertzberg, K Sun (Washington, University, Seattle, Wash), and W S Jones (Lockheed Research Laboratories, Palo Alto, Calif) Astronautics and Aeronautics, vol 17, Mar 1979, p 41-49 22 refs Grant No NGL 49-002-044

The concept of a laser-powered aircraft is discussed. Laser flight would be completely compatible with existing airports and air-traffic control, with the airplane using kerosene only power, up to a cruising altitude of 9 km where the laser satellite would lock on and beam laser energy to it. Two major components make up the laser turbofan, a heat exchanger for converting laser radiation into thermal energy, and conventional turbomachinery. The laser power satellite would put out 42 Mw using a solar powered thermal engine to generate electrical power for the closed-cycle supersonic electric discharge CO laser, whose radiators, heat exchangers, supersonic diffuser, and ducting will amount to 85% of the total subsystem mass Relay satellites will be used to intercept the beam from the laser satellite, correct outgoing beam aberrations, and direct the beam to the next target. A 300-airplane fleet with transcontinental range is projected to save enough kerosene to equal the energy content of the entire system, including power and relay satellites, in one vear ΑА

A79-26598 # Laser propulsion R F Weiss, A N Pirri, and N H Kemp (Physical Sciences, Inc., Woburn, Mass.) Astronautics and Aeronautics, vol. 17, Mar. 1979, p. 50-58, 30 refs

Progress in laser-propulsion component technology is discussed, together with an assessment of future expectations. The thruster design concepts are described, considering the continuous wave (CW) laser-powered devices relying on an aerodynamic window to introduce a steady laser beam into the 'combustion' chamber, and the repetitively pulsed (RP) laser-powered devices whose unsteady gasdynamics allow windowless operation CW- and RP rocket engines are described, noting that in both cases a considerable amount of research and systems analysis remains to be performed before optimum prototype designs can be specified. Investigations concern ing laser propulsion for drag make up, orbit and plane changes, as well as interplanetary missions are taken into account, as is a study of four generic systems for transporting payloads from LEO to GEO It is concluded that the solar power satellite and laser propulsion are expected to depend upon each other for full maximum exploitation and cost-effectiveness

A79-26626 Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5-7, 1979, Technical Papers Conference sponsored by the American Institute of Aeronautics and Astronautics New York, American Institute of Aeronautics and Astronautics, Inc , 1979 380 p Members, \$35 , nonmembers, \$45

A foam impact attenuation system is considered along with simulation studies of the flight dynamics of gliding parachute systems, the practical aspects of reefing cutter design, balloon concepts for scientific investigation of Mars and Jupiter, the development and testing of a shipboard launched balloon system, the propagation of stress/strain pulses in woven textiles, biaxial stress measurements on cloth samples and bias constructed parachute models, and a fabrication and quality assurance procedure to assure a symmetrical lifting parachute. Attention is also given to the mechanical properties of polyethlene balloon films and forming conditions of their tubular film process, and experimental technique for data acquisition from parachutes in flight, the determination of meaningful performance parameters from bench tests of barometric staging units, and data management in the decelerator industry.

A79-26627 # Foam Impact Attenuation System S R Mehaffie (USAF, Flight Dynamics Laboratory, Wright Patterson AFB, Ohio) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 1-10 8 refs (AIAA 79 0416)

A ground impact attenuation system for aerospace vehicles based on foamed-in-place polyurethane foam has been developed. The concept was reduced to practice and developed to the prototype stage during a three year, in house, Air Force investigation beginning in 1975. A series of 91 full scale tests of the FIAS (Foam Impact Attenuation System) against the requirements of the AQM 34V remotely piloted vehicle demonstrated the systems's performance with a 60-sec operating time. Subsequent work has produced a foam dispensing system capable of achieving a FIAS deployment time of 5 sec. Spinoffs from this program have created new concepts in deployable composite structures.

A79-26628 # Simulation studies of the flight dynamics of gliding parachute systems. T F Goodrick (US Army, Natick Research and Development Command, Natick, Mass.) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 57, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 11-16. (AIAA 79-0417)

A six-degree of freedom flight simulation program is described which models the flight dynamics of a gliding airdrop system utilizing gliding canopies such as the Parafoil. The program allows study of response to manual and automatic control inputs utilizing flexible output formats. Examples are given of program applications.

for analysis of dynamic stability and two types of turn control for the Parafoil (Author)

A79-26631 # Development and testing of a shipboard launched balloon system K L TeKrony (Raven Industries, Inc., Sioux Falls, S Dak.) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5.7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 38.44 (AIAA 79-0420)

A balloon system has been developed and tested which permits inflation and launch in winds up to 45 knots within the limited confines on board Navy ships. The system consists of a launch platform and balloon system. The launch platform provides orientation and constraint for the balloon system during inflation and until launch. The balloon system consists of tandem balloons, flight sequencing devices, a 15 pound payload and associated containers. The tandem balloons consist of a smaller reinforced tow balloon and a main balloon which is protected within the packing container until shortly after launch. After in-flight deployment, the main balloon inflates during ascent through a transfer fitting located between the two balloons.

A79-26635 # Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause G S Gokhale (Tata Institute of Fundamental Research, Bombay, India), R T Redkar, M N Joshi, S Sreenivasan, and J V S Rao (Tata Institute of Fundamental Research, Hyderabad, India) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex. March 5-7, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 69-75. (AIAA 79-0426)

On the basis of detailed analysis of cap lengths of balloons flown from high latitudes, design specifications are drawn for gore length to be covered with cap material, sufficient to cover the inflated portion of the balloon, while it is passing through the critical tropopause region for zero-circumferential stress, zero-superpressure and flat top design balloon and for the conditions prevailing in the equatorial tropopause Reference is made to the capped balloons flown from Balloon-Facility in India (17.5 deg N, 78.6 deg E) which had inadequate gore lengths covered with caps and which had considerably high rate of tropopause failures. Reference is also made to the Brazilian Campaign (23 deg S) conducted by the French Group, wherein 100% success was obtained with capped balloons, which had appropriate gore lengths covered with cap be balloons, which had appropriate gore lengths covered with cap be balloons, which had appropriate gore lengths covered with cap be balloons.

A79-26636 # Fabrication and quality assurance procedure to assure a symmetrical lifting parachute R E Rychnovsky (Sandia Laboratories, Livermore, Calif) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc, 1979, p 76-79 Contract No AT(29-1)-789 (AIAA 79-0427)

For lifting parachutes used to deliver payloads at high velocities, parachute symmetry is very important. The forces generated by the high-velocity delivery create unacceptably high roll moments unless the parachute is very symmetrical. Because these strict symmetry requirements were new to the parachute industry, fabrication and quality assurance procedures had to be developed. Five 13 foot lifting parachutes were fabricated using the new procedures the first two had major discrepancies and the final three had minor discrepancies. The rolling moments of these parachutes, which were lower than the moments of lifting parachutes that had been fabricated without these controls, met the roll moment requirements for the lifting parachute system being developed. The procedures developed could also be used for conventional ribbon parachutes to increase the speed and accuracy of fabrication. (Author)

A79-26638 # Design criteria for and development of Kevlar ribbon parachutes W R Pinnell (USAF, Flight Dynamics Labora

tory, Wright Patterson AFB, Ohio) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 89-99 5 refs. (AIAA 79-0430)

A test effort to validate criteria and to establish performance parameters for conical ribbon parachutes fabricated from textile materials based on the DuPont para aramid fiber marketed as Keylar-29 is reported. Criteria for selection of material strength for major parachute components are discussed relative to test results Effects of reefing on drag area and opening shock factors are experimentally developed and compared to similar data for nylon parachutes A two-stage reefing system was demonstrated and drag area (sq ft) values for various reefing ratios were established. All test items were 15.3 ft nominal diameter 20 degree conical continuous ribbon parachutes. Data gathered during 18 drop tests from F 4 aircraft and 13 tests utilizing a rocket powered sled are presented and these two test methods are compared. Test Mach numbers ranged from 21 to 98 at the test item line stretch condition Drop test altitudes ranged from 5300 to 41,400 ft MSL and sled data were collected at an altitude of 4070 ft. Maximum opening forces as high as 29,000 lb were recorded (Author)

A79-26641 # Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute W B Pepper, Jr (Sandia Laboratories, Albuquerque, N Mex) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 119-126 5 refs Research supported by the US Department of Energy (AIAA 79-0433)

A total of 70 tests, including static, rocket sled-launched, rocket-boosted and aircraft drops, have been used to develop the 24-ft-diameter hybrid Kevlar-29/nylon ribbon parachute for recovery of the 765-lb store. The parachute has been deployed successfully over the environmental temperature range of -65 F to +160 F and has operated successfully over the design range of deployment speeds from 330 KCAS to Mach 1.2 at sea level.

A79-26649 # The influence of ballonet motions on the longitudinal stability of tethered aerostats J Delaurier (Toronto, University, Toronto, Canada) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 174-182, 12 refs Research supported by the National Research Council of Canada (AIAA 79-0445)

To date, tethered-aerostat stability analyses have assumed the ballonet air to be 'frozen' with respect to the rest of the aerostat Also, it was assumed that the least stable, and hence most important, longitudinal mode of motion was the first mode, where the cable's and aerostat's motions are so coupled as to approximate an 'upsidedown pendulum' The present analysis shows that when motion of the internal air and gas is allowed, a third mode appears whose stability may be equal to, or less than, that of the first mode, for current aerostat designs. The degree of the third-mode's stability is primarily controlled by the ballonet's fore-and-aft constraint and damping, current design practices applied to larger and higher altitude aerostats could give rise to systems with serious stability problems at lower altitudes. However, this investigation also shows that moderate increases in constraint and damping, which should be achievable by ballonet redesign, would strongly stabilize the third mode (Author)

A79-26650 # Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements M W Higgins (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York,

American Institute of Aeronautics and Astronautics, Inc., 1979, p. 183-191 (AIAA 79-0446)

An analytical technique designed to assist a recovery system designer in arriving at a reasonable recovery system design is presented, discussed and applied to two problems commonly faced by designers. The technique allows a designer to arrive at an initial recovery system design given the initial and final dynamic pressures, the total weight, the parachute opening shock factor and the maximum allowable design limit load. The technique currently assumes a subsonic, vertically descending payload being decellerated by a fast inflating parachute. Potential means of reducing or eliminating the effects of these assumptions will be discussed.

(Author)

A79-26651 # A simple physical model of a descending parachute D J Cockrell and J A Eaton (Leicester, University, Leicester, England) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc, 1979, p 192-194, 375 5 refs Research supported by the Ministry of Defence (AIAA 79 0447)

Appreciation of the ways in which variation of parachute geometric parameters, such as rigging line length and canopy porosity, can affect descent performance is limited because of the complexity of the necessary predictive computer models. In this paper a simple physical model, to supplement rather than to supplant existing complex models, is developed. The model is constructed diagrammatically, establishing the linear second-order simultaneous equations which describe the longitudinal oscillations. Some consideration is given to motion about the axis of symmetry Conclusions are drawn about effects which various geometric parameters have on the dynamics of the system and comparisons are drawn between responses from this and from more sophisticated models.

(Author)

A79-26652 # Flight simulation of a vehicle with a two stage parachute system P R Schatzle and W H Curry (Sandia Labora tories, Albuquerque, N Mex.) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5.7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 195.203.7 refs. Research supported by the U.S. Department of Energy (AIAA 79-0448)

A quick response, 9-DOF (degree-of-freedom) hybrid computer code has been developed to simulate the flight of an aircraft delivered, parachute retarded vehicle. The mathematical model and its implementation are discussed. The particular case of a vehicle with a first stage. Lifting parachute and second-stage descent parachute is investigated. Results compare well with those obtained from an existing 12-DOF digital code and from full-scale flight test. (Author)

A79-26653 # Parachute inflation control using an attached apex drogue B W Roberts (Sydney, University, Sydney, Australia) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 57, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 204-210. 7 refs. (AIAA 79-0449)

The inflation time of a given parachute can be increased by the use of skirt hesitators, reefing lines, apex stretch fabric or similar techniques. On the other hand the inflation time can be reduced by the use of pocket bands or central rigging lines. Yet little use has been made of a drogue attached to the apex in order to increase the inflation time. This drogue increases the rigging line tension during the early stages of the inflation and thereby increases the inflation time. It also reduces the fabric loading by an order of magnitude. The technique has been studied in depth using computer procedures, while rocket sled tests show some interesting flight trends. (Author)

A79-26654 # A first-order theory for the effects of line ties on parachute deployment K E French (Lockheed Missiles and

Space Co, Inc, Sunnyvale, Calif) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 211 214 (AIAA 79-0450)

Line ties temporarily restrain a fold or folds of a parachute until deployment. The use of ties extends the time required for deployment and reduces the relative velocity between the chute and its attached forebody prior to line stretch. This paper develops a first-order theory for calculation of the effects of line ties on chute deployment time and relative velocity. Solutions are presented graphically in terms of the dimensionless parameters of the problem for a pilot-extracted-and deployed parachute for the case of fore body velocity constant during deployment. Solutions are also given for the case of forebody acceleration constant during deployment. The problem of incorporating tie test data into parachute system design is briefly discussed. (Author)

A79-26655 # Parachute partial inversions R B Calkins (USAF, Aeronautical Systems Div , Wright-Patterson AFB, Ohio) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5-7, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 215-219. (AIAA 79-0451)

Parachute inversions have long been a problem with some types of parachute. The present paper deals with the causes, misconceptions, symptoms, and cures of inversion. A discussion of motion-picture studies of partial inversion provides some insight into the phenomenon and its causes. This knowledge could lead to potential solutions and to better parachute designs.

A79-26659 # A new life saving application for the parachute E D Vickery (Sky Sports, Inc., Ellington, Conn.) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5.7, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 245-249 (AIAA 79-0456)

In the past few years the rapid growth of the hang-gliding sport, accompanied by equally rapid improvements in glider performance and pilot skills, has created a need for a parachute back-up system. The paper outlines a brief history of hang gliding, categories of accidents, parachute requirements, problems relative to the glider configuration which require solutions, parachute configurations and attachment systems to prevent fatalities, and usage of the parachute as a life-saving device. It is concluded that the parachute has proven to be an efficient lifesaver in the new aviation application.

A79-26660 # Factors and tradeoffs affecting ram-air parachutes designed for civilian personnel applications M W Higgins (USAF, Life Support Systems Program Office, Wright Patterson AFB, Ohio) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 250-260 7 refs (AIAA 79-0457)

A brief outline is presented of the sport parachute market size and composition over the period 1971-1978 which is marked by the large scale introduction to and utilization of ram air parachutes. Then the study identifies the major parachute performance requirements of each competitive event, and determines the areas where ram-air parachutes appear to meet the performance requirements. Attention is given to identifying some of the ram air parachute design factors and subsystems that affect the performance requirements, with particular reference to weight and volume, deployment, inflation, glide, and handling characteristics. The discussion presented provides the user with some background information on the development and performance of the ram-air parachute.

A79-26661 # Commercial parachutes J D Reuter (Pioneer Parachute Co , Manchester, Conn) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex , March 5 7, 1979, Technical Papers New York, American

Institute of Aeronautics and Astronautics, Inc., 1979, p. 261-268 (AIAA 79-0458)

This paper discusses certain aspects of commercial emergency parachutes and hardware. Current technology and existing regulations would permit the manufacture of emergency parachutes as small as 19 feet in diameter, but opening shock forces must be attenuated. Inverted inflation is the most common cause of emergency parachute malfunctions. A significant reduction in this type of anomaly is possible by use of a simple skirt-wrap arrangement. A light-weight commercial separable riser link is found to have adequate structural margins if properly installed and tightened.

(Author)

A79-26662 # Longitudinal oscillation damping for fully-inflated parachute canopies D J Cockrell, J A Eaton (Leicester, University, Leicester, England), and C J Morgan In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 269-273 Research supported by the Ministry of Defence (AIAA 79-0459)

Two factors contributing to the damping of a parachute's oscillations are considered, the first dependent on the moment of the aerodynamic force developed on the canopy about the system's body axes origin, the second on the additional drag which results from the variation in linear velocity over the canopy caused by the angular velocity of oscillation. This second contribution is shown to be of the same order of size as the former. An estimate of its size is made, experimental techniques for its measurement described and suggestions made as to how it may be incorporated into parachute descent performance computer models. (Author)

A79-26663 # The validity of the Leicester computer model for a parachute with fully-deployed canopy J A Eaton and D J Cockrell (Leicester, University, Leicester, England) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex, March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc, 1979, p 274-279 15 refs Research supported by the Ministry of Defence (AIAA 79-0460)

Measures taken to validate a computer model of a parachute with fully deployed canopy are described. By a sensitivity analysis parameters, which affect stability are identified. Drop tests of prototype and large-scale models under wind-free conditions, devised to provide flight data for comparison with predictions, are outlined along with a description of the instrumentation. Ways in which information is obtained on inertial effects, instantaneous local angles of attack and on the relevance of data derived from wind-tunnel tests on rigid-canopy models are considered. Included is a note on the effect of Reynolds number on the oscillatory motion of parachutes.

(Author)

A79-26671 # Hardware options for gliding airdrop guidance systems. T F Goodrick (U.S. Army, Natick Research and Development Command, Natick, Mass.) In Aerodynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5-7, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 345-350 7 refs. (AIAA 79-0471)

Two aerospace electronics firms were asked to survey the market for components suited to the requirements for guiding cargo airdrop systems utilizing high-performance gliding canopies. Systems which can be produced in modules to achieve the full range of performance from radial homing to full state guidance are identified and described along with systems capable of other partial state guidance schemes in addition to radial homing and which provide full state data with the addition of separate range measurement components. Thus the availability of components that can be integrated into suitable guidance systems is demonstrated.

A79-26673 # Development and initial test results of parachutes with automatic inflation modulation /AIM/ D 8 Webb (Irvin Industries Canada, Ltd., Fort Erie, Ontario, Canada) In Aero dynamic Decelerator and Balloon Technology Conference, 6th, Houston, Tex., March 5-7, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 363-374 5 refs. (AIAA 79 0467)

The paper discusses the development program required to investigate new canopy control methods and to eventually produce a final improved personnel canopy. This development program is referred to as the automatic inflation modulation (AIM) concept. It is shown that fast, controlled, and consistent opening of the canopies can be achieved with the Webb chute device. Significant load alleviation and square wave type force/time traces are obtained at high deployment speeds with the use of a unidirection stretch fabric Variable automatic reefing of the canopy and consequent longer development times can be obtained with the pull-down vent-line option of the Webb chute device.

A79-26725

Air fleet and facility planning via optimal control models V V S Sarma (Indian Institute of Science, Bangalore, India) and K Ramchand (Central Servicing Development Organization, Kanpur, India) IEEE Transactions on Systems, Man, and Cybernetics, vol SMC-9, Mar 1979, p 131-142 15 refs

A study is presented which is aimed at developing techniques suitable for effective planning and efficient operation of fleets of aircraft typical of the air force of a developing country. An important aspect of fleet management, the problem of resource allocation for achieving prescribed operational effectiveness of the fleet, is considered. For analysis purposes, it is assumed that the planes operate in a single flying-base repair-depot environment. The perennial problem of resource allocation for fleet and facility buildup that faces planners is modeled and solved as an optimal control problem. These models contain two 'policy' variables representing investments in aircraft and repair facilities. The feasibility of decentralized control is explored by assuming the two policy variables are under the control of two independent decisionmakers guided by different and not often well coordinated objectives.

LAuthor

A79-26753 Digital target extraction at civil air traffic control radar installations in the Federal Republic of Germany and possibilities for its further development from the point of view of the Federal Institute of ATC (Die digitale Zielextraktion an zivilen Flugsicherungsradaranlagen in der BRD und Moglichkeiten für ihre Weiterentwicklung aus der Sicht der BFS) B Cloos (Bundesanstalt für Flugsicherung, Frankfurt am Main, West Germany) in Symposium on Radar Technology, 3rd, Hamburg, West Germany, September 14-16, 1977, Reports

Dusseldorf, Bucherei der Ortung und Navigation, 1978, p. 25, 27-37, 39-46. In German

The digital target extractor of the German Federal Institute of ATC constitutes an evaluation system for primary and secondary radar video signals which has the function to recognize real and suppress false targets. The target data are processed and compressed in preparation for a narrow-band data transfer and an automatic evaluation of the data as a basis for the display of the air traffic conditions. The radar data of 10 digital target extractors are currently used in four control centers of the Federal Institute of ATC and in two EUROCONTROL centers. Most control centers use purely synthetic displays. Certain problems regarding the operation of the digital target extractors are discussed together with possible improvements.

A79-26754 New approaches concerning the implementation of radar target extractors with the aid of very fast microprogrammable data processors (Neue Wege der Realisierung von Radarzielextraktoren mit Hilfe von sehr schnellen mikroprogrammierbaren Datenprozessoren) W Luschnitz (Telefunken AG, Ulm, West Germany) In Symposium on Radar Technology, 3rd, Hamburg, West Germany, September 14-16, 1977, Reports Dusseldorf, Bucherei der Ortung und Navigation, 1978, p 47, 49-69 In German

An employment of microprocessors for target-extraction applications appears desirable in connection with a number of advantages related to their use. These advantages include an establishment of standard hardware items, the achievement of flexibility on the basis of programming, improved maintenance characteristics, and improvements regarding the storage requirements for spare parts. However, the operational requirements make it necessary to employ microprocessors with high operating speeds. The functional operations must, therefore, be designed in such a way that they can be performed by a fast microprogrammable microprocessor. A description is presented of the properties which a microprocessor must have for the considered applications, taking into account details of its use and the design of suitable extractor processing procedures. It was found that requirements for instruction times of about 100 nanoseconds could not be satisfied by a commercially available microprocessor. A suitable microprocessor was, therefore, developed G R

A79-26759 Concept of modular software for the stepwise construction of radar data processing systems with minicomputers, taking into account as example the Airtrack System (Konzeption modularer Software für den stufenweisen Aufbau von Radardatenverarbeitungssystemen mit Minicomputern /am Beispiel des Airtrack-Systems/) G A Liebelt (Telefunken AG, Ulm, West Germany) In Symposium on Radar Technology, 3rd, Hamburg, West Germany, September 14 16, 1977, Reports Dusseldorf, Bucherei der Ortung und Navigation, 1978, p 191, 193-207, 209-218 In German

The considered system concept is based on the possibility of a stepwise construction of air traffic control systems in the case of gradually increasing performance requirements or increasing automatization. A basic system with a central target data processing computer is in the case of increasing processing requirements extended with the aid of autarkic subsystems. The characteristics of the application software make it possible to place in the case of system extensions modules in the process computers of the subsystems. The system concept of the new air traffic control system Airtrack is used to illustrate the hardware configuration and software structure involved.

A79-26760 Hardware and software structure of a coordination system for air traffic control on the basis of flight plan data (Hard- und Softwarestruktur eines Koordinationssystems für die Flugsicherung auf der Grundlage von Flugplandaten) J Zurn (Telefunken AG, Ulm, West Germany) In Symposium on Radar Technology, 3rd, Hamburg, West Germany, September 14-16, 1977, Reports Dusseldorf, Bucherei der Ortung und Navigation, 1978, p. 219-245 In German

The coordination system provides communication possibilities for several users among each other with the aid of computer-controlled table display devices. A control computer processes flight plans and indicates them in the form of 'electronic control strips' on data display devices. The display devices have a touch input feature. The system is so conceived that it can also operate without automatic radar data input. A special touch function for an input of data regarding the times at which an aircraft passes over defined reporting points is used to update flight plan data.

A79-26761 Problems of computer-aided tracking, giving particular attention to radar which can be electronically turned (Probleme der rechnergestutzten Zielverfolgung unter besonderer Berucksichtigung des elektronisch schwenkbaren Radars) G van Keuk (Gesellschaft zur Forderung der astrophysikalischen Forschung, Forschungsinstitut für Funk und Mathematik, Werthhoven, West Germany) In Symposium on Radar Technology, 3rd, Hamburg, West Germany, September 14-16, 1977, Reports

Dusseldorf, Bucherei der Ortung und Navigation, 1978, p 246-259 5 refs. In German

Aspects of signal acquisition and sensor data processing are examined and aspects of track-while-scan operation in the case of conventional radar and a radar with the considered design features are compared. A description is presented of computer controlled

tracking in the case of the ELRA system which has been designed in connection with efforts to develop an electronically controlled radar system. The requirements of the ELRA radar system are satisfied with the aid of tracking algorithms of higher precision employed in a phased array radar using adaptive computer controlled target tracking.

GR

A79-26828 Residual-stress formation during the thermal hardening of components in gas-turbine engines B A Kravchenko, G N Gutman, and G N Kostina (Problemy Prochnosti, May 1978, p. 12-15.) Strength of Materials, vol. 10, no. 5, Jan. 1979, p. 507-511 Translation

Thermal strengthening (i.e., heating followed by intensive cooling) is an effective technique for components designed for high temperature operation. In the present paper, the residual stresses generated by this treatment in gas turbine engine components are calculated for various types of cooling with allowance for the real strain curve of the material. The influence of the scale factor is examined.

A79-26830 Operational experience with linked-blade high-output gas-turbine A A Mukhin, A A Kovalev, A N Vedin, and A A Simakov (*Problemy Prochnosti, May* 1978, p 18-21) Strength of Materials, vol 10, no 5, Jan 1979, p 514-517 Translation

The technical state of the contact surfaces of shrouded turbine blades was studied to determine the appropriate overhaul period Graphs showing the arrangement of the blades and shrouds are given, along with plots of the shroud tightness vs the mode of engine operation, plots of the stress vs the shroud clearance, plots of the maximal clearance in test stand and in flight conditions, and plots of the shroud clearance vs the blade pitch. The vibration frequencies are analyzed as a function of the clearance. The influence on wear of various coatings and of the working temperature of the blade material is studied.

A79-26838 Thermal cycling endurance problems in gasturbine parts N D Kuznetsov (*Problemy Prochnosti*, June 1978, p 3-7) Strength of Materials, vol 10, no 6, Feb 1979, p 621-625 7 refs. Translation

The present review of gas turbine disk and blade failures points toward a major contribution of thermal cycling to the failure of these and other engine components. The complexity of the action of thermal cycling loads is demonstrated on the basis of an airliner engine. Methods of evaluating the thermal fatigue strength of gas-turbine engines are examined, and the need for the development of mathematical models that would take into consideration all the factors affecting thermal cyclic fatigue is pointed out.

A79-26841 Prediction of gas-turbine alloy creep characteristics I P Bulygin, E R Golubovskii, and I I Trunin (Problemy Prochnosti, June 1978, p. 19-21.) Strength of Materials, vol. 10, no 6, Feb. 1979, p. 636-638. Translation

Experimental creep data obtained in the present study for the heat resistant cast nickel alloy ZhS6U are shown to correlate well with values calculated on the basis of the equation describing the creep rate as a function of the load and temperature. The value of the creep strain computed over the time to failure are shown to lie within confidence bounds obtained for a confidence probability of 0.95 with allowance for experimentally determined variance values.

A79-26865 # Plane problems of aerothermooptics (Ploskie zadachi aerotermooptiki) N E Galich (Leningradskii Politekhnicheskii Institut, Leningrad, USSR) Inzhenerno-Fizicheskii Zhurnal, vol 36, Feb 1979, p 320-326 11 refs In Russian

The development of thermogasdynamic waveguides is of importance to optical communication links. In the present paper, the propagation of light in nonuniformly heated laminar subsonic gas streams is analyzed with a view toward using them to control light beams. An exact solution to the problem of refraction in a two-dimensionally nonuniform medium is obtained, showing that the ratio of the refractive index gradients has a decisive influence on the angle of refraction. The propagation of light near a heated isothermal plate situated in a uniform gas stream is examined, and the influence of the thermal flux on light intensity is identified.

A79-26871 # FAA air traffic control automation - Programs and trends S B Poritzky and A G Zellweger (FAA, Washington, D C) In Radio Technical Commission for Aeronautics, Technical Symposium and Annual Assembly Meeting, Washington, D C, November 16, 17, 1978, Proceedings Washington, D C, Radio Technical Commission for Aeronautics, 1978, p 29-42

It is pointed out that the cost of air traffic control (ATC) will rise dramatically if the increasing demand is to be well served. One of the major cost elements in operating the ATC system will be, as it is today, the FAA workforce The controller/aircraft ratio is going to remain high as long as every ATC transaction with an IFR aircraft is personally handled by a controller Technology alternatives in the aircraft and on the ground offer the opportunity of a less labor-intensive system. Thus, FAA is actively pursuing technology alternatives with the objective of lowering projected ATC system costs. The FAA's near-term major systems development activities include programs designed to aid en route and terminal controllers with their planning and separation tasks. Attention is given to prospects for automation, automated en route ATC, automated terminal service, ideas regarding a replacement computer system, and G R collision avoidance systems

A79-26874 # Avionics systems needed to optimize V/STOL potential D A Petersen (U S Army, Avionics Research and Development Activity, Fort Monmouth, N J) In Radio Technical Commission for Aeronautics, Technical Symposium and Annual Assembly Meeting, Washington, D C , November 16, 17, 1978, Proceedings Washington, D C , Radio Technical Commission for Aeronautics, 1978, p. 121-127

It is pointed out that the existing terminal area air traffic control and landing systems are unsuitable for the full utilization of the V/STOL potential. The superior maneuvering, slow speed, and steep approach capabilities of V/STOL aircraft offer the potential for flying tighter patterns with closer separations under conditions of high traffic density in the terminal areas. The V/STOL aircraft is generally used for short, high priority missions (averaging 20 to 30 minutes) in which fuel can be traded for payload. Another topic considered concerns avionic system integration with the airframe Digital technology, particularly in the LSI and microprocessor areas, has evolved to the point that the operational problems are amenable to solution through application of digital techniques at the system level. New hardware developments are also examined, taking into account navigation systems, displays, and wire and obstacle avoidance systems.

A79-26875 * # Cockpit displays and the growing role of the pilot in the ATC system E G Lyman (NASA, Aeronautical Man-Vehicle Technology Div , Washington, D C) In Radio Technical Commission for Aeronautics, Technical Symposium and Annual Assembly Meeting, Washington, D C , November 16, 17, 1978, Proceedings Washington, D C , Radio Technical Commission for Aeronautics, 1978, p 129-135

It is pointed out that advances in avionics and computer technology have reached the point where serious attention may be given to structuring a new controlled air traffic environment. The principal feature of such an environment is related to the capability of pilots to perform certain active ATC functions from the cockpit. The main function is concerned with the ability to maintain safe.

separation from other aircraft under all meteorological conditions. Technical features available to permit such a functional change include such concepts as the Discrete Address Beacon System, a full capability. Beacon Collision Avoidance System, data links, computer generated displays, and flight management computers.

A79-26876 * # A comparison of linear acoustic theory with experimental noise data for a small-scale hovering rotor F Farassat (Joint Institute for Advancement of Flight Sciences, Hampton, Va), C E K Morris, Jr (NASA, Langley Research Center, Hampton, Va), and P A Nystrom (NASA, Langley Research Center, Joint Institute for Advancement of Flight Sciences, Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79 0608 10 p 18 refs Army-supported research, Grant No NsG-1474

Linear acoustic calculations based on full aerodynamic data as input are presented and compared with measured cases reported by Boxwell et al. (1978). The full aerodynamic data are obtained using three programs giving radial loading, chordwise loading, and chordwise position of transition. It is shown that in the theoretical results the most significant noise source mechanism is due to blade thickness. Thus the conclusions of Boxwell et al. as to the importance of nonlinearities around the blades are upheld. These conclusions concern the width, shape and the level of the acoustic pressure calculated from linear acoustic theory. Some of the approximations involved in the application of acoustic analogy using quadrupole sources are discussed. It is necessary that the near- and far field problems of rotating blades be treated together as shown for the case of an oscillating sphere.

A79-26877 * # Measured and predicted noise of the AVCO-Lycoming YF-102 turbofan engine B J Clark, J G McArdle, and L Homyak (NASA, Lewis Research Center, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0641 9 p 8 refs

Acoustic testing of the AVCO Lycoming YF 102 turbofan engine was done on a static test stand at Lewis Research Center in support of the Quiet Short Haul Research Aircraft (QSRA) acoustic design. Overall noise levels are dominated by the fan noise emanating from the exhaust duct, except at high power settings when combination tones are generated in the fan inlet. Component noise levels, calculated by noise prediction methods developed at Lewis Research Center for the ANOP program, are in reasonable agreement with the measured results. Far-field microphones placed at ground level were found superior to those at engine centerline height, even at high frequencies. (Author)

A79-26879 * # Wave propagation in ducts using the finite element method R K Majjigi (General Electric Co., Cincinnati, Ohio), R K Sigman, and B T Zinn (Georgia Institute of Technology, Atlanta, Ga.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79 0659. 9 p. 12 refs. Grant No. NsG-3036

The paper outlines a comparative study designed to assess and compare the accuracy of the finite element method (FEM) for linear and quadratic elements as applied to problems in duct acoustics. The acoustic disturbances are assumed to be irrotational and isentropic so that the problem can be formulated in terms of the acoustic velocity potential. It is shown that for the case of plane wave propagation in a hard-walled annular cylinder, the accuracy of the FEM solution can be increased at higher frequencies by using quadratic triangular elements instead of linear triangular elements. Evidence is presented to enhance the confidence in applying the developed FEM by comparing results with those obtained by other independently developed numerical approaches such as an integral equation technique and a finite difference method.

A79-26881 * # Full-scale engine tests of bulk absorber acoustic inlet treatment. L J Heidelberg and L Homyak (NASA, Lewis Research Center, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0600 10 p 6 refs

Three different densities of Kevlar bulk absorber fan inlet treatment were tested on a YF 102 turbofan engine. This bulk absorber material may have potential for flight application. Far-field noise measurements were made and the attenuation properties of the three treatment densities were compared. In addition the best bulk treatment was compared to the best single degree of freedom, SDOF (honeycomb and perforated cover sheet) treatment from another investigation. Although the density was varied over a large range, (3 to 1) the effect on attenuation was small. The highest density treatment, 11.8 lb/cu. ft, had a somewhat broader attenuation bandwidth. The comparison of the best bulk and SDOF treatments showed the bulk to have a greater attenuation bandwidth. At the design frequency both types of treatment had almost equal performance. (Author)

A79-26882 # A finite element subvolume technique for structural-borne interior noise prediction J F Unruh (Southwest Research Institute, San Antonio, Tex.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79-0585. 10 p. 23 refs.

Finite element structural and finite-element acoustic representa tions of a flexible structure and receiving (enclosed) acoustic volume are used to formulate the equations of motion for a coupled structural acoustic system in a study of structural borne noise. The number of coupled equations is reduced prior to forced harmonic response analysis by expanding the structural equations of motion in terms of their normal mode eigenvectors, and the interior acoustic nodal equations are reduced to modal form via an acoustic subvolume technique. A test fixture is developed to experimentally obtain hardwall acoustic modes, coupled structural-acoustic modes and interior sound pressure levels for forced harmonic input in a geometrically complex shaped enclosure. Through comparison with experimental results, the acoustic subvolume analysis technique is shown to be an accurate analysis tool for predicting structure borne noise, while it reduces the computational effort required for finite element acoustic analysis

A79-26885 * # Sound radiation from hyperboloidal inlet ducts Y C Cho American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0677 10 p 15 refs Grant No NGR-09-010 085

This paper presents rigorous solutions for the problem of sound radiation from various inlet ducts including hyperboloidal (or hyperbolic) inlet ducts and circular ducts with wide flange. The numerical results include the complex conversion (or reflection) coefficients and the radiation directivity for the various incident wave modes—spinning modes as well as axisymmetric modes. The analysis utilizes hyperboloidal wave functions which are defined here as a class of eigensolutions of the wave equation for oblate spheroidal coordinates, and is valid for the whole frequency range including frequencies above and below the cutoff frequencies of duct modes involved. (Author)

A79-26887 # Discrete noise spectrum generated by an acoustically excited jet V Kibens (McDonnell Douglas Corp., St Louis, Mo.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79-0592 9 p. 16 refs

The shear layer of an axisymmetric air jet (Re = 50,000) was perturbed using a symmetrical acoustic excitation chamber surrounding the nozzle at a frequency fe = fs, where fs is the shear-layer instability frequency. The excitation organized the large scale structures in the shear layer into a sequence of three successive vortex-

pairing stages at fixed streamwise locations, producing the subharmonic frequencies fe/2, fe/4, and fe/8. The pressure spectra in the near field and the acoustic spectra in the far field contained peaks at the frequencies corresponding to the rate of formation of large-scale turbulent structures through vortex pairing. The broadband noise of the excited jet was reduced by as much as 10 dB compared with the nonexcited jet.

(Author)

A79-26893 * # The application of finite element techniques to acoustic transmission in lined ducts with flow R J Astley (Canterbury, University, Christchurch, New Zealand) and W Eversman (Missouri Rolla, University, Rolla, Mo) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12 14, 1979, Paper 79-0660 13 p 11 refs Grant No. NSG-7192

The finite element method (FEM) is used to analyze the propagation of sound in two-dimensional nonuniform ducts carrying a compressible subsonic mean flow Galerkin and residual least squares (RLS) methods with natural and forced boundary conditions are considered. The accuracy of FEM results for the eigenvalue and transmission problems is assessed by comparison with alternative numerical schemes for nonuniform ducts. The results presented and those from associated investigations indicate that modal coupling is a significant feature of the acoustic field, especially at high Mach numbers. A multimodal model therefore appears to be essential if any reliable conclusions are to be drawn in the context of turbofan inlet regions. Improvements to the eigenvalue scheme following the implementation of higher-order Hermitian elements indicate a similar modification for the transmission problem.

A79-26894 # Direct experimental verification of the theoretical model predicting rotor noise generation S Léwy, J Lam bourion, C Malarmey, B Rafine (ONERA, Châtillon-sous-Bagneux, Hauts-de-Seine, France), and M Perulli (ONERA, Châtillon-sous Bagneux, Hauts-de Seine, Compiègne, Universite de Technologie, Compiègne, France) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0658 10 p 9 refs

The well known theoretical model predicting the space structure of acoustic waves generated by a rotor can be directly verified by measuring pressure fluctuations on rotating blades. Such a comparison was obtained for the first time on an ONERA experimental ducted fan Time variations of squared amplitudes of lines are studied. If various blade loading harmonics are considered along with an acoustic tone, it appears that correlation coefficients reach appreciable values only for source frequencies generating propagating waves, while they remain very weak for evanescent modes. (Author)

A79-26895 * # The annoyance of multiple noisy events A Ahumada, Jr (Stanford University, Stanford, Calif) and D C Nagel (NASA, Ames Research Center, Moffett Field, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79 0653 7 p 9 refs

A total of 24 subjects (17 M, 7 F) was tested in an experimental study of annoyance rating of multiple noisy events (30 sets of noise bursts). The scaling technique known as functional measurement was used to determine whether annoyance integrates additively over events and if so, to measure the power law exponent which relates the levels of the events to the additive scale values. To this end, groups of three noises were presented at three levels in a factorial arrangement to check the additivity hypothesis and to estimate the scaling function. Also, a series of sets of noises of constant level but varying in set size were considered. The functional measurement of annoyance ratings of sets of three simulated flyovers showed that the integration of annoyance can be represented as an additive process in terms of scale values that are power functions of the sound power with a power-law exponent near 0.7.

A79-26896 # Propagation of buzz-saw noise in a nonuniform medium M S Tsal (Boeing Commercial Aeroplane Co. Seattle, Wash.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79-0639 8 p. 11 refs

The Whitham's wavefront expansion technique is used to ana lyze the propagation of buzz-saw noise in the contoured inlet of the jet engine. When the gradient of the axial mean flow velocity along the duct axial direction of the propagation of buzz-saw noise becomes more positive or the blade spacing becomes narrower, then more energy is dissipated. As the power setting goes higher, the energy at the inlet opening spreads over a wider range of radiation angles and shifts to small radiation angles to the duct axis. (Author)

A79-26905 # Sound absorption caused by vorticity shedding, demonstrated with a jet flow D W Bechert (Deutsche Forschungs und Versuchsanstalt für Luft- und Raumfahrt, Institut für Turbulenzforschung, Berlin, West Germany) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0575 11 p 44 refs

From previous measurements it has become evident that a low frequency sound wave can be absorbed significantly when transmitted through a nozzle and a jet flow. The basic underlying physical phenomenon is, that acoustic energy is converted into energy of fluctuating vorticity, which is shed from the nozzle edge. In the meantime, different theories have become available which already yield an excellent quantitative description of this effect. These theories are discussed, and the simplest of them, a multipole analysis, is derived. It is demonstrated that this absorption effect is not restricted just to jet flows and occurs also in flows through apertures or through blade rows. A variety of applications is shown including a jet noise multifler and a new non-reflective termination. (Author)

A79-26907 * # On sound radiation from the trailing edge of an isolated airfoil in a uniform flow J C Yu (NASA, Langley Research Center, Hampton, Va) and M C Joshi (Joint Institute for Advancement of Flight Sciences, Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0603 18 p 24 refs

An experimental investigation has been conducted to determine the physical process of the noise production from the trailing edge of an isolated two-dimensional airfoil embedded in a low turbulence uniform mean flow. The Reynolds number of the airfoil based on chord was greater than 1,000,000 and that the boundary layer was fully turbulent at the trailing edge. Smoke injection technique and spark shadowgraphy were used to study the structural features of the boundary layer. Two point joint statistical analyses were made on the surface pressure, the radiated sound and the relationship between the two quantities. Operating conditions included two free stream velocities and two angles of attack for both a naturally developed and an artificially tripped boundary layer. Flow visualizations revealed the existence of large scale coherent motions in the outer region of the boundary layer. The observed coherent motions had scales of the order of boundary layer thickness and a convection velocity near the free stream velocity. The production process of the airful trailing edge noise was determined to be the convection of the large scale coherent eddies over the trailing edge of the airfoil. The noise field so generated was found to be rather coherent and dipole-like (Author)

A79-26908 * # An experimental study of USB flap noise reduction through mean flow modification M C Joshi (Joint Institute for Advancement of Flight Sciences, Hampton, Va) and J C Yu (NASA, Langley Research Center, Acoustics and Noise Reduction Div, Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0607 11 p 15 refs

The effect of mean flow modification on the noise production of upper surface blown flaps has been studied experimentally. Mean

velocity profile at the nozzle exit was modified from the usual 'top-hat' shape to 'Gamma' and 'L'-shaped profiles The 'L'-modification caused noise reduction around and above the peak frequency of the 'top-hat' spectrum when compared on an equal thrust per exit area basis Modification to 'Gamma'-shaped profile resulted in a shift of the spectrum to lower frequencies and a lower overall noise reduction These modifications alter the development of the large scale disturbances in the upper shear layer and trailing edge wake of the wall jet geometry (Author)

A79-26909 # Considerations for the design of inlet flow conditioners for static fan noise testing. R B Ginder, R C Kenison, and A D Smith (National Gas Turbine Establishment, Farnborough, Hants, England) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0657 9 p 10 refs

Reductions in distortion tone level of up to 10 dB have already been achieved with a hemispherical honeycomb flow conditioner Ways of achieving further reductions are investigated in acoustic and aerodynamic tests on flow conditioner elements. Turbulence reduction measurements indicate that adding a gauze downstream of the honeycomb is much more effective than increasing the cell depth. Some tests concerning the importance of the duct boundary layer region which shed further light on earlier work are discussed. Aspects relevant to outdoor full-scale engine tests are emphasized and some preliminary results from such tests are given. (Author)

A79-26911 * # Effects of inflow distortion profiles on fan tone noise calculated using a 3-D theory H Kobayshi (NASA, Lewis Research Center, Cleveland, Ohio, National Aerospace Laboratory, Tokyo, Japan) and J F Groeneweg (NASA, Lewis Research Center, Turbomachinery Noise Section, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0577 11 p 12 refs

Calculations of the fan tone acoustic power and modal structure generated by complex distortions in axial inflow velocity are presented. The model used treats the rotor as a rotating three-dimensional cascade and calculates the acoustic field from the distortion-produced dipole distribution on the blades including noncompact source effects. Radial and circumferential distortion shapes are synthesized from Fourier Bessel components representing individual distortion modes. The relation between individual distortion modes and the generated acoustic modes is examined for particular distortion cases. Comparisons between theoretical and experimental results for distortions produced by wakes from upstream radial rods show that the analysis is a good predictor of acoustic power dependence on disturbance strength.

A79-26912 # Diagnostic evaluation of jet noise suppression mechanisms P R Gliebe (General Electric Co., Aircraft Engine Group, Cincinnati, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0674 11 p 11 refs U S Department of Transportation Grant No OS-30034 DOT Task 3

A unified aeroacoustic jet noise prediction method has been developed, based on the modeling of principal noise generation and emission mechanisms from first principles. It is demonstrated herein that this jet noise prediction method is a useful diagnostic tool for assessing the relative importance of the various mechanisms for a given notzle type. The relative contributions of (1) turbulent mixing noise suppression, (2) shock cell broadband noise suppression, (3) convective amplification suppression, and (4) fluid shielding attenuation have been evaluated for a high element number multi-chute suppressor, to arrive at a plausible explanation for how multi-element suppressors suppress jet noise. This explanation, an alternative view to historical conceptions of jet noise suppression, suggests an approach to designing low noise suppressor nozzles. (Author)

A79-26915 # Interior noise path identification in light aircraft using multivariate spectral analysis L Keefe (Wyle Labora-

tories, Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0644 9 p 7 refs

The interior noise at the copilot's position in a light aircraft has been modelled as the single output of a multiple input system consisting of five vibrating fuselage panels located in the propeller plane adjacent to the copilot. Using the techniques of multivariate spectral analysis, residual interior noise spectra were calculated in an attempt to rank the panels by their effect on interior levels. The analysis revealed that no more than 35% of the noise energy could be traced to these panels, and that it was their collective, coherent motion, rather than that of any one, which radiated the sound Difficulties in applying these spectral techniques and interpreting their results were traced to numerical errors during processing and the lack of a clear physical analogue to the mathematical conditioning process. Suggestions for surmounting both these problems are presented.

A79-26917 * # The effect of throttling on forward radiated fan noise P R Gliebe (General Electric Co., Aircraft Engine Group, Evendale, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79 0640 12 p. 14 refs. NASA sponsored research

A study was undertaken to evaluate the effect of operating line throttling on inlet arc noise from high speed fans. Experimental measurements on a 1/4-scale fan stage tested in an anechoic chamber, with and without inlet turbulence control devices, were utilized to assess the effect of constant speed throttling on the forward arc radiated noise characteristics. Different effects were observed in different speed ranges with different types of inflow turbulence control. These effects were correlated with some of the current theories on fan noise generation mechanisms, and partial success was achieved in attempting to relate the various theoretical models to the observed trends. The results of this study have an important bearing on estimating the noise characteristics of new fan designs from scaling the measured characteristics of previously tested fans.

(Author)

A79-26918 # The sound power spectrum of shock-free jets C L Morfey and G P Howell (Southampton, University, Southampton, England) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0595 12 p 28 refs Research supported by Rolls Royce, Ltd

Sound power data from a program of jet mixing noise experiments, conducted using 2 in dia nozzles, are presented in normalized 1/3-octave form for a range of Strouhal numbers. Forward and rear arc contributions to the power are given separately. In addition, the power radiated into the geometric acoustics cone of silence is evaluated and is found to dominate the rear arc power at Strouhal numbers below 1/2, once the jet velocity exceeds the ambient sound speed. The implications of the data are discussed in terms of radiation from wave-like large-scale structures in the turbulent jet. Finally, the possible back-reaction of the sound field on the jet flow is discussed for subcritical jets (jet Mach number less than 1). (Author)

A79-26919 # Coaxial jet noise in flight V M Szewczyk (Rolls-Royce, Ltd., Derby, England) American Institute of Aeronautics and Astronautics Aeroacoustics Conference, 5th Seattle, Wash., Mar. 12-14, 1979, Paper 79 0636 10 p. 12 refs

The effect of flight on full scale coaxial jet noise is presented Several recommendations concerning future flyover exercises are made regarding the importance of microphone placement, airframe noise, atmospheric section data and engine/aircraft performance data Careful noise data comparisons show how the flight velocity index is now close to the model simulation values particularly when account is taken of internal noise, aircraft installation effects and the distributed nature of mixing noise. Significant reductions at 90 deg and in the rear arc occurs but the popular forward arc lift is shown to be caused by an intrusive level of airframe noise. (Author)

A79-26920 * # Airframe noise measurements on a small-scale model of a supersonic transport concept in an anechoic flow facility J S Preisser (NASA, Langley Research Center, Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0666 10 p. 15 refs

Airframe noise has been measured on a 015 scale model of an advanced supersonic transport concept (AST 100) in an anechoic flow facility. The model was equipped with leading- and trailing edge flaps, noise and main landing gears, and engine nacelles. Each of these components was deployed, individually and collectively, to determine their contribution to the noise field. Results are presented which show that in the clean configuration the aircraft displays a symmetric dipole directivity, whereas in the more complex landing approach configuration the directivity peaks in the forward quadrant. It was found that the landing approach noise was due chiefly to the landing gear, the trailing edge flaps, and the aeroacoustic interaction between the two. (Author)

A79-26923 * # Noise from struts and splitters in turbofan exit ducts M R Fink (United Technologies Research Center, East Hartford, Conn.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79-0637. 10 p. 13 refs. Contract No. NAS3 17863

An analytical method for calculating noise radiation from isolated airfoils in turbulent flow was combined with a method for calculating transmission of sound through a subsonic exit duct and with an empirical far field directivity shape. This combination provides a method for predicting engine internally generated noise from radial struts and stators and annular splitter rings. Calculated sound power spectra, directivity, and acoustic pressure spectra are compared with data. These data were for noise caused by a fan exit duct splitter ring, large-chord stator blades, and turbine exit struts. However, the lack of turbulence intensity and scale length measurements for these flow ducts prevented an absolute validation of the prediction method.

A79-26924 * # Twin jet shielding S P Parthasarathy, R F Cuffel, and P F Massier (California Institute of Technology, Jet Propulsion Laboratory, Pasadena, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0671 14 p 5 refs Research sponsored by the Lockheed-California Co

For an over-the-wing/under-the-wing engine configuration on an airplane, the noise produced by the upper jet flow is partially reflected by the lower jet. An analysis has been performed which can be used to predict the distribution of perceived noise levels along the ground plane at take-off for an airplane which is designed to take advantage of the over/under shielding concept. Typical contours of PNL, the shielding benefit in the shadow zone, and the EPNL values at 3.5 nautical miles from brake release as well as EPNL values at sideline at 0.35 nautical miles have been calculated. This has been done for a range of flow parameters characteristic of engines producing inverted velocity profile jets suitable for use in a supersonic cruise vehicle. Reductions up to 6.0 EPNdB in community noise levels can be realized when the over engines are operated at higher thrust and the lower engines simultaneously operated with reduced thrust keeping the total thrust constant.

A79-26925 * # Reduction of rotor-turbulence interaction noise in static fan noise testing R A Kantola and R E Warren (GE Corporate Research and Development Center, Schenectady, N Y) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0656 18 p 22 refs Contract No NAS3-17853

Three effective inlet cleanup methods are described. A flared reverse cone inlet is used to eliminate wakes from the fan casings and/or probe supports Boundary layer suction is employed ahead of the fan rotor and on the outer flare of the cone to reduce the boundary layer turbulence and remove any residual wakes. To reduce the midstream turbulent intensity and length scales, a turbulence control structure is used which is constructed with both a layer of honeycomb and a fine mesh screen. The effects of these cleanup methods are quantified by measuring the far-field noise in an anechoic chamber, using a high-speed 20-in -diam fan of the current high passband type. The changes in the turbulent field impinging on this rotor are quantified by mapping the streamwise and transverse turbulent properties (spectra, intensity and length scale) with crossed hot film probes. It is convincingly shown that it is possible to clean up the inlet flow of a static fan noise test facility to a point where the static acoustic data simulate flight data

A79-26926 * # Evaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine W L Jones, J G McArdle, and L Homyak (NASA, Lewis Research Center, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0654 11 p 9 refs

Two inflow control devices, (ICD's) one in-duct and the other external to the duct, were tested on a JT15D engine to determine their ability to remove inflow turbulence without altering the sound transmission to the far field. The objective of the program was to develop means of accurately simulating flight fan noise on ground static test stands. The results generally indicated that both the in-duct and external ICD's were effective in reducing the inflow turbulence and the fan blade passing frequency tone generated by the turbulence. The external ICD was essentially transparent to the propagating fan tone but the in-duct ICD caused attenuation under most conditions. (Author)

A79-26927 * # Some effects of applying sonic boom minimization to supersonic cruise aircraft design R J Mack and C M Darden (NASA, Langley Research Center, High Speed Aerodynamics Div , Hampton, Va) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0652 8 p 16 refs

This paper presents a discussion of an aircraft shaping method to control sonic boom over pressure levels along with the analysis of wind-tunnel data which validated the method. The results indicate that the sonic boom minimization method can guide the design team choices of aircraft planform and component arrangement toward a low boom-level configuration while permitting sufficient freedom and flexibility to satisfy other design criteria. Further, it is shown that off-design flight conditions do not drastically change the overpressure sonic boom shape and strength.

A79-26928 # An airborne reference noise source for studying airplane flyover noise propagation and measurement C R Hogstedt and E M Lowder (Douglas Aircraft Co , Long Beach, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0650 8 p

To improve the repeatability of airplane flyover noise measurements, an Airborne Reference Noise Source (ARNS) was developed to study noise propagation and measurement variables. ARNS is a high-amplitude noise generator mounted under a light airplane. The purpose is to approximate the significant portion of a fan-jet spec trum during a flyover, but with the advantages of being inherently stable in output and economical to operate. As ARNS is flown at various altitudes, ground and airborne noise and weather data are recorded. The resultant data are analyzed for correlation between changes in weather and measurement parameters and changes in noise levels. (Author)

A79-26929 # An acoustic problem in anechoic chambers arising from exhaust noise testing B A Turner (National Gas Turbine Establishment, Farnborough, Hants , England) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0649 7 p

In anechoic chambers built for evaluating the noise of engine exhaust systems, gross distortions in sound level have been found in the forward arc of jets with internally-generated tones. A series of experiments has isolated the lip of the exhaust collector as the source of the distortions. As a consequence of the strong downstream directivities of jet and core noise, high sound levels are incident on the collector lip and it requires only a small fraction of this sound to be scattered into the forward arc for the noise levels there to be affected. The problem was solved by improving the acoustic design of the lip.

(Author)

A79-26930 # Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight W D Bryce (National Gas Turbine Establishment, Farnborough, Hants, England) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79 0648 13 p 32 refs

The problem of explaining the changes of engine exhaust noise in going from static to flight conditions has puzzled research workers for some years. This paper reviews briefly the various programmes of experimental research which have been carried out on this topic at NGTE over the last five years and highlights the results from some recent model-scale experiments. It is concluded that, together with the characteristics established for jet and core noise in flight, acoustic and aerodynamic effects arising from the installation of engines in aircraft constitute necessary, perhaps sufficient, features of the required explanation.

(Author)

A79-26931 * # Turboprop interior noise studies E H Dowell (Princeton University, Princeton, N J) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0647 19 p 14 refs Grant No NsG 1253

The modal theory of acoustoelasticity is applied to the determination of the sound levels caused by a prescribed external sound excitation which is transmitted through a cylindrical shell. A circumferential traveling pressure wave excitation is studied as representative of a propeller sound field. It is shown how other excitations such as point mechanical loading, plane wave and reverberation random may be synthesized by superposition of circumferential waves. Representative numerical results illustrate the importance of structural and acoustic frequency matching in the determination of interior sound levels and clarify the role of the cylindrical shell ring frequency. An exploratory study of a double wall geometry is conducted.

A79-26932 * # Characteristics of propeller noise on an aircraft fuselage related to interior noise transmission J S Mixson, C K Barton (NASA, Langley Research Center, Hampton, Va), A G Piersol, and J F Wilby (Bolt Beranek and Newman, Inc, Canoga Park, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0646 13 p 13 refs

Exterior noise was measured on the fuselage of a twin-engine, light aircraft at four values of engine rpm in ground static tests and at forward speeds up to 36 m/s in taxi tests Propeller noise levels, spectra, and correlations were determined using a horizontal array of seven flush-mounted microphones and a vertical array of four flush-mounted microphones in the propeller plane. The measured levels and spectra are compared with predictions based on empirical and analytical methods for static and taxi conditions. Trace wavelengths of the propeller noise field, obtained from point-to-point correlations, are compared with the aircraft sidewall structural dimensions, and some analytical results are presented that suggest the sensitivity of interior noise transmission to variations of the propeller noise characteristics. (Author)

A79-26933 * # Noise transmission - Turboprop problem R Vaicaitis (Columbia University, New York, N Y), M Slazak, and M T Chang American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0645 11 p 26 refs Grant No NsG-1450

An analytical model is presented to predict low frequency (1000 Hz and below) noise transmission into aircraft. Noise transmission is determined by solving the acoustic wave equation for the interior noise field, the equivalent 'smeared' monocoque shell equation for overall fuselage vibrations and skin-stringer panel equation for local vibrations of panels and stringers. The solution to this system of equations is obtained by using a Galerkin-like procedure. The modes and frequencies for skin stringer panels are determined by a transfer matrix method. Results include noise transmission through discretely stiffened panels and cabin noise due to turbulent boundary layer and propeller passage harmonics for a turboprop type aircraft. (Author)

A79-26935 # An experimental study of the influence of flight-stream turbulence on jet mixing noise D J Way (National Gas Turbine Establishment, Farnborough, Hants, England) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0617 11 p 16 refs

Experimental tests, aimed at highlighting aeroengine installation effects, have been conducted using a model scale jet with a flat plate of about 3 nozzle diameters square positioned to one side of the jet pipe and perpendicular to the flight stream. The presence of this plate increased the jet noise measured in flight by up to 20 dB, apparently as a consequence of the wake turbulence being shed into the jet flow. The magnitude of this aerodynamic installation effect is found to correlate with the ratio of the flight speed to the jet velocity, and to be independent of the jet temperature. (Author)

A79-26936 * # Effects of simulated forward flight on jet noise, shock noise and internal noise K K Ahuja, H K Tanna, and B J Tester (Lockheed-Georgia Co., Marietta, Ga.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12.14, 1979, Paper 79-0615. 11 p. 12 refs. Contract No. NAS3 20050.

Inflight simulation experiments are conducted in an anechoic free-jet facility to examine the flight effects on various combinations of jet noise, shock noise and internal noise. The jet mixing noise component reduces with forward velocity at all angles and frequencies. When jet mixing noise is contaminated with internal noise, forward motion provides a noise reduction in the rear arc and a noise increase in the forward arc, with little change at 90 deg. The results are similar for shock-containing jets. It is found that the existing anomalies between full-scale flight data and model-scale flight simulation data could well be due to the contamination of the flight data by internal noise. (Author)

A79-26937 # Flight effects on noise generated by the JT8D engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot wind tunnel F G Strout (Boeing Commercial Airplane Co, Seattle, Wash) and A Atencio, Jr (US Army, Air Mobility Research and Development Laboratory, Moffett Field, Calif) American Institute of Aeronautics and Astronautics, Aero-acoustics Conference, 5th, Seattle, Wash, Mår 12-14, 1979, Paper 79-0614 10 p

A JT8D-17R engine with inverted primary and fan flows was tested under static conditions and in the NASA-Ames 40- by 80 foot wind tunnel to determine static and flight noise characteristics. The major purpose of the program was to evaluate flight effects on noise generated by the inverted flow profile of a large scale engine. This jet noise suppressor concept is of particular interest to advanced supersonic transport engine cycle studies where high jet velocities create a serious noise problem during takeoff operation. The engine with inverted flow was tested with conical, plug, 20-lobe nozzles, and an acoustic shield. Wind tunnel results show that forward velocity causes a significant reduction in peak PNL suppression but only modest reductions in peak OASPL and EPNL suppression.

EPNL suppression ranged from 4.0 EPNdB for the basic inverter to 7.5 EPNdB for the inverter with 20-lobe nozzle and acoustic shield When compared with the JT8D engine with internal mixer, the inverted flow configuration provides more EPNL suppression under both static and flight conditions (Author)

A79-26938 # An investigation of model helicopter rotor blade slap at low tip speeds J E Hubbard, Jr and W L Harris (MIT, Cambridge, Mass) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0613 8 p. 13 refs Grant No DAAG29 C-027

An investigation of helicopter blade slap was performed on a 1.27 meter diameter model rotor with a NACA 0012 blade section, -8 deg linear twist in an open jet wind tunnel enclosed in an anechoic chamber. The effects of number of blades, blade pitch, advance ratio, and shaft angle on the generation and intensity of blade slap have been investigated. The effect of each parameter was determined by varying the parameter of interest while keeping the others constant. The directivity associated with blade slap at low tip speeds was measured in a direction perpendicular to the tunnel wind axis. The results of this investigation are based on a subjective definition of blade slap.

(Author)

A79-26939 * # An acoustical study of the XV-15 Tilt Rotor Research Aircraft A Lee (Lockheed Missiles and Space Co , Inc , Sunnyvale, Calif) and M Mosher (NASA, Ames Research Center, Moffett Field, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0612 7 p

Acoustic data were obtained during a full-scale test of the XV-15 Tilt Rotor Research Aircraft in the Ames 40- by 80-Foot Wind Tunnel The XV-15 has two 25-ft-diameter, three-bladed rotors at the tips of a 32-ft span wing The rotors are used as lifting rotors, as propellers, and in various intermediate stages. Acoustic waveforms, dBA, and spectra as functions of different rotor conditions are presented and discussed. The noise level was found to be sensitive to change in rotor-disk angle of attack in the helicopter configuration. Much higher noise levels and harmonic contents were found in the helicopter mode than in the airplane mode. The measurements are compared with existing theoretical predictions which include wind-tunnel wall reflections.

(Author)

A79-26940 * # Radiation of an acoustic source near the trailing edge of a wing in forward motion L Ting (New York University, New York, NY) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0605 10 p 8 refs Grant No NsG-1469

The acoustic sources simulating engine or jet noise are located near the trailing edge. During landing or take-off operations the flap angle is not small. Solutions for the scattering of the acoustic sources, monopoles, dipoles or quadrupoles, by the wing with the flap at finite angle are constructed for the case that the acoustic wave length is much larger than the length of the flap but may be of the same order as the chord. For each given geometry of the flap and the position of the singularities, critical orientations of the dipoles and the quadrupoles are defined along which the noise becomes 'suppressed', i.e., the far field pressure becomes one order smaller

(Author)

A79-26941 * # Separation of core noise and jet noise S P Parthasarathy, R F Cuffel, and P F Massier (California Institute of Technology, Jet Propulsion Laboratory, Pasadena, Calif) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12-14, 1979, Paper 79-0589 8 p Contract No NAS7-100

A method of identification and measurement of core noise and jet noise separately has been developed based on cross-correlation of signals from microphones located at widely separated angles in the far field of a jet. The different coherent properties of core noise and jet noise are used in this method to achieve this separation.

Experimental data obtained in a small scale facility is analyzed to demonstrate that this method can be used successfully to separate the mean square pressures of core noise and jet noise (Author)

A79-26942 # Combustion noise prediction update P Y Ho and V L Doyle (General Electric Co , Aircraft Engine Group, Cincinnati, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash , Mar 12 14, 1979, Paper 79-0588 7 p 25 refs

A parametric expression for the prediction of direct combustion noise is presented. It correlates the combustion noise with combustor steady-state parameters for a variety of existing conventionally designed gas turbine engines. Recent work, particularly on the low emission combustor programs, (i.e. radial staged, double annular design, etc.), has introduced certain new concepts and techniques in detailed combustor design. Some severe noise escalation was reported for the change from the conventional configuration although these low emission combustors were generally operated at the same overall engine conditions and were physically interchangeable within the same installation. With the use of the effective combustor discharge temperature, as proposed in this update, good agreement was obtained between the data and the predicted result.

A79 26943 * # Master Plan for prediction of vehicle interior noise E H Dowell (Princeton University, Princeton, N J) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-582 22 p 171 refs Grant No NsG 1253

Substantial advances have been made in improving the analytical methods available for prediction of interior noise and providing an experimental data base for their assessment and validation. A review of recent accomplishments, including representative results, is presented in the context of a Master Plan. It is suggested that modal representations of structural walls and acoustic cavities provide a useful conceptual and computational theoretical framework for including the mass, stiffness and damping of both the structure and acoustic cavity. Geometrical details and acoustic damping (absorption) are included in a rigorous manner. Future efforts, both near term and long term, are identified which are required to complete the Master. Plan and provide the noise control practitioner with access to these improved methods.

A79-26944 * # Analysis of radiation patterns of interaction tones generated by inlet rods in the JT15D engine M F Heidmann, A V Saule, and J G McArdle (NASA, Lewis Research Center, Cleveland, Ohio) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0581 14 p 10 refs

A79-26945 * # Unsteady stator response to upstream rotor wakes G F Franke (Allis-Chalmers Corp., York, Pa.) and R E Henderson (Pennsylvania State University, University Park, Pa.) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash., Mar. 12-14, 1979, Paper 79-0579. 14 p. 18 refs. Navy-supported research, Grant No. NGR-39-009-275.

The results are presented of an investigation of the unsteady pressures generated on a stator due to its interaction with the wakes shed by an upstream rotor. The influence of stator solidity, incidence flow angle and rotor/stator spacing are discussed. The results show that the major influence is due to stator solidity, particularly at large values of incidence angle. Comparisons of the measured data with an existing unsteady cascade analysis show similar trends in the chordwise variation of the predicted and measured unsteady pressure difference across the blades. Comparisons with an isolated airfoil analysis indicate the influence of solidity and unsteady blade-to-blade interaction. All comparisons were conducted for an incompressible flow with a reduced frequency of approximately 5.0. (Author)

A79-26946 # Aerodynamic and acoustic comparisons of scaled-down and actual engine jets G Elias (ONERA, Châtillonsous-Bagneux, Hauts-de-Seine, France) and C Schmidt (SNECMA, Paris, France) American Institute of Aeronautics and Astronautics, Aeroacoustics Conference, 5th, Seattle, Wash, Mar 12-14, 1979, Paper 79-0574 7 p 5 refs

With a view to better understand the acoustical differences between the jet of an actual engine and its scaled-down model, a test program has been carried out jointly by ONERA and SNECMA on a J-85 engine with convergent nozzle and a model of this nozzle Results, obtained in both subcritical and supercritical conditions, concern (1) the mean aerodynamic flow, (2) the turbulence level and spectrum, (3) the space-time correlation function of turbulence, (4) the azimuthal structure of the near field and the near field-turbulence correlations in the analysis of these results, the differences observed in turbulence measurements close to the nozzle exit, and their similarity in the downstream region, are emphasized (Author)

A79-26966 Filter weight minimization for rectified superconducting alternator power supplies T A Stuart (Toledo, University, Toledo, Ohio) and M W Tripp (Detroit Edison Co., Detroit, Mich.) In PESC '78, Power Electronics Specialists Conference, Syracuse, N Y , June 13-15, 1978, Record New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 168-177. 6 refs. Grants No. AF-AFOSR-76-2997, No. AF-AFOSR-77-3413

The paper describes the minimum weight design of the output filter of a phase-controller rectified superconducting alternator for power supply. By means of an approximation of the constant flux linkages for the rotor windings, it is possible to derive a set of nonlinear simultaneous equations that can be solved numerically. When these equations are solved, an expression for the instantaneous output voltage can be obtained, and the harmonics of the instantaneous output voltage are obtained from its Fourier series. Then the filter can be designed to provide a specified amount of harmonic attenuation. Fault current calculations are expedited by the method of constant flux linkages also. Once the energy densities and filtering requirements are specified, the required values of the energy and current density for minimum filter weight can be determined. P.T.H.

A79-26980 Application of fracture mechanics to design Edited by J J Burke (U S Army, Army Materials and Mechanics Research Center, Watertown, Mass) and V Weiss (Syracuse University, Syracuse, N Y) New York, Plenum Press (Sagamore Army Materials Research Conference Proceedings, No 22), 1979 344 p \$39 50

Test methods for fracture mechanics design data are considered along with pressure vessels, structures, rotating components, and recent improvements in electron fractographic analyses. Attention is given to fracture toughness testing, methods for dynamic fracture resistance testing, the analysis of fatigue crack growth rate data, proof test criteria for thin walled pressure vessels, practical fracture mechanics applications to design of high pressure vessels, the application of fracture mechanics to pipeline design, fracture design for structural steels, the application of fracture mechanics to prevention and control of subcritical crack growth and fracture in advanced high-performance ship structures, a fracture mechanics evaluation of generator rotors, practical applications of fracture mechanics to turbine engine rotors, and fracture mechanics and fail-safe design for helicopter rotor structures.

A79-26986 Fracture mechanics and fail-safe design for helicopter rotor structures M J Rich (United Technologies Corp., Sikorsky Aircraft Div., Stratford, Conn.) in Application of fracture mechanics to design New York, Plenum Press, 1979, p. 303-320. 19 refs

Fracture mechanics analysis is now being extensively employed in design for fail-safety of metal alloy helicopter rotor system components. The importance of fracture mechanics analysis has been to temper the use of high strength alloys by requiring properties which provide a high residual strength and greater residual life. Controlled fracture, with reliable inspection methods, appears to be the key for fail-safe design. A combination of 'safe-life' and 'fail-safe' design philosophies offers a lighter weight solution for increased safety. The new advanced composite materials appear to offer even greater reliability by virtue of their much lower rate of crack propagation. However, fracture mechanics analysis will now have to emphasize the residual strength aspect for composites due to their relatively lower fracture toughness.

A79-27000 # Experimental investigation of the effect of surface discontinuity on step-backward flow M I I Rashed (Cairo University, Cairo, Egypt), R M El-Taher, and M A Ghazy (King Abdulaziz University, Jeddah, Saudi Arabia) Journal of Engineering Sciences, vol 4, Nov 1978, p 143-152 10 refs

The effect of geometrical changes upstream of separation of the flow past an ogive slender body on the flow in the neighborhood of a backward-facing step was investigated experimentally. Geometrical changes upstream of separation were produced by a movable plate changing the form of a surface discontinuity. Pressure distributions along the surface of the back facing step and longitudinal mean and fluctuating velocity components across transverse section of the model surface were measured at Reynolds number of 873,000 at mean flow velocity of 30 18 m/sec and freestream turbulence level of about 0.3% It was found that the largest base pressure corresponds to a small step surface discontinuity. The surface discontinuity generally decreased the pressure of the back-facing step bottom surface A large step surface discontinuity distorted the velocity profile and increased the turbulence intensity in the mixing layer downstream. The turbulence intensity in the back-facing step flow due to shallow cutouts was larger than that due to a step discontinuity of the same dimensions

Rakhmatulin's hypothesis concerning flow past porous bodies (1950) in combination with a scheme of vortex wake generation is used to derive an integrodifferential equation describing the unsteady aerodynamic (e.g., gust) loading of a deformable infinitely thin airfoil. The vortex wake in the case of aperiodic motions is considered finite. Attention is given to the development of the lift force, and it is shown that the irrotational part of the lift force depends on the higher derivatives of velocity with respect to time.

В.

A79-27093 Future avionics - Keeping capability up, costs down B Walsh *Military Electronics/Countermeasures*, vol. 5, Feb. 1979, p. 26, 28, 30, 31

Factors contributing to the rise in avionics costs are discussed, and current and projected Air Force initiatives to reduce acquisition and support costs are reviewed. While new technology offers many benefits, the funds needed to acquire and support new and existing avionics are limited, especially as inflation continues to erode the purchasing power of finite defense dollars. Further, several cycles of technology-enhanced systems create the proliferation problem where a number of earlier generation systems remain in the operational inventory along with the resources needed to support them. The AF Regulation 800-28 (implemented 1978), designed to provide policies and guidelines for lowering avionics costs, includes a detailed treatment of various practical activities, such as the creation of a

living data base and definition of required planning processes A master plan that will include information on how the Air Force plans to develop, acquire, maintain, and modify avionics equipment over the next 15 years is being formulated A A

A79-27121 # Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials O Fujiwara and N Muroya (Japan Air Self Defense Force, Aeromedical Laboratory, Tachikawa, Japan) Japan Air Self Defence Force, Aeromedical Laboratory, Reports, vol 19, Sept 1978, p 75-85 5 refs In Japanese, with abstract in English

Aircraft interior noise levels during flight were recorded along with their spectra, and syllabic articulation tests were performed to evaluate the noise reduction performance of the new interior materials of the C-1 cargo aircraft. The new materials attenuated the noise by more than 2-3 dB(A) over the old ones. The syllabic articulation scores were improved by about 17%. The noise level improvement was not always noticeable subjectively.

A79-27129

Advanced en route air traffic control automation B M Horowitz (Mitre Corp., Bedford, Mass.) In EASCON 78, Electronics and Aerospace Systems Convention, Arlington, Va., September 25-27, 1978, Record

New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 48-51. U.S. Department of Transportation Contract No FA70WA-2448

In the current en route air traffic control (ATC) system air traffic controllers are responsible for deriving instructions for pilots which will expedite the flow of traffic and maintain separation between aircraft. These instructions are issued by voice over the radio. This paper discusses the separation and flow functions with regard to some possible advanced automation system concepts aimed at increasing the productivity of the en route ATC system. Here, productivity is a term used to mean the total number of aircraft that can be simultaneously handled by a given number of controllers. Thus, if traffic grows but controller staffing remains constant, productivity has been increased. (Author)

A79-27135

TASAR, a thinned adaptive synthetic aperture radar R S Berkowitz and E N Powers (Pennsylvania, University, Philadelphia, Pa) In EASCON '78, Electronics and Aerospace Systems Convention, Arlington, Va, September 25-27, 1978, Record

New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 135-142-9 refs

Valley Forge Research Center (VFRC) is studying a high resolution airborne radar technique. This system employs a synthetic aperture, but it differs from conventional approaches in that adaptive beamforming is used to organize the array, and a highly thinned array is synthesized through the use of a limited number of randomly spaced sample points. These two characteristics lead to greatly reduced computational requirements and reduced tolerances on the geometry of the array. The VFRC program has involved both design studies and experimentation. System concepts and the required algorithms are discussed. Also the design of the experimental hardware and the expected results of the first experiments are described.

A79-27139 # Operational evaluation of an Air Traffic Control Radar Beacon System open array antenna. C A Miller and W G Collins (FAA, Washington, D C) In EASCON '78, Electronics and Aerospace Systems Convention, Arlington, Va , September 25-27, 1978, Record New York, Institute of Electrical and Electronics Engineers, Inc , 1978, p 176-185 7 refs

The open array antenna described provides a shaped elevation pattern with sharp underside cutoff. This cutoff reduces ground illumination and associated nulls in the interrogator surveillance pattern and also reduces the effective radiated power directed at low-angle reflecting surfaces which are sources of false targets in the air traffic control environment. A theoretical comparison of the open array with the existing standard antenna shows that a 6-8 dB reduction in illumination of reflecting surfaces at the horizon is

possible when the two antennas are adjusted to provide equivalent surveillance coverage in reflective-ground environments. The results of evaluations at three operational sites show that from 40 to 90 percent of the reflection false targets were eliminated by the array with coverage better than that available from the standard antenna. The reflecting surfaces that generated significant numbers of false targets with the open array were large structures that extended 1-2 deg above the antenna. Auxiliary techniques are sometimes required to control this false target residue.

(Author)

A79-27144 # SEATRACKS - A millimeter wave radar fire control system G E Layman (U S Navy, Naval Surface Weapons Center, Silver Spring, Md) In EASCON '78, Electronics and Aerospace Systems Convention, Arlington, Va , September 25-27, 1978, Record New York, Institute of Electrical and Electronics Engineers, Inc , 1978, p 211-216

The advantages and limitations of millimeter wave radar for shipboard fire control applications are discussed. Emphasis is placed on the development of the SEATRACKS (small elevation angle track and surveillance) feasibility radar system. The system concept combines a low elevation surveillance system with 35-GHz monopulse tracking radar in a single system. Its advantages are noted, including narrow beamwidth, precision tracking, good performance in clutter and multipath environments, and good jamming immunity.

A79-27145 Estimation of target elevation angle from 2-D radars E N Khoury In EASCON '78, Electronics and Aerospace Systems Convention, Arlington, Va , September 25-27, 1978, Record New York, Institute of Electrical and Electronics Engineers, Inc , 1978, p 217-226 5 refs Navy-supported research

Unstabilized 2-D (range, azimuth) shipboard radars measure target azimuth in a plane which is rolled and pitched with respect to a horizontal coordinate system centered at the antenna. This procedure produces azimuth bias errors which are functionally related to the ship's roll, pitch, and heading, as well as the target azimuth and elevation angles. The present paper demonstrates the advantages of implementing a 3-loop filter for 2-D unstabilized radars in order to stabilize the data and to obtain an elevation estimate. The advantages are discussed in terms of increased estimation accuracy and reduced fire control acquisition times.

A79-27203 # Laminar boundary layer with foreign gas injection on a conical body K Matsuno (National Aerospace Laboratory, Chofu, Tokyo, Japan) and R Kawamura (Tokyo, University, Tokyo, Japan) Tokyo, University, Institute of Space and Aeronautical Science, Report no 565, vol 43, Dec 1978, p 247-270 19 refs

The theory of laminar boundary layer with foreign gas injection on a nonaxisymmetric conical body at supersonic flight is discussed Emphasis is placed on estimating the mutual influence of mass injection and the cross-flow (or 'secondary flow') on the local heat transfer and skin friction, with the over-all flowfield equations solved by using the small perturbation method. Solutions were compared with experimental data, and the effects of mass injection on the boundary layer characteristics examined. The following results were obtained. (1) the major effect of mass injection is to reduce the local heat transfer and skin friction, (2) the maximum value of the cross-flow velocity component increases with increasing mass injection rates, and (3) in the case of noncircular cones, such as the elliptic cone, at angles of attack, no points at which the local heat transfer and the meridional skin friction have maximum values coincide with the windward side at which the peak pressure occurs.

A79-27297 GASP IV simulation model for the composites and bonding production facility D W Starks (McDonnell Aircraft Co, St Louis, Mo) In Winter Simulation Conference, Miami Beach, Fla, December 4-6, 1978, Proceedings Volume 2

Piscataway, N J , Institute of Electrical and Electronics Engineers, Inc , 1978, p. 843-848

This article describes the operation of the composites and bonding production facility of McDonnell Aircraft Company in St. Louis

It explains why a simulation of this area was needed, gives an overview of the simulation, and describes how the industrial engineers use the results of the simulation (Author)

A79-27313 Potential uses of rapidly solidified alloys in gas turbine engines. A R Cox (United Technologies Corp., Pratt and Whitney Aircraft Group, West Palm Beach, Fla.) and E C van Reuth (Defense Advanced Research Projects Agency, Arlington, Va.) In Rapidly quenched metals III, Proceedings of the Third International Conference, Brighton, England, July 3-7, 1978 Volume 2 London, Metals Society, 1978, p. 225-231 5 refs. ARPA Order 3152

The extension of rapid solidification processing to superalloy compositions allows alloy modifications to be made which are characteristically outside the range possible by current superalloy process methods. Eutectic regions are eliminated in gamma-gamma prime alloys, so that higher additions of gamma-prime partitioning elements can be added.

PTH

A79-27319 Why doesn't aircraft accident investigation prevent accidents G B Parker (Southern California, University, Los Angeles, Calif) (International Society of Air Safety Investigators, International Seminar, 9th, Seattle Wash, Oct 1978) SAFE Journal, vol 9, Spring 1979, p 5-9 13 refs

Accident statistics in general aviation are analyzed, together with a discussion of the root causes. A general aviation statistics list covering accidents from 1967 through 1977 shows that the accident rate has dropped from 27 6 accidents per 100,000 flight hours a year to 11.8 It is pointed out, however, that no reduction in fatal accidents has been observed. A list of accident statistics by category. including instructional, business, corporate, aerial application, and air taxi flying, indicates that pleasure flying accounted for the 52 5% of the accidents in 1976. A comparison of the pleasure flying accident rate with the US Air Force accident rate for 1976 shows that the first was 7 28 times higher than the latter. It is argued that pilot errors and adverse weather conditions, which account for the bulk of aircraft accidents, are conditions and not root causes Social, emotional and other stresses, as well as lack of proper pilot education on weather and safety, and deficiencies in forecasting and operations procedures are some of the root causes suggested

A79-27352 # The coming of age of digital electronics in commercial transports J McWha and L R Smith (Boeing Commercial Airplane Co, Seattle, Wash) In Atlantic Aeronautical Conference, Williamsburg, Va, March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 1-8 8 refs (AIAA 79-0686)

As in every other sphere of industry, digital technology has gradually found a place in commercial aviation. The new generation of airplanes will depend heavily on digital signal processing for sensor, computer, and display systems. Benefits of these new systems will be improved performance, reliability, and self test capability, resulting in lower cost-of-ownership. This paper presents the layman with some background on the increasing use of digital systems in current transports and a preview of some of the systems in current transports and a preview of some of the systems in development for new commercial transports, particularly the Boeing 767. Some of the anticipated benefits of the new systems are discussed. The problems to be faced during certification of flight critical digital systems are briefly addressed. (Author)

A79-27353 # Development of modern airfoil sections for high subsonic cruise speeds. B Eggleston (de Havilland Aircraft of Canada, Ltd., Downsview, Ontario, Canada), D J Jones, and G M Elfstrom (National Research Council, Ottawa, Canada) In Atlantic Aeronautical Conference, Williamsburg, Va., March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p 9-16 19 refs (AIAA 79-0687)

Some recent Canadian work on the design and test of airfoils for high subsonic aircraft is reviewed. Comparisons of theory and experiment are presented for two 16% thick airfoils. One airfoil was designed using numerical optimization while the other was designed by inverse methods with refinements to improve performance. The inverse design airfoil improved maximum lift coefficients 20% at all Mach numbers tested (0.2-0.80) and demonstrated that a concave pressure recovery was not detrimental. Anticipated improvements due to natural laminar flow were not realized at high subsonic Mach numbers and high Reynolds numbers (20 x 10 to the 6th). (Author)

A79-27354 # Crashworthiness tests on model aircraft fuselage structures R C Tennyson, J S Hansen, H Teichman (Toronto, University, Toronto, Canada), F Cicci, and M Ioannou (de Havilland Aircraft of Canada, Ltd., Structural Research Group, Toronto, Canada) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 17.26. 13 refs. National Research Council of Canada Grant No. A-9185, Canadian Transportation Development Agency Grant No. 01SU,T8200-7-7536 (AIAA 79.0688)

This report presents results from our continuing program involved with the crashworthiness impact tests on scale model aluminum fuselage structures. Level and oblique angle drop tests have been conducted for varying wing loads, descent velocities and angles of incidence. Dynamic measurements of strain and g loads at discrete locations have been obtained together with high speed photographs of the failure modes for comparison with a lumped mass-stiffness model of the structure using a finite element approximation. The range of tests include lightly loaded structures right through to catastrophic collapse of the fuselage. (Author)

A79-27355 # Design against fatigue - Current trends W T Kirkby, P J E Forsyth, and R D J Maxwell (Royal Aircraft Establishment, Farnborough, Hants, England) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 27-39 6 refs (AIAA 79 0689)

The current state-of-the art in design against fatigue of aircraft structures is reviewed. An outline is given of the design philosophies which have evolved to meet the fatigue problem over the past three decades. Problems of design and operation are summarized with reference to fatigue loads, design trends and developments (e.g., active control technology and in-service load measurement), design methods (e.g., the finite element method), and fatigue design with metallic as well as with composite materials.

A79-27356 # New technology in commercial aircraft design for minimum operating cost D J Stewart and B S Campion (British Aerospace, Weybridge, Surrey, England) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 40-51 (AIAA 79-0690)

Potential gains from the application of various forms of advanced technology to commercial aircraft are examined in terms of direct operating cost (DOC) and fuel consumed. It is found that substantial DOC and fuel reductions can be obtained even relative to the standard of the most recent short/medium haul aircraft to enter service. These gains result mainly from the utilization of advances in wing design, stability augmentation, load alleviation, and composite materials. For the most advanced designs, high aspect ratios are required for minimum DOC and may approach the limit of practicability for a number of technical reasons.

A79-27357 # Transonic wing design for transport aircraft G Krenz (Vereinigte Flugtechnische Werke Fokker GmbH, Bremen West Germany) In Atlantic Aeronautical Conference, Williamsburg

Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 52-61 (AIAA 79-0692)

An aerodynamic design philosophy based on pressure distribution types in chord- and span-wise directions is presented. A two-dimensional airfoil section development forming the basis of wing design is outlined illustrating progressive improvements in section performance during wind tunnel tests. The basic section was employed to design two wings with inboard shapes corresponding to different design concepts. Consideration is given to the shock development over both wings along with a comparison of drag characteristics. A weak forward shock at the inboard wing results in lower drag as compared to a pronounced double-shock system.

A79-27358 # Compromise between economic concerns and application of new technologies in the definition of a new airplane project G Cormery (Societe Nationale Industrielle Aérospatiale, Paris, France) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979. p. 62-71 (AIAA 79 0693)

Some remarks are presented on tradeoffs between costs and the need to introduce advanced technologies in aircraft development programs. A critical discussion is presented on optimization and assessment criteria, including minimization of DOC or TOC, maximization of life cycle profitability, minimization of LCC for military aircraft, and minimization of fuel consumed. An approach to solving the general tradeoff problem is presented.

A79-27359 * # Advanced supersonic technology and its implications for the future C Driver (NASA, Langley Research Center, Hampton, Va) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26 28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 72-78 18 refs (AIAA 79-0694)

A brief overview of the NASA Supersonic Cruise Research (SCR) program is presented. The SCR program has identified significant improvements in the areas of aerodynamics, structures, propulsion, noise reduction, takeoff and landing procedures, and advanced configuration concepts. These improvements tend to overcome most of the problems which led to the cancellation of the National SST program. They offer the promise of an advanced SST family of aircraft which are environmentally acceptable, have flexible range-payload capability, and are economically viable. The areas of technology addressed by the SCR program have direct application to advanced military aircraft and to supersonic executive aircraft.

A79-27360 # How to get the world airborne W M Hawkins (Lockheed California Co , Burbank, Calif) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p. 79.87 (AIAA 79-0695)

Ways to accelerate the spread of air transportation in developing countries are discussed. Consideration is given to the cost of new transportation systems, the character of the new market, the necessary hardware, whether emphasis should be placed on cargo or passengers, and how such programs should be started.

B J

A79-27361 # Ski-jump - A great leap for tactical airpower J W Fozard (British Aerospace, Weybridge, Surrey, England) In Atlantic Aeronautical Conference, Williamsburg, Va, March 26 28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 88-104 12 refs. (AIAA 79-0696)

The ski-jump concept involves the launching of a V/STOL jet from an upward-inclined ramp. This paper reviews the ski-jump launching principle and gives consideration to ramp constraints, and operational implications for land and ships. It is noted that the originality of the ski-jump launch lies not so much in the

performance gain as in its utter simplicity and absence of penalty for the vectored thrust fighter using it

A79-27362 # New airborne armament systems Y Thiriet (Avions Marcel Dassault Breguet Aviation, Saint-Cloud, Hauts-de-Seine, France) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 105-113 (AIAA 79-0697)

New aircraft weapon systems are reviewed with attention given to the need for multimission armament at the design stage and the problem of armament qualification. Particular consideration is given to store carriage qualification, store separation qualification, adapted launchers, and aiming systems.

B J

A79-27363 # Supersonic combat aircraft design J Fletcher and B R A Burns (British Aerospace, Warton Div , Preston, Lancs , England) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 114-122 (AIAA 79-0699)

Some aspects of the state of the art of supersonic combat aircraft design are reviewed with attention to design for high agility, design for high mobility, operations in the face of persistent airfield attack, operations in a highly hostile airborne environment, and overall system versatility. These requirements imply the need for a wide versatility and adaptability in the final weapons system, as an absolute minimum the designer must attempt to avoid any undue sensitivity to a change in operating factors. It is suggested that transformation of a fighter to a bomber or vice versa should be a natural mutation and that the final cost will be smaller if the appropriate variations have been accounted for in the beginning.

A79-27364 # Perspectives of technological development for helicopters G Beziac (Societe Nationale Industrielle Aérospatiale, Division Helicopteres, Marignane, Bouches-du-Rhône, France) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 123-135 (AIAA 79-0701)

The paper surveys the present technical status of the helicopter and estimates the possible technological improvements of each aircraft component. A computer program based on theoretical modeling of weights, engine fuel consumptions and parasitic drags is used to define the general characteristics and essential performance data of the helicopter which will be in production in the year 2000 (Author)

A79-27365 # Evaluation of IFR handling qualities of helicopters using the NAE airborne V/STOL simulator S Kereliuk and M Sinclair (National Aeronautical Establishment, Flight Research Laboratory, Ottawa, Canada) In Atlantic Aeronautical Conference, Williamsburg, Va, March 26-28, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 136-145 (AIAA 79-0702)

The NAE airborne simulator is being used in a series of experiments to study the validity of the flying qualities requirements laid down in the FAA's Interim Standard for helicopter IFR (instrument flight rules) certification and in recent revisions to that document The aim of the experiments is to bridge the gap between these FAA criteria and the substantial base of helicopter and V/STOL handling qualities data which has already been established Consideration is given to a preliminary phase of the flight test program in which some simple helicopter configurations were evaluated in simulated two-pilot and single-pilot IFR environments

A79-27366 # Future advanced technology rotorcraft M V Lowson and D E H Balmford (Westland Helicopters, Ltd., Yeovil, Somerset, England) In Atlantic Aeronautical Conference, Williams-

burg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p. 146-157, 13 refs. (AIAA 79-0705)

Rotorcraft technology has advanced significantly in the last decade, primarily in the areas of aerodynamics, dynamics, structures and materials. Further advances in technology, particularly in digital avionics, are in prospect. Advances in all these areas are described, and the potential benefits to future helicopters are examined. Possible designs for future civil and military helicopters taking advantage of the technology advance are presented. The relevance of the technology to other configurations of rotorcraft is discussed. It is concluded that the benefits now in prospect for the helicopter could make the development risk of novel rotorcraft configurations unattractive, except for new operational roles such as the remotely piloted helicopter.

(Author)

A79-27367 # Some new approaches for wind-tunnel testing through the use of computers P Poisson-Quinton (ONERA, Châtillon sous Bagneux, Hauts-de-Seine, France) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 158 171 9 refs (AIAA 79-0707)

New approaches for wind-tunnel testing methods designed by ONERA are described. The operating conditions, design objectives, system architecture, and software considerations of the computer system installed in the ONERA F1 pressurized low speed tunnel are taken into account. A new rig designed for the large S1 Modane tunnel to study difficult subsonic flight regimes, including ground or gust effect, is considered, as is a new transonic test section for reducing transonic wall interference. A special automatic rig installed in the S2 Modane tunnel to examine quickly the trajectory of stores separating from an aircraft so as to eliminate the possibility of danger is discussed in detail together with an active control system for flutter suppression on a dynamic model tested at transonic regime.

ΑА

A79-27368 # Recent developments in active control technology W Kubbat and O Sensburg (Messerschmitt-Bolkow-Blohm GmbH, Airplane Div., Ottobrunn, West Germany) In Atlantic Aeronautical Conference, Williamsburg, Va., March 26-28, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 172-182, 22 refs (AIAA 79-0708)

The paper reviews today's spectrum of active control technology (ACT) These tools, which are ranging from relaxed static stability, direct force control, post stall up to the control of elastic modes are described, together with examples of application Major application possibilities are pointed out. Recent and current German experimental ACT-programs are briefly described, together with their status and many test results.

A79-27369 # Findings of the Ottawa-Montreal STOL demonstration service B B Myers (Transport Canada, Research and Development Centre, Montreal, Canada) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 183-191 (AIAA 79-0710)

The application of Short Take-Off and Landing (STOL) technology to intercity transportation has been a subject of considerable controversy. In an attempt to break this type of deadlock the Canadian government undertook to demonstrate a STOL intercity service. The Montreal Ottawa route was chosen following the study of several Canadian locations. Attention is given to aspects of planning and implementation, project costs, airtransit operations, passenger acceptance, air carrier costs, air carrier revenues, facilities costs, STOL system potential, energy considerations, and questions of community reaction.

A79-27370 # Enhanced capabilities of future fighters as a result of HiMAT G Fair and M R Robinson (Rockwell International Corp , Los Angeles, Calif) In Atlantic Aeronautical Conference, Williamsburg, Va , March 26-28, 1979, Technical Papers

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 192-198 (AIAA 79-0698)

Studies conducted by Government and industry indicate that air-to-air fighters will be needed in substantial numbers. The ability to meet the simultaneous requirements of high aircraft performance, substantial quantities, and low cost will depend to a large extent on technology applications. The Highly Maneuverable Aircraft Technology (HiMAT) program sponsored by NASA and the Air Force was directed toward accelerated low-cost development and flight demonstration of advanced technologies for significantly increased maneuverability and combat effectiveness in future fighters. The HiMAT program includes building two remotely piloted research vehicles, which are scale models of the advanced fighter design.

A79-27371 * # XV-15 Tilt Rotor Research Aircraft - Program report J P Magee (NASA, Ames Research Center, U.S. Army, Aeromechanics Laboratory, Moffett Field, Calif.) and K. G. Wernicke (Bell Helicopter Textron, Fort Worth, Tex.). In Atlantic Aeronautical Conference, Williamsburg, Va., March 26-28, 1979, Technical Papers New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 201-210. 15 refs (AIAA 79-0704)

This paper is a status report of the NASA/Army XV-15 Project. The basic tilt-rotor concept and the XV-15 Tilt-Rotor Research Aircraft are discussed and some results of full-scale wind-tunnel tests in the Ames 40 by 80-Foot Wind Tunnel are presented. Flight test data are included to give preliminary performance, noise, and vibration data in hover and as far into transition flight as are available at the time of presentation. Information concerning vehicle aero dynamics and airloads obtained as a result of both wind-tunnel and flight tests are provided with some conclusions as to the ramifications of the data in terms of design criteria and configuration layout (Author).

A79-27388 How to add satellite navigational accuracy and stability to existing offshore NAV Systems P J Icenbice, Jr (JMR Instruments, Inc., Chatsworth, Calif.) In Oceans '78 The ocean challenge, Proceedings of the Fourth Annual Combined Conference, Washington, D C, September 6 8, 1978 Washington, D C, Marine Technology Society, New York, Institute of Electrical and Electronics Engineers, Inc., 1978, p. 478 484

This paper describes how to employ the accuracy and reliability of the NNSS (TRANSIT) satellite receiver data, as an input to improve the accuracy of a 'NAV' SYSTEM which has multiple input data ports. The multiple sensor data from ten or more inputs are accepted by the covariance matrix computational microprocessor, along with the position fix signals from the JMR-2 Doppler Survey Receiving Sub-system. These data are processed to provide multiple outputs for navigation, survey, control and data logging. The helmsperson is provided with a display and the data are recorded on tape. Since different applications require different sensors, this universal design is capable of accepting signals from many sensors with different characteristics. (Author)

A79-27416 Elimination of scale and luminance distortions in thermal imaging systems with a large field of view V G Klochkova, D N Krasnikov, and B V Ukhov (Optiko-Mekhanicheskaia Promyshlennost', vol 45, May 1978, p 8-10) Soviet Journal of Optical Technology, vol 45, May 1978, p 276 278 Translation

When a thermal image is being recorded on photographic film that is continuously moving past the screen of a CRT operating in single-line scanning mode, the elimination of scale distortions through the use of a nonlinear electron beam sweep leads to a constant ratio of the tangents of the viewing and deflection angles in

the CRT and consequently to considerable film density nonuniformity. The density falloff can be eliminated by increasing the luminance toward the end of the line for a constant signal at the CRT input.

PTH

A79-27424 * # Wind-tunnel studies of the effects of simulated damage on the aerodynamic characteristics of airplanes and missiles M L Spearman (NASA, Langley Research Center, Hampton, Va) American Defense Preparedness Association, Vulnerability and Survivability Symposium, 4th, Tyndall AFB, Fla, Mar 14, 15, 1979, Paper 15 p 7 refs

In order to assess the effects on static aerodynamic characteristics of battle damage to an aircraft or missile, wind tunnel studies were performed on models from which all or parts of the wing or horizontal or vertical tail had been removed. The effects of damage on the lift, longitudinal stability, lateral stability and directional stability of a swept-wing fighter are presented, along with the effects of wing removal on the control requirements of a delta-wing fighter Results indicate that the loss of a major part of the vertical tail will probably result in the loss of the aircraft at any speed, while the loss of major parts of the horizontal tail generally results in catastrophic instability at subsonic speeds but, at low supersonic speeds, may allow the aircraft to return to friendly territory before pilot ejection Major damage to the wing may be sustained without the loss of aircraft or pilot. The loss of some of the aerodynamic surfaces of cruise or surface-to-air missiles may result in catastrophic instability or may permit a ballistic trajectory to be maintained, depending upon the location of the lost surface with respect to the center of gravity of the missile ALW

A79-27571 * Simultaneous measurements of ozone outside and inside cabins of two 8-747 airliners and a Gates Learjet business jet P J Perkins and D Briehl (NASA, Lewis Research Center, Cleveland, Ohio) In Conference on Atmospheric Environment of Aerospace Systems and Applied Meteorology, New York, N Y, November 14-16, 1978, Preprints

Boston, Mass , American Meteorological Society, 1978, p. 39 44 15 refs

Recently, passengers and crew members on long distance commercial flights have filed complaints after suffering symptoms of ozone sickness. Studies were conducted to determine the frequency and concentration of ozone in commercial jet transports. The airliner problem with ozone prompted NASA to determine the ozone concentrations that might be encountered in the cabin of a small business jet. Simultaneous measurements of atmospheric ozone levels and ozone levels in the cabins of jet aircraft were necessary because of the wide and rapid variability of atmospheric ozone in flight. It was found that the atmospheric ozone concentrations in the case of B-747 airliners vary widely during a flight. A constant difference, or ratio, between ozone concentrations outside and inside the cabin does not exist.

A79-27572 Environmental models for moisture absorption by aircraft composites N D Dvoskin, W A Wolter, and V Jordan (Grumman Aerospace Corp., Bethpage, N Y) In Conference on Atmospheric Environment of Aerospace Systems and Applied Meteorology, New York, N Y, November 14-16, 1978, Preprints

Boston, Mass , American Meteorological Society, 1978, p 45-50 6 refs

A description is presented of the initial portion of a study which was performed to assess the durability of advanced composite materials that have been exposed to realistic moisture environments. The portion described, the environmental definition task, was performed to define the runway exposure of fighter, bomber, and transport aircraft to realistic moisture environments at Air Force bases around the world. Realistic runway storage models for determining moisture absorption of advanced composite structures in Air Force aircraft were defined in terms of hour-by-hour variables for each month of the year. The effects of solar radiation on structural skin surface temperature and relative humidity were computed for a high infrared

emissivity typical of organic finishes and several values of surface solar absorptivity G R

A79-27574 The Dulles International Airport wind-shear detection system - Statistical results: A J Bedard, Jr (NOAA, Wave Propagation Laboratory, Boulder, Colo.) In Conference on Atmospheric Environment of Aerospace Systems and Applied Meteorology, New York, N.Y., November 14-16, 1978, Preprints

Boston, Mass, American Meteorological Society, 1978, p. 57-66, 10 refs. FAA supported research

The Dulles system, comprised of a Doppler acoustic microwave radar and a dense network of surface sensors recorded more than 160 events. The statistics of these events are reviewed and their implications are discussed for the design of systems of surface sensors, particularly for the detection of thunderstorm outflows. Histograms showing frequency of various types of events as a function of month-of-year are considered, taking into account thunderstorms, squall-lines and fronts, boundary layer effects, gravity-shear waves, gravity waves, and high winds. Attention is given to surface wind observations, surface pressure observations, Doppler acoustic-microwave radar observations. The statistics of observations related to boundary layer effects are also examined.

A79 27575 * Stable boundary layer wind shear model for aircraft flight hazard definition W Frost (FWG Associates, Inc, Tullahoma, Tenn), S T Wang (Tennessee, University, Tullahoma, Tenn), and D W Camp (NASA, Marshall Space Flight Center, Huntsville, Ala) In Conference on Atmospheric Environment of Aerospace Systems and Applied Meteorology, New York, N Y, November 14 16, 1978, Preprints Boston, Mass, American Meteorological Society, 1978, p 67-74 10 refs US Department of Transportation Contract No FA76 WAI-620

It is pointed out that wind shear, particularly at the lower altitudes in the terminal area, has been identified as being hazardous to aircraft operations. Accurate and reliable wind profiles are required for use in fast time and manned flight simulation studies aimed at fully defining and understanding the wind shear hazard. A description is presented of wind speed profiles for neutral and stable atmospheric conditions developed for the simulation studies to improve the safety and reliability of operations in the terminal area. The wind shear is mathematically modeled and the mathematical scenarios are presented in a format for direct application to wind shear hazard/flight simulation studies.

A79-27576 * A spectral analysis of thunderstorm turbulence and jet transport landing performance J McCarthy, E F Blick, and R R Bensch (Oklahoma, University, Norman, Okla) In Conference on Atmospheric Environment of Aerospace Systems and Applied Meteorology, New York, N Y, November 14-16, 1978, Preprints

Boston, Mass , American Meteorological Society, 1978, p 75-82 9 refs NSF Grant No ATM-74-03406-A02, Contract No NASS 31377

A description is presented of a study which examines not only wind shear, but considers the velocity spectrum of the wind, as it may affect the flight of an aircraft. A model reported by McCarthy and Blick (1976) and by Blick et al. (1978) is considered. The model simulated the approach performance of a Boeing 727-type aircraft, as affected by the time series winds measured along the aircraft's longitudinal axis. Attention is given to the model and its implications, wind shear simulations, and the use of the model in the study of a crash on June 24, 1975.

A79-27599 # Path in rocket technology Selected works, 1924-1946 (Put' v raketnoi tekhnike - Izbrannye trudy, 1924-1946) V P Glushko Moscow, Izdatel'stvo Mashinostroenie, 1977 503 p 123 refs. In Russian

Selected papers are presented from the early period of the work of V P Glushko, the rocket pioneer. The papers cover a wide range

of subjects, including rocket engine design, fuel injection systems, and combustion processes. A bibliography of works published by Glushko in the period 1924-1945 on jet and rocket engines and interplanetary flight is presented.

A79-27648 # Introduction to the computer-aided design of flight vehicles (Vvedenie v mashinnoe proektirovanie letatel'nykh apparatov) V P Mishin and M I Osin Moscow, Izdatel'stvo Mashinostroenie, 1978 128 p 68 refs. In Russian

The basic principles of the computer aided design of spacecraft are formulated and attention is given to various methods of design optimization, with particular emphasis placed on numerical methods of structural synthesis. As examples, algorithms for the design and optimization of planetary descent vehicles and interplanetary probes are examined.

.

A79-27656 Cryohydrogen-fuel for tomorrow's commercial aircraft G D Brewer (Lockheed-California Co, Burbank, Calif) in Applications of cryogenic technology Volume 7 - Proceedings of the Conference on Cryogenic Energy Systems, Oak Brook, III, May 16-18, 1978 Flushing, N Y, Scholium International, Inc., 1978, p. 87-104, 6 refs

Studies performed for NASA on the potential use of liquid hydrogen as an aircraft fuel are summarized Particular consideration is given to a recently completed study on how utilization of LH2 will affect the design of the engine and fuel system for a representative subsonic passenger transport. It is concluded that adoption of cryohydrogen as the fuel for future commercial aircraft will reduce the need for oil imports, reduce pollution, and provide lower cost and more energy-efficient transportation.

A79-27666 Air Force applications of lightweight superconducting machinery C E Oberly (USAF, Aero Propulsion Laboratory, Wright-Patterson AFB, Ohio) In Applications of cryogenic technology Volume 7 - Proceedings of the Conference on Cryogenic Energy Systems, Oak Brook, III, May 16-18, 1978

Flushing, N Y , Scholium International, Inc , 1978, p 293-334 45 refs

Consideration is given to the dominant factors which affect the development of such Air Force airborne superconducting machinery as alternators, MHD magnets, and energy storage devices. These factors include lightweight structure design and severe losses induced by transient fields and conductor motion. Adequate structure, stabilizing matrix and cooling are difficult to design because of weight and volume restrictions. The promise of greater thermal margin in advanced superconducting materials such as flexible multifilament Nb3Sn and the weight saving potential of advanced structural materials provides impetus for continued Air Force development programs.

B J

A79-27672 New airborne display concepts (Nouveaux concepts des visualisations embarquees) M Coussedière (Thomson CSF, Paris, France) (Colloque sur l'Integration des Systemes, Paris, France, Feb 10, 11, 1977) Sciences et Techniques de l'Armement (Mémorial de l'Artillerie Française), vol 52, no 4, 1978, p 613-627 In French

The paper outlines some novel concepts for airborne display systems. The concepts are intended to suppress the overburden imposed on aircrew members by the increasing number of display, monitoring and control instruments in the cockpit. Various electronic devices using very high luminance multichrome CRTs allow integration of a large number of data into small-size instruments. New technologies presently studied (plasmas, liquid crystals, LEDs, etc.) are expected to supersede the CRT-based instrumentation, with other specific applications in the near future.

A79-27674 Study of the structure of an integrated system of flight control, navigation and display (Etude d'organisation d'un

système integré de pilotage, navigation et visualisation) C Roquefeuil (Colloque sur l'Intégration des Systemes, Paris, France, Feb 10, 11, 1977) Sciences et Techniques de l'Armement (Mémorial de l'Artillerie Française), vol 52, no 4, 1978, p 639-656 In French

The integrated system under study is intended for transport aircraft. Optimization of the efficiency/cost ratio has lead to the adoption of tradeoffs between automatic and instrument control, centralized and shared processing, analog and digital processing, multiplex digital links (bus) and separate links, and electronic and electromechanical displays. The proposed structure separates from the rest of the system the set of equipment needed for the critical landing in poor visibility condition.

A79-27675 Tests of an integrated piloting, navigation, and display system (Essais d'un système intégre de pilotage, navigation et visualisation) A Klopfstein (Centre d'Essais en Vol, Bretigny-sur-Orge, Essonne, France) (Colloque sur l'Intégration des Systemes, Paris, France, Feb 10-11, 1977) Sciences et Techniques de l'Armement (Memorial de l'Artillerie Française), vol 52, no 4, 1978, p 657-670 In French

The paper describes an experimental integrated piloting, navigation, and display system to be flown in a Caravelle test bed. A series of ground tests, flight simulator tests, and flight tests is planned. The testing program will be used to evaluate the capability of the system to meet the main goals of reducing crew work load, optimizing pilot-system dialog, adaptation and evolution suppleness, maintainability, performance improvement, and safety increase.

A79-27727 Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics R S Agachev and B A Kumirov (Aviatsionnaia Tekhnika, vol. 21, no. 1, 1978, p. 10-15.) Soviet Aeronautics, vol. 21, no. 1, 1978, p. 5-9 Translation

A method for calculating the velocity loss coefficient in the steady two dimensional flow behind air cooled turbine blades is proposed, and the theoretical assumptions employed are verified experimentally Experimental results obtained with blades perforated at the leading edge showed that the cooling air blowing intensity has a very small effect on the velocity losses and the blade exit angle Likewise, the influence of coolant discharge on the pressure distribution over a perforated blade was found to be insignificant

V P

A79-27728 Two-frequency-range theory of unstable turbulent combustion oscillations in a jet engine combustion chamber II - Analysis of the characteristic equation and comparison with experiment S K Aslanov (Aviatsionnaia Tekhnika, vol. 21, no. 1, 1978, p. 16-21.) Soviet Aeronautics, vol. 21, no. 1, 1978, p. 10. 14. 6 refs. Translation

A79-27731 Instability of fluid flow in centrifugal injector B S Drobiazko and V P Pavlovskii (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 37-41) Soviet Aeronautics, vol 21, no 1, 1978, p 27 30 Translation

The spontaneous changes in the mode of operation of two-component swirl injectors, leading to abrupt changes in flow rate and pressure gradient, were studied experimentally. This phenomenon is shown to be associated with the instability of the continuous swirling flow and rapid transition of the swirling flow to a cavitating flow.

. V E

A79-27737 Influence of bypass ratio on jet engine weight N S Lamekin and A S Bogdanov (Aviatsionnaia Tekhnika, vol. 21, no. 1, 1978, p. 68-73.) Soviet Aeronautics, vol. 21, no. 1, 1978, p. 52-56. Translation

In the method proposed for calculating the weight of a bypass turbojet engine, the weight is expressed as a cubic polynomial in the

characteristic dimension. The calculation of the weight of a bypass engine is illustrated by an example. The influence of the thrust and the bypass ratio on engine weight is evaluated. It is shown that bypass ratios between 5 and 7 should be used in minimum-weight design.

V.P.

A79-27740 Comparison of BTJES and TJE characteristics in supersonic cruising flight B D Fishbein (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 86-92) Soviet Aeronautics, vol 21, no 1, 1978, p 67-71 8 refs Translation

The paper deals with the nonlinear programming problem of fuel minimization for a boosted bypass turbojet engine at a thrust equal to that of a conventional turbojet engine. The problem is solved by a method of direct search without recourse to derivatives. The results are diagrammed and discussed.

A79-27742 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element V K Shchukin, A A lakshin, V A Filin, N S Idiatullin, and N A Nadyrov (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 100-104) Soviet Aeronautics, vol 21, no 1, 1978, p 77-80 6 refs Translation

The experiments described were carried out to study the local convective heat transfer from a gas flow with suspended finely dispersed 0.2 to 12-micron aluminum oxide particles to the walls of a throttle whose flow area consists of two plane curvilinear supersonic nozzles. The presence of the particles was found to intensify substantially the heat release to the wall

A79-27743

Axial compressor operation with radially non-uniform inflow A N Aniutin, A F Brekhov, V N Ershov, and V G Prokopovich (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 105-107) Soviet Aeronautics, vol 21, no 1, 1978, p 81-83 Translation

The structure of the flow in two three stage axial-flow compressors was studied at uniform and radially nonuniform inlet flows, at a peripheral speed of 118 m/sec at the blade tips. Traversing of the flow behind the rotors and at the inlet was carried out. The results obtained indicate that the individual stages act to equalize the flow. This compensating action of the stages is quantitatively assessed. V.P.

A79-27744 Influence of bypass ratio change on fan aerodynamic characteristics V P Gerasimenko, V N Ershov, V A Koval', and G V Pavlenko (Aviatsionnaia Tekhnika, vol. 21, no. 1, 1978, p. 108-111.) Soviet Aeronautics, vol. 21, no. 1, 1978, p. 84-86 Translation

In the wind tunnel experiments described, the influence of changes in bypass ratio on the characteristics of the main duct, the region of stable fan operation, and the incipient traveling stall was studied. Bypass ratios of 0.5, 1.0, and 2.0 were used in the tests. The results are plotted and discussed.

A79-27745 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A I Gleizer (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 111-113) Soviet Aeronautics, vol 21, no 1, 1978, p 87-90 7 refs Translation

The paper deals with the problem of optimizing the balancing of flexible gas-turbine engine rotors by rational selection of the balancing parameters. A solution is obtained by a search technique where a point in the parameter space is defined by means of numbers which form a specific sequence (the so-called LP-sequence). The effectiveness of the balancing technique proposed is demonstrated by examples.

A79-27746 Method for digital computer calculation of unsteady temperature fields in turbomachine discs V V Zhuikov and V I Lokai (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 114-120) Soviet Aeronautics, vol 21, no 1, 1978, p 91-96 Translation

A numerical method is proposed for calculating steady and unsteady temperature fields in the meridional cross sections of turbine disks for time variable boundary conditions over the disk profile. The temperature dependence of the disk material's heat conductivity is taken into consideration. For illustration, the method is applied to practical examples.

A79-27748 Intensification of fuel vaporization in aircraft gas turbine engines by electrical forces. A S Kokin, 8 G Popov, and V A Bondar' (Aviatsionnaia Tekhnika, vol 21, no 1, 1978, p 124-127) Soviet Aeronautics, vol 21, no 1, 1978, p 101-104 6 refs Translation

A79-28034 An optical communication system for aircraft T N Rodgers (USAF, Armament Development and Test Center, Eglin AFB, Fla) In Laser and fiber optics communications, Proceedings of the Seminar, San Diego, Calif , August 28, 29, 1978 Bellingham, Wash , Society of Photo-Optical Instrumentation Engineers, 1978, p. 108-113

The design objectives of the Optical Communicator System (OCS) are to minimize problems associated with the modification of a USAF aircraft in order to render it capable of supporting an RDT&E effort. With the OCS, data is transmitted via a modulated noncoherent light beam from the data source to the instrumentation pod. Wiring is confined to the amount required to obtain the data and connect it to the OCS components located in the instrumentation pod. Thus the OCS decreases the cost of modifications and will allow carriage of instrumentation pods aboard aircraft that previously could not be modified by conventional methods.

A79-28040 Military fiber optics applications D J Albares (U S Naval Ocean Systems Center, San Diego, Calif) In Laser and fiber optics communications, Proceedings of the Seminar, San Diego, Calif , August 28, 29, 1978 Bellingham, Wash , Society of Photo-Optical Instrumentation Engineers, 1978, p 160-162 18 refs

Advantages of fiber optics over electrical transmission anticipated for military systems as well as for many commercial applications include wide bandwidth, low attenuation, small size and weight, immunity from electrical interference, absence of signal leakage or crosstalk, and high temperature tolerance Optical fiber communications offers major improvements in the vital areas of weight, size, and susceptability to EMI, EMP, and crosstalk to military aircraft. For fixed and mobile landbased military systems the advantages of interference immunity, lack of signal leakage, wide bandwidth, and small size and weight offered by fiber optics are very important. Attention is also given to shipboard and undersea applications.

A79-28058

Multimode radar processor J R Gaskill, Jr, L F Goldstein, E J Kapp, E Trujillo (Hughes Aircraft Co, Culver City, Calif), and J P Shanklin (USAF, Avionics Laboratory, Wright-Patterson AFB, Ohio) In Real time signal processing, Proceedings of the Seminar, San Diego, Calif, August 28, 29, 1978

Bellingham, Wash, Society of Photo-Optical Instrumentation Engineers, 1978, p 141-149

The multimode radar processor (MRP) is a general purpose programmable digital signal processor for multimode radar avionic systems in high-performance combat aircraft. Based on LSI ECL, MRP implements a shared resource architecture organized to take advantage of the structured nature of signal processing functions and thus performs these functions at speeds much higher than possible with a general purpose computer. Through its highly reconfigurable

modular design, the MRP can fill the requirements of many different sensor applications and thus potentially demonstrates lower cost and higher reliability

B J

A79-28097 IR scanning camera measurements of an exhaust plume from an axisymmetric nozzle afterbody model at transonic Mach numbers J A Roux (ARO, Inc., Arnold Air Force Station, Tenn.) and R Glidewell (USAF, Aero Propulsion Laboratory, Wright-Patterson AFB, Ohio) In Modern utilization of infrared technology IV, Proceedings of the Seminar, San Diego, Calif., August 30, 31, 1978 Bellingham, Wash., Society of Photo-Optical Instrumentation Engineers, 1978, p. 215-232

An AGA Thermovision System 680 was used in studying the IR signature from an axisymmetric nozzle afterbody model at transonic Mach numbers (M=0.0,0.6,0.9,1.3). Radiance measurements from the exhaust plume in the CO2 emission band were observed through a narrow spectral filter (4.21-4.41 microns). Results are presented in the form of axial and radial plume radiance profiles. Such spatially resolved plume radiance measurements serve as a flow visualization to reveal shock structure and as a baseline for plume radiation model prediction. (Author)

A79-28122 Air Force applications for optical rotation rate sensors W K Stowell (USAF, Avionics Laboratory, Wright-Patterson AFB, Ohio), R W McAdory (USAF, Armament Laboratory, Eglin AFB, Fla), and R Ziernicki (USAF, Systems Command, Andrews AFB, Washington, D C) In Laser inertial rotation sensors, Proceedings of the Seminar, San Diego, Calif, August 30, 31, 1978 Bellingham, Wash, Society of Photo-Optical Instrumentation Engineers, 1978, p. 166-171

Optical rotational sensors (ORSs) based on laser technology are ideal strapped down devices showing great potential for use in advanced inertial systems. Possible applications include aircraft inertial reference systems, tactical weapon guidance, attitude and rate sensing in flight control, ballistic missiles, strategic cruise missiles, pointing, and tracking. A critical factor common to all these applications, regarding ORSs in general and ring laser gyros in particular, is cost. This, and some other major factors that could prolong the entry of ORSs into the Air Force inventory are examined.

A79-28139

Aircraft velocity and altitude measurements using a tunable diode laser M J Rudd (Bolt Beranek and Newman, Inc., Cambridge, Mass.) In Laser spectroscopy - Applications and techniques, Proceedings of the Seminar, San Diego, Calif., August 30, 31, 1978

Bellingham, Wash., Society of Photo-Optical Instrumentation Engineers, 1978, p. 150-155 6 refs. Contract No. F49620-78-C-0023

A technique is proposed here for the on board measurement of an aircraft's speed and altitude by measuring the Doppler shift and linewidth of laser radiation which is resonantly scattered from carbon dioxide molecules in the air. The system employs a small, low power, tunable laser diode which gives a small, lightweight system with low power consumption. The technique promises to work very well at high altitudes (100,000 ft) and speeds (Mach 10). (Author)

A79-28160

A three-channel high resolution-TV image generation system J A Mays and R E Holmes (Systems Research Laboratories, Inc., Dayton, Ohio) In Visual simulation and image realism, Proceedings of the Seminar, San Diego, Calif., August 30, 31, 1978

Bellingham, Wash., Society of Photo-Optical Instrumentation Engineers, 1978, p. 28-35

The paper deals with a three-channel high-resolution imagegeneration system which consists of a matrix of three TV cameras capable of operating with the output of a single wide-angle (140 deg FOV) optical probe The TV cameras are capable of correcting the geometrical errors of the optical probe, the television display, and display optics as well as the internal scanning errors of the cameras themselves from an external control panel. Three video images, in conjunction with a suitable matrix of displays, are capable of presenting a continuous visual scene, 140 deg wide and 45 deg high, with a resolution of 2400 TV lines per picture width.

V.P.

A79-28161 Aviation wide angle visual system /AWAVS/-Visual system performance E F Kashork (US Navy, Naval Training Equipment Center, Orlando, Fla) and J A Turner (Singer Co , Link Div , Kirkwood, NY) In Visual simulation and image realism, Proceedings of the Seminar, San Diego, Calif , August 30, 31, 1978 Bellingham, Wash , Society of Photo-Optical Instrumentation Engineers, 1978, p 36-42

This paper is intended to provide a continuance of information and data on the Navy's Wide Angle Visual Flight Simulator, designed to investigate improvements in visual systems technology and define simulator hardware performance requirements for Naval Aviation training. A general overview of the visual system hardware and its developed performance levels is presented. The initial configuration for carrier takeoff and landings includes a high resolution monochrome television camera which generates a narrow field of view target displayed in a low resolution seascape background. The target image is inset into the background and both images are electronically corrected for lens and perspective distortions by raster computers. The simulation has negligible error in perspective distortion to a target range of 2300 feet, and within 2 arc minutes beyond. Current visual performance measurements are presented and discussed.

(Author)

A79-28184 Siting criteria for MLS stations II R M Cox and E F Kolb (Bendix Corp., Communications Div., Baltimore, Md.) Airport Forum, vol. 9, Feb. 1979, p. 35-38, 40, 42-44. In English and German

Siting criteria for MLS stations are discussed, considering azimuth and elevation antenna site, the missed-approach azimuth and flare antenna siting, the co-location of MLS with ALS and ILS, site preparation, installation, as well as checkout and calibration. An MLS ground station is normally configured so as to match the equipment to the specific site, thereby minimizing the investment equipment, with the goal being uniform quality signal-in space at all sites. The widest acceptable beamwidth must be chosen for basic antennas, currently available in 1 to 3 deg beamwidths. Flare (15 deg) and missed approach (3 deg) antennas may be added where needed, while redundancy and no-break power may be added where required. The basic antennas are sited in a manner similar to ILS, although MLS is tolerant of most adverse situations, and grading and filling is not required. Installations and checkout procedures are not extensive, and certification procedures are expected to be somewhat simpler than those required for ILS

A79-28185 An offshore airport that works - Nagasaki M Hirai (Japan Civil Aviation Bureau, Planning Div , Tokyo, Japan) Airport Forum, vol 9, Feb 1979, p 69 74 In English and German

The construction of the Nagasaki airport (completed in 1975) is considered, noting that the noise problem was completely solved through the offshore location. Parameters of flight operations, size and speed of aircraft, and passenger numbers are presented, indicating sharp increases in all these areas from 1975 to 1978. The regularity of operations is assessed, showing excellent results. It is concluded that there is a growing possibility that scheduled international services may be inaugurated fairly soon.

A79-28223 Design of proportional-plus-integral controllers for multivariable systems H Seraji (Arya Mehr University of Technology, Teheran, Iran) International Journal of Control, vol 29, Jan 1979, p. 49-63 9 refs

The paper puts forward a simple method for the design of multivariable proportional-plus-integral (PI) controllers to achieve pole placement. The controller acts directly on the available outputs of the system so that complications of state reconstruction and implementation of state feedback are avoided.

PTH

A79-28251 Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads Conference sponsored by AIAA, ASME, ASCE, and AHS New York, American Institute of Aeronautics and Astronautics, Inc., 1979, 371, p. \$50

Papers are presented on such topics as minimum weight structural design by the optimality criterion and projection method, divergence of forward swept wings, aeroelastic tailoring studies in fighter aircraft design, and finite element approaches for determining stresses and internal forces in geometrically nonlinear structural analysis. Consideration is also given to design and fabrication of advanced titanium structures, the reentry performance of carbon-carbon nosetips, statistical estimation of economic life for aircraft structures, and static strength predictions for bolted joints in composite materials.

A79-28252 # SDM lecture - Introduction of new SDM technology into production systems R N Hadcock (Grumman Aerospace Corp , Bethpage, N Y) In Structures, Structural Dynamics, and Materials Conference, 20th, St Louis, Mo , April 4-6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 1-10 21 refs (AIAA 79-0719)

The application of new Structures, Structural Dynamics and Materials (SDM) technology to aircraft design is a long and difficult process. Necessary ingredients include need, availability, opportunity, confidence, and an acceptable cost. The present paper examines some past examples (WWII fighter aircraft) of new SDM technologies and presents the best approach for removing many of the difficulties and accelerating the process.

A79-28255 # Divergence of forward swept composite wings T A Weisshaar (Virginia Polytechnic Institute and State University, Blacksburg, Va) In Structures, Structural Dynamics, and Materials Conference, 20th, St Louis, Mo , April 4-6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc , 1979, p 51-59 11 refs Grant No AF-AFOSR-77-3423 (AIAA 79-0722)

A laminated box beam model is used to develop algebraic expressions for predicting the static aeroelastic divergence characteristics of forward swept wings constructed of composite materials Aerodynamic strip theory is used to predict the loads due to wing bending and torsional deformation. The expressions presented show that because of elastic coupling between wing bending and torsion the wing divergence may be precluded for reasonably large forward sweep angles.

B J

A79-28257 # Aeroelastic tailoring studies in fighter aircraft design W E Triplett (McDonnell Aircraft Co, St Louis, Mo) In Structures, Structural Dynamics, and Materials Conference, 20th, St Louis, Mo, April 4-6, 1979, Technical Papers on Dynamics and Loads

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 72-78. 5 refs. (AIAA 79-0725)

Studies have been conducted on the use of the directional properties of composite material to provide design improvements for fighter aircraft. The TSO (Aeroelastic Tailoring and Structural Optimization) computer program, which was developed by the AFFDL, was used in these investigations. The configurations evaluated covered a wide spectrum of fighter aircraft aerodynamic surfaces, including (1) the F-15 composite wing, (2) a preliminary

design horizontal tail, (3) a prototype aircraft wing and (4) a future conceptual aircraft wing Both drag reduction and increased roll effectiveness, with no weight cost, are predicted for the F-15 composite wing A unique minimum weight design is shown for the preliminary design horizontal tail, in which the anisotropic characteristics of the composite material are used to perform the dual function of strength and flutter balance weight A more conventional optimum flutter solution, based on outer panel wing root pitch restraint increases, is shown for the prototype aircraft wing Finally, significant wing twist, offering potential aerodynamic benefits, can be obtained on the conceptual aircraft wing (Author)

A79-28258 # An aeroelastic optimization procedure for composite high aspect ratio wings D Gimmestad (Boeing Co., Seattle, Wash.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 79-86 8 refs. (AIAA 79-0726)

A computer program has been developed which optimizes the structure of a composite high aspect ratio wing. The program sizes composite box beam structure using aeroelastic loads in an iterative fashion. Anisotropic beam bending-torsion coupling effects are included. An aeroelastic design demonstration was performed which shows some of the effects of beam anisotropy on aeroelastic loads, structure weight, stability and control and flutter for both composite and conventional metal wings.

(Author)

A79-28260 # Structural development of the Modernized Chinook helicopter transmission gearing C O Albrecht (Boeing Vertol Co., Philadelphia, Pa.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads
York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 96-104 (AIAA 79 0728)

The CH-47D or Modernized Chinook helicopter utilizes the most recent state-of-the-art drive system developments for the design, fabrication, and qualification of its four different gearboxes. Those developments related to gearing include use of finite element analyses, fabrication techniques that eliminate bolted joints, and the use of gear stress measurements as part of the qualification program. The means by which structural optimization of the gearing is obtained using these approaches is discussed (Author)

A79-28263 * # Accuracy of an approximate static structural analysis technique based on stiffness matrix eigenmodes J Sobieszczański-Sobieski (NASA, Langley Research Center, Hampton, Va) and P Hajela (Iowa State University of Science and Technology, Ames, Iowa) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4 6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 127-136 (AIAA 79-0748)

Use of the stiffness matrix eigenmodes, instead of the vibration eigenmodes, as generalized coordinates is proposed for condensation of static load deflection equations in finite element stiffness method. The modes are selected by strain energy criteria and the resulting fast, approximate analysis technique is evaluated by applications to idealized built up wings and a fuselage segment. The best results obtained are a two-order of magnitude reduction of the number of degrees of freedom in a high aspect ratio wing associated with less than one percent error in prediction of the largest displacement.

(Author)

A79-28270 # Structural aluminum materials for the 1980's R F Simenz and M K Guess (Lockheed-California Co., Burbank, Calif.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on

Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 181-187, 12 refs. (AIAA 79-0755)

Developments in processing and alloying techniques have resulted in property improvements and increased potential application for advanced aluminum alloys in both subsonic and supersonic aircraft Lockheed-California Company engineers see the advanced aluminum alloys emerging as a promising material in addition to the advanced composites and titanium alloys for current and future aircraft. Alloys receiving the bulk of attention include the high-strength corrosion-resistant 7050 alloy, the high-strength CT90, CT91 and 9051 powder alloys, and the aluminum-lithium alloys for subsonic applications. Combinations of powered alloys, aluminum-lithium and mechanical alloying are being considered for high temperature supersonic applications. (Author)

A79-28272 # Design and fabrication of advanced titanium structures C Paez and R W Messler, Jr (Grumman Aerospace Corp , Bethpage, N Y) In Structures, Structural Dynamics, and Materials Conference, 20th, St Louis, Mo , April 4 6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p 208-220 13 refs USAF supported research (AIAA 79 0757)

The paper deals with some advanced processing technologies developed for titanium fabrication. The weight advantages are documented which are achievable when innovative structural design concepts are employed. Hot isostatic pressing and welding as a means of building up structures are discussed, along with specific application areas. Superplastic forming/diffusion bonding is given particular attention, including such specific areas as material superplasticity, diffusion bonding, process parameters and their effects on material properties, skin stabilization techniques, and structural concepts for advanced airframes.

A79-28275 # Statistical estimation of economic life for aircraft structures J N Yang (George Washington University, Washington, D.C.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4 6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 240-248 33 refs. Contract No. F33615 77-C-3123 (AIAA 79-0761)

An analytical methodology for statistically predicting the economic life of aircraft structures is presented. The approach allows for the determination of the economic life based on either one of the following two criteria. (1) rapid increase of the number of crack damages exceeding the economic repair crack size, and (2) rapid increase of the maintenance cost, including the costs of inspection and repair. The formulation is general enough for practical applications. While the inspection and repair maintenance procedure has a significant impact on aircraft structural reliability and safety, its effect on the economic life is shown to be limited. Numerical examples are worked out to demonstrate the application of the methodology.

(Author)

A79-28287 # Structural stiffening of transmission housings with metal matrix materials J W Lenski, Jr (Boeing Vertol Co., Philadelphia, Pa.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 333-340.5 refs. Grant No. DAAJ02-74-C-0040. (AIAA 79-0806)

The application of metal matrix composite materials for helicopter transmission housing has many potential benefits including decreased deflections, increased dynamic component life and reduced vibration/noise levels. These improvements result from the selective stiffening of identified areas of high strain density. The effects of substituting metal matrix composites for a monolithic magnesium transmission housing has been evaluated both analytically and experimentally. Noise levels and accelerations were measured on a CH-47C

forward transmission which was selectively stiffened. In addition, basic housing elements have been fabricated using high-modulus fibers (Fiber FP) via direct casting technology and tested to determine material properties. Initial test results indicate a three time increase of the modulus of elasticity of magnesium by the use of a Fiber FP/magnesium metal matrix composite material. (Author)

A79-28288 # Fuel tank sealant requirements for advance high performance aircraft M F George, Jr and R V Burton, Jr (Lockheed California Co, Burbank, Calif) In Structures, Structural Dynamics, and Materials Conference, 20th, St Louis, Mo, April 4-6, 1979, Technical Papers on Dynamics and Loads New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 341-345 (AIAA 79-0807)

Advanced integral fuel tank sealants for high performance aircraft will be discussed identifying material property requirements to perform satisfactorily in the environment and airframe design. To provide continuity, a brief historical evolution of material systems will be presented including evaluated elastomers and developmental problems. Laboratory and flight test experience confirmed practicality of production application, handling and field performance.

(Author)

A79-28289 # Design and development of an helicopter rotor hub and elastomeric bearing P Donguy (Societe Europeenne de Propulsion Saint-Medard en-Jalles, Gironde, France) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 348-355 (AIAA 79-0815)

The paper deals with some recent advances which resulted in the development of a spherical laminated elastomeric bearing for a light helicopter rotor hub. One of the main problems encountered was service life, which was found to depend strongly on good shaping. The 'hydroflex' technique is shown to be very promising both with respect to service life and ease of designing.

A79-28290 * # Combined strength and aeroelastic wing synthesis via constraint approximation J Mullen, Jr (Nielsen Engineering and Research, Inc., Mountain View, Calif.) In Structures, Structural Dynamics, and Materials Conference, 20th, St. Louis, Mo., April 4-6, 1979, Technical Papers on Dynamics and Loads

New York, American Institute of Aeronautics and Astronautics, Inc., 1979, p. 356-366 24 refs. Contract No. NAS2 8558 (AIAA 79-0724)

A numerical optimization program using constraint approximations for preliminary sizing of wing structural design parameters to satisfy simultaneous strength and aeroelastic requirements is described. The effects of wing flexibility on loads and flutter are included. The iterative procedure approximates wing internal load distributions and flutter response in generating design constraints. Though a linear Taylor series approximation to the variation of flutter speed is made, constraints in general are formulated as nonlinear and solved in a minimum weight problem using a feasible directions search. The technique is demonstrated for the determination of the optimal ply orientations and for simultaneous sizing for strength and flutter with simple constraint approximations. (Author)

A79-28376 # Wing rock due to aerodynamic hysteresis L V Schmidt (U S Naval Postgraduate School, Monterey, Calif) Journal of Aircraft, vol. 16, Mar. 1979, p. 129 133 9 refs

An analysis is presented using control theory concepts to show that aerodynamic hysteresis of the form of relay action can lead to lateral-directional limit cycle motions. These limit cycle motions are usually described in a colloquial sense as airframe wing rock. The aerodynamic details leading to wing-rock oscillations will vary with airframe configuration, and usually the exact description of the aerodynamic nonlinearity is difficult to obtain or predict. The pur pose of the studies described herein is to promulgate a flight mechan.

ics analysis technique which by virtue of its simplicity offers the analyst an insight into potential candidate aerodynamic mechanisms (Author)

A79-28377 # Formation of a trailing vortex M S Francis (USAF, Frank J Seiler Research Laboratory, Colorado Springs, Colo) and D A Kennedy (Colorado, University, Boulder, Colo) Journal of Aircraft, vol 16, Mar 1979, p 148-154 16 refs USAF-sponsored research

The incompressible flowfield in the vicinity of a lifting rectangular finite wing is investigated experimentally to ascertain the nature and detailed characteristics of the formation of a trailing vortex. The mean velocity field was mapped directly using a linearized constant temperature hot-wire anemometry probe in conjunction with a precision wind-tunnel traversing mechanism. The associated vorticity field was inferred from these measurements through a spatial contour integration procedure. The existence of several identifiable flow regions exhibiting similar characteristics was established and verified with both hot-wire and flow visualization data. The nature of the near surface bound vorticity distribution is described including a map of the Prandtl-bound vortex filaments. Measurements at the wing trailing edge show that the properly nondimensionalized characteristic vorticity distribution in this region is independent of angle of attack Shed vorticity emanating from the lower aerodynamic surface near the wing tip was observed to roll up adjacent to the tip and roll over onto the upper wing surface at a chordwise location which depends on the wing orientation. The presence and behavior of this structure which possesses an identifiable core is suggested as the cause of the modified pressure distribution (lift increment) normally observed in this region (Author)

A79-28380 # Factors affecting residual strength prediction of a cracked aircraft structure M M Ratwani and D P Wilhem (Northrop Corp , Hawthorne, Calif) Journal of Aircraft , vol 16, Mar 1979, p 209-214 6 refs Contract No F33615-72-C-1796

Various factors influencing the analytical residual strength prediction of a cracked, stiffened structure are discussed. The influence of flexibility of attachment on crack openings, stresses in the substructure and fasteners, and J-integral values are presented. The flexibility of a fastener is shown to have considerable influence on the elastic stress intensity factors. The J-integral values computed by assuming an elastic, Dugdale-type plastic zone, and Pradtl-Reuss material behavior are compared. The analytical results of crack openings and strains in the stiffeners are compared with experimental results.

(Author)

A79-28381 # A decision theory model for health monitoring of aeroengines V V S Sarma (Indian Institute of Science, Bangalore, India), K V Kunhikrishnan, and K Ramchand *Journal of Aircraft*, vol. 16, Mar. 1979, p. 222-224, 7 refs.

The Spectrometric Oil Analysis Program (SOAP) is an indirect method of health monitoring of aeroengines. Under SOAP the volume of lubricating oil in the engine sump and the concentration of various metals in the oil are of prime importance. The concentrations of the desired elements are directly used to represent engine wear. In this paper a decision theoretical model using SOAP data for the health monitoring of aeroengines is developed. A deterministic model and a stochastic model are derived and discussed. A technique (sequential probability ratio test) that uses a combination of Kalman filtering and decision theory is presented for the problem of malfunction detection in aeroengines through oil sample analysis.

STAR ENTRIES

N79-17794 British Library Lending Div Boston Spa (England) COMPARISON OF THE AERODYNAMIC PROPERTIES OF AN AEROPLANE WITH THE TAIL-FIRST CONFIGURATION AND WITH THE CONVENTIONAL CONFIGURATION

J Staszek Nov 1978 27 p refs Transl into ENGLISH from Pr Inst Lotnictwa (Poland) v 63 1975 p 63-77 (BLL-RTS-11520) Avail British Library Lending Div Boston Spa Engl

The range of lift and drag coefficients was determined for the wing alone and for the wing together with the tailplane for the tail-first configuration in comparison with conventional layout. The effect of deflection of the streams flowing from the tailplane on the main wing in the tail-first configuration was analyzed as a way of reducing the influence of deflection of the streams by the following means: (1) employment of wing twist for a preferred angle of attack. (2) selection of the angle of incidence of the tailplane (3) selection of correct aspect ratio of the tailplane and (4) selection of optimum location of the wing relative to the tail. Results indicate that in certain conditions the tail-first configuration has characteristics that are similar to the properties of the conventional layout and in certain configurations it is preferable in view of the possibility of obtaining maximum values of the lift coefficient.

N79-17796*# National Aeronautics and Space Administration Ames Research Center Moffett Field Calif

AERODYNAMIC PROPERTIES OF A FLAT PLATE WITH CAVITY FOR OPTICAL-PROPAGATION STUDIES

Donald A Buell Jan 1979 100 p refs (NASA-TM-78487 A-7450) Avail NTIS HC A05/MF A01 CSCL 01A

Transonic wind-tunnel tests were performed on a flat plate with and without a cube-shaped cavity and antiresonance devices Measurements were made of the optical propagation and serodynamic properties of the boundary and shear layers. The model and its velocity profiles and pressures are described.

SES

N79-17797*# National Aeronautics and Space Administration Hugh L Dryden Flight Research Center Edwards Calif

AN IMPROVED SYSTEM FOR USE IN CONDUCTING WAKE INVESTIGATION FOR A WING IN FLIGHT Patent Applica-

Lawrence C Montoya and Paul F Bikle inventors (to NASA) Filed 28 Feb 1979 19 p

(NASA-Case-FRC-11024-1 US-Patent-Appl-SN-015983) Avail NTIS HC A02/MF A01 CSCL 01A

A pressure measuring system is described for use in obtaining in-flight wing profile drag measurements for low values of dynamic pressure and Reynolds number. The system is supported by a wing in flight which has a total pressure head arranged in spaced relation with a wake (as the wake is generated by the wing) and a reference static pressure head adapted to be displayed along an accurate path through the wake. A total pressure port and a static pressure port are included. A differential transducer is connected to the heads through a pressure switching device provided to selectively connect the heads to the transducer in opposed relation. Thus, a single differential transducer is adapted to be utilized in obtaining differential pressure measurements for the wake.

N79-17798*# Bell Aerospace Textron Buffalo N Y
GENERAL PURPOSE COMPUTER PROGRAM FOR INTERACTING SUPERSONIC CONFIGURATIONS USER'S
MANUAL

W Crill and B Dale [1977] 115 p refs (Contract NAS1-13986)

(NASA-CR-145128) Avail NTIS HC A06/MF A01 CSCL 01A

The input data required to execute the computer program ISCON are described. The program generates a numerical procedure for the determination of unsteady aerodynamic forces on arbitrarily interacting wings and tails in supersonic flow. A velocity potential gradient method is used. Constant Mach number is assumed throughout the flow field. Lifting surfaces are represented by trapezoidal elements which can be generated automatically by the program. The wake field is represented by rectangular strip elements. The formulation is reviewed as well as input overview and input format. Instruction on how to use ISCON a sample problem and the restart feature are discussed. Program size limitations computer program flow and error messages are also included along with a description of the SS31 program used to compute the coefficients of surface spline.

ARH

N79-17799*# Boeing Commercial Airplane Co Seattle Wash SUMMARY REPORT OF THE SECOND WIND TUNNEL TEST OF THE BOEING LFC MODEL

D George-Falvy 26 Jul 1978 27 p refs (Contract NAS1-14630)

(NASA-CR-157792) Avail NTIS HC A03/MF A01 CSCI

An 8-ft span 20-ft chord 30 deg swept wing section having provisions for laminar boundary control over the first 30% of the upper surface and the first 15% of the lower surface was tested in a 5-ft by 8-ft wind tunnel to explore the sensitivitity of laminar flow to various forms of disturbances such as surface imperfections contamination off-design pressure distribution (increased crossflow) and imposed noise. The test equipment used and instrumentation of the model are described. Typical results obtained from configurations with spanwise ridges and spanwise rows of disks are discussed as well as suction flow characteristics at reduced incidence.

A R H

N79-17800*# Old Dominion Univ Research Foundation Norfolk

EXPERIMENTAL STUDIES ON THE EFFECTS OF A STING SUPPORT ON THE PRESSURE DISTRIBUTION AROUND A SPHERICAL OBJECT Progress Report, Aug 1977 - Aug 1978

P S Barna (Old Dominion Univ.) Feb 1979 38 p refs (Grant NsG-1143)

(NASA-CR-158127) Avail NTIS HC A03/MF A01 CSCL 01A

Experiments were conducted on a spherical object 2.5 inches in diameter to obtain the pressure distribution around its meridan plane. In most of the tests the sphere was provided with a tail consisting of a circular cylinder that was attached directly to the rear with its axis in alignment with the center of the sphere. In some tests the tail was removed and the sphere alone was tested for comparison purposes. The main object of the tests was to obtain information on tail interference with the pressure distribution. The results of the tests show that the pressure distribution was affected by the presence of the tail to a minor extent only while major differences occurred with the variation of the Reynolds number. The experiments were performed both in an open as well as inside a closed wind tunnel under steady flow conditions at Reynolds numbers ranging from 091 to 26 x 100000 LS

N79-17801*# Lockheed-California Co Burbank
DELTA METHOD, AN EMPIRICAL DRAG BUILDUP
TECHNIQUE Final Report, 1 Mar - 31 Dec 1978
Richard C Feagin and William D Morrison Dec 1978 177 p
refs

(Contract NAS2-8612)

(NASA-CR-151971 LR-27975-Vol-1) Avail NTIS

HC A09/MF A01 CSCL 01A

An empirical drag correlation technique was developed from analysis of 19 subsonic and supersonic military aircraft and 15 advanced or supercritical airfoil configurations which can be applied in conceptual and advanced aircraft design activities The Delta Method may be used for estimating the clean wing drag polar for cruise and maneuver conditions up to buffet onset and to approximately Mach 20 This technique incorporates a unique capability of predicting the off-design performance of advanced or supercritical airfoil sections. The buffet onset limit may also be estimated. The method is applicable to wind tunnel models as well as to full scale configurations. This technique has been converted into a computer code for use on the IBM 360 and CDC 7600 computer facilities at NASA AMES Results obtained using this method to predict known aircraft characteristics are good and agreement can be obtained within a degree of accuracy judged to be sufficient for the initial processes of preliminary design

N79-17802*# United Technologies Corp East Hartford Conn THE INFLUENCE OF SWEEP ON AERODYNAMIC LOADING OF AN OSCILLATING NACA0012 AIRFOIL VOLUME 2 DATA REPORT

A O St Hilaire and F O Carta Feb 1979 388 p ref (Contract NAS1-14873)

(NASA-CR-145350) Avail NTIS HC A17/MF A01 CSCL 01A

The effect of sweep on the dynamic response of the NACA 0012 airfoil was investigated. Unsteady chordwise distributed pressure data were obtained from a tunnel spanning wing equipped with 21 single surface transducers (13 on the suction side and 8 on the pressure side of the airfoil). A compilation of all the response data obtained during the test program is presented. These data are in the form of normal force chord force lift force pressure drag and moment hysteresis loops derived from chordwise integrations of the unsteady pressure distributions The hysteresis loops are organized in two main sections. In the first section the loop data are arranged to show the effect of sweep (Delta = 0 and 30 deg) for all available combinations of mean incidence angle pitching amplitude reduced frequency chordwise Mach number. The second section shows the effect of chordwise Mach number on the swept wing response for all available combinations of mean incidence angle pitching amplitude and reduced frequency

N79-17803*# Old Dominion Univ Research Foundation Norfolk Va

EXPERIMENTS ON TANDEM DIFFUSERS WITH BOUNDARY-LAYER SUCTION APPLIED IN BETWEEN

P Stephen Barna Feb 1979 59 p refs

(Contracts NAS1-14193)

(NASA-CR-158957) Avail NTIS HC A04/MF A01 CSCL 01A

Experiments were performed on conical diffusers of various configurations with the same but rather unusually large 16.1 area ratio. Because available performance data on diffusers fall short of very large area ratio configurations an unconventional design consisting of two diffusers following each other in tandem was proposed. Both diffusers had the same area ratio of 4.1 but had different taper angles. While for the first diffuser (called leading) the angle remained constant for the second (called follower) the taper angle was stepped up to higher values Boundary layer control by way of suction was applied between the diffusers and a single slot suction ring was inserted between them The leading diffuser had an enclosed nominal divergence angle 2 theta = 5 degrees while the follower diffusers had either 10 20 30 or 40 degrees respectively giving 4 combinations. The experiments were performed at four different Reynolds numbers with various suction rates. The rates indicate a general improvement in the performance of all diffusers with boundary layer suction. It appears that the improvement of the pressure recovery depends on both the Reynolds number and the suction rate and the largest increase 0.075 was found at the lowest R sub e when the follower divergence was 2 theta = 40 degrees Author

N79-17804*# National Aeronautics and Space Administration Ames Research Center Moffett Field Calif

WIND-TUNNEL INVESTIGATION OF THE THRUST AUG-MENTOR PERFORMANCE OF A LARGE-SCALE SWEPT WING MODEL

David G Koenig and Michael D Falarski (Army Aviation Res and Develop Command St Louis Mo.) Feb 1979 58 p

(NASA-TM-X-73239 AVRADCOM-TR-78-55(AM)) Avail NTIS HC AO4/MF AO1 CSCL O1A

Tests were made in the Ames 40- by 80-foot wind tunnel to determine the forward speed effects on wing-mounted thrust augmentors. The large-scale model was powered by the compressor output of J-85 driven viper compressors. The flap settings used were 15 deg and 30 deg with 0 deg 15 deg and 30 deg aileron settings. The maximum duct pressure and wind tunnel dynamic pressure were 66 cmHg (26 in Hg) and 1190 N/sq m (25 lb/sq ft) respectively. All tests were made at zero sideslip. Test results are presented without analysis.

JMS

N79-17805*# Texas A&M Univ College Station Dept of Aerospace Engineering

INVERSE TRANSONIC AIRFOIL DESIGN METHODS INCLUDING BOUNDARY LAYER AND VISCOUS INTERACTION EFFECTS Semiannual Progress Report, 1 Aug 1978 - 31 Jan 1979

Leland A Carlson 31 Jan 1979 16 p refs (Grant NsG-1174)

(NASA-CR-158136 TAMRF-3224-79-01) Avail NTIS HC A02/MF A01 CSCL 01A

The development and incorporation into TRANDES of a fully conservative analysis method utilizing the artificial compressibility approach is described. The method allows for lifting cases and finite thickness airfoils and utilizes a stretched coordinate system. Wave drag and massive separation studies are also discussed.

N79-17806*# National Aeronautics and Space Administration Langley Research Center Hampton Va

A MODIFICATION TO LINEARIZED THEORY FOR PREDICTION OF PRESSURE LOADINGS ON LIFTING SURFACES AT HIGH SUPERSONIC MACH NUMBERS AND LARGE ANGLES OF ATTACK

Harry W Carlson Feb 1979 39 p refs (NASA-TP-1406 L-12654) Avail NTIS HC A03/MF A01 CSCL 01A

A new linearized-theory pressure-coefficient formulation was studied. The new formulation is intended to provide more accurate estimates of detailed pressure loadings for improved stability analysis and for analysis of critical structural design conditions. The approach is based on the use of oblique-shock and Prandtl-Meyer expansion relationships for accurate representation of the variation of pressures with surface slopes in two-dimensional flow and linearized-theory perturbation velocities for evaluation of local three-dimensional aerodynamic interference effects. The applicability and limitations of the modification to linearized theory are illustrated through comparisons with experimental pressure distributions for delta wings covering a Mach number range from 1.45 to 4.60 and angles of attack from 0 to 25 degrees.

N79-17807*# Grumman Aerospace Corp Bethpage N Y AN IMPROVED SUPERSONIC, THREE-DIMENSIONAL, EXTERNAL, INVISCID FLOW FIELD CODE Final Report Frank Marconi and Frank Koch Mar 1979 30 p refs (Contract NAS1-14162)

(NASA-CR-3108) Avail NTIS HC A03/MF A01 CSCL 01A A numerical procedure was developed to compute the inviscid super/hypersonic flow fields about complex vehicle geometries accurately and efficiently. A second-order accurate finite difference scheme is used to integrate the three-dimensional Euler equations in regions of continuous flow while all shock waves are computed as discontinuities via the Rankine-Hugoniot jump conditions. Conformal mappings are used to develop a computational grid. The effects for equilibrium air are included using curve fits of Mollier charts. This report deals only with modifications to these procedures in four specific areas inlet mass ingestion subsonic axial Mach number improved conformal mappings and vehicles.

flying at yaw. In each area both the modifications to the computational procedures and computer code are discussed G Y

N79-17808*# National Aeronautics and Space Administration Langley Research Center Hampton Va

STABILITY AND CONTROL CHARACTERISTICS OF A MONOPLANAR ELLIPTIC MISSILE MODEL AT MACH NUMBERS FROM 1 60 TO 2 86

Wallace C Sawyer and Giuliana Sangiorgio Feb 1979 49 p refs

(NASA-TP-1352 L-12268) Avail NTIS HC A03/MF A01 CSCL 01A

An investigation was conducted of a monoplanar maneuverable missile concept having a nose forebody with a circular cross section and a centerbody and afterbody with elliptical cross sections. The tests involved several component changes and were conducted in the low Mach number test section of the Langley Unitary Plan wind tunnel at Mach numbers of 160 216 and 2.86 at angles of attack ranging from -4 degs to 28 degs and at sideslip angles ranging from -4 degs to 8 degs. The most significant result was that at the highest Mach number (2.86) the configuration with the infrared nose produced nearly twice the axial force as the same configuration with the radar nose The cranked wing had a destabilizing effect on the longitudinal stability and had no effect on the lateral-directional stability The nose strakes had no effect longitudinally and were detrimental to the lateral-directional stability Author

N79-17809*# National Aeronautics and Space Administration Langley Research Center Hampton Va

AN EXPERIMENTAL WIND-TUNNEL INVESTIGATION OF A RAM-AIR-SPOILER ROLL-CONTROL DEVICE ON A FORWARD-CONTROL MISSILE AT SUPERSONIC SPEEDS A B Blair Jr Dec 1978 191 p refs (NASA-TP-1353 L-12518) Avail NTIS HC A09/MF A01 CSCL 01A

A parametric experimental wind-tunnel investigation was made at supersonic Mach numbers to provide design data on a ram-air-spoiler roll-control device that is to be used on forward-control cruciform missile configurations. The results indicate that the ram-air-spoiler tail fin is an effective roll-control device and that roll control is generally constant with vehicle attitude and Mach number unless direct canard and/or forebody shock impingement occurs. The addition of the ram-air-spoiler tail fins resulted in only small changes in aerodynamic-center location. For the ram-air-spoiler configuration tested, there are large axial force coefficient effects associated with the increased fin thickness and ram-air momentum loss.

N79-17810*# National Aeronautics and Space Administration Marshall Space Flight Center Huncsville Ala

SPACE SHUTTLE AFTERBODY AERODYNAMICS/PLUME SIMULATION DATA SUMMARY

Kenneth L Blackwell and Leroy M Hair (REMTECH Inc Huntsville Ala) Dec 1978 195 p refs

(NASA-TP-1384 M-276) Avail NTIS HC A09/MF A01 CSCL 01A $\,$

A series of parametric wind tunnel tests was conducted to provide a base for developing a simulation of afterbody/base aerodynamics for multibody/multibase rocket-powered vehicles (such as Space Shuttle) which use unheated air as the simulant gas in development wind tunnel tests. The tests described were parameterized on external configuration nozzle internal configuration base geometry propulsion gas type and freestream Mach number (0.5 to 3.5) The tests were conducted over a 4-year period Presented in this report are the data and pertinent reference information necessary to perform an analysis which would lead to a simulation procedure. The type of data obtained during the tests described herein include model base afterbody and nozzle internal surface static pressure distributions model chamber pressure and temperature and freestream conditions Also included is a brief description of simulation procedures that were used by the Space Shuttle program

N79-17811*# Boeing Vertol Co Philadelphia Pa
ROTARY-WING AERODYNAMICS VOLUME 2 PERFORMANCE PREDICTION OF HELICOPTERS Final Report
C N Keys and W Z Stephniewski ed Jan 1979 242 p
refs

(Contract NAS2-7007)

(NASA-CR-3083) Avail NTIS HC A11/MF A01 CSCL 01A Application of theories as well as special methods of procedures applicable to performance prediction are illustrated first on an example of the conventional helicopter and then winged and tandem configurations. Performance prediction of conventional helicopters in hover and vertical ascent are investigated. Various approaches to performance prediction in forward translation are presented. Performance problems are discussed only this time a wing is added to the baseline configuration and both aircraft are compared with respect to their performance. This comparison is extended to a tandem Appendices on methods for estimating performance guarantees and growth of aircraft concludes this volume.

N79-17812*# MacNeal-Schwendler Corp Los Angeles Calif AEROELASTIC ADDITION TO NASTRAN Final Report William P Rodden Robert L Harder and E Dean Bellinger Mar 1979 116 p refs

(Contract NAS1-13034)

(NASA-CR-3094) Avail NTIS HC A06/MF A01 CSCL 01A A description is given of the additions made to the NASTRAN program to allow analysis of aeroelastic phenomena Several methods for flutter analysis (termed K PK KE methods) are included as well as the means for calculating random and gust response of aerodynamic surfaces and bodies under fluid flow Doublet lattice mach box and piston theory aerodynamics are all incorporated Interference between bodies and surfaces is accounted for and several basic illustrative examples are presented.

N79-17813*# National Aeronautics and Space Administration Langley Research Center Hampton Va

AERODYNAMIC SIDE-FORCE ALLEVIATOR MEANS Patent

Dhanvada M Rao inventor (to NASA) (Old Dominion Univ Norfolk Va) Filed 12 Mar 1979 14 p Sponsored by NASA (NASA-Case-LAR-12326-1 US-Patent-Appl-SN-019541) Avail NTIS HC A02/MF A01 CSCL 01A

An apparatus is presented for alleviating high angle-of-attack side force on slender pointed cylindrical forebodies such as fighter aircraft missiles and the like employing a symmetrical pair of helical separation trips to disrupt the leeside vortices normally attained. The novelty of the invention appears to reside in the use of a pair of symmetrical separation trips to force boundary layer separation and thereby disrupt the leeside vortices normally attained on slender pointed cylindrical forebodies such as fighter aircraft and missiles to thereby alleviate high angle of attack side forces and yawing moments.

N79-17814# Messerschmitt-Boelkow-Blohm G m b H Ottobrunn (West Germany)

VORTEX MODELS ON MISSILE CONFIGURATIONS [WIREBELMODELLE AN FLUGKOERPERN]

G Gregoriou and D Nikolitsch Bonn DOKZENTBW 1977 58 p refs In GERMAN ENGLISH summary Sponsored by Bundesmin fuer Verteidigung

(BMVG-FBWT-77-27) Avail NTIS HC A04/MF A01 DOKZENTBW DM 30

A computer program developed for the determination of aerodynamic coefficients at high angle-of-attack was improved. Due to the modification of the originally used vortex model the physical properties of the flow pattern are described more adequately the range of applicability of the method is enlarged appreciably and the aerodynamic coefficients can now be determined almost up to 90 degree incidence. A 4-vortex model for the determination of the downwash on missile configurations was developed to replace the 2-vortex model of the slender-body-theory. Aerodynamic coefficients can be computed at arbitrary roll and Mach number with or without control deflection for both tail-control and wing-control configurations.

N79-17815# Technische Universitaet Munich (West Germany) Lehrstuhl A fuer Thermodynamik

HEAT GENERATION IN CAVITIES AT HIGH VELOCITY FLIGHTS [WAERMEENTWICKLUNG IN HOHLRAEUMEN BEIM SCHNELLFLUG]

R Schaellig Bonn DOKZENTBW 1977 96 p refs In GERMAN ENGLISH summary Sponsored by Bundesmin fuer Verteidiauna

(BMVG-FBWT-77-28) Avail NTIS HC A05/MF A01

The resonance-pipe effect and mean values for the pressure higher than the equivalent total pressures are discussed. Even for nonisentropic flows approximations for the extreme pressures and temperatures at the closed end are derived which fit with the calculations of the method of characteristics up to Ma infinity = 1 for the outflow Mach number. There are local- and time dependent supersonic flows in pipes with variable cross section The heating of the pipe end is attributed to a coupling effect of solid temperature boundary layer and gas-space through heat conduction together with the pressure oscillation of the gas The produced temperature rise is calculated as a function of a turbulence parameter which is still to be determined

N79-17816# Bundesministerium der Verteidigung Bonn (West Germany)

CONTRIBUTION TO THE DEVELOPMENT OF THEORETICAL CALCULATIONS FOR THE DESIGN AND OPTIMIZATION LIFTING BODIES (SOLUTION OF THREE-DIMENSIONAL BASIC THERMO FLUID DYNAMICS **EQUATIONS WITH STRONG INTERACTING ATTACHED** AND SEPARATED FLOW FIELDS) [BEITRAG ZUR ENT-WICKLUNG PRAXISGERECHTER THEORETISCHER BE-RECHNUNGSMETHODEN FUER ENTWURF UND OPTI-MIERUNG VON FLUGKOERPERN (LOESUNG DER DREIDI-MENSIONALEN GRUNDGLEICHUNGEN DER THERMOFL-UIDDYNAMIK BEI STARKER WECHSELWIRKUNG ZWISC-HEN ANLIEGENDEN UND ABGELOESTEN STROEMUNG-SBEREICHEN)

Alfred Walz Bonn DOKZENTBW 1978 43 p refs In GERMAN **ENGLISH** summary

(BMVG-FBWT-78-4) Avail NTIS HC A03/MF A01, DOK-ZENTRW DM 30

Prediction methods for the aero-thermodynamical behavior of lifting bodies or jet engines must include the prediction of strong interacting flow field effects such as generated by flow separation and vortex formations which are decisively influencing the pressure distribution boundary layer development and vice versa. The transition to turbulence as well as the influence of chemical reactions on boundary layer and/or turbulent jet flow must also be considered. A numerical method for solving the generally valid 3D-NAVIER-STOKES equations was developed and tested giving correct results for the fully complex flow field up to Re is greater than 10 to the 6th power with reasonable time expense. A critical survey on the present state of art of 3D-turbulent (and compressible) boundary layer prediction methods and its empirical inputs is presented. Methods are proposed for including results about turbulent boundary behavior into the quasi-laminar NAVIER-STOKES scheme ARH

N79-17817# Royal Aircraft Establishment Bedford (England) Aerodynamics Dept

BOUNDARY LAYER TRANSITION MEASUREMENTS ON THE AEDC 10 DEG CONE IN THREE RAE WIND TUNNELS AND THEIR IMPLICATIONS

D G Mabey London Aeron Res Council 1978 56 p refs Supersedes RAE-TR-76077 ARC-37395 (ARC-R/M-3821 BR64190 RAE-TR-76077 ARC-3795) Avail

NTIS HC A04/MF A01 HMSO £ 5 PHI

The 10 degs cone was tested in a large number of transonic wind tunnels to investigate the influence of free stream pressure fluctuations on transition Reynolds numbers. Measurements made on the cone in three wind tunnels are described in the 8ft x 8ft subsonic/supersonic tunnel the cone transition Reynolds numbers were relatively high and the pressure fluctuations low In the 3ft x 4ft high supersonic speed tunnel the transition Reynolds numbers were high and there were strong unit Reynolds number effects. In the 8ft x 6ft tunnel transition was controlled by an effective roughness either at the cone tip or the microphones the tunnel pressure fluctuations varied appreciably with Mach number and were high at subsonic speeds. The results show that surface pressure fluctuation measurements at supersonic speeds are sensitive to the degree of smoothness of the surface particularly in the transition region of the boundary layer A tentative classification of the aerodynamics facilities used for transition tests is suggested

N79-17818# Technische Hogeschool Delft (Netherlands) Dept of Aerospace Engineering

A SLENDER DELTA WING OSCILLATING IN SURFACE WAVES

R Coene Dec 1977 88 p refs

(VTH-LR-257 VTH-456) Avail NTIS HC A05/MF A01

An experimental investigation of some cases of unsteady propulsion in non-uniform flow conditions is discussed. A not-so-deeply submerged rigid slender delta wing-like body is towed horizontally through a regular train of surface waves. At the same time the body is forced to carry out heaving and pitching oscillations at the frequency of encounter. The results are compared with theoretical predictions based on slender body potential flow assumptions. The experiments tend to confirm the theoretical prediction that energy can be extracted from the waves in such a way that it can be used efficiently for propulsion The results are relevant to the theory of swimming of cetacea and fishes in waves and to the theory of the resistance of ships in a wavy sea. Additional theoretical considerations are inclu-

N79-17819# Technische Hogeschool Delft (Netherlands) Dept of Aerospace Engineering

INTERACTION OF THE SUPERSONIC FLOW BELOW A SUPERSONIC FREE JET WING AND Α **DIMENSIONAL SITUATION)**

F J F deJong Apr 1978 53 p refs (VTH-LR-268) Avail NTIS HC A04/MF A01

The interaction of the compression field below a wing in supersonic flow and supersonic jet parallel to the wing chord was investigated to verify the suggestion that the sonic boom generated by a supersonic transport aircraft might be substantially reduced by a suitable arrangement of the propulsive jets. A theoretical investigation showed that the effect of the inviscid jet did have the desired direction but was very small Experiments were made to investigate the effect of turbulence however no extra effect was found. No significant advantages are to be expected of practical application of the special configuration studied

N79-17820# Dornier-System G m b H Friedrichshafen (West Theoretical Aerodynamics Group Germany)

THEORETICAL INVESTIGATIONS OF REAL GAS EFFECTS IN CRYOGENIC WIND TUNNELS Final Report

Bernhard Wagner and Wolfgang Schmidt Dec 1976 82 p

(DS-FB-76/50B) Avail NTIS HC A05/MF A01

Real gas effects in cryogenic nitrogen flows were calculated using the Beattle-Bridgeman equation of state. The investigations include Prandtl-Meyer expansions oblique shocks transonic small perturbation theory transonic flow past a NACA 0012 aerofoil and shock boundary layer interaction. The two last cases mentioned were treated with the aid of finite volume tech-FOS

N79-17821# National Transportation Safety Board Washington D C

AIRCRAFT ACCIDENT REPORT MIDAIR COLLISION INVOLVING A FALCON JET, N121GW, AND A CESSNA 150M, N6423K, MEMPHIS, TENNESSEE

30 Nov 1978 42 p

(NTSB-AAR-78-14) Avail NTIS HC A03/MF A01

The Falcon Jet which was on an instrument flight rules flight plan had an instructor pilot and three students on board An instructor pilot and one passenger were aboard the Cessna 150M The Cessna was VFR and was receiving Stage III radar service. The aircrafts were under control of Memphis tower

controllers and were in radar and radio contact with the tower The weather in the Memphis area was Scattered clouds at 4 500 feet and visibility--6 miles with haze. The National Transportation Safety Board determined that the probable cause of this accident was the failure of controller personnel to separate the aircraft as required by procedures established for a terminal radar service area to insure that proper coordination was effected to issue appropriate traffic advisories and the failure of each flightcrew to see and avoid the other aircraft

N79-17822*# Lockheed-Georgia Co Marietta CARGO/LOGISTICS AIRLIFT SYSTEM STUDY (CLASS).

VOLUME 1 J M Norman R D Henderson F C Macey and R P Tuttle Hampton Va NASA Nov 1978 338 p

(Contract NAS1-14967)

LG78ER0266-Vol-1) (NASA-CR-158915 NTIS Avail

HC A15/MF A01 CSCL 01C

Current and advanced air cargo systems are evaluated using industrial and consumer statistics. Market and commodity characteristics that influence the use of the air mode are discussed along with a comparison of air and surface mode on typical routes Results of on-site surveys of cargo processing facilities at airports are presented and institutional controls and influences on air cargo operations are considered

N79-17823*# Lockheed-Georgia Co Marietta CARGO/LOGISTICS AIRLIFT SYSTEM STUDY (CLASS). VOLUME 2

J M Norman R D Henderson F C Macey and R P Tuttle Hampton Va NASA Nov 1978 334 p refs (Contract NAS1-14967)

(NASA-CR-158916 LG78ER0267-Vol-2) HC A15/MF A01 CSCL 01C

Air containerization is discussed in terms of lower freight rates size and pallet limitations refrigeration backhaul of empties and ownership. It is concluded that there is a need for an advance air cargo system as indicated by the industry/transportation case studies and a stimulation of the air cargo would result in freight rate reductions

N79-17824*# Lockheed-Georgia Co Marietta CARGO/LOGISTICS AIRLIFT SYSTEM STUDY (CLASS). **EXECUTIVE SUMMARY**

J M Norman R D Henderson F C Macey and R P Tuttle Hampton Va NASA Nov 1978 37 p (Contract NAS1-14967)

(NASA-CR-158959 LG78ER0265) NTIS Avail

HC A03/MF A01 CSCL 01C

The current air cargo system is analyzed along with advanced air cargo systems studies. A forecast of advanced air cargo system demand is presented with cost estimates. It is concluded that there is a need for a dedicated advance air cargo system and with application of advanced technology reductions of 45% in air freight rates may be achieved FOS

N79-17825# National Aviation Facilities Experimental Center Atlantic City N J

FULL-SCALE FIRE MODELING TESTS OF A COMPACT RAPID RESPONSE FOAM AND DRY CHEMICAL POWDER DISPENSING SYSTEM Final Report, Jul 1975 - Aug

George B Geyer Lawrence M Neri and Charles H Urban Oct 1978 81 p refs

(FAA Proj 081-431-100)

FAA-RD-78-105) (FAA-NA-78-24 NTIS

HC A05/MF A01

The firefighting capability of a rapid firefighting system of the dual-agent type capable of dispensing Aqueous-Film-Forming-Foam (AFFF) or dry chemical powder either singly or in combination was established. Fire control times were determined for three 6 percent and two 3 percent-type AFFF agents and five dry chemical powders on 35 and 824 foot diameter Jet A fuel fires at nominal discharge rates of 3.5 and 7.0 pounds per second Foam ground patterns were developed for the five AFFF agents and the effective throw range of each of the five dry

chemical powders was determined A means was developed for estimating the response time of a rapid fire-intervention vehicle to attend to any part of the operational area of an airport in a hypothetical aircraft accident situation. The methodology was based upon the results obtained by conducting a series of segmented time trials of basic maneuvers the sum of which closely approximated the actual vehicle response time Experiments tend to indicate that the Twinned Agent Unit (TAU) would be capable of extinguishing the practical critical fire area associated with U.S. Index A aircraft within 120 seconds S.E.S.

N79-17826# National Transportation Safety Board Washington

AIRCRAFT ACCIDENT REPORT CONTINENTAL AIR LINES. INCORPORATED, MCDONNELL-DOUGLAS DC-10-10 N68045, LOS ANGELES, CALIFORNIA, MARCH 1, 1978 25 Jan 1979 52 p refs

(NTSB-AAR-79-1) Avail NTIS HC A04/MF A01

As the aircraft departed the wet load-bearing surface of the runway the left main landing gear collapsed and fire erupted from the left wing area. The aircraft slid to a stop about 664 feet from the departure end of the runway. The left side of the aircraft was destroyed. Of the 184 passengers, 2 infants, and 14 crewmembers aboard 2 passengers were killed and 28 passengers and 3 crewmembers were seriously injured during the evacuation of the aircraft. The probable cause of the accident was the sequential failure of two tires on the left main landing gear and the resultant failure of another tire on the same landing gear at a critical time during the takeoff roll. These failures resulted in the captain's decision to reject the takeoff. The cumulative effect of the partial loss of aircraft braking because of the failed tires and the reduced braking friction achievable on the wet runway surface which increased the accelerate-stop distance to a value greater than the available runway length contributed to the accident. These factors prevented the captain from stopping the aircraft within the runway confines

N79-17828# National Transportation Safety Board Washington D C Bureau of Technology

LISTING OF ACCIDENTS/INCIDENTS BY MAKE AND MODEL, US CIVIL AVIATION, 1977

19 Dec 1978 198 p

(NTSB-AMM-78-12) Avail NTIS HC A09/MF A01

This publication contains a listing of all U.S. civil aviation accidents/incidents occurring in calendar year 1977 sorted by aircraft make and model Included are the file number aircraft registration number date and location of the accident aircraft make and model and injury index for all 4427 accidents/ incidents occurring in this period. This publication will be published

N79-17829# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING MIDAIR COLLISIONS. US GENERAL AVIATION, 1977

19 Dec 1978 62 p

(NTSB-AMM-78-13) Avail NTIS HC A04/MF A01

There are 34 accidents included 17 of which involve fatal accidents. The facts conditions circumstances and probable cause(s) for each accident are presented Additional statistical information is tabulated by kind of flying phase of operation injury index altitude of occurrence airport proximity aircraft damage pilot certificate injuries and casual factor(s) SES

N79-17830# National Transportation Safety Board Washington, D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING TURBINE POWERED AIRCRAFT, US GENERAL AVIATION, 1977

19 Dec 1978 99 p

(NTSB-AMM-78-14) Avail NTIS HC A05/MF A01

This publication contains reports of US general aviation turbine powered aircraft accidents occurring in 1977. Included are 129 accident Briefs 37 of which involve fatal accidents The brief format presents the facts conditions circumstances and probable cause(s) for each accident. Additional statistical information is tabulated by type of accident phase of operation

injury index aircraft damage pilot certificate injuries and cause/factor(s) This publication will be published annually

N79-17831# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING ROTORCRAFT, US **GENERAL AVIATION, 1977**

19 Dec 1978 179 p

(NTSB-AMM-78-15) Avail NTIS HC A09/MF A01

There are 276 accidents included 29 of which involve fatal accidents. The facts conditions circumstances and probable cause(s) for each accident are presented. Additional statistical information is tabulated by type of accident phase of operation injury index aircraft damage kind of flying pilot certificates injuries and causes and related factors

N79-17832# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF FATAL ACCIDENTS INVOLVING WEATHER AS A CAUSE/FACTOR, US GENERAL AVIATION, 1977 19 Dec 1978 259 p

(NTSB-AMM-78-16) Avail NTIS HC A12/MF A01

Reports are presented of all fatal US general aviation accidents involving weather as a cause/factor for the year 1977 Included are 258 fatal accidents in the brief format. This format presents the facts conditions circumstances and probable cause(s) for each accident. Additional statistical information is tabulated on all accidents involving weather as a cause/factor by type of accident phase of operation injury index aircraft damage pilots certificate injuries and cause/factor(s)

N79-17833# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING ALCOHOL AS A CAUSE/FACTOR, US GENERAL AVIATION, 1977 19 Dec 1978 43 p

(NTSB-AMM-78-17) Avail NTIS HC A03/MF A01

There are 47 accidents included 41 of which involve fatal accidents. The facts conditions circumstances and probable cause(s)/factor(s) for each accident are presented Additional statistical information is tabulated by type of accident phase of operation injury index aircraft damage pilot certificate injuries and causal factor(s)

N79-17834# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING MISSING AND MISSING LATER RECOVERED AIRCRAFT, US GENERAL **AVIATION, 1977**

19 Dec 1978 65 p

(NTSB-AMM-78-18) Avail NTIS HC A04/MF A01

There are 63 accidents included 11 of which cover missing aircraft not recovered and 52 missing later recovered. The facts conditions circumstances and probable cause(s) for each accident are presented Additional statistical information is tabulated by type of accident phase operation injury index aircraft damage pilot certificate injuries and causal factor(s)

N79-17835# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS, INVOLVING CORPORATE/ **EXECUTIVE AIRCRAFT, US GENERAL AVIATION, 1977** 19 Dec 1978 59 p

(NTSB-AMM-78-19) Avail NTIS HC A04/MF A01

There are 60 accidents included 18 of which involve fatal accidents. The facts conditions circumstances and probable cause(s) for each accident are presented Additional statistical information is tabulated by type of accident phase of operation SES injuries and causal/factor(s)

N79-17836# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING AMATEUR/HOME **BUILT AIRCRAFT, US GENERAL AVIATION, 1977**

19 Dec 1978 71 p (NTSB-AMM-78-20) HC A04/MF A01

There are 106 accidents 21 of which involve fatalities. The facts conditions circumstances and probable causes(s)/factor(s) for each accident are presented. Additional statistical information is tabulated by type of accident phase of operation injury index aircraft damage pilot certificate injuries and casual/factor(s)

N79-17837# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING AERIAL APPLICATION OPERATIONS, US GENERAL AVIATION, 1977 19 Dec 1978 319 p

(NTSB-AMM-78-21) Avail NTIS HC A14/MF A01

This publication contains reports of US general aviation aerial application accidents occurring in 1977. Included are 454 accident Briefs 30 of which involve fatal accidents. The brief format presents the facts conditions circumstances and probable cause(s) for each accident. Additional statistical information is tabulated by type of accident phase of operation injury index aircraft damage pilot certificate injuries kind of operation and causes/factors. This publication will be published annually

N79-17838# National Transportation Safety Board Washington D C Bureau of Technology

BRIEFS OF ACCIDENTS INVOLVING COMMUTER AIR CARRIERS AND ON-DEMAND AIR TAXI OPERATIONS, US **GENERAL AVIATION, 1977**

19 Dec 1978 153 p

(NTSB-AMM-78-22) Avail NTIS HC A08/MF A01

There are 37 commuter air carrier and 180 on-demand air taxi and accident briefs. The facts conditions circumstances and probable cause(s) for each accident are presented. Additional statistical information is tabulated by type of operation injuries aircraft weight and cause(s) and related factor(s)

N79-17839# Technische Hogeschool Delft (Netherlands) Dept of Aerospace Engineering

WORST CASE TIME HISTORIES CAUSING LARGEST DEVIATIONS FROM A DESIRED FLIGHT PATH **ANALYTICAL APPROACH**

J C VanderVaart Apr 1978 43 p refs (VTH-LR-267) Avail NTIS HC A03/MF A01

An analytical method to find wind or turbulence time-histories causing largest deviations of aircraft motion variables is described Basic concepts of linear system theory is used to show that the largest deviation of a particular aircraft variable is caused by a turbulence time-history that is proportional to the time-reversed impulse response of that particular variable. A maximum deviation caused by the (deterministic) worst case time-history is shown to be proportional to the variance of the motion variable in the (imagery) stochastic case if the aircraft is considered to be perturbed by white noise random turbulence The problem of finding worst case responses is reduced to that of the statistics of a white noise driven linear system. Some possibilities are suggested for the use of this concept as a tool in designing control systems aimed at making an aeroplane less sensitive to the class of low frequency turbulence usually denoted by the term windshears SES

N79-17840# Federal Aviation Administration Washington D C Systems Research and Development Service

COLLISION AVOIDANCE AN ANNOTATED BIBLIOGRAPHY Final Report, May 1972 - Nov 1977 Dorothy E Bulford Dec 1977 308 p

(FAA-NA-78-8) Avail NTIS HC A14/MF A01

A bibliography of 859 annotated references to collision avoidance are presented. These references are to literature issued. since April 1972 Corporate author personal name and subject indexes are included

N79-17841# Systems Control Inc Palo Alto Calif RNAV ROUTE DESIGN-TERMINAL AREA DESIGN PRO-CEDURES AND TRANSITION AREA DESIGN GUIDELINES Final Report

E D McConkey and A G Halverson Jan 1978 221 p (DOT-FA72WA-3098)

(FAA-RD-78-61) Avail NTIS HC A10/MF A01

Techniques are presented which can be used to produce terminal and transition area route structures that are designed for use by aircraft equipped with area navigation (RNAV) computers. The route design processes were developed during investigation into RNAV route structures for terminal and enroute airspace. The design techniques provide for the consideration of user and air traffic control (ATC) requirements. Among the user considerations are minimization of the number of waypoints and the reduction of aircraft time and fuel penalties by utilizing the RNAV routes. The ATC considerations include procedural separation of arriving and departing aircraft organization of the terminal area according to traffic flow and provision for sufficient maneuvering airspace to permit efficient traffic separation procedures. The terminal area design process is characterized by a set of procedures by which the route structure is developed The data requirements and the data processing programs which can aid in the design process are described. The terminal design procedure describes the means by which the terminal waypoints can be located by considering traffic demand. Techniques for locating feeder fixes and providing traffic patterns for several active runway combinations are included. Procedures for developing efficient vertical aircraft profiles are described FOS

N79-17843*# National Aeronautics and Space Administration Langley Research Center Hampton Va

ALGORITHMS AND LOGIC FOR INCORPORATING MLS BACK AZIMUTH INFORMATION INTO THE NASA TCV B-737 AIRPLANE AREA NAVIGATION SYSTEM

Charles E Knox Jan 1979 21 p refs

(NASA-TM-80039) Avail NTIS HC A02/MF A01 CSCL 17G

Navigation position estimates are based on range information form a randomly located DME and MLS back azimuth angular information. The MLS volmetric coverage checks are performed to ensure that proper navigation inputs are being utilized. These algorithms and volumetric checks were designed so that they could be added to most existing area navigation systems with minimum software modification.

N79-17847* National Aeronautics and Space Administration Ames Research Center Moffett Field Calif

CONSTANT LIFE ROTOR FOR A HEAVIER THAN AIR CRAFT Patent

Robert H Stroub inventor (to NASA) Issued 30 Jan 1979 8 p Filed 25 Jul 1977 Supersedes N77-28111 (15 - 19 p 2486)

(NASA-Case-ARC-11045-1 US-Patent 4 137 010

US-Patent-Appl-SN-818916 US-Patent-Class-416-51

US-Patent-Class-416-88 US-Patent-Class-416-89

US-Patent-Class-416-132R US-Patent-Class-416-138) Avail US Patent and Trademark Office CSCL 01C

A rotor blade extended radially from a hub characterized by an elongated spar and a plurality of axially aligned shells pivotally mounted on the spar is presented. Each has an aerodynamic center located in trailing relation with the spar and supported thereby for simultaneous axial and angular displacement as centrifugal forces are applied a pitch controller plus a plurality of pivotal pitch limiting arms transversely related to the spar. A push-pull link interconnecting the arms is used for imparting simultaneous pivotal motion, whereby the angular relationship of the arms to the spar is varied for varying the motion of the trucks along the arms for thus limiting the pitch of the segments about the spar.

Official Gazette of the U.S. Patent and Trademark Office

N79-17848*# Lockheed-Georgia Co Marietta ADVANCED SYSTEM DESIGN REQUIREMENTS FOR LARGE AND SMALL FIXED-WING AERIAL APPLICATION SYSTEMS FOR AGRICULTURE

J T Hinely Jr and R Q Boyles Jr Hampton Va NASA Jan 1979 302 p refs (Contracts NAS1-15185 NAS1 15186) (NASA-CR-158939 LG79ER0005) HC A14/MF A01 CSCL 01C

Avail NTIS

Several candidate aircraft configurations were defined over the range of 1000 to 10 000 pounds payload and evaluated over a broad spectrum of agricultural missions. From these studies baseline design points were selected at 3200 pounds payload for the small aircraft and 7500 pounds for the large aircraft The small baseline aircraft utilizes a single turboprop powerplant while the large aircraft utilizes two turboprop powerplants. These configurations were optimized for wing loading aspect ratio and power loading to provide the best mission economics in representative missions. Wing loading of 20 lb/sq ft was selected for the small aircraft and 25 lb/sq ft for the large aircraft. Aspect ratio of 8 was selected for both aircraft. It was found that a 10% reduction in engine power from the original configurations provided improved mission economics for both aircraft by reducing the cost of the turboprop. Refined configurations incorporate a 675 HP engine in the small aircraft and two 688 HP engines in the large aircraft

N79-17849* Kansas Univ Lawrence

THE DEVELOPMENT OF THE DAST I REMOTELY PILOTED RESEARCH VEHICLE FOR FLIGHT TESTING AN ACTIVE FLUTTER SUPPRESSION CONTROL SYSTEM Ph D Thesis Final Report

David L Grose Feb 1979 365 p refs (Contract NAS1-4007) (NASA-CR-144881) Avail NTIS HC A16/MF A01 CSCL 01C

The development of the DAST I (drones for aerodynamic and structural testing) remotely piloted research vehicle is described The DAST I is a highly modified BQM-34E/F Firebee II Supersonic Aerial Target incorporating a swept supercritical wing designed to flutter within the vehicle's flight envelope. The predicted flutter and rigid body characteristics are presented. A description of the analysis and design of an active flutter suppression control system (FSS) designed to increase the flutter boundary of the DAST wing (ARW-1) by a factor of 20% is given. The design and development of the digital remotely augmented primary flight control system and on-board analog backup control system is presented. An evaluation of the near real-time flight flutter testing methods is made by comparing results of five flutter testing techniques on simulated DAST I flutter data. The development of the DAST ARW-1 state variable model used to generate time histories of simulated accelerometer responses is presented. This model uses control surface commands and a Dryden model gust as inputs. The feasibility of the concept of extracting open loop flutter characteristics from closed loop FSS responses was examined. It was shown that open loop characteristics can be determined very well from closed loop subcritical responses

N79-17850*# Rockwell International Corp Los Angeles Calif FORMULATION OF AERODYNAMIC PREDICTION TECH-NIQUES FOR HYPERSONIC CONFIGURATION DESIGN Feb 1979 114 p refs

(Contract NAS1-15075)

(NASA-CR-158994) Avail NTIS HC A06/MF A01 CSCL 01C

An investigation of approximate theoretical techniques for predicting aerodynamic characteristics and surface pressures for relatively slender vehicles at moderate hypersonic speeds was performed Emphasis was placed on approaches that would be responsive to preliminary configuration design level of effort Supersonic second order potential theory was examined in detail to meet this objective. Shock layer integral techniques were considered as an alternative means of predicting gross aerodynamic characteristics. Several numerical pilot codes were developed for simple three dimensional geometries to evaluate the capability of the approximate equations of motion considered. Results from the second order computations indicated good agreement with higher order solutions and experimental results for a variety of wing like shapes and values of the hypersonic similarity parameter M delta approaching one.

N79-17851*# National Aeronautics and Space Administration Langley Research Center Hampton Va

EFFECTS OF LAMINAR FLOW CONTROL ON THE PERFORMANCE OF A LARGE SPAN-DISTRIBUTED-LOAD FLYING-WING CARGO AIRPLANE CONCEPT

Lloyd S Jernell Jun 1978 23 p refs

(NASA-TM-78715) Avail NTIS HC A02/MF A01 CSCL 01C

The effects of laminar flow control (LFC) on the performance of a large span-distributed-load flying-wing cargo airplane concept having a design payload of 2 669 MN and range of 5 93 Mm were determined Two configurations were considered. One employed laminarized flow over the entire surfaces of the wing and vertical tails with the exception of the estimated areas of interference due to the fuselage and engines. The other case differed only in that laminar flow was not applied to the flaps elevons spoilers or rudders. The two cases are referred to as the 100 percent and 80 percent laminar configurations, respectively. The utilization of laminar flow control results in reductions in the standard day sea level installed maximum static thrust per engine from 240 kN for the non-LFC configuration to 205 kN for the 100 percent laminar configuration and 209 kN for the 80 percent case. Weight increases due to the LFC systems. cause increases in the operating empty weights of approximately 3 to 4 percent. The design takeoff gross weights decrease approximately 3 to 5 percent. The FAR-25 takeoff field distances for the LFC configurations are greater by about 6 to 7 percent Fuel efficiencies for the respective configurations are increased 33 percent and 23 percent

N79-17852*# Vought Corp Hampton Va

EVALUATION OF A LONG-ENDURANCE-SURVEILLANCE REMOTELY-PILOTED VEHICLE WITH AND WITHOUT LAMINAR FLOW CONTROL

R V Turriziani W A Lovell J E Prince C B Quartero and S F Washburn Feb 1979 56 p refs

(Contract NAS1-13500)

(NASA-CR-159006) Avail NTIS HC A04/MF A01 CSCL 01C

Two aircraft were evaluated using a derated TF34-GE-100 turbofan engine one with laminar flow control (LFC) and one without The mission of the remotely piloted vehicles (RPV) is one of high-altitude loiter at maximum endurance. With the LFC system maximum mission time increased by 6.7 percent L/D in the loiter phase improved 14.2 percent and the minimum parasite drag of the wing was reduced by 65 percent resulting in a 37 percent reduction for the total airplane. Except for the minimum parasite drag of the wing the preceding benefits include the offsetting effects of weight increase suction power requirements, and drag of the wing-mounted suction pods. In a supplementary study using a scaled-down rather than derated version of the engine on the LFC configuration a 17.6 percent increase in mission time over the airplane without LFC and an incremental time increase of 10.2 percent over the LFC airplane with derated engine were attained. This improvement was due principally to reductions in both weight and drag of the scaled engine

N79-17854*# National Aeronautics and Space Administration Langley Research Center Hampton Va

LED INSTRUMENT APPROACH INSTRUCTION DISPLAY
Barry D Meredith W Lane Kelly IV and Roger K Crouch
Jan 1979 18 p

(NASA-TM-78823) Avail NTIS HC A02/MF A01 CSCL 01D A display employing light emitting diodes (LED s) was developed to demonstrate the feasibility of such displays for presenting landing and navigation information to reduce the workload of general aviation pilots during IFR flight. The display consists of a paper tape reader digital memory control electronics digital latches and LED alphanumeric displays. A presentable digital countdown clock-timer is included as part of the system to provide a convenient means of monitoring time intervals for precise flight navigation. The system is a limited capability prototype assembled to test pilot reaction to such a device under simulated IFR operation. Pilot opinion indicates that the display is helpful in reducing the IFR pilots workload when used with a runway approach plate. However the development of a compact low power second generation display was recommended which

could present several instructions simultaneously and provide information update capability. A microprocessor-based display could fulfill these requirements.

N79-17855# Westinghouse Defense and Electronic Systems Center Baltimore Md Systems Development Div

INTEGRATED THERMAL AVIONICS DESIGN (ITAD) Final Report

R F Porter E R Levitt Y Lord R T Dolbeare and R H Worsham Jun 1978 156 p refs (Contract F33615-77-C-2074)

(AD-A061227 Rept-78-0610 AFFDL-TR-78-76) Avail NTIS HC A08/MF A01 CSCL 01/3

This volume contains a description of the ITAD study program results. It includes definition of the computer facility requirements and software and shows by example the improvement to be made in Life Cycle cost when ITAD is applied to the design of electronic equipment.

Author (GRA)

N79-17856 British Library Lending Div Boston Spa (England) SEPARATION AND INVESTIGATION OF WEAR PARTICLES FROM AERO-ENGINES

E Jantzen 4 May 1978 12 p refs Transl into ENGLISH from Z Flugwiss und Weltraumforsch (West Germany) v 1 pt 3 1971 p 193-199

(BLL-Risley-TR-3308-(9091 9F)) Copyright Avail British Library Lending Div Boston Spa Engl

After a survey of the methods of separating wear particles from engine oils a detailed description of filters and filtration techniques is given Investigations with the scanning electron microscope on the size and form of wear particles from aero-engines are then presented. The methods advantages and results of analysis of individual wear particles by the energy-dispersive technique in the scanning microscope are discussed.

N79-17858*# Hamilton Standard Windsor Locks Corin INTERACTIVE MULTI-MODE BLADE IMPACT ANALYSIS Final Report, Jan 1976 - Aug 1977 and Feb 1978 - Aug 1978

A Alexander and R W Cornell Aug 1978 301 p refs (Contract NAS3-20091)

(NASA-CR-159462) Avail NTIS HC A16/MF A01 CSCL 21E

The theoretical methodology used in developing an analysis for the response of turbine engine fan blades subjected to soft-body (bird) impacts is reported and the computer program developed using this methodology as its basis is described. This computer program is an outgrowth of two programs that were previously developed for the purpose of studying problems of a similar nature (a 3-mode beam impact analysis and a multi-mode beam impact analysis). The present program utilizes an improved missile model that is interactively coupled with blade motion which is more consistent with actual observations. It takes into account local deformation at the impact area blade camber effects and the spreading of the impacted missile mass on the blade surface In addition, it accommodates plate-type mode shapes. The analysis capability in this computer program represents a significant improvement in the development of the methodology for evaluating potential fan blade materials and designs with regard to foreign object impact resistance SES

N79-17859*# National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio

COLD-AIR PERFORMANCE OF FREE POWER TURBINE DESIGNED FOR 112-KILOWATT AUTOMOTIVE GASTURBINE ENGINE 2 EFFECTS OF VARIABLE STATORVANE-CHORD SETTING ANGLE ON TURBINE PERFORMANCE Final Report

Kerry L McLallin and Milton G Kofskey Feb 1979 53 p

(Contract EC-77-A-31-1011)

(NASA-TM-78993 DOE/NASA/1011-78/28 E-9775) Avail NTIS HC A04/MF A01 CSCL 21A

The cold-air performance of an axial-flow power turbine with a variable stator designed for a 112-kW automotive gas-turbine

engine was determined at speeds from 30 to 110 percent of design and at pressure ratios from 111 to 267 Performance is presented in terms of equivalent mass flow torque power and efficiency for stator-vane-chord setting angles of 26 degs 30 degs 35 degs (design) 40 degs 45 degs and 50 degs Turbine braking performance at a nominal stator setting angle of 107 degs is also presented. Turbine efficiency increased with increasing stator setting angle A 10-point efficiency increase was obtained by opening the stator from the design setting angle of 35 degs to a setting angle of 45 degs Author

N79-17860# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR THE TURBINE ENGINE EXHAUST EMISSIONS VOLUME 1 PROGRAM DESCRIPTION AND RESULTS Interim Report, Aug 1974 -Jun 1977

Melvin Platt and E R Norster May 1978 153 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-6-Vol-1 FAA-NA-77-179-Vol-1

FAA-RD-78-56-Vol-1) Avail NTIS HC A08/MF A01

Turbine emission degradation was studied. An introduction to the program a description of the test schedule equipment procedures and data processing techniques as well as a discussion of the test data itself were included. A total of 519 repetitious emission tests were conducted over a period of 22 months on units of the following engine types JT8D-9 JT8D-7 JT3D-3B JT9D-3B JT9D-3A RB211-22B and CF700-2D Emissions of CO2 CO HC NO NOx and smoke were monitored in addition to various engine operating parameters over an eight-mode test cycle ranging from cold idle to take-off and back to hot idle

JMS

N79-17862# Dornier-System G m b H Friedrichshafen (West Germany)

ENGINE DYNAMICS [TRIEBWERKSDYNAMIK]

M Buchstaller Bonn DOKZENTBW 1978 162 p refs GERMAN ENGLISH summary Sponsored by Bundesmin fuer Verteidigung

(BMVG-FBWT-78-6) Avail NTIS HC A08/MF A01

Simulation groups of Dornier fighters maneuvers are studied with the aid of digital and/or hybrid computation. The influence of energy management on fighters maneuvers is considered Simulation runs were done with three aircraft comparing maneuvers with frequent RPM changes and with different initial conditions for the whole flight envelope. The results in low speed area for light fighters using engine dynamics indicate a rise in speed time reduction for maneuvers better set in position to opponent and reducing time in opponent's threat area. The results for heavier fighters indicate important tactical advantages at high speed level

N79-17863# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR THE TURBINE ENGINE EXHAUST EMISSION VOLUME 2 JT8D-9 TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 382 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-7-Vol-2 FAA-NA-77-179-Vol-2

FAA-RD-78-56-Vol-2) Avail NTIS HC A17/MF A01

Degradation of turbine engine emissions was examined A compilation of all emission test data and analysis data used in the development of degradation factors for the JT8D-9 engine type is presented. Maintenance data for the test units during the period of testing as well as analyses of the samples of fuel used in each test are included

N79-17864# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 3 JT3D-7 TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 376 p refs 8 Vol (Contract DOT-FA74NA-1100) (NREC-1238-8-Vol-3 FAA-NA-77-179-Vol-3 FAA-RD-78-56-Vol-3) Avail NTIS HC A17/MF A01

Emission test data and analysis data used in the development of degradation factors for the JT8D-7 engine are presented along with maintenance data for the test units during the period of testing Analyses of the samples of fuel used in each test are included

N79-17865# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 4 JT3D-7 TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 373 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-9-Vol-4 FAA-NA-77-179-Vol-4

FAA-RD-78-56-Vol-4) Avail NTIS HC A16/MF A01

Degradation factors for the JT3D-7 engine were developed Emission test data analysis data maintenance data for the test units for the period of testing and analyses of the samples of fuel used in each test are presented in tabular form

N79-17866# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 5 JT3D-3B TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 374 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-10-Vol-5 FAA-NA-77-179-Vol-5

FAA-RD-78-56-Vol-5) Avail NTIS HC A16/MF A01

Tests were conducted to determine degradation factors for pollutant emissions from various aircraft engines. Emission test data for the JT3D-3B engine are presented Analysis data used in the development of degradation factors, maintenance data for the test units during the period of testing and analyses of the samples of fuel used in each test are included

N79-17867# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 6 JT9D-3A TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 376 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-11-Vol-6 FAA-NA-77-179-Vol-6

FAA-RD-78-56-Vol-6) Avail NTIS HC A17/MF A01

Emission test data and analysis data used in the development of degradation factors for the JT9D-3A engine type are presented Maintenance data for the test units during the period of testing as well as analyses of the samples of fuel used in each test are included

N79-17868# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 7 RB211-22B TEST

DATA Interim Report, Aug 1974 - Jun 1977 May 1978 318 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-12-Vol-7 FAA-NA-77-179-7

FAA-RD-78-56-Vol-7) Avail NTIS HC A14/MF A01

A compilation of all emission test data and analysis data used in the development of degradation factors for the RB211-22B engine type is presented. Maintenance data for the test units during the period of testing and analyses of the samples of fuel used in each test are included JMS

N79-17869# Northern Research and Engineering Corp Cambridge Mass

TIME DEGRADATION FACTORS FOR TURBINE ENGINE EXHAUST EMISSIONS VOLUME 8 C700-2D TEST DATA Interim Report, Aug 1974 - Jun 1977

May 1978 319 p refs 8 Vol (Contract DOT-FA74NA-1100)

(NREC-1238-13-Vol-8 FAA-NA 77-179-Vol-8

FAA-RD-78-56-Vol-8) Avail NTIS HC A14/MF A01

Degradation of turbine engine emissions is reported Emission test data and analysis data used in the development of degradation factors for the CF700-2D engine type are presented Maintenance data for the test units during the period of testing as well as analyses of the samples of fuel used in each test are given

JMS

N79-17870# Aeronautical Research Associates of Princeton Inc. N. J.

GUST LOAD ESTIMATION USING A SIMPLIFIED POWER SPECTRAL TECHNIQUE Final Report, Apr 1977 - Apr 1978

Guy Williamson Oct 1978 26 p refs

(ARAP-362 FAA-RD-78-118) Avail NTIS HC A03/MF A01 A one-degree-of-freedom power spectral technique for estimating gust loads on aerodynamic surfaces produced by atmospheric turbulence is presented A procedural flow chart to guide the designer in the use of this technique and sample calculations are included.

N79-17871*# National Aeronautics and Space Administration Langley Research Center Hampton Va

THEORETICAL AND EXPERIMENTAL INVESTIGATION OF GROUND INDUCED EFFECTS FOR A LOW-ASPECT-RATIO HIGHLY SWEPT ARROW-WING CONFIGURATION

Paul L Coe Jr and James L Thomas Jan 1979 100 p refs (NASA-TM-80041) Avail NTIS HC A05/MF A01 CSCL 01C

An investigation was conducted in the Langley V/STOL tunnel to determine the influence of ground proximity on the aerodynamic characteristics of a low aspect ratio highly swept arrow wing configuration. The tests were conducted using a moving belt ground plane to simulate ground heights varying from 0.1 to 1.0 wing spans. The experimental results show that as the height above the ground decreases the configuration experiences substantial increases in lift and reductions in induced drag Although a significant percentage of these ground-induced performance improvements are lost due to trim requirements the net performance improvement remains quite favorable. The tests also show that decreasing ground height results in a marked increase in the tail downwash factor and therefore results in a substantial increase in the horizontal tail contribution to longitudinal stability. Comparison of the experimental results with results predicted by a planar vortex lattice theoretical model shows that the theoretical model provides a good estimate of the ground induced effect on lift drag and longitudinal stability for the wing-body combination J M S

N79-17872*# National Aeronautics and Space Administration Ames Research Center Moffett Field Calif

CONFIGURATION MANAGEMENT AND AUTOMATIC CONTROL OF AN AUGMENTOR WING AIRCRAFT WITH VECTORED THRUST

Luigi S Cicolani B Sridhar and George Meyer Mar 1979 138 p refs

(NASA-TP-1222 A-7099) Avail NTIS HC A07/MF A01 CSCL 01C

An advanced structure for automatic flight control logic for powered-lift aircraft operating in terminal areas is under investigation at Ames Research Center. This structure is based on acceleration control acceleration commands are constructed as the sum of acceleration on the reference trajectory and a corrective feedback acceleration to regulate path tracking errors. The central element of the structure termed a Trimmap uses a model of the aircraft aerodynamic and engine forces to calculate the control settings required to generate the acceleration commands. This report describes the design criteria for the Trimmap and derives a Trimmap for Ames experimental augmentor wing jet STOL research aircraft.

N79-17875# National Aerospace Lab Amsterdam (Netherlands) Flight Div

THE NEED OF STICK FORCE STABILITY FOR ATTITUDE-STABILIZED AIRCRAFT, PART 2

H A Mooij and M F C vanGool 31 Jan 1977 75 p refs (Contracts NIVR-1745 RB-RLD-1976-1 3 1) (NLR-TR-77027-H) Avail NTIS HC A04/MF A01

Flight tests related to the effect of various levels of (artificial) positive stick force stability on the longitudinal controllability in the landing approach of an attitude-stabilized aircraft are described Approach performance and pilot commentary of 60 ILS/VASIS approaches flown with a twin-engined jet transport were analyzed. The aircraft was operated at a speed corresponding to the bottom of the thrust required versus speed curve Feedback of a signal proportional to the difference between the actual and the reference airspeed was used to generate (artificial) stick force stability. For the intermediate gradient of positive stick force stability investigated a modest reduction of airspeed deviation on the approach was measured pilot effort and glide path tracking perforamnce did not differ from those in the case of neutral stick force stability. For a high gradient of positive stick force stability (approximately 2.8 lbs per 6 knots) a marked increase in pilot effort and serious degradation of glide path control performance were measured

N79-17876# Naval Civil Engineering Lab Port Hueneme Calif AIRFIELD MARKING PAINTS STATE-OF-THE-ART Final Report

Richard W Drisko Sep 1978 45 p refs (Contract DOT-FA78WAI-847)

(FAA-RD-78-104) Avail NTIS HC A03/MF A01

Information on the composition of such paints federal specifications available test methods reflectorization methods deterioration mechanism skid-resistance relationships surface preparation application requirements and alternative marking systems is presented information on traffic paints was used where it was relevant. Recommended airfield marking practices to provide practical information to people responsible for airfield marking are summarized. While currently used airfield marking practices are considered adequate improved materials and/or methods may significantly reduce maintenance costs and may be necessary for more restrictive regulations that are anticipated.

 $\mbox{N79-17877}\#$ National Aviation Facilities Experimental Center Atlantic City N J

SURVEY OF RADAR SIMULATION TRAINING AT ATC FIELD FACILITIES Final Report, Jun 1977 - Mar 1978
Stephen Karovic and Theodore Rundall Sep 1978 51 p refs (FAA Proj 216-103-100)

(FAA-NA-78-27 FAA-RD-78-77) Avail NTIS

HC A04/MF A01

The results of a system-wide review of the current air traffic control enroute and terminal radar simulation training capability are discussed. Teams of air traffic controllers from NAFEC and from the field with engineering support visited 10 en route air traffic control centers and 17 terminals equipped with Automated Radar Terminal Systems (ARTS) Training personnel from three other ARTS facilities were interviewed. It was found that the field simulation systems, although originally designed only as software checkout tools now provide the field facilities with a radar training capability far surpassing that previously possible. Despite the generally wide acceptance and acclaim given this new capability shortcomings were uncovered which limit the training effectiveness and full utilization of the system These shortcomings including problems with equipment software staffing etc are identified and discussed Specific recommendations are made for the purpose of enhancing air traffic control radar simulation training in field facilities including software modifications increased staffing improved communications and in terminals an increased number of displays Author

N79-17878# Federal Aviation Agency Palmdale Calif RUNWAY SURFACE CONDITION SENSOR 6 Nov 1978 6 p

(AC-150/5220-13) Avail NTIS HC A02/MF A01

Methods for predicting and detecting pavement surface ice formation are considered Equipment design and performance specifications selection of sensors and installation of sensors are discussed

N79-17879# Air Force Inst of Tech Wright-Patterson AFB

DEVELOPMENT OF SMART TARGET FOR SIMULATION OF ONE-ON-ONE AIR-TO-AIR COMBAT MS Thesis

Dennis A Leuthauser Mar 1978 166 p refs (AD-A056739) AFIT/GAE/AA/78M-7)

NTIS HC A08/MF A01 CSCL 15/7

The feasibility of using an adaptive maneuvering target for air-to-air combat simulation in the large amplitude multimode aerospace research simulator was investigated. A computer program was developed which enabled the target to make tactical decisions based on aircraft states make variations in decision parameters corresponding to differences in pilots and provide control inputs to fly actual air combat maneuvers. Validation of the simulated target was accomplished by numerous test runs to ensure that simulated maneuvers were realistic and that continuity between mameuvers at different pilot skill levels was valid Author

N79-17880# Technische Hogeschool Delft (Netherlands) Dept of Aerospace Engineering

TWO-SEGMENT APPROACH INVESTIGATION ON A MOVING-BASE PILOTED FLIGHT SIMULATOR

G Bekebrede and M Baarspul Apr 1978 111 p refs (VTH-LR-250) Avail NTIS HC A06/MF A01

The objectives of the study were to investigate the influences of the following qualitative variables on the accuracy of the landing approach and on the pilot workload (1) the influence of the approach profile (2) the influence of atmospheric and (3) the influence of lateral autopilot control. Regression analysis was applied to the recorded data as well as to the pilot-ratings obtained after each run. The results of the analysis indicate that the glide slope configuration, the presence of atmospheric turbulence and applied automatic lateral control do have significant influences on the pilot's actions and on the pilot ratings. Noise contours demonstrating possible noise reductions as a consequence of the two-segment noise abatement approaches are presented For the two-segment approaches the sound pressure level can be significantly reduced depending on the observers location At respectively 6 n mi and 3 5 n mi from touchdown at the vertical projection of the flightpath the sound pressure level reductions amount to 11 PNdb and 7 PNdb respectively ĹS

N79-17966# National Aviation Facilities Experimental Center Atlantic City N J

POOL FIRE RADIATION THROUGH A DOOR IN A SIMULATED AIRCRAFT FUSELAGE Final Report, Aug -Dec 1977

Thor I Eklund Dec 1978 44 p refs Original contains color illustrations

(FAA Proj 181-521-000)

(FAA-NA-78-38 FAA-RD-78-135) Avail NTIS HC A03/MF A01

Small-scale methods of simulating postcrash fuel spill fires adjacent to fuselage open doors are evaluated. Pool fires in a quiescent environment were scaled down and their radiant heat transfer through fuselage doorways evaluated. Steel ducts of 1, 2 3 and 4 foot diameter were employed as models Analytic solutions to radiative transfer equations were developed and matched with the experimental heat fluxes at two locations within each model. The analysis demonstrates that the doorway can be treated as a radiating black body surface of 1874 F, and that heat fluxes to other areas around the doorway can be calculated. A comparison of heat flux to the model exterior was compared with existing full-scale fire test data

N79-18012# National Aerospace Lab Amsterdam (Netherlands) Structures and Materials Div

ENVIRONMENTAL EFFECTS ON CRACK GROWTH IN FLIGHT-SIMULATION TESTS ON 2024-T3 AND 7075-T6 MATERIAL

J Schilve F A Jacobs and P J Tromp 13 Jul 1978 57 p refs

(Contract NIVR-1725)

(NLR-TR-76104-U) Avail NTIS HC A04/MF A01

Flight-simulation tests based on a standardized gust load spectrum were carried out in normal air very dry air and salt water Specimen thicknessess were t = 2 mm and t = 10mm mean stress in flight was 70 or 55 MN/sq m in all cases a significant effect of the environment was found. Fatigue lives for t = 10 mm were much shorter than for t = 2 mm. The more severe flights caused noticeable crack growth delays thus having a predominant effect on crack growth. Technical implications of the test results are discussed.

N79-18057*# Union Carbide Corp Tonawanda N Y STUDY OF HYDROGEN RECOVERY SYSTEMS FOR GAS VENTED WHILE REFUELING LIQUID-HYDROGEN FUELED AIRCRAFT

C R Baker Feb 1979 70 p refs (Contract NAS1-14698)

(NASA-CR-158991) Avail NTIS HC A04/MF A01 CSCL 21P

Methods of capturing and reliquefying the cold hydrogen vapor produced during the fueling of aircraft designed to utilize liquid hydrogen fuel were investigated. An assessment of the most practical economic and energy efficient of the hydrogen recovery methods is provided

N79-18074*# Little (Arthur D.) Inc. Cambridge Mass. AN ASSESSMENT OF THE RISKS PRESENTED BY THE USE OF CARBON FIBER COMPOSITES IN COMMERCIAL AVIATION VOLUME 1 FINAL REPORT **VOLUME 2** SUPPORTING APPENDICES Final Report

Ashok S Kalelkar Joseph Fiksel Phani P K Raj and Donald B Rosenfield Jan 1979 426 p refs (Contract NAS1-15380)

(NASA CR-158989) Avail NTIS HC A19/MF A01 CSCL

Carbon fiber (CF) composites are being used to an increasing extent in commercial aircraft due to their excellent structural properties. Since carbon fibers are highly conductive, a potential risk was identified in the event that an aircraft with CF composite structures is involved in an accidental fire. If carbon fibers are released from the fire they could disperse in the atmosphere and eventually cause damaging short circuits in electronic equipment at remote locations. This phenomenon could conceivably result in economic losses. The purpose of this study was to assess the risks presented to the nation as a whole by the use of CF composites in commercial aircraft in terms of the potential economic losses from air carrier accidents

N79-18075*# Little (Arthur D.) Inc. Cambridge Mass AN ASSESSMENT OF THE RISKS PRESENTED BY THE USE OF CARBON FIBER COMPOSITES IN COMMERCIAL AVIATION EXECUTIVE SUMMARY

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 1-24

Avail NTIS HC A19/MF A01 CSCL 12B

To support the investigation experimental data from a number of different sources were used including tests of carbon fibers (CF) release from burning composites and vulnerability tests for selected equipment. Field survey were conducted in the vincinity of several major airports in order to characterize the types of facilities that might be exposed to CF releases. Census data were employed to enumerate the number of residential and commercial establishments in the vicinity of the 26 large hub airports. These data formed part of the input to a risk simulation model which produced a conditional risk profile showing the probability of different amounts of loss given that an accidental release of CF has occurred A national risk profile was developed which estimates the annual losses due to CF usage in commercial aircraft based upon the anticipated usage in 1993 GY

N79-18076*# Little (Arthur D.) Inc. Cambridge Mass OVERVIEW OF THE CARBON FIBER PROBLEM In its An Assessment of the Risks Presented by the Use of

Carbon Fiber Composites in Com Aviation Jan 1979 p 25-41 refs

Avail NTIS HC A19/MF A01 CSCL 13L

Carbon fibers (CF) composite structures are being utilized more as alternatives to metals in both civilian and military applications. They are valued for their light weight and high strength as well as for their ease of designing structures with specific shapes and sizes. However, a problem may exist due to the high conductivity of CF. CF are manufactured from a precursor material which is subjected to great stress and heat treatment causing a change in the nhysical and electrical properties. The fibers are bound together by a matrix of epoxy. In the event of fire (aircraft accident), the epoxy would burn away releasing these fibers into the atmosphere. When these fibers come in contact with electronic equipment, they might cause damage to by settling on electrical junctions. An overview is given of the objectives for a study and the approach and methodology developed for determination of risk profiles.

N79-18078*# Little (Arthur D.) Inc. Cambridge Mass PROBABILISTIC ANALYSIS OF AIR CARRIER ACCIDENTS

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 61-90 refs

Avail NTIS HC A19/MF A01 CSCL 13L

In order to estimate the potential risks due to carbon fibers (CF) released from aircraft accidents it was necessary to quantify the probability of an accident or incident at a major hub airport. This probability was contingent upon various conditions surrounding the incident including the phase of operation aircraft type and the weather conditions. The type of accident predicted was categorized according to its location relative to the runway and the severity of damage sustained. The methodology utilized to estimate the probability of a specific type of accident is outlined and the various models that were developed in the course of this work are described.

N79-18079*# Little (Arthur D) Inc Cambridge Mass CARBON FIBER RELEASE CONDITIONS

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 91-100 refs

Avail NTIS HC A19/MF A01 CSCL 13L

The methodology and data sources analyzed to determine the carbon fiber release scenarios for aircraft accidents are presented. The scenarios consisted of a set of probability distributions for each of the variables judged to have impact on carbon dispersion and economic loss. Most of the distributions were independent of each other, but some were correlated. The set of probability distributions for all of the variables considered was used as input to a risk simulation. Because of this simulation approach unique scenarios that encompassed a whole set of variables were not identified rather the emphasis was on a distribution for each individual variable.

N79-18080*# Little (Arthur D.) Inc. Cambridge Mass CARBON FIBER DISPERSION MODELS USED FOR RISK ANALYSIS CALCULATIONS

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 101-124

Avail NTIS HC A19/MF A01 CSCL 13L

For evaluating the downwind ground level exposure contours from carbon fiber dispersion two fiber release scenarios were chosen. The first is the fire and explosion release in which all of the fibers are released instantaneously. This model applies to accident scenarios where an explosion follows a short-duration fire in the aftermath of the accident. The second is the plume release scenario in which the total mass of fibers is released into the fire plume. This model applies to aircraft accidents where only a fire results. These models are described in detail.

N79-18083*# Little (Arthur D) Inc Cambridge Mass ESTIMATION OF ECONOMIC LOSSES

in its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 160-177

refs

Avail NTIS HC A19/MF A01 CSCL 05C

If the concentration of carbon fibers (CF) is high after their dispersion due to an aircraft fire there is a significant possibility that a number of residential commercial and industrial establishments might be affected by electronic equipment failure Estimating economic losses from CF release involves characterizing an entire spectrum of buildings and electronic equipment within a given community. A number of simplified assumptions were made to reduce the data collection requirements to manageable proportions. A limited number of facility categories were identified and assumed to be relatively homogeneous. The detailed examination of potential losses on an industry-by-industry basis is an important area for future investigation.

N79-18084*# Little (Arthur D) Inc Cambridge Mass MONTE CARLO SIMULATION OF SINGLE ACCIDENT AIRPORT RISK PROFILE

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 178-192 refs

Avail NTIS HC A19/MF A01 CSCL 12A

A computer simulation model was developed for estimating the potential economic impacts of a carbon fiber release upon facilities within an 80 kilometer radius of a major airport. The model simulated the possible range of release conditions and the resulting dispersion of the carbon fibers. Each iteration of the model generated a specific release scenario which would cause a specific amount of dollar loss to the surrounding community. By repeated iterations a risk profile was generated showing the probability distribution of losses from one accident. Using accident probability estimates the risks profile for annual losses was derived. The mechanics are described of the simulation model the required input data and the risk profiles generated for the 26 large hub airports.

N79-18085*# Little (Arthur D) Inc Cambridge Mass SYNTHESIS OF NATIONAL RISK PROFILE

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 193-216 refe

Avail NTIS HC A19/MF A01 CSCL 12B

The methodology used and results obtained in computing the national risk profile for carbon fibers (CF) released after an aircraft accident (fire or explosion) are presented. The computation was performed by use of twenty-six individual conditional risk profiles together with the extrapolation of these profiles to other U.S. airports. The risk profile was obtained using 1993. CF utilization forecasts but numbers of facilities were taken from 1972 and 1975 census data while losses were expressed in 1977 dollars.

N79-18086*# Little (Arthur D) Inc Cambridge Mass INTERPRETATION OF RESULTS

In its An Assessment of the Risks Presented by the Use of Carbon Fiber Composites in Com Aviation Jan 1979 p 217-232 refs

Avail NTIS HC A19/MF A01 CSCL 12B

An analysis of the risks to the nation which may arise due to carbon fiber release from air carrier accidents was presented. The purpose of this report is to place these risks in perspective by examining their implications for society as a whole. Some additional aspects of risk estimation which were not dealt with by simulation modeling approach are addressed and open issues which may require further study are indicated.

N79-18115# Communications Research Centre Ottawa (Ontario) Dept of Communications

THE SEARCH AND RESCUE SATELLITE (SARSAT) SYSTEM PROJECT

H L Werstiuk and A E Winter In AGARD Operational Modelling of the Aerospace Propagation Environ Vol 1 and 2 Nov 1978 12 p refs

Avail NTIS HC A99/MF A01

The application of satellite technology as an aid to search and rescue (SAR) was studied. The work included examination

of SAR requirements and the investigation of various system concepts culminating in proof-of-concept experiments using the AMSAT OSCAR satellites during 1975 and 1976. In the experiments signals from simulated Emergency Locator Transmitters (ELTs) were received by the polar-orbiting OSCAR 6 satellite and relayed to a ground station at the Communications Research Centre (CRC) By the processing of Doppler information contained in this relayed signal, the position of the ELT could be determined with an accuracy of 5-15 km. The experimental techniques and earlier results obtained in the program are described.

N79-18156# Federal Aviation Administration Washington D C SHORT RANGE TERMINAL RADAR (SRTR) DEFINITION STUDY Final Report. Oct 1974 - Oct 1975

Sep 1978 138 p refs Prepared in cooperation with APL Laurel Md Lincoln Lab MIT and MITRE Corp McLean Va (FAA Proj 023-241)

(FAA-RD-78-64) Avail NTIS HC A07/MF A01

N79-18229# Air Force Flight Dynamics Lab Wright-Patterson AFB Ohio Atmospheric Electricity Hazards Group

EVALUATION OF THE RYAN STORMSCOPE AS A SEVERE WEATHER AVOIDANCE SYSTEM FOR AIRCRAFT Preliminary Report

Timothy J Seymour and Robert K Baum In Florida Inst of Technol FAA-Florida Inst of Technol Workshop on Grounding and Lightning Technol Mar 1978 p 29-35 refs

Avail NTIS HC A08/MF A01

The Ryan Stormscope was evaluated for use as a severe weather avoidance system for aircraft. An instrumented T-39B aircraft was flown in the vicinity of thunderstorm activity while displays of the Stormscope and onboard weather radar were documented photographically. The coordinates of the Stormscope display points and their acquisition times were interfaced to an onboard computer system for post-flight data reduction and comparison with the ground-based LDAR system. Preliminary analysis of the data shows that Stormscope exhibits reasonably good correlation with weather radar precipitation contours. Stormscope does not exhibit the tight clustering of data points characteristic of the groundbased LDAR system a result which is attributed to inaccuracies in the Stormscope ranging system.

Author

N79-18237# Lightning and Transients Research Inst. St. Paul

AN RF COMPATIBLE LIGHTNING DIVERTER STRIP

John Robb Jay Cline (Dayton-Granger Aviation Inc.) John Raney (Dayton-Granger Aviation Inc.) and J Dunn (US Air Force Eglin AFB) In Florida Inst. of Technol FAA-Florida Inst. of Technol Workshop on Grounding and Lightning Technol Mar. 1979 p. 91-95

Avail NTIS HC A08/MF A01

Airborne and Ground Radome Lightning protection with superior RF characteristics is discussed. Dayton-Granger STRIKE-GUARD is examined along with a presentation of laboratory test data. Additional material is presented describing major thunderstorm penetrations by USAF.

N79-18238# Air Force Flight Dynamics Lab Wright-Patterson AFB Ohio Atmospheric Electricity Hazards Group PROTECTION/HARDENING OF AIRCRAFT ELECTRONIC SYSTEMS AGAINST THE INDIRECT EFFECTS OF LIGHTNING

John C Corbin Jr In Florida Inst of Technol FAA-Florida Inst of Technol Workshop on Grounding and Lightning Technol Mar 1979 p 97-103 refs

Avail NTIS HC A08/MF A01

A number of different approaches which can be applied to protect or harden aircraft and their electronic systems against the indirect effects of lightning are discussed in this paper. The basic approaches include (1) hardening the external structure to prevent or greatly reduce the penetration of if energy into the aircraft (2) shielding equipment and cables (3) hardening electronic circuits and (4) combinations of all three. The use of filters, limiters circuit design and functional hardening are described as techniques which can be applied for protecting electronic circuits. A systems approach is recommended for achieving an optimum hardened configuration.

N79-18242# Grumman Aerospace Corp Bethpage N Y INDUCED EFFECTS OF LIGHTNING ON AN ALL COMPOSITE AIRCRAFT

R A Perala (Mission Research Corp.) K Lee (Mission Research Corp.) and R Cook (Mission Research Corp.) In Florida Inst. of Technol. FAA-Florida Inst. of Technol. Workshop on Grounding and Lightning Technol. Mar. 1979. p. 127-131. refs.

(Contract F33615-77-C 5169)

Avail NTIS HC A08/MF A01

Results are presented for lightning induced cable currents and voltages on typical cable runs inside an all composite aircraft. Both a direct stroke and a nearby stroke are considered. Results are also given for the case in which the aircraft is coated with 6-mil aluminum flame spray. It is shown that as expected the direct stroke induces the largest voltages but the effects of the nearby strike are not negligible.

Author

N79-18246# Lightning Technologies Inc Pittsfield Mass A NEW STANDARD FOR LIGHTNING QUALIFICATION TESTING OF AIRCRAFT TECHNICAL OVERVIEW, DEFINITIONS AND BASIC WAVEFORMS

J Anderson Plumer In Florida Inst of Technol FAA-Florida Inst of Technol Workshop on Grounding and Lightning Technol Mar 1979 p 155-163 refs

Avail NTIS HC A08/MF A01

In an effort to provide widely accepted criteria representative of a severe environment. Society of Automotive Engineers Committee AE4-L (on lightning) and a similar group in UK prepared documents defining lightning waveforms and testing techniques for aerospace vehicles and hardware. Agreement exists on the criteria to be employed for qualification testing and the US. Committee has drafted a US military standard for lightning qualification testing based on this criteria. This paper summarizes the scope lightning strike zone definitions and test waveforms presented in the draft standard.

N79-18274# Tuebingen Univ (West Germany) ELECTRIC CHARGING OF HELICOPTERS [ELEKTRISCHE AUFLADUNG VON HUBSCHRAUBERN]

R Muehleisen and H J Fischer Bonn DOKZENTBW 1978 76 p refs in GERMAN ENGLISH summary Sponsored by Bundesmin fuer Verteidigung (BMVG-FBWT-78-7) Avail NTIS HC A05/MF A01 DOK-

ZENTBW DM 30

In order to improve aircraft safety and reduce accidents electrical measurements were made on UH 1D and CH 53 helicopters to determine charging in the atmospheric electric field charging by exhaust gases and charging from external forces such as precipitation and dust. The electric discharger mounted on the CH 53 helicopter is helpful only during fine weather but not in the cases of high field strength. An improved method for discharging is recommended.

N79-18284*# National Aeronautics and Space Administration Langley Research Center Hampton Va

PRESSURE AND HEAT-TRANSFER DISTRIBUTIONS IN A SIMULATED WING-ELEVON COVE WITH VARIABLE LEAKAGE AT A FREE-STREAM MACH NUMBER OF 69

William D Deveikis and Whitney Bartlett Dec 1978 53 prefs

(NASA-TM-74095 L-12591) Avail NTIS HC A04/MF A01 CSCL 20D

An experimental aerodynamic heating investigation was conducted to determine effects of hot boundary-layer ingestion into the cove on the windward surface between a wing and elevon for cove seal leak areas nominally between 0 and 100 percent of cove entrance area. Pressure and heating-rate distributions were obtained on the wing and elevon surfaces and on the cove walls of a full-scale model that represented a section of the cove region on the space shuttle orbiter. Data were obtained for both attached and separated turbulent boundary layers upstream of the unswept cove entrance. Average free-stream Mach number was 6.9 average free-stream unit Reynolds numbers were 131 x 10 to the 6th power and 440 x 10 to the 6th power per meter (0.40 x 10 to the 6th power and 1.34×10 to the 6th power per foot) and average total temperature was 1888 K (3400 R) Cove pressures and heating rates varied as a function of seal leak area independent of leak aspect ratio. Although cove heating rates for attached flow did not appear intolerable it was postulated that convective heating in the cove may increase with time. For separated flow the cove environment was considered too severe for unprotected interior structures of control surfaces Author

N79-18286*# Northrop Corporate Labs Hawthorne Calif A WATER TUNNEL FLOW VISUALIZATION STUDY OF THE F-15 Final Report

Dale J Lorincz Dec 1978 96 p refs (Contract NAS4-2526) (NASA-CR-144878 NOR-78-176) HC A05/MF A01 CSCL 20D

ail NTIS

Water tunnel studies were performed to qualitatively define the flow field of the F-15 aircraft. Two lengthened forebodies one with a modified cross-sectional shape were tested in addition to the basic forebody. Particular emphasis was placed on defining vortex flows generated at high angles of attack. The flow visualization tests were conducted in the Northrop diagnostic water tunnel using a 1/48-scale model of the F-15 Flow visualization pictures were obtained over an angle-of-attack range to 55 deg and sideslip angles up to 10 deg. The basic aircraft configuration was investigated in detail to determine the vortex flow field development vortex path and vortex breakdown characteristics as a function of angle of attack and sideslip Additional tests showed that the wing upper surface vortex flow fields were sensitive to variations in inlet mass flow ratio and inlet cowl deflection angle. Asymmetries in the vortex systems generated by each of the three forebodies were observed in the water tunnel at zero sideslip and high angles of attack

N79-18296* National Aeronautics and Space Administration Langley Research Center Hampton Va

APPARATUS FOR MEASURING AN AIRCRAFT'S SPEED AND HEIGHT Patent

William R Young and Charles W Stump inventors (to NASA) Issued 23 Jan 1979 7 p Filed 9 Mar 1978 Supersedes N78-22115 (16 - 13 p 1667)

(NASA-Case-LAR-12275-1 US-Patent-4 135 817 US-Patent-Appl-SN-885065 US-Patent-Class-356-28

US-Patent-Class-358-107) Avail US Patent and Trademark

Office CSCL 14B

An apparatus for measuring aircraft horizontal speed and height above ground without the need for airborne cooperative devices is presented. Two ground level TV cameras separated by a measured distance and pointed at zenith are placed in line.

by a measured distance and pointed at zenith are placed in line with the projection of the expected path of the aircraft. Speed is determined by measuring the time that it takes the aircraft to travel between the fields of view of the two TV cameras using zenith crossings as the reference points. Height is determined by correlating the speed with the time required to cross the field of view of either of the two cameras.

Official Gazette of the U.S. Patent and Trademark Office

N79-18318* National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio

COMPOSITE SEAL FOR TURBOMACHINERY Patent

Robert C Bill and Lawrence P Ludwig inventors (to NASA) Issued 23 Jan 1979 5 p Filed 27 May 1977 Supersedes N77-24498 (15 - 15 p 1999)

(NASA-Case-LEW-12131-1 US-Patent-4 135 851 US-Patent-Appl-SN-801290 US-Patent-Class-415-174

US-Patent-Class-415-200) Avail US Patent and Trademark Office CSCL 11A

A gas path seal suitable for use with a turbine engine or compressor is provided. A shroud wearable or abradable by the abrasion of the rotor blades of the turbine or compressor protects the rotor blades. A compliant backing surrounds the shroud. The backing may be made of corrugated sheets or the like with adjacent layers having off-set corrugations with axes of the folds parallel to the rotor axis. The sheets may be bonded together at points of contact by brazing welding or the like. In another embodiment a compliant material is covered with a thin ductile layer. A mounting fixture surrounds the backing

Official Gazette of the U.S. Patent and Trademark Office

N79-18320*# Lockheed-California Co Burbank Advanced Development Projects Div

FABRICATION AND EVALUATION OF ADVANCED TITANIUM STRUCTURAL PANELS FOR SUPERSONIC CRUISE AIRCRAFT

L Payne Washington NASA Mar 1977 80 p refs Film supplements L1204 and L1205 to this report are available on loan from National Aeronautics and Space Administration Langley Research Center Hampton Va 23665

(NASA-CR-2744 SP-4508) Avail NTIS HC A05/MF A01 CSCL 01C

Flightworthy primary structural panels were designed fabricated and tested to investigate two advanced fabrication methods for titanium alloys. Skin-stringer panels fabricated using the weldbraze process and honeycomb-core sandwich panels fabricated using a diffusion bonding process, were designed to replace an existing integrally stiffened shear panel on the upper wing surface of the NASA YF-12 research aircraft. The investigation included ground testing and Mach 3 flight testing of full-scale panels and laboratory testing of representative structural element specimens. Test results obtained on full-scale panels and structural element specimens indicate that both of the fabrication methods investigated are suitable for primary structural applications on future civil and military supersonic cruise aircraft.

N79-18470 British Library Lending Div Boston Spa (England) AERODYNAMIC BEHAVIOR OF FIBRES AND SAMPLING OF RESPIRABLE DUST

W Walkenhorst Jul 1978 20 p refs Transl into ENGLISH from Staub Reinhaltung der Luft (West Germany) v 37 no 9 1977 p 323-328

(BLL-RTS-11267) Avail British Library Lending Div Boston Spa Engl

Straight fibers of the same size have different aerodynamic diameters according to the sedimentation direction. In inclined positions the sedimentation and effective force no longer coincide in direction. In shear flow the fibers may perform a gyratory motion or their longitudinal axis can set itself practically in the flow direction. Bent fibers mostly present in actual cases perform rotational motion in shear flow. A mean value of the aerodynamic diameter therefore sets in In respiratory passages the fibers are deposited according to their aerodynamic diameters. In addition to this, a blocking effect plays a role primarily for bent fibers. A pre-elutriator with sheet stack is proposed and gives to the blocking effect.

N79-18475# Argonne National Lab III
AIRPORT VICINITY AIR POLLUTION MODEL
ATED VERSION USER'S GUIDE Final Report
L A Conley and D M Rote Sep 1978 126 p refs
(Contract DOT-FA71WAI-223)
(FAA-RD-78-111) Avail NTIS HC A07/MF A01

A discussion of the theoretical considerations fundamental to the Airport Vicinity Air Pollution Model Abbreviated Version as well as program flow diagrams essential to understanding the theory is presented. Required sequential card data input to the program is illustrated along with substitution options for program constants Additionally an example problem and a program listing are provided G Y

N79-18686*# National Aeronautics and Space Administration Langley Research Center Hampton Va

APPLICATIONS OF DIFFRACTION THEORY TO AERO-**ACOUSTICS**

Donald L Lansing Liu Chen-Huei and Thomas D Norum Jan 1979 14 p refs To be presented at the VKI/AGARD Special Course Brussels 28 May 1979 1 Jun 1979 (NASA-TM-80053) Avail NTIS HC A02/MF A01 CSCL 20A

A review is given of the fundamentals of diffraction theory and the application of the theory to several problems of aircraft noise generation propagation and measurement. The general acoustic diffraction problem is defined and the governing equations set down Diffraction phenomena are illustrated using the classical problem of the diffraction of a plane wave by a half-plane Infinite series and geometric acoustic methods for solving diffraction problems are described. Four applications of diffraction theory are discussed the selection of an appropriate shape for a microphone the use of aircraft wings to shield the community from engine noise the reflection of engine noise from an aircraft fuselage and the radiation of trailing edge noise

N79-18687*# National Aeronautics and Space Administration Langley Research Center Hampton Va

VARIABILITY OF ANNOYANCE RESPONSE DUE TO AIRCRAFT NOISE

Thomas K Dempsey and Jimmy M Cawthorn Mar 1979 77 p refs

(NASA-TP-1335 L-12483) Avail NTIS HC A05/MF A01 CSCL 20A

An investigation was conducted to study the variability in the response of subjects participating in noise experiments. This paper presents a description of a model developed to include this variability which incorporates an aircraft-noise adaptation level or an annoyance calibration for each individual. The results indicate that the use of an aircraft-noise adaption level improved prediction accuracy of annoyance responses (and simultaneously reduced response variation) Author

N79-18799# Federal Aviation Administration Washington D C HELICOPTER OPERATIONS DEVELOPMENT PLAN

Sep 1978 116 p (FAA-RD-78-101 PAR-517-78)

NTIS Avail

HC A06/MF A01

The Helicopter Operations Development Plan is designed to provide for upgrading and development of all those criteria standards procedures systems and regulatory activities which will allow safe timely and economical integration of the helicopter into all-weather operations in the National Airspace System It describes a five-year development program whose objective is to improve the National Airspace System so as to enable helicopters to employ their unique capabilities. These areas are covered in the plan (1) IFR Helicopter Operations (2) Navigation Systems Development (3) Communication Systems Development, (4) Helicopter Air-Traffic Control (5) Weather Environment (6) All-Weather Heliport Development (7) IFR Helicopter Certification Standards (8) Helicopter Icing Standards (9) Helicopter Crashworthiness and (10) Helicopter Noise Characterization The FAA groups other Federal Government agencies and other organizations participating in this effort are identified Program management responsibilities are addressed A program schedule with milestones is presented and program funding requirements are identified LS

N79-18886# General Dynamics Corp San Diego Calif F-18 HIGH ANGLE OF ATTACK TESTING

Philip F Oestricher and Robert C Ettinger (AFFTC Edwards AFB Calif) In SETP SETP Tech Rev Vol 14 No 2 1979 p 1-10

Avail NTIS HC A10/MF A01

A fly-by-wire flight control system is developed to allow a fighter pilot the maneuverability of reckless abandon Vigorous air combat maneuvering without the concern of maintaining the aircraft was proved Ballistic flight and full lateral stick rolls were examined. The angle of attack and structural limiting features. were found to provide protection in air combat maneuvering

SES

N79-18888# McDonnell-Douglas Corp., St. Louis Mo. F-18 STATUS REPORT

John E Krings In SETP SETP Tech Rev Vol 14 No 2 1979 p 21-25

Avail NTIS HC A10/MF A01

The entire F-18 program including the design of the cockpit displays weapon system integration and approach configuration is outlined. Fly-by-wire digital system of the F-18 is described Aerodynamic refinements were finalized in flight simulations

N79-18889# Israeli Air Force Zahal FLIGHT TESTING THE KFIR

Yıtzhak Peer In SETP SETP Tech Rev Vol 14 No 2 1979 p 26-37

Avail NTIS HC A10/MF A01

The canard concept to improve the supersonic maneuvering of the Mirage 3 aircraft is developed. This test program included redesign of the cockpit integration of modern weapons delivery system with headup display the improvement of the flight control system and aerodynamic configurations modification design. An engine for greater combat maneuvers was examined SES

N79-18890# Rockwell International Corp Canoga Park Calif Collins Avionics and Missiles Group

COCKPIT MANAGEMENT

C I Rice In SETP SETP Tech Rev Vol 14 No 2 1979 p 39-42

Avail NTIS HC A10/MF A01

A challenge to avionic manufacturers, airframe manufacturers, and test pilots is presented. Cockpit management in general aviation air transport, and military aircraft are discussed

N79-18891# Garrett Corp Torrance Calif SMALL FAN-JET ENGINES

Ivan E Speer In SETP SETP Tech Rev Vol 14 No 2 1979 p 43-51

Avail NTIS HC A10/MF A01

The changes from straight jets to medium bypass fans in business aircraft power plants are presented. The cycle for business aircraft at higher altitudes is discussed. The changes to the fan engine to improve fuel consumption reduce weight increase reliability and durability and reduce noise are described

N79-18892# NCR Corp , Los Angeles, Calif CORPORATE AVIATION IN THE 1980'S

Donald T Keeley In SETP SETP Tech Rev Vol 14 No 2 1979 p 52-56

Avail NTIS HC A10/MF A01

The problems of corporate aviation and corporate aircraft are discussed. The planned environment of the airline pilots commuter pilots, military pilots, and test pilots was studied

SES

N79-18893# Cincinnati Univ Ohio THE LEARJET LONGHORN SERIES THE FIRST JETS WITH WINGLETS

Neil A Armstrong and Peter T Reynolds (Gates Learjet Corp.) In SETP SETP Tech Rev Vol 14 No 2 1979 p 57-66

Avail NTIS HC A10/MF A01

The Gates Learjet Model 28 is described following the first test flight. The cruise fuel flow is increased and the takeoff and landing performance is improved. The cruise fuel flow reductions are the result of several factors. (1) the aircraft can operate at higher altitudes due to the added wing area. (2) for the same payload and range the takeoff weight will be lower because less mission fuel is required, and (3) drag is reduced by removing the tip tanks increasing the aspect ratio and adding the winglets.

N79-18894*# National Aeronautics and Space Administration Langley Research Center Hampton, Va

FLYING NASA'S TERMINAL CONFIGURED VEHICLE AGAINST THE MICROWAVE LANDING SYSTEM

Lee H Person, Jr and Kenneth R Yenni In SETP SETP Tech Rev , Vol 14, No 2 1979 p 110-123

Avail NTIS HC A10/MF A01 CSCL 01C

Technology for advanced airborne systems and flight procedures to improve terminal-area operations in ATC environment is developed. The terminal configured vehicle (TCV) aircraft, its integrated digital electronic displays and flight controls, and how the pilot interfaces with the aircraft to fly precise curved descending approaches using Microwave Landing System (MLS) guidance are discussed.

N79-18895# Lockheed Aircraft Corp Burbank, Calif
DEVELOPMENT OF THE L-1011 FLIGHT MANAGEMENT
SYSTEM

Donald A Moor *In* SETP SETP Tech Rev, Vol 14 No 2 1979 p 124-134

Avail NTIS HC A10/MF A01

The Lockheed/Army Flight Management System is described in preparation to make present and future generations more efficient A means for automatic precise control of aircraft speeds and engine thrust during climb cruise and descent, full time performance management in areas of near neutral speed-thrust stability, reducing crew workload and offering a large potential for fuel savings are discussed

SES

N79-18896# Boeing Co Seattle Wash
THE CONTINUITY FACTOR IN AIRCRAFT DEVELOPMENT

A M Johnston In SETP SETP Tech Rev Vol 14, No 2 1979 p 135-145

Avail NTIS HC A10/MF A01

The continuity factor is the respective sequential application of tested and desirable and undesirable technologies. Vehicle models are studied to indicate when the continuity factor is appropriately applied and the respective product excels. SES

N79-18897# Rockwell International Corp Canoga Park Calif XF4D SKYRAY DEVELOPMENT NOW IT CAN BE TOLD Robert O Rahn In SETP SETP Tech Rev Vol 14, No 2 1979 p 147-161

Avail NTIS HC A10/MF A01

The XF4D is a single-place low aspect ratio, delta-wing interceptor-type airplane which is described. Primary longitudinal and lateral control is accomplished by use of differentially acting elevons located along the trailing edge of either wing. Longitudinal and lateral trim is obtained from trimmers located inboard of the elevons Directional stability and control are obtained from a single swept vertical surface lying in the plane of symmetry The elevons are actuated by a single irreversible power control system with feel for the pilot provided by a system utilizing electrical magnetic clutches. Rudder operation by the pilot is by a direct-connected cable system. The airplane is equipped with a yaw damper which also actuates the rudder through a servo-system A manual flight control system for the elevons was provided should failure of the power system occur. An emergency auxiliary electrically-driven hydraulic pump was added for flight tests. A unique four-wheel landing gear was designed which utilized a small retractable tail wheel to absorb the tail loads during high angle of attack landings

N79-18903 Johns Hopkins Univ, Baltimore Md SOME ASPECTS OF UNSTEADY INSECT AERODYNAMICS ACCELERATION POTENTIAL METHODS IN PLANE UN-STEADY AIRFOIL THEORY, AND MEASUREMENTS OF UNSTEADY-PERIODIC FORCES GENERATED BY THE BLOWFLY Ph.D. Thesis

Richard Hugh Buckholz 1978 363 p Avail Univ Microfilms Order No 7906436

A simple dynamic force balance was developed and applied to the measurement of the instantaneous lift and drag forces generated by a blowly flying fixed in a wind tunnel. The novel force balance was a simple, taut, wire string with fixed ends, the live insect is mounted near the strong midpoint. The instantaneous force exerted by the blowfly's thorax on the wire was measured by detection of miniscule wire motion. This force was attributed to both wing inertial forces and wing aerodynamic forces. Subsequently, the former were computed from the kinematics of fly wings as photographed and measured by Nachtigall (1966). The phase relation between the wing kinematics and the streamwise insect forces was measured. It was found that the periodic lift and drag forces experienced by the insect s thorax during flapping flight contained a surprisingly small amount of higher harmonics of the wing beating frequency.

Dissert Abstr

N79-18909 Iowa State Univ of Science and Technology, Ames CALCULATION OF SUPERSONIC VISCOUS FLOW OVER DELTA WINGS WITH SHARP SUBSONIC LEADING EDGES Ph D Thesis

Yvon Clovis Vigneron 1978 79 p Avail Univ Microfilms Order No 7904026

Two complementary procedures were developed to calculate the viscous supersonic flow over conical shapes at large angles of attack with application to cones and delta wings. In the first approach, the flow was assumed to be conical and the governing equations were solved at a given Reynolds number with a time-marching explicit finite difference algorithm. In the second method the parabolized Navier-Stokes equations were solved with a space-marching implicit noniterative finite difference algorithm. This latter approach was not restricted to conical shapes and provided a large improvement in computational efficiency over published methods. Results from the two procedures agree very well with each other and with available experimental data.

Dissert Abstr

N79-18914*# National Aeronautics and Space Administration, Washington, D C

VORTEX PATTERN DEVELOPMENT ON THE UPPER SURFACE OF A SWEPT WING AT HIGH ANGLE OF ATTACK

J Mirande V Schmitt and H Werle Mar 1979 35 p refs Transl into ENGLISH of Conf paper from ONERA, Paris Presented at AGARD Reunion sur I Aerodynamique des Grandes Incidences Sandefjord, Norway 4-6 Oct 1978 Original language document was announced as A79-18554 Transl by Kanner (Leo) Associates Redwood City Calif

(Contract NASw-3199)

OPTIMIZATION

(NASA-TM-75377 ONERA-TP-1978-124, Memoire-12) Avail NTIS HC A03/MF A01 CSCL 01A

An experimental study based on a swept wing, was undertaken in the water tunnel and the wind tunnel at low speeds with a view to improving the understanding of the intervening phenomena and to make easier their modelling. The vortex flow effects on the wing are first illustrated from global effort measurements and static pressure distributions. The domain of existence of this type of flow is deduced as a function of both sweep angle and angle of attack. By a phenomenological study in the water tunnel an attempt is made to describe the physical pattern of the vortex flow from its formation near the apex to its breakdown at the trailing edge. Lastly, by means of a clinometric probe the flow field over the wing is determined.

LS

N79-18916*# National Aeronautics and Space Administration Ames Research Center, Moffett Field, Calif APPROXIMATION CONCEPTS FOR NUMERICAL AIRFOIL Garret N Vanderplaats Mar 1979 38 p refs (NASA-TP-1370 A-7682) Avail NTIS HC A03/MF A01 CSCL 01A

An efficient algorithm for airfoil optimization is presented. The algorithm utilizes approximation concepts to reduce the number of aerodynamic analyses required to reach the optimum design. Examples are presented and compared with previous results. Optimization efficiency improvements of more than a factor of 2 are demonstrated. Improvements in efficiency are demonstrated when analysis data obtained in previous designs are utilized. The method is a general optimization procedure and is not limited to this application. The method is intended for application to a wide range of engineering design problems.

N79-18916*# National Aeronautics and Space Administration Ames Research Center, Moffett Field, Calif

INERTIAL DYNAMICS OF A GENERAL PURPOSE ROTOR
Ronald W DuVal Mar 1979 34 p refs

(NASA-TM-78557 A-7731) Avail NTIS HC A03/MF A01 CSCL 01A

The inertial dynamics of a fully articulated stiff rotor blade are derived with emphasis on equations that facilitate an organized programming approach for simulation applications. The model for the derivation includes hinge offset and six degrees of freedom for the rotor shaft. Results are compared with the flapping and lead-lag equations currently used in the Rotor Systems Research Aircraft simulation model and differences are analyzed.

Author

N79-18917*# Kansas Univ Center for Research Inc Lawrence Flight Research Lab

ANALYSIS OF SOME AERODYNAMIC CHARACTERISTICS DUE TO WING-JET INTERACTION

Greg L Fillman and C Edward Lan Mar 1979 126 p refs (Grant NsG-1139)

(NASA-CR-158349 CRINC-FRL-281-4) Avail NTIS HC A07/MF A01 CSCL 01A

The results of two separate theoretical investigations are presented A program was used which is capable of predicting the aerodynamic characteristics of both upper-surface blowing (USB) and over-wing blowing (OWB) configurations. A theoretical analysis of the effects of over-wing blowing jets on the induced drag of a 50 deg sweep back wing was developed. Experiments showed net drag reductions associated with the well known lift enhancement due to over-wing blowing. The mechanisms through which this drag reduction is brought about are presented. Both jet entrainment and the so called wing-jet interaction play important roles in this process. The effects of a rectangular upper-surface blowing jet were examined for a wide variety of planforms. The isolated effects of wing taper, sweep, and aspect ratio variations on the incremental lift due to blowing are presented. The effects of wing taper ratio and sweep angle were found to be especially important parameters when considering the relative levels of incremental lift produced by an upper-surface blowing configuration MMM

N79-18921# Von Karman Inst for Fluid Dynamics, Rhode-Saint-Genese (Belgium)

WINGS

W Stahl In its Missile Aerodyn Vol 1 1976 62 p refs

Avail NTIS HC A23/MF A01

Material is presented on low aspect ratio wings to provide an insight into the flow field and to discuss some of the effects of the flow on the wing Experimental evidence as obtained in wind tunnels by various flow visualization techniques and from pressure meaurements made on the model surfaces or in the outer flow are used to help in designing a wing with some desired properties. Some results of force measurements are presented to give an idea of the aerodynamic characteristics of such wings. A short survey is also given on some of the better known theoretical methods for the prediction of the aerodynamic characteristics of wings. Results obtained from some of the theories are compared to the results from experiments.

N79-18925# Messerschmitt-Boelkow-Blohm G m b H Munich (West Germany)

AIRBREATHING ENGINES - AERODYNAMIC ASPECTS

Guenther Jungclaus In Von Karman Inst for Fluid Dyn Missile Aerodyn, Vol 1 1976 40 p refs

Avail NTIS HC A23/MF A01

The interrelation between air inlet and the engine and the types of inlet are discussed. Air inlet design is discussed with respect to flow modes flow around the cowl mass flow vs pressure relationship starting conditions efficiency definitions and multiple-shock diffusers. Some special problems dealing with interference angle of attack and nonstationary flow are presented.

N79-18926# Illinois Univ at Urbana-Champaign Urbana Dept of Mechanical and Industrial Engineering

ANALYSIS OF BASE-FLOW PROBLEMS DURING POWERED SUPERSONIC FLIGHT

A L Addy In Von Karman Inst for Fluid Dyn Missite Aerodyn Vol 1 1976 100 p refs

Avail NTIS HC A23/MF A01

At supersonic flight speeds aircraft and missile performance during powered flight can be significantly affected by the separated flow region formed at the base of the vehicle by the interaction between the freestream and propulsive-nozzle flows. The proper evaluation of the effects of this separated-flow region the base-flow region is a difficult and recurring problem in aerodynamic design. Due to the generality, flexibility, and potential for extension the Chapman-Korst component model provides a means for the qualitative and quantitative evaluation of the effect on the afterbody-base problem of all pertinent design and performance parameters. The object of these notes is to present the theoretical bases for the generalized Chapman-Korst model, to demonstrate the capabilities and limitations of the model, to compare experimental and theoretical results and to discuss areas requiring further development.

N79-18933# Hawker Siddeley Dynamics Ltd Hatfield (England) Naval Weapons Div

THE PLACE OF AERODYNAMICS IN THE DESIGN PROCESS

J I Haworth /n Von Karman Inst for Fluid Dyn Missile Aerodyn Vol 2 1976 143 p

Avail NTIS HC A23/MF A01

The subject of how aerodynamics is dealt with in its practical application to missile design and development is the aim of this lecture. An explanation of the main stages involved in the inception and growth of a major project is given and the underlining principles which govern the whole of the design and development work is explained it is shown how the aerodynamic requirements are derived from the overall missile design and performance requirements. The steps taken to meet these requirements leading to the specification of the aerodynamic characteristics, and the verification of these, are outlined in general this lecture aims at stating what the aerodynamics has to do, and why these tasks arise.

G Y

N79-18946*# National Aeronautics and Space Administration Ames Research Center, Moffett Field Calif

SOME RECENT PROGRESS IN TRANSONIC FLOW COMPUTATION

William F Ballhaus In Von Karman Inst for Fluid Dyn Computational Fluid Dyn Vol 1 1976 122 p refs

Avail NTIS HC A19/MF A01 CSCL 01A

Although the development of a finite difference relaxation procedure to solve the steady form of equations of motion gave birth to the study of computational transonic aerodynamics and considerable progress has been made using the small disturbance theory, no general analytical solution method yet exists for transonic flows that include three dimensional unsteady and

viscous effects Two techniques are described which are useful in computational transonic aerodynamics applications. The finite volume method simplifies the application of boundary conditions without introducing the constriction associated with small disturbance theory. Governing equations are solved in a Cartesian coordinate system using a body-oriented and shock-oriented mesh network. Only the volume and surface normal directions of the volume elements must be known. The other method configuration design by numerical optimization, can be used by aircraft designers to develop configurations that satisfy specific geometric performance constraints. Two examples of airfoil design by numerical optimization are presented.

N79-18961# Dornier-Werke G m b H Friedrichshafen (West Germany) Theoretical Aerodynamics Group
PROGRESS IN TRANSONIC FLOW COMPUTATIONS
ANALYSIS AND DESIGN METHODS FOR THREE-

Wolfgang Schmidt In Von Karman Inst for Fluid Dyn Computational Fluid Dyn Vol 2 1976 56 p refs

Avail NTIS HC A19/MF A01

DIMENSIONAL FLOWS

The difference schemes used for the evaluation of supercritical transonic wings and wing-body combinations at Dornier are described and compared with those used in relaxation methods elsewhere Special attention is given to different assumptions made because of the small perturbation form of the equations A flow chart of the analysis and design system is presented which shows how the use of different blocks minimizes the input information needed The possible procedure to be used in designing a new configuration is illustrated including the proof of the off-design behavior and the check on possible constraints.

N79-18956# Boeing Vertol Co Philadelphia, Pa INTERACTIONAL AERODYNAMICS OF THE SINGLE ROTOR HELICOPTER CONFIGURATION VOLUME 8 FREQUENCY ANALYSES OF WAKE SINGLE FILM DATA, BASIC CONFIGURATION WAKE EXPLORATION Final Report, 15 Mar 1977 - 13 Feb 1978

Philip F Sheridan Sep 1978 482 p refs (Contract DAAJ02-77-C-0020)

(AD-A062013, USARTL-TR-78-23H-Vol-8) Avail NTIS HC A21/MF A01 CSCL 01/3

This is the second of the three volumes of Volume VIII containing frequency spectrographs of the model helicopter hub/rotor wake velocities derived from the single-film velocity transducer data. This sub-volume deals with the wake characteristics of the baseline configurations.

Author (GRA)

N79-18957# Purdue Univ , Lafayette Ind School of Aeronautics and Aeronautics

INVESTIGATION OF TORSION FREE WING TREND FLUTTER MODELS Final Report, 1 Feb 1977 - 31 Aug 1978

Henry T Y Yang and C H Wan 15 Sep 1978 60 p refs (Grant AF-AFOSR-3265-77 AF Proj 2307) (AD-A061942, AFOSR-78-1514TR) Avail NTIS HC A04/MF A01 CSCL 20/4

Four types of aluminum plate flutter models of a torsion free wing (TFW) were studied (1) cantilever wing (2) pitch restrained wing, (3) TFW with forward trim surface, and (4) TFW with aft trim surface. Models (3) and (4) included the effect of fuselage. Free vibration analyses were performed by using the finite element program NASTRAN Generalized aerodynamic forces were computed by using the program LAT2D based on the subsonic lifting surface theory of Kussner Flutter speeds and frequencies were predicted by using the program FLTTR based on the V-g method. The predicted flutter speeds were compared with available computed and tested results predicted flutter speeds for the four models were compared with each other and conclusions were made. To determine the designs that yielded higher flutter speeds, parametric studies were conducted by varying each of the six parameters thickness parameter of the wing, thickness parameter of either trim surface. location of the wing pivot length of the boom, swept angle of

the wing, and swept angle of either trim surface. The effect of these parameters on the flutter speeds of models (3) and (4) were plotted as trend curves and discussions and conclusions were made.

Author (GRA)

N79-18958# Boeing Vertol Co Philadelphia, Pa
INTERACTIONAL AERODYNAMICS OF THE SINGLE ROTOR
HELICOPTER CONFIGURATION. VOLUME 6-A ONETHIRD OCTAVE BAND SPECTROGRAMS OF WAKE SINGLE
FILM DATA, BUILDUP TO BASELINE Final Report, 15 Mar
1977 - 13 Feb 1978

Philip F Sheridan Sep 1978 303 p (Contract DAAJ02-77-C-0020 DA Proj 1L2-62209-AH-76) (AD-A061994, USARTL-TR-78-23F-Vol-6-A) Avail NTIS HC A14/MF A01 CSCL 01/3

This is the first of the three volumes of Volume VI containing one-third octave band spectrographs of the model helicopter hub/rotor wake velocities derived from the single-film velocity transducer data. This sub-volume deals with the wake changes as the model is built up to the baseline configuration.

Author (GRA)

N79-18959# Boeing Vertol Co., Philadelphia, Pa INTERACTIONAL AERODYNAMICS OF THE SINGLE ROTOR HELICOPTER CONFIGURATION VOLUME 8-C FREQUEN-CY ANALYSES OF WAKE SINGLE FILM DATA, HUBCAPS AND AIR EJECTORS Final Report, 15 Mar 1977 - 13 Feb 1978

Philip F Sheridan Sep 1978 286 p (Contract DAAJ02-77-C-0020, DA Proj 1L2-62209-AH-76) (AD-A061995, USARTL-TR-78-23H-Vol-8-C) Avail NTIS HC A13/MF A01 CSCL 01/3

This is the third of the three volumes of Volume VIII containing frequency spectrographs of the model helicopter hub/rotor wake velocities derived from the single-film velocity transducer data. This sub-volume deals with the effects of hub caps and air ejector systems on wake velocities.

Author (GRA)

N79-18960*# National Aeronautics and Space Administration Ames Research Center, Moffett Field Calif

EVALUATION OF A WAKE VORTEX UPSET MODEL BASED ON SIMULTANEOUS MEASUREMENTS OF WAKE VELOCITIES AND PROBE-AIRCRAFT ACCELERATIONS

Barbara J Short and Robert A Jacobsen Mar 1979 42 p refs

(NASA-TM-78561 A-7735) Avail NTIS HC A03/MF A01 CSCL 01C

Simultaneous measurements were made of the upset responses experienced and the wake velocities encountered by an instrumented Learjet probe aircraft behind a Boeing 747 vortex-generating aircraft. The vortex-induced angular accelerations experienced could be predicted within 30% by a mathematical upset response model when the characteristics of the wake were well represented by the vortex model. The vortex model used in the present study adequately represented the wake flow field when the vortices dissipated symmetrically and only one vortex pair existed in the wake.

N79-18961# National Transportation Safety Board Washington D C Bureau of Accident Investigation

AIRCRAFT ACCIDENT REPORT ALLEGHENY AIRLINES, INC. BAC 1-11, N1550, ROCHESTER, NEW YORK, JULY 9, 1978

8 Feb 1979 52 p refs

(NTSB-AAR-79-2) Avail NTIS HC A04/MF A01

After completing a precision approach and landing in visual flight conditions, the aircraft overran the end of the runway crossed a drainage ditch and came to rest 728 ft past the end of the runway threshold. Although the aircraft was damaged substantially when it hit the drainage ditch there was no fire. There were 73 passengers and a crew of 4 on board, one passenger was injured seriously. The probable cause of the accident was the captain's complete lack of awareness of airspeed vertical speed and aircraft performance throughout an ILS approach and landing in visual meteorological conditions which resulted in his landing the aircraft at an excessively high speed and with insufficient runway remaining for stopping the aircraft.

but with sufficient aircraft performance capability to reject the landing well after touchdown. Contributing to the accident was the first officers failure to provide required callouts which might have altered the captain to the airspeed and sink rate deviations. The Safety Board was unable to determine the reason for the captain's lack of awarness or the first officers failure to provide required callouts.

ARH

N79-18962# Air Force Inst of Tech Wright-Patterson AFB Ohio

ANALYSIS OF THE FUNCTIONAL REQUIREMENTS FOR AN INTELLIGENT AIRBORNE COMPUTER SYSTEM M S Thesis

Ronald Itsuo Morishige 1978 49 p refs (AD-A061649 AFIT-CI-79-8) Avail NTIS HC A03/MF A01 CSCL 01/2

The use of artificial intelligence methods in an airborne computer system can enhance flight safety by reducing the possibility of pilot error caused by inadequate or misleading information. The intelligent computer system would have the ability to screen information for relevancy to the current situation. The selection of information requires knowledge of the context which may depend upon the phase of flight, the condition of the aircraft or external factors. The phase-based context might be represented by scripts. The condition-based and the external context can be represented by a cause-effect net. Knowledge of context will not only enable priority resolution of information but also definitions of goals for generating plans to cope with abnormal situations.

Author (GRA)

N79-18968 Old Dominion Univ, Norfolk, Va DESIGN, CALIBRATION, AND APPLICATION OF A SENSOR FOR MEASURING TIME DEPENDENT ANGLE OF ATTACK OF HELICOPTER BLADES Ph D Thesis

Weiyuan Henry Liu 1978 206 p

Avail Univ Microfilms Order No 7904820

Various pressure probes were designed and tested which could be attached to helicopter blades when a helicopter is in flight. The pressure probes consisted of spherical heads which were held in place by cylindrical shanks. Built inside the heads were transducers to measure the pressure differential between pressure ports which were located on the front portion of the spherical head facing the airstream. Data was obtained over a range of airstream velocity of 11.6 to 88.4 m/s(38 to 290 ft/sec), corresponding to Reynolds numbers of 24.000 184.000 based on the sphere diameter. Both static and dynamic tests were performed. For the dynamic testing cases the probe oscillating frequency was varied from 1.59 to 5.20 Hz, covering the range of frequencies typical of helicopter blade motion.

Dissert Abstr

N79-18969# Dynamics Research Corp., Wilmington Mass Systems Div

AN ANALYSIS OF FUEL CONSERVING OPERATIONAL PROCEDURES AND DESIGN MODIFICATIONS FOR BOMBER/TRANSPORT AIRCRAFT VOLUME 1. EXECUTIVE SUMMARY Finel Report, 7 Jun 1976 - 7 Jul 1978 R Aggarwal Jul 1978 24 p refs

(Contract F33615-76-C-3104)

(AD-A061746 R-247U-Vol-1 AFFDL-TR-78-96-Vol-1) Avail NTIS HC A02/MF A01 CSCL 01/3

Various proposed improvements in the design and operational procedures for bomber/transport aircraft are evaluated. The evaluation is performed in terms of the estimated savings in fuel consumption and in Direct Operating Cost (DOC). As an aid in the evaluation of design modifications graphs of fuel and DOC savings as a function of the design parameters are developed. These graphs are based on actual mission trajectory data rather than some type trajectory profile. The actual mission data is presented in terms of histograms which provide statistical information concerning altitude air speed take-off weight landing weights, and mission time. Separate analyses are performed on the following aircraft the B-52G the B-52H the KC-135, the C-141, the C-130 and the C-5A.

N79-18970# Naval Test Pilot School Patuxent River, Md PRINCIPLES OF HELICOPTER PERFORMANCE Robert B Richards 8 Mar 1968 142 p refs (AD-A061671. USNTPS-T-1) Avail NTIS HC A07/MF A0

(AD-A061671, USNTPS-T-1) Avail NTIS HC A07/MF A01 CSCL 01/13

This textbook is used as the primary reference for the Helicopter Performance Course at the U.S. Naval Test Pilot School. The Helicopter Performance Course is an integral part of the School curriculum the particular requirements of which influence the manner and degree of development of these notes. The course is intended to provide a background for the helicopter performance flight projects conducted by the students. The helicopter with emphasis on the main rotor is analyzed in various flight conditions to determine the major factors which influence the performance. Simplified analysis is first applied to hover and then extended to include translational conditions after which consideration is given to the effect of some of the more significant simplifications.

N79-18971# Calspan Corp Buffalo N Y TOTAL ENVIRONMENT SURVIVABILITY METHODOLOGY Final Report, Oct 1977 - Mar 1978

Charles J Krebs Hans G Reif, and William E Ring Wright-Patterson AFB, Ohio AFFDL Jul 1978 105 p refs (Contract F33615-77-C-2102 AF Proj 2402) (AD-A061888 CALSPAN-6200-X-2 AFFDL-TR-78-90) Avail NTIS HC A06/MF A01 CSCL 12/2

This report documents the results of an analytical study to develop an architecture for a Total Environment Survivability (TES) methodology to provide a capability to evaluate the relative importance of (1) threats on technologies and (2) technologies on air flight vehicle non-nuclear survivability in the total environment. This methodology couples mission effectiveness and life cycle cost analysis techniques to yield a final measure of merit (MOM) or payoff for each technology evaluated. Three candidate methodologies are described which were studied and compared to arrive at the final selected approach. The selected methodology is described in detail along with a qualitative assessment of the methodology using a candidate technology and threat problem. The report also documents the development plan for the implementation of the methodology. Author (GRA)

N79-18972# Naval Air Development Center, Warminster, Pa Aircraft and Crew Systems Technology Directorate

STATISTICAL REVIEW OF COUNTING ACCELEROMETER DATA FOR NAVY AND MARINE FLEET AIRCRAFT Semiannual Summary Report, 1 Jan 1962 - 30 Jun 1978 Alan M Kaniss 1 Nov 1978 159 p

(AD-A061894 NADC-13920-2) HC A08/MF A01 CSCL 01/3 Avail NTIS

This report is a specialized summary of normal acceleration data recorded by counting accelerometers. Data are separated by calendar time and mission category. Only data reported in the counting accelerometer program are included. Author (GRA)

N79-18973*# University of Southern Illinois, Carbondale Dept of Electrical Sciences and Systems Engineering GASP-PL/I SIMULATION OF INTEGRATED AVIONIC

GASP-PL/I SIMULATION OF INTEGRATED AVIONIC SYSTEM PROCESSOR ARCHITECTURES MS Thesis Glen A Brent Sep 1978 274 p refs

(Grant NsG-2238)

(NASA-CR-158244) Avail NTIS HC A12/MF A01 CSCL 01D

A development study sponsored by NASA was completed in July 1977 which proposed a complete integration of all aircraft instrumentation into a single modular system. Instead of using the current single-function aircraft instruments computers compiled and displayed inflight information for the pilot. A processor architecture called the Team Architecture was proposed. This is a hardware/software approach to high-reliability computer systems. A follow-up study of the proposed Team Architecture is reported. GASP-PL/1 simulation models are used to evaluate the operating characteristics of the Team Architecture. The problem model development simulation programs and results at length are presented. Also included are program input formats outputs and listings.

N79-18974# Naval Research Lab , Washington D C SOFTWARE REQUIREMENTS FOR THE A-7E AIRCRAFT Kathryn L Heninger John W Kallander David L Parnas and John E Shore 27 Nov 1978 523 p refs (AD-A061751 NRL-MR-3876) Avail NTIS HC A22/MF A01 CSCL 01/3

The Naval Research Laboratory and the Naval Weapons Center are engaged in a joint project to redesign and rebuild the A-7E Operational Flight Program (OFP) using several advanced software engineering principles. This report is the first product of the project It describes the required behavior of the OFP without describing an implementation. It also describes relevant characteristics of the A-7 computer, sensors, and display devices Primarily intended as a reference document for the rest of the project this report also serves as a complete example of good requirements definition. Its organization allows rapid answering of specific questions. A large amount of information is presented concisely and precisely in formats that facilitate checking for completeness and consistency. The documentation techniques illustrated by this report should be useful for other software development projects Author (GRA)

N79-18975 Tennessee Univ Knoxville

INVESTIGATION OF THE AERODYNAMIC AND ACOUSTIC PERFORMANCE OF A LOW-PRESSURE RATIO TANDEM-

BLADE COMPRESSOR Ph D Thesis
Jenn-Gang John Cherng 1978 224 p
Avail Univ Microfilms Order No 7903408

The experimental results show that the tandem blade configuration is capable of reducing the rotor-stator interaction noise by reducing the radial wake distortion behind the rotor blades, especially at highly loaded conditions i e higher rotor speeds. Span wise circulation distribution can have a significant influence on noise generation for the single rotor and for the rotor-stator combinations. The design parameters of an axial flow compressor such as the blade twist angle rotor solidity rotor degree of reaction and hydraulic efficiency etc., were investigated A series of computations on the effects of geometric changes on the flow characteristics of tandem-blade compressor rotors Dissert Abstr are presented

N79-18976*# Shaker Research Corp Ballston Lake N Y TURBOJET BLADE VIBRATION DATA ACQUISITION DESIGN AND FEASIBILITY TESTING Final Report

J L Frarey, N J Petersen (Amherst Systems) and D A Hess Nov 1978 72 p

(Contract NAS3-21015)

SRC-78-TR-36) (NASA-CR-159505 Avail HC A04/MF A01 CSCL 21E

A turbojet blade vibration data acquisition system was designed to allow the measurement of blade vibration. The data acquisition system utilizing 96 microprocessors to gather data from optical probes, store sort and transmit to the central computer is described. Areas of high technical risk were identified and a two-microprocessor system was breadboarded and tested to investigate these areas. Results show that the system was feasible and that low technical risk would be involved in proceeding with the complete system fabrication

N79-18977*# Naval Air Propulsion Test Center Trenton NJ ROTOR FRAGMENT PROTECTION PROGRAM STATIS-TICS ON AIRCRAFT GAS TURBINE ENGINE ROTOR FAILURES THAT OCCURRED IN US COMMERCIAL AVIATION DURING 1976 Final Report, 1975 - 1976

R A DeLucia and J T Salvino Jul 1978 30 p

(NASA Order C-41581-B)

NAPC-PE-9) (NASA-CR-159474 Avail NTIS

HC A03/MF A01 CSCL 21E

Statistical information relating to the number of gas turbine engine rotor failures which occurred during 1976 in commercial aviation service use is presented. The predominant failure involved blade fragments 88 percent of which were contained Although fewer rotor rim disk, and seal failures occurred all were uncontained Sixty-seven percent of the 186 rotor failures occurred during the takeoff and climb stages of flight

N79-18979# Von Karman Inst for Fluid Dynamics Rhode-Saint-Genese (Relaum)

TURBINE BLADE COOLING

1976 539 p refs Partly in ENGLISH and FRENCH Lecture held at Rhode Saint Genese Belgium, 12-16 Jan 1976 (VKI-Lecture-Series-83) Avail NTIS HC A23/MF A01

An introductory lecture presented the contemporary trends in gas turbine development and their impact on turbine design A survey of the techniques and information available on heat transfer coefficients and cooling efficiency was made, with emphasis on impingement and film types of cooling. The test corrosion phenomena was reviewed. The possibility of cooling by fluids other than air was discussed. The methods for calculation of stresses deformation, fatigue and life expectancy of cooled blades was described. The interaction between cooling requirements and aerodynamic design was considered

N79-18980# Societe Nationale d Etude et de Construction de Moteurs d Aviation, Melun (France)

TURBINE BLADE COOLING

Jerome Francois In Von Karman Inst for Fluid Dyn Turbine Blade Cooling 1976 22 p refs

Avail NTIS HC A23/MF A01

Increasing the compression ratio and maximum temperature of thermodynamic cycles influences the design of gas turbines The various cooling techniques used not only multiply the number of parameters to be considered in blade design, but also complicate the technology and interfere with aerodynamics. Problems involved in the design of a blade capable of withstanding high temperatures relate not only to thermodynamics, but also to aerodynamics heat, resistance, technology and fabrication methods. The finally constructed blade will represent a compromise of the respective requirements of each of these disciplines

Transl by ARH

N79-18984# Creare Inc Hanover, N H Fluids/Thermal Engineering Div

ALTERNATIVE TURBINE COOLING TECHNOLOGY

Turbine David Japikse In Von Karman Inst for Fluid Dyn Blade Cooling 1976 39 p refs

Avail NTIS HC A23/MF A01

Alternatives to conventional gas turbine airfoil cooling (compressor discharge air) have existed for more than three decades. Air cooling gained early popularity due to convenience now restructured energy values offer incentive to consider alternatives A variety of demonstrated airfoil cooling alternatives are reviewed and a careful assessment of the current technology base for designing alternative cooling methods is presented here A speculative view of future alternative applications is offered

N79-18986# Rolls-Royce Ltd , Derby (England) Derby Engine

THE AERODYNAMIC PENALTIES ASSOCIATED WITH TURBINE BLADE COOLING

B Barry In Von Karman Inst for Fluid Dyn Turbine Blade Cooling 1976 36 p refs

Avail NTIS HC A23/MF A01

A state of the art review of the cooled aero engine turbine design field is provided in particular the interactions between the aerodynamic and cooling requirements/constraints of the turbine. The processes which a designer goes through to establish the preliminary characteristics of the turbine are considered. The aerodynamic and cooling interactions and losses are also considered

N79-18990# Von Karman Inst. for Fluid Dynamics, Rhode-Saint-Genese (Belgium) Dept of Turbomachinery

TIME MARCHING FINITE AREA METHOD

Michel Couston In its Transonic Flows in Axial Turbomachinery, Vol 1 1976 42 p refs

Avail NTIS HC A13/MF A01

Aerodynamically efficient blades linked to the knowledge of shock strength and position because a slight blade profile variation ca induce strong shock waves and boundary layer separation are discussed A numerical method to solve the steady transonic blade to blade flow in axial turbomachinery is developed A two dimensional problem using the isentropic assumption was examined The damping surface, rotor tip and stator hub sections, blade velocity distribution. Mach number and wall profiles were investigated.

N79-18997# Von Karman Inst for Fluid Dynamics Rhode-Saint-Genese (Belgium)

OUTLET AIR ANGLE PREDICTION FOR SUBSONIC FLOW CASCADES

R VanDenBraembussche *In its* Transonic Flows in Axial Turbomachinery, Vol 2 1976 34 p refs

Avail NTIS HC A18/MF A01

In order to define the unique outlet air angle corresponding to real flow, three groups of criteria were developed (1) relates the outlet air angle to overall geometrical data (2) relates the outlet air angle to local flow condition at the trailing edge and contains the Kutta condition, and (3) directly relates the outlet air angle to the viscous inviscid interation of the flow SES

N79-19000# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Porz (West Germany)

COMPARISON BETWEEN FLOWS IN CASCADES AND ROTORS IN THE TRANSONIC RANGE 1 BASIC CONSIDERATIONS

H Starken In Von Karman Inst for Fluid Dyn Transonic Flows in Axial Turbomachinery Vol 2 1976 18 p refs

Avail NTIS HC A18/MF A01

Five different parameters which influence a comparison between stationary cascade tests results and axial flow turbomachine measurements are discussed. The parameters are (1) cascade projection. (2) axial velocity. (3) position of reference planes, (4) data reduction method and (5) viscosity effects.

SES

N79-19001# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt. Porz (West Germany)

COMPARISON BETWEEN FLOWS IN CASCADES AND ROTORS IN THE TRANSONIC RANGE 2 INVESTIGATION OF TWO TRANSONIC COMPRESSOR CASCADES AND COMPARISON WITH ROTOR DATA

H A Schreiber In Von Karman Inst for Fluid Dyn Transonic Flows in Axial Turbomachinery Vol 2 1976 32 p refs

Avail NTIS HC A18/MF A01

The influence of the axial velocity density ratio on the transonic cascade flow by varying the sidewall contraction was studied. The flow behavior the static pressure transonic and supersonic range on the shock wave configuration, the shock losses and the throat area inside of the blade are described.

SES

N79-19002# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Porz (West Germany)

COMPARISON BETWEEN FLOWS IN CASCADES AND ROTORS IN THE TRANSONIC RANGE 3: COMPARISON OF EXPERIMENTAL AND THEORETICAL RESULTS OF FLOW STUDIES ON BLADE-TO-BLADE SURFACES IN AN AXIAL COMPRESSOR ROTOR

R Dunker, P Strinning and H G Hungenberg In Von Karman Inst for Fluid Dyn Transonic Flows in Axial Turbomachinery Vol 2 1976 19 p refs

Avail NTIS HC A18/MF A01

A nonintrusive flow-velocity measuring method on an optical basis is described. This technique is developed for applications in turbomachines, where extremely difficult test conditions are normally present. Results of experimental investigations and of

quasi-three-dimensional calculations in axial compressor rotors are compared. The results demonstrate the capability of this technique for future research work on turbomachines and especially for the development of the aerodynamic calculation methods.

N79-19004# Naval Research Lab Washington D C Ocean Technology Div

FAILURE STUDIES OF A THIRD STAGE FAN DISK FROM A TF-30 TURBINE ENGINE Final Report

W H Vaughan, R J Sanford J M Krafft, W H Cullen and J W Dally (Maryland Univ., College Park) 13 Nov 1978 29 p refs

(AD-A061801, NRL-MR-3874) Avail NTIS HC A03/MF A01 CSCL 21/5

A detailed failure analysis was made of a fan disk from the third stage of the Navy's turbo-jet engine in order to gain a better understanding of the origin and growth kinetics of the cracks that had developed in service. The in service stress that had caused the cracks to originate was determined by a two dimensional photoelastic and holographic stress analysis. A further experimental stress analysis was made to determine the stress intensity factor, after the crack had formed as a function of crack length. These results were compared with a fractographic study of the bearing surface and the fracture surface. It was found that the striation spacings were in good agreement with the calculated values of the stress intensity factor. Some conclusions were drawn concerning the origin and growth mechanism of these cracks.

N79-19005# ARO, Inc., Arnold Air Force Station, Tenn COMPARISONS OF TURBINE ENGINE COMBUSTOR EXHAUST EMISSIONS MEASUREMENTS USING THREE GAS-SAMPLING PROBE DESIGNS Final Report, 1 Dec 1976 - 30 Aug 1977

R J Bryson and J D Few Nov 1978 67 p refs (AD-A061733, AEDC-TR-78-7) Avail NTIS HC A04/MF A01 CSCL 21/5

The effects of sampling probe design and probe operating procedures on measurements of concentrations of nitric oxide (NO), oxides of nitrogen (NOx), carbon monoxide (CO), carbon dioxide (CO2), total hydrocarbons (CxHy), and gaseous hydrogen (H2) in the exhaust of a turbine engine combustor were studied Measurements of the concentrations were made using commercial gas analysis instruments and three types of gas-sampling probes The probe types were a tubular inlet probe a quick-quench probe, and a dilution probe. Diluent gas (N2, A, He) and diluent flowrate effects on measurements were studied for the dilution probe Effects of sampling surface material and sample residence time in the probe were investigated for the tubular inlet probe, and the effects of pressure ratio across the quick-quench probe were determined At fuel-to-air ratios greater than 0.01, the levels of NO, NOx and CO2 were somewhat smaller for the quick-quench and dilution probes than for the tubular inlet probe The measured concentrations of carbon monoxide and unburned hydrocarbons, however, were greater for the quickquench and dilution probes than for the tubular inlet probe

Author (GRA)

N79-19006 Ohio State Univ , Columbus

AEROSERVOELASTIC STABILITY ANALYSIS OF AN AIRPLANE WITH A CONTROL AUGMENTATION SYSTEM Ph.D. Thesis

Robert Lee Moore 1978 200 p

Avail Univ Microfilms Order No 7902191

The aeroservoelastic stability equations of motion, including the airframe dynamics the unsteady aerodynamics, and the control augmentation system were developed by using a modal representation in the Laplace domain. For this formulation, the unsteady aerodynamics were transformed from the commonly used frequency domain into the Laplace domain. Fitted Laplace polynomial fractions for the Laplace transformed generalized aerodynamic forces were derived. These fitted Laplace polynomial fractions were formulated for a given flight condition (i.e., a particular Mach number and altitude) were applicable for all frequencies within the desired frequency fit range, and were

most valid for Laplace arguments near the imaginary axis (small positive or negative damping) along which the fit was made and which was the region of the greatest physical interest for stability

Dissert Abstr

N79-19007# General Electric Co , Binghamton, N Y Aerospace Controls and Electrical Systems Dept

DIRECT DRIVE CONTROL VALVE FOR FLY-BY-WIRE FLIGHT CONTROL SYSTEM ACTUATORS Final Report, Apr 1976 - Dec 1977

D Hogan and J E Rinde Mar 1978 144 p refs (Contract F33615-76-C-3037)

(AD-A062030 ACS-11595 AFFDL-TR-78-32) Avail NTIS HC A07/MF A01 CSCL 01/3

The development of a high force linear motor suitable for directly actuating an aircraft hydraulic power control valve used on a flight control system actuator is described A breadboard unit was fabricated and tested and met the 80 lb midpoint force requirement with an input of 4.4 amperes (1.1 amps/coil). A modified F-4 aileron actuator incorporating the force motor and position LVDTs met the frequency response requirements. Three sets of brassboard equipment each consisting of a modified F-4 aileron actuator incorporating a new force motor and position LVDTs and an electronic control box were designed fabricated and tested. One set was subjected to and satisfactorily completed flightworthiness tests. The remaining are available for flight testing.

N79-19008# Northrop Corp Hawthorne Calif Aircraft Div VALIDATION OF MIL-F-9490D GENERAL SPECIFICATION FOR FLIGHT CONTROL SYSTEM FOR PILOTED MILITARY AIRCRAFT VOLUME 1 SUMMARY OF YF-17 AND C-5A VALIDATIONS Final Report, Apr 1976 - Jan 1977

S Dobos-Bubno Larry B Hartsook, Ralph J Hylton and Harold A Valery Apr 1977 56 p refs (Contract F33615-76-C-3034)

(AD-A061807 NOR-77-06-Vol-1 AFFDL-TR-77-7-Vol-1) Avail

NTIS HC A04/MF A01 CSCL 01/3

This volume presents a summary of two studies performed to validate the new MIL-F-9490D Specification. This work was accomplished by the Northrop Corporation Aircraft Division using the YF-17 Lightweight Fighter, and the Lockheed-Georgia Company using the C-5A Heavy Logistics Transport. This validation was based on existing ground test flight test and analytical data as was available for this validation process. Each applicable paragraph was examined with regard to practicability accuracy, and completeness as a requirement for procurement, design test and installation of flight control systems for future piloted military aircraft. Recommendations have been made with regard to changes considered necessary to improve the practicability accuracy and completeness of the specification and to improve or update the Users Guide.

N79-19009# Northrop Corp Hawthorne Calif Aircraft Div VALIDATION OF MIL-F-9490D GENERAL SPECIFICATION FOR FLIGHT CONTROL SYSTEM FOR PILOTED MILITARY AIRCRAFT VOLUME 2 YF-17 LIGHTWEIGHT FIGHTER VALIDATION Final Report, Apr 1976 - Jan 1977

S Dobos-Bubno and Larry B Hartsook Apr 1977 364 p refs

(Contract F33615-76-C-3034)

(AD-A062008, NOR-77-06-Vol-2 AFFDL-TR-77-7-Vol-2) Avail NTIS HC A16/MF A01 CSCL 01/3

This study was conducted to validate military specification MIL-F-9490D. Flight Control Systems-Design Installation and Test of Piloted Aircraft, General Specification For, dated 6 June 1975 by checking the specification requirements utilizing the experience and knowledge derived during the recent procurement of the YF-17 Lightweight Fighter. This validation was based on existing ground test flight test and analytical data as was available for this validation process. Each applicable paragraph was examined with regard to practicability, accuracy, and completeness as a requirement for procurement, design test and installation of flight control systems for future piloted military aircraft Recommendations were made with regard to changes considered necessary to improve the practicability accuracy, and complete-

ness of the specification and to improve or update the Users Guide Author (GRA)

N79-19010*# Bolt, Beranek and Newman, Inc., Canoga Park, Calif

COMPUTER-AIDED COLLECTION OF DEMOGRAPHIC DATA WITHIN DAY-NIGHT LEVEL CONTOURS TWO TEST CASES Final Report

Harry Seidman and Connice Bravelly Aug 1978 30 p refs (Contract F33615-76-C-0528)

(AD-A061657 BBN-3702 AMRL-TR-78-39) Avail NTIS HC A03/MF A01 CSCL 20/1

This study demonstrates the feasibility of automating a procedure for counting the number of people exposed to various levels of aircraft noise near airbases. The procedure involves developing contours of equal noise exposure about military installations based on aircraft noise and performance data and airport operational/flight track information using the NOISEMAP computer program developing polygon descriptions of the noise contours that are compatible with commercially available demographic programs using census tract data and outputing for land use planning purposes, demographic and socio-economic data for present or future years as a function of predicted noise exposure level.

N79-19112*# Boeing Commercial Airplane Co Seattle, Wash DEVELOPMENT OF FIRE TEST METHODS FOR AIRPLANE INTERIOR MATERIALS Final Report

Everett A Tustin Oct 1978 301 p refs

(Contract NAS9-15168)

(NASA-CR-160119, D6-48071) Avail NTIS

HC A14/MF A01 CSCL 21B

Fire tests were conducted in a 737 airplane fuselage at NASA-JSC to characterize jet fuel fires in open steel pans (simulating post-crash fire sources and a ruptured airplane fuselage) and to characterize fires in some common combustibles (simulating in-flight fire sources) Design post-crash and in-flight fire source selections were based on these data Large panels of airplane interior materials were exposed to closely-controlled large scale heating simulations of the two design fire sources in a Boeing fire test facility utilizing a surplused 707 fuselage section. Small samples of the same airplane materials were tested by several laboratory fire test methods. Large scale and laboratory scale data were examined for correlative factors Published data for dangerous hazard levels in a fire environment were used as the basis for developing a method to select the most desirable material where trade-offs in heat, smoke and gaseous toxicant evolution must be considered Author

N79-19122# Naval Research Lab Washington D C NEW AGENTS FOR THE EXTINGUISHMENT OF MAGNESIUM FIRES Final Report, Aug 1976 - Sep 1977

Kenneth D Lawrence Frederick W Williams and Richard G Gann Apr 1978 31 p refs

(MIPR-FY8952-76-65017)

(AD-A061664 NRL-6180-376-KDL-FWW-NJS

CEEDO-TR-78-19) Avail NTIS- HC A03/MF A01 CS 13/12

Ground glass powders (frits) have been evaluated as possible suppressants for magnesium fires. Conceptually, these would melt and form a glass coating on the surface of the burning metal isolating it from the oxygen supply. Some frits containing oxides of magnesium and lithium reacted violently with the burning magnesium. However several low melting frits proved to be good suppressants and were better than commercial suppressants.

Author (GRA)

N79-19149# Teledyne CAE Toledo Ohio

ADVANCEĎ TURBÍNE ENGINE GAS GENERATOR (ATEGG) FRACTOGRAPHY OF CAST NICKEL BASE SUPERALLOYS Final Report, 1 Oct 1975 - 30 Jun 1978

Nov 1978 28 p

(Contract F33657-76-C-0215)

(AD-A061701 TCAE-1567-Vol-4 AFAPL-TR-77-30-Vol-4) Avail NTIS HC A03/MF A01 CSCL 11/6 This report documents Teledyne CAE's efforts to correlate the fracture surfaces of cast nickel-base superalloys to known conditions of low cycle fatigue testing (strain range partitioning) Rene 80 and In-100 low cycle fatigue test specimens (supplied by NASA-Lewis and TRW materials laboratories) were examined by means of scanning electron microscope (SEM). The fractography obtained with the SEM can be compared to actual engine component failures and will provide strong indications of the metal temperature, creep conditions strain levels, and cycles imposed, during the events leading to component failure

Author (GRA)

N79-19314*# Pratt and Whitney Aircraft, East Hartford Conn Commercial Products Div

STRAIN GAGE SYSTEM EVALUATION PROGRAM Final Report

G W Dolleris, H J Mazur and E Kokoszka, Jr Dec 1978 126 p

(Contract NAS3-20298)

(NASA-CR-159486, PWA-5615-3) Avail NTIS HC A07/MF A01 CSCL 14B

A program was conducted to determine the reliability of various strain gage systems when applied to rotating compressor blades in an aircraft gas turbine engine. A survey of current technology strain gage systems was conducted to provide a basis for selecting candidate systems for evaluation. Testing and evaluation was conducted in an F 100 engine. Sixty strain gage systems of seven different designs were installed on the first and third stages of an F 100 engine an Nineteen strain gage failures occurred during 62 hours of engine operation, for a survival rate of 68 percent. Of the failures, 16 occurred at blade-to-disk leadwire jumps (84 percent), two at a leadwire splice (11 percent) and one at a gage splice (5 percent). Effects of erosion, temperature, G-loading, and stress levels are discussed Results of a post-test analysis of the individual components of each strain gage system are presented.

N79-19351# Nuovo Pignone SpA, Florence (Italy) TRANSONIC COMPRESSORS FOR HEAVY GASES PART 1 SELECTIONS OF THE AERO-DESIGN PARAMETERS

E Benvenuti In Von Karman Inst for Fluid Dyn Ind Compressor, Vol 1 1976 31 p refs

Avail NTIS HC A14/MF A01

The problems of correctly applying test data obtained for cascades and stages operating with air to designing heavy gas compressor stages are outlined. Some differences to be expected in the compressor performance are examined. It is concluded that the aerodynamic design of a multistage transonic axial compressor for very heavy gases has in general more severe constaints than the design of an air compressor of the same pressure ratio and specific flow. Some criteria for the selection of the design aerodynamic parameters are indicated, when high efficiency and good operating range are requested.

N79-19352# Nuovo Pignone SpA Florence (Italy) TRANSONIC COMPRESSORS FOR HEAVY GASES PART 2 AERO-MECHANICAL CONSIDERATIONS, TESTING AND OPERATION

E Benvenuti In Von Karman Inst for Fluid Dyn Ind Compressors Vol 1 1976 34 p refs

Avail NTIS HC A14/MF A01

Some comparisons are made between the design of transonic stages operating with air and that of stages operating with heavy gases taking blades stresses natural frequencies and flutter into consideration. It is shown that, in general, the mechanical constaints on the aerodynamic design are less severe for the heavy gas compressor than for the equivalent air compressor. When testing a compressor design for a certain gas using different gas, care must be taken in selecting the test gas properties and an appropriate data correlation must be used by defining performance parameters, suitable to represent the

compressor performance when operating with different gases Performance maps are shown which were calculated on the basis of typical stage characteristics, using, the stage-stacking technique G Y

N79-19353# United Technologies Research Center East Hartford, Conn

TURBOMACHINERY FLUTTER INTRODUCTORY CON-CEPTS

Franklin O Carta In Von Karman Inst for Fluid Dyn Ind Compressors, Vol 1 1976 26 p refs

Avail NTIS HC A14/MF A01

An attempt is made to acquaint the reader with several turbomachinery flutter problems confronting the design engineer Some of the ways in which the designer can cope with these problems are suggested. The reader is exposed to the basic differences between wing flutter and turbomachinery blade flutter. This is helpful in establishing the areas in which elementary theories can be used to explain basic principles G.Y.

N79-19354# United Technologies Research Center East Hartford, Conn

IDENTIFICATION OF VARIOUS FLUTTER REGIMES AND DISCUSSION OF DYNAMIC STALL

Franklin O Carta In Von Karman Inst for Fluid Dyn Ind Compressors Vol 1 1976 45 p refs

Avail NTIS HC A14/MF A01

An attempt is made to identify several of the specific flutter problems that are of concern to the turbomachinery designer Following a general historical account of the early attempts to cope with various flutter problems relevant to turbomachines a detailed survey of single degree of freedom torsional stall flutter is given. Although the phenomenon is experienced by all rotating blade systems only isolated airfoil studies relevant to helicopters and propelliers are extensive enough to produce a truly predictive design system. However, this prediction relies heavily on empiricism.

N79-19363# Von Karman Inst for Fluid Dynamics, Rhode-Saint-Genese (Belgium)

AERODYNAMIC AND MECHANICAL FACTORS AFFECTING THE SURGE LINE INLET FLOW DISTORTION INFLUENCES ON AXIAL FLOW COMPRESSORS

J Colpin In its Ind Compressors Vol 2 1976 15 p refs

Avail NTIS HC A11/MF A01

An inlet flow distortion is one of the compressor perturbations to be considered in designing a turbomachine. Two of the most important practical methods the parallel compressor model and the Melick model available for the prediction of the effects of inlet flow distortion on the surge line shift are presented it appears that both models give satisfactory results at the moment but without adding new fundamental elements to the knowledge of the flow phenomena. This would necessarily reduce their range of application. There is a need for a deeper insight in the flow physics in order to link the global approach to a detailed study of the unsteady response of the rotating rows which would improve the prediction methods.

N79-19365# Von Karman Inst for Fluid Dynamics Rhode-Saint-Genese (Belgium)

COMBUSTION PROBLEMS IN GAS TURBINE APPLICA-

1977 505 p refs Proc of lectures held on 10-14 Jan 1977 (VKI-Lecture-Series-93) Avail NTIS HC A22/MF A01

A discussion is given of the combustion problems in gas turbines with emphasis on the combustion process the combustion chamber, and application in the aeronautical and industrial fields

N79-19366# Purdue Univ Lafayette Ind COMBUSTION IN THE GAS TURBINE, PARTS 1, 2, 3

A H Lefebvre In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 28 p

Copyright Avail NTIS HC A22/MF A01

Reference to the conventional P-V diagram for a turbo-jet cycle shows that between the compression and expansion stages there is a stage in which the working fluid (air) expands at constant pressure This expansion is achieved in a practical system through heating of the air by injection and combustion of a liquid fuel. The useful work output of the engine is related to the area within the P-V loop. Thus a large degree of expansion will give a large work output. Since, however, the gas is being expanded by raising its temperature, a practical limit to the degree of expansion attainable is set by the maximum temperature limits of the engine components, especially the turbine.

N79-19368# Purdue Univ , Lafayette, Ind FUEL INJECTION

A H Lefebvre In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 43 p

Copyright Avail NTIS HC A22/MF A01

A survey is presented of various methods of achieving an atomized spray and to the influence of atomizer geometry and chamber operating conditions on spray characteristics. The influence of spray characteristics on various important aspects of combustion performance is discussed. Attention is centered mainly on pressure atomizers, but consideration is also given to other methods of atomization, such as air-blast atomization and centrifugal atomization. A brief discussion is given on the relative merits of the various types of fuel injector, with particular emphasis on aircraft systems in which the fuel injection process plays a much more dominant role than in the case of industrial engines.

N79-19369# Purdue Univ Lafayette, Ind DIFFUSERS FOR GAS TURBINE COMBUSTION SYSTEMS A H Lefebvre In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 12 p refs

Copyright Avail NTIS HC A22/MF A01

It is a characteristic of axial flow compressors that a high axial velocity is needed to achieve a high outlet pressure in a small number of stages. Thus it is necessary to reduce the velocity of the compressor efflux. A five-fold reduction is typical and is achieved by fitting a diffuser between the compressor outlet and the upstream end of the flame tube. The simplest and aerodynamically most efficient diffuser is a diverging circular duct. Such a diffuser will have an optimum divergence angle for minimum pressure loss, and consideration of the flow regimes in a diffuser of increasing angle will show the physical basis for such an optimum.

N79-19372# Purdue Univ Lafayette, Ind IGNITION IN THE GAS TURBINE

A H Lefebvre In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 45 p refs

Copyright Avail NTIS HC A22/MF A01

The trend towards higher flight speeds and engines of higher compression ratio produced a gradual deterioration in the environmental conditions of the ignition unit and igniter plug At the same time there has been an increasing demand for improvements in performance life and reliability of ignition equipment. Thus the problem of ignition, particularly in aircraft engines, is one of continuing importance and is discussed in some detail.

N79-19376# Purdue Univ Lafayette Ind CONTROL OF AIR POLLUTION FROM AIRCRAFT AND AIRCRAFT ENGINES

A H Lefebvre In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 5 p

Copyright Avail NTIS HC A22/MF A01

Tables and graphs are presented of the data relating to air pollution from aircraft and aircraft engines

N79-19380# Rolls-Royce Ltd., Derby (England) THE DESIGN AND DEVELOPMENT OF HIGH PERFORMANCE COMBUSTORS

A B Wassell In Von Karman Inst for Fluid Dyn Combust Probl in Gas Turbine Appl 1977 65 p refs

Copyright Avail NTIS HC A22/MF A01

Design considerations for combustors have grown in importance namely Weight Production Cost and Pollutant Emissions. The inter-relation between these factors are discussed in general terms, but most attention is focused on two factors which are critical in combustor development programmes for high duty systems. Linear Cooling and Combustor Outlet Temperature Distribution. The advent of pollution controls re-emphasised the need for minimising the quantity of air required for linear cooling and the operation at increasing turbine inlet temperature requires improvements in the pattern factor. Thus the accurate quantification of the pattern factor has become important. Past methods failed to define the pattern factor with sufficient accuracy but new statistical appraisals of temperature distribution have been developed to enable them to be quantified with more precision.

N79-19385# Von Karman Inst for Fluid Dynamics Rhode-Saint-Genese (Belgium)

INDUSTRIAL CENTRIFUGAL COMPRESSORS, VOLUME 1 1977 215 p refs Proc of lectures held on 21-25 Feb 1977 2 Vol

(VKI-Lecture-Series-95) Avail NTIS HC A10/MF A01

Flow modeling and design techniques for centrifugal compressors are discussed as well as the perspectives opened up by the application of boundary layer calculations

N79-19386# Von Karman Inst for Fluid Dynamics Rhode-Saint-Genese (Belgium)

FLOW MODELLING AND AERODYNAMIC DESIGN TECHNIQUES FOR CENTRIFUGAL COMPRESSORS

R vandenBraembussche *In its* Ind Centrifugal Compressors Vol 1 1977 77 p refs

Copyright Avail NTIS HC A10/MF A01

The differences between industrial and advanted application centrifugal compressors are summarized. In comparison to axial flow compressors, the main difficulties for centrifugal compressors are the complexity of the flow and the complexity of the boundaries. The latter may be simplified by using one-dimensional approximations including incidence losses friction and eventual separation. Flow equations may be simplified by using quasior fully-three dimensional calculations of inviscid flow. Singularity conformal transformation streamline curvature finite difference, and finite element methods are used to follow a flow from inlet to diffuser outlet. The local behavior of the flow is discussed and relevant applicable design methods are examined. A R H

N79-19387# Ecole Centrale de Lyon (France) VISCOUS FLOWS IN CENTRIFUGAL COMPRESSORS K D Paparliou /n Von Karman Inst for Fluid Dyn Ind Centrifuga

K D Papailiou In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors, Vol 1 1977 58 p refs

Copyright Avail NTIS HC A10/MF A01

Although the calculation of the flow in a radial compressor is actually realized on the basis of a quasi-three dimensional model which results from the superposition of two two-dimensional models the flow in a radial compressor does not behave in this simple way. Factors that must be considered include the influence of the hub and tip wall shear layers boundary layer separation and its behavior, and the effect of blade curvature and Coriolis effect on turbulence. The flow in the meridional plane is considered. Secondary flow behavior is calculated by averaging circonferentially the turbulent Navier-Stokes equations. The flow in the blade-to-blade plane is considered. Accurate calculations of separation and acceptable calculations of the

separated boundary layer are obtained. The curvature and Coriolis effect are determined using an integral method of boundary layer calculation

N79-19388# Societe Creusot-Loire Paris (France) Div Energie

APPLICATION OF AERODYNAMIC DESIGN TECHNIQUES TO PROCESS COMPRESSOR DESIGN

J M Duchemin J Jehl, and M Roustan In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors Vol 1 1977 66 p refs

Copyright Avail NTIS HC A10/MF A01

The computing system developed at Creusot-Loire to accurately predict performances upgrade existing machinery and establish new designs is described. Some theoretical results and a comparison between performance testing and calculation are

N79-19389# Von Karman Inst for Fluid Dynamics, Rhode-Saint-Genese (Belgium)

INDUSTRIAL CENTRIFUGAL COMPRESSORS, VOLUME 2 1977 335 p refs Proc of lectures held on 21-25 Feb 1977 2 Vol

(VKI-Lecture-Series-95) Avail NTIS HC A15/MF A01

Factors to be considered for optimal design and performance of turbocompressors are discussed with emphasis on thermodynamic properties and component configurations

N79-19390# Gutehoffnungshuette Sterkrade A G Oberhausen (West Germany)

DESIGN OF MULTISTAGE COMPRESSORS WITH CONSID-ERATION OF THE REAL BEHAVIOR OF GAS AND GAS MIXTURES

L Turanskyj In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors, Vol 2 1977 102 p refs in BELORUSSIAN

Copyright Avail NTIS HC A15/MF A01

The thermodynamic equations of state provide the basis for correlations used to describe the p-v-T behavior of real gases and their mixtures. With the help of these equations, the enthalpy and entropy are determined and used in a design procedure to calculate multistage compressors. The design procedure is fundamentally explained Problems involved in real gas behavior are considered in the prediction of the off-design behavior of multistage turbocompressors. Typical machines in practical service are described to indicate the variety of uses of modern turbocompressors Author

N79-19391# Ruhr Univ Bochum (West Germany)

A STRESS AND STRAIN ANALYSIS OF INDUSTRIAL RADIAL COMPRESSOR IMPELLERS USING THE FRAME-WORK METHOD

W Fister and H Heiderich In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors, Vol 2 1977 58 p

Copyright Avail NTIS HC A15/MF A01

The simplified strength analysis of impellers is based on classical computational methods of shell theory leading to the analytical solution of differential equations. However, the state of stress of the whole impeller particularly the regions of maximum stress are decisively influenced by the inherent strength of the blades. The blading arrangement and geometry must be considered. according to the actual design. A computational procedure is described that makes possible an approximated strength determination of radial compressor impellers of an industrial geometry with and without a cover disk and subjected to centrifugal forces ARH

N79-19392# Nuovo Pignone SpA Florence (Italy) DEVELOPMENT TESTING OF STAGES FOR CENTRIFUGAL PROCESS COMPRESSORS

E Benvenuti In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors, Vol 2 1977 130 p refs

Copyright Avail NTIS HC A15/MF A01

The features and capabilities of test rigs designed and set up for systematically testing industrial centrifugal compressor stages are discussed and an outline of testing requirements and limitations associated with the use of results both for manufacturing design and for component development is given Some types of instrumentation and particular equipment used in testing are described and the complexity of flow fields existing in some relevant areas along the gas flowpath is shown, for evaluating measurement reliability and outlining some related component development problems. Test data reduction methods and correlation requirements are presented and the convenience of setting up standard stage series of known or reliably predictable performance is assessed An example of agreement between predicted and experimental performance is shown for a multi-stage compressor consisting entirely of standard stages directly derived from tested configurations

N79-19393# Creare, Inc. Hanover N.H. TURBOCHÄRGER DESIGN AND DEVELOPMENT

D Japikse and J Goebel In Von Karman Inst for Fluid Dyn Ind Centrifugal Compressors Vol 2 1977 41 p refs

Copyright Avail NTIS HC A15/MF A01

Turbocharging diesel engines as a retrofit method of increasing maximum engine output usually result in better fuel economy Turbocharger/engine system performance is examined and different matching issues are discussed. A sample turbocharger aerodynamic design is pursued through each design phase Highlights of the aerodynamic technology base are presented Topics covered in design optimization include impeller performance, vaneless and semivaneless space recovery and channel diffuser recovery ARH

N79-19396# Northwestern Univ Evanston III Dept of Mechanical Engineering and Astronautical Sciences

THERMOELASTIC AND DYNAMIC PHENOMENA IN SEALS

Special Report, Jan - Sep 1978
Yih-Tsuen Wu and Ralph A Burton Sep 1978 49 p refs (Contract N00014-75-C-0761)

Rept-5341-427-3) (AD-A061754 NTIS Avail HC A03/MF A01 CSCL 21/5

An analysis of a seal model is made where the rotating element has both fixed tilt and two-lobe waviness. The stator is assumed to be gimbal mounted and to have inertial mass Hydrodynamic lubrication is assumed following the short bearing or narrow seal model. Conditions are examined where the stator precesses in synchronism with the rotor rotation. Particular interest is given to operating conditions where such behavior Author (GRA) appears to degenerate

N79-19412 Kansas Univ Lawrence

EXPERIMENTAL AND FINITE ELEMENT INVESTIGATION OF THE BUCKLING CHARACTERISTICS OF A BEADED SKIN PANEL FOR A HYPERSONIC Ph D Thesis

William Harry Siegel 1978 149 p Avail Univ Microfilms Order No 7904230

The project reported on involved the testing of a hypersonic beaded skin panel to failure. The primary interest was focused upon the buckling characteristics of the panel under pure compression with boundary conditions similar to those found in a wing mounted condition. Three primary phases of analysis are included. These phases include. Experimental testing of the panel to failure, Finite element structural analysis of the beaded panel with the computer program NASTRAN, A summary of the semiclassical buckling equations for the beaded panel under purely compressive loads. A comparison of each of the analysis methods is also included Dissert Abstr

N79-19414*# California Univ at Los Angeles NONLINEAR EQUATIONS OF EQUILIBRIUM FOR ELASTIC HELICOPTER OR WIND TURBINE BLADES UNDERGOING MODERATE DEFORMATION Final Report

Avin Rosen and Peretz P Friedmann Dec 1978 104 p refs (Grant NsG-3082 Contract E(49-26)-1028)

(NASA-CR-159478 UCLA-ENG-7718, DOE/NASA/3082-78/1) Avail NTIS HC A06/MF A01 CSCL

DOE/NASA/3082-78/1) Avail NTIS HC A06/MF A01 CSCI 20K

A set of nonlinear equations of equilibrium for an elastic wind turbine or helicopter blades are presented. These equations are derived for the case of small strains and moderate rotations (slopes). The derivation includes several assumptions which are carefully stated. For the convenience of potential users the equations are developed with respect to two different systems of coordinates, the undeformed and the deformed coordinates of the blade. Furthermore, the loads acting on the blade are given in a general form so as to make them suitable for a variety of applications. The equations obtained in the study are compared with those obtained in previous studies.

N79-19418# Lockheed-California Co Burbank

FRACTURE MECHANICS FOR STRUCTURAL ADHESIVE BONDS, PART 2, PHASE 2 Final Report, 1 Jul 1977 -30 Jun 1978

T R Brussat, S T Chiu and S Mostovoy Aug 1978 107 p

(Contract F33615-75-C-5224)

(AD-A061805, LR-28652-Pt-2 AFML-TR-77-163-Pt-2) Avail NTIS HC A06/MF A01 CSCL 13/5

Research results are presented of crack propagation tests and fracture mechanics analysis of laboratory joints and specimens bonded with FM-73 adhesive and containing bondline cracks New baseline specimens and tests are developed analyzed and used for Mode I and mixed-mode fracture mechanics testing of adhesives Baseline test data are reported for FM-73 including increasing load (fracture toughness) tests in laboratory air and sustained-load hot-water-immersed tests. Results of fatique crack growth tests are presented at two stress ratios, two environments. and three cyclic frequencies for three different baseline specimen geometries and three different mixes of Modes I and II Fracture mechanics prediction methodology is demonstrated using results of nine da/dN tests of structural joint specimens immersed in hot water. Two different finite element analysis procedures are used to calculate strain energy release rate as a function of crack size. Then the baseline data enables crack growth rate estimation. Multiple cracking is considered based on measurements of final crack sizes on the fracture surfaces on the failed specimens. The estimated crack growth rates correlate well with the experimental data Author (GRA)

N79-19606# German Army Hospital, Munich (West Germany) Rescue Center

RESCUE HELICOPTERS IN PRIMARY AND SECONDARY MISSIONS

B Gorgass G Frey, W Stotz G Kugler, and I Karger In AGARD Operational Helicopter Aviation Med Dec 1978 5 p refs Prepared in cooperation with Allgemeiner Deutscher Automobil-Club-e V, Munich West Ger

Avail NTIS HC A99/MF A01

The experience of the Federal Republic of Germany in the use of rescue helicopters in the civilian rescue service on a trial basis in 1967 and 1968 is summarized. The area of operations of rescue helicopter bases is considered in terms of geographical distribution of hospitals and special clinics as well as the population density and airspeed of the helicopter. The composition of the technical and medical crew the range of functions and operation tactics, the range of patients transported and the medical equipment onboard the rescue helicopter are among the topics covered.

N79-19614# Sikorsky Aircraft, Stratford, Conn Dept of Engineering

UH-60A MEDEVAC KIT

Horace T Hone In AGARD Operational Helicopter Aviation Med Dec 1978 9 p

Avail NTIS HC A99/MF A01

A kit designed for converting the standard BLACK HAWK aircraft to medical evacuation configuration, after removal of eight troop seats is described. Four crash-attenuated litters are carried,

plus a 60 Hz, 115 volt power pack that permits the use of regular hospital equipment by casualities in transit. Litters can be loaded transversely from either side of the aircraft. A lifting facility is provided for the upper litters.

N79-19615# Societe Nationale Industrielle Aerospatiale Marignane (France) Helicopter Div

CASUALTY EVACUATION BY HELICOPTER

Louis Vachon and Wilfrid Messens In AGARD Operational Helicopter Aviation Med Dec 1978 18 p ref In ENGLISH and FRENCH

Avail NTIS HC A99/MF A01

Casualty evacuation procedures which allow in-flight performance of all medical actions required for reanimation and small surgery together with transmission of medical data to the hospital are described An in-flight test of DAUPHIN, a modern ambulance installation for helicopters, on the occasion of a traffic accident simulation and, at the same time, an actual evacuation mission, is documented A full success demonstrated the validity of the concept.

N79-19616# Canadian Armed Forces Base Hospital, Bushell Park (Saskatchewan)

DEVELOPMENT OF CASUALTY EVACUATION KIT FOR THE LIGHT OBSERVATION HELICOPTER (KIWA)

R M Goede In AGARD Operational Helicopter Aviation Med Dec 1978 5 p refs

Avail NTIS HC A99/MF A01

The design and testing of a casualty evacuation kit utilizing the Kiowa helicopter is described. This kit consisted of a stretcher support frame, aluminum stretcher and two rear doors with bubble extensions to ensure the necessary width to transport one patient across the rear passenger compartment. Flight testing was carried out to determine the aerodynamic characteristics of the Kiowa aircraft with the kit installed. This kit was designed to fit any Kiowa helicopter in the Canadian Forces fleet. In the event of an aircraft crash, this kit could be installed in the first available aircraft in approximately fifteen minutes.

N79-19621# Army Aeromedical Research Lab Fort Rucker, Ala

US ARMY AVIATION FATIGUE-RELATED ACCIDENTS, 1971 - 1977

Gerald P Krueger and Yvonna F Jones *In* AGARD Operational Helicopter Aviation Med Dec 1978 11 p refs

Avail NTIS HC A99/MF A01

An accident data survey was made to determine how frequently aviator crew fatigue may have contributed to US Army aviation accidents from 1971 to 1977 All accident reports in the US Army Agency for Aviation Safety (USAAAVS) data base were reviewed Aviator fatigue was deemed to be a contributing factor in 42 rotary wing accidents which resulted in a total of 51 fatalities and 63 personnel injuries. Fatigue contributed to 10 fixed wing accidents resulting in three fatalities and five injuries. These fatigue related accidents are categorized by aircraft and mission type and by time of day and day of week of the accident. Pilots activities prior to the accidents which promote the likelihood of pilot fatigue contributions are described. The personnel and equipment costs of these accidents to the Army are estimated, and the relative importance of such accidents to the total US Army aviation accident picture is assessed.

N79-19625# Sikorsky Aircraft Stratford, Conn ADVANCEMENTS IN HELICOPTER COCKPIT TECHNOL-OGY

Howard P Harper In AGARD Operational Helicopter Aviation Med Dec 1978 7 p refs

Avail NTIS HC A99/MF A01

The requirements of future missions are discussed in terms of the need for advanced controls and displays and improvements in cockpit vision, workload, and comfort. A number of technological areas are reviewed as candidates for inclusion in an advanced cockpit. A cockpit design incorporating this technology is presented.

N79-19631# Naval Air Development Center Warminster Pa Aircraft and Crew Systems Technology Directorate

DESIGN PROCEDURE FOR AN INFORMATION TRANSFER METHOD CUBITS FOR ALLOCATING PANEL AREA FOR AIRCREW STATION CONTROLS AND DISPLAYS

Patrick M Curran In AGARD Operational Helicopter Aviation Med Dec 1978 10 p refs

Avail NTIS HC A99/MF A01

A systematic and objective method for the allocation of panel areas in aircrew workspaces was developed. The developed procedure is based on (1) the criticality of the control or display on crew safety and mission effectiveness (2) the frequency of utilization and (3) the amount of information which is conveyed by the operator to the system through control actuation or which is conveyed to the operator by the display presentation. This procedure utilizes a computational method called CUBITS to establish a single figure of merit for the allocation of panel space. This method also deals with the number of control settings and accuracy required in the computation of the amount of information being transferred.

N79-19641# Army Aeromedical Research Lab, Fort Rucker Ala

VISUAL POCKETS A DESIGN PARAMETER FOR HELICOPTER INSTRUMENT PANELS

R W Bailey and David D Glick /n AGARD Operational Helicopter Aviation Med Dec 1978 4 p refs

Avail NTIS HC A99/MF A01

The concept of fixation points between instruments ('Visual Pockets') for instrument flight of helicopters was proposed as a new concept to reduce pilot workload and improve performance it was also proposed that this concept be applied to cockpit instrument panel design. In view of the significance attached to this revolutionary concept of Visual Pockets' a review and perspective of helicopter pilot visual information requirements are presented with special emphasis on the impact of Visual Pocket concepts.

N79-19643# Human Engineering Labs Aberdeen Proving Ground Md

INTERNAL COCKPIT REFLECTIONS OF EXTERNAL POINT LIGHT SOURCES FOR THE MODEL YAH-64 ADVANCED ATTACK HELICOPTER

Christopher C Smyth In AGARD Operational Helicopter Aviation Med Dec 1978 16 p refs

Avail NTIS HC A99/MF A01

The US Army Human Engineering Laboratory (HEL) developed a computer program for computing the internal cockuit reflections on the transparent canopy surfaces of external point light sources Computations were completed for the YAH-64 advanced attack helicopter (low glare canopy design) The results show that primary reflections as seen from the pilot's position are possible on (1) the upper rear corners of the forward side canopy surfaces (2) the upper edges of the rear sides, and (3) the sides of the top surface Computations were also completed for the copilot's position and show possible reflections on the front and side surfaces A computer graphics output is used to show reflection points on canopy layouts and perspectives of the cockpit J M S

 $\mbox{N79-19646}\#$ Army Avionics Research and Development Activity, Fort Monmouth \mbox{N} J

A SURVEY OF COMMUNICATIONS IN THE HIGH NOISE ENVIRONMENT OF ARMY AIRCRAFT

Mitchell S Mayer and Arthur W Lindberg In AGARD Operational Helicopter Aviation Med Dec 1978 18 p refs

Avail NTIS HC A99/MF A01

In Army aircraft, the noise environment consists of a continuous noise level comprised of a mixture of random (broadband) and periodic frequencies (the aircraft noise signature or whine) and in the case of gunships, transient high-level noise bursts generated by the weapons systems. The noise environment reaching the aviator's ear is comprised of direct

ambient noise penetration and communications systems processed noise (during periods of communications use, or open mike operations). The most insidious impact of the high noise levels is the long-term permanent hearing threshold shift, or hearing loss that the aviator may incur from his prolonged exposure to the aircraft's interior sound pressure levels. Improvement of speech intelligibility under all flight conditions will improve the aviator's effectiveness by reducing the number of transmission repetitions necessary to assure that a message is correctly conveyed, thus reducing the distraction level during critical mission phases. Reducing the ambient aircraft noise processed by the communications system will further improve speech intelligibility and reduce this particular increased noise contribution to pilot stress.

N79-19647# Royal Aircraft Establishment Farnborough (England) Human Engineering Div SOME ASPECTS OF HELICOPTER COMMUNICATIONS

G M Rood and E J Lovesey In AGARD Operational Helicopter Aviation Med Dec 1978 7 p refs

Avail NTIS HC A99/MF A01

Factors that influence helicopter radio communications are examined. These include the characteristics of the signal transmitter and receivers and their siting, the effects of noise and distortion of the signals, and the ability of the operator to perceive the signals while performing other tasks. The interface of the man with the equipment and the helicopter environment and the effect of the helicopter environment upon his ability to receive and process audio signals is emphasized. Helicopter noise levels helmet attenuation, signal masking total operator noise dose, and crew task difficulty are considered in terms of improving the overall helicopter/crew efficiency.

N79-19653# Michigan Univ Ann Arbor Inst of Highway Safety Research

OCCUPANT INJURY MECHANISMS IN CIVIL HELICOPTER ACCIDENTS

Richard G Snyder In AGARD Operational Helicopter Aviation Med Dec 1978 14 p refs Sponsored in part by FAA and NTSB

Avail NTIS HC A99/MF A01

Mechanisms incurred in several selected accidents involving roll-over, rotor blade strike and seat and restraint system failures are discussed. The present injury and fatality rate could be reduced in civil accidents by improved restraints including use of upper-torso belts energy-absorbing seats, crashworthy fuel systems and increased use of protective helmets. J M S

N79-19654# Army Agency for Aviation Safety Fort Rucker, Ala

COMPARATIVE INJURY PATTERNS IN US ARMY HELICOPTERS

Laurel D Sand *In* AGARD Operational Helicopter Aviation Med Dec 1978 7 p refs

Avail NTIS HC A99/MF A01

The type of injuries body area injured, and cause of injuries to 740 U.S. Army aviators involved in 388 rotary wing accidents from 1 January 1972 through 30 September 1977 are examined Considerations are given to two main areas (1) relationship to injury regarding the aviator's height, weight, and location aboard the aircraft, cockpit condition, and aircraft altitude, and (2) comparison of present injury experience with previous injury studies. The results, through statistical analyses show that not one or even combinations of those factors listed were significant in injury causation. Further, comparisons of injuries show that the overall injury pattern has not changed significantly in the past 20 years. For example, injuries to the extremities, the head, and the spine continue to be among the leading body areas to be injured. Also, 94 percent of all accidents from 1957 to the present were classified as survivable but produced 33 percent of all fatalities

N79-19655# Army Agency for Aviation Safety Fort Rucker

ENGINEERING ANALYSIS OF CRASH INJURY IN ARMY **AIRCRAFT**

James E Hicks In AGARD Operational Helicopter Aviation Med Dec 1978 11 p refs

Avail NTIS HC A99/MF A01

A methodology for identification of crashworthiness deficiencies in Army aircraft is discussed. The methodology provides for injury and impact data to be extracted from accident reports using a specially developed injury coding system Personnel injuries are costed through a technique which provides for consideration of each injury based on its relative severity as determined by medical examination Crash injury causes are identified and ranked according to the magnitude of their effect and probability of occurrence. The technique is designed to provide recommendations as to the most urgent crashworthiness research/development/procurement efforts for consideration by aircraft systems managers and aviation research laboratories. An application of the methodology to an operated Army aircraft is shown Preliminary results as to the more significant crash hazards in this aircraft are discussed. Recommendations are made as to the use of the methodology and to additional investigation aids which would improve the future identifications of crash hazards

N79-19657# Army Agency for Aviation Safety, Fort Rucker

ASSESSMENT OF THE BENEFITS OF AIRCRAFT CRASH-WORTHINESS

Andrew E Gilewicz In AGARD Operational Helicopter Aviation Med Dec 1978 8p refs

Avail NTIS HC A99/MF A01

An assessment is made of the economic benefits of providing crashworthiness improvements within future Army helicopters Crashworthiness features which would be most worthwhile in preventing or reducing injury and hardware damage are discussed from a cost effectiveness standpoint. Predictions of future accident losses for a number of candidate utility helicopter replacements are given. Projections were derived based on each helicopter's crashworthiness design features and the effectiveness in injury and hardware damage prevention. The technical adequacy of the design requirements is verified based on typical Army helicopter crash impacts J M S

N79-19658# Army Aviation Research and Development Command, Fort Eustis Va Applied Technology Lab CRASHWORTHY HELICOPTER SEATS AND OCCUPANT

RESTRAINT SYSTEMS

George T Singley, III and Stanley P DesJardins (Simula Inc., Tempe, Ariz) In AGARD Operational Helicopter Aviation Med Dec 1978 32 p refs

Avail NTIS HC A99/MF A01

Seats and restraint systems offering substantial improvements in comparison to existing helicopters with respect to strength body restraint, and crash force attenuation are described. These seat and restraint systems are capable of retaining the seated occupant in the same relative position within the aircraft throughout the 95th percentile potentially survivable accident without the occupant being subjected to conditions in excess of human tolerance Cockpit and cabin seat and restraint systems retention strengths are shown to withstand drop and sled tests with velocity changes of 50 ft/sec and peak accelerations of 48G for drop tests and 30G for sled tests. This increased strength is achieved with lightweight designs and is made possible by the application of load limiting principles. This crash force attenuation characteristic limits the impact loading not only of the seat structure but also of the seat occupant

N79-19659# Royal Air Force Inst of Aviation Medicine Farnborough (England)

SOME IMPROVEMENTS TO THE UK HELICOPTER COCK-PIT

D C Reader In AGARD Operational Helicopter Aviation Med Dec 1978 3 p refs

Avail NTIS HC A99/MF A01

The human-factor aspects of helicopters are discussed. These include improvements to the restraint harnesses the location and methods of stowage of the survival aids, and the strength, adjustment and anti-vibration properties of the crew seats Experiments conducted to investigate the feasibility of different configurations of flight control are described J M S

N79-19660# Army Aeromedical Research Lab Fort Rucker, Ala

HELICOPTER CRASHWORTHY FUEL SYSTEMS AND THEIR EFFECTIVENESS IN PREVENTING THERMAL INJURY

Stanley C Knapp, Pierre Allemond (Army Agency for Aviation Safety, Ft Rucker, Ala) and David H Karney In AGARD Operational Helicopter Aviation Med Dec 1978 7 p refs

Avail NTIS HC A99/MF A01

All Army helicopter accidents during the period 1968-1976 are reviewed and classified by survivability and whether or not the aircraft was equipped with a crashworthy fuel system. Accident associated fatalities and injuries are reclassified as to the primary injury involved and its relationship to the existence of any postcrash fire The direct costs involved in the care of thermal fatalities and thermal injuries are calculated using the most conservative estimates. It is shown that the helicopter crashworthy fuel system essentially eliminated postcrash fatalities and injuries in accidents involving helicopters equipped with the new system

N79-19661# Arizona State Univ , Tempe Engineering Safety

A METHOD FOR SELECTING A CRASHWORTHY FUEL SYSTEM DESIGN

S Harry Robertson and James W Thurbow In AGARD Operational Helicopter Aviation Med Dec 1978 6 p

Avail NTIS HC A99/MF A01

A rating method that a crashworthy fuel system designer can use to help determine the amount of hardware and special design considerations needed to obtain a desired reduction in the fuel system fire hazard level is discussed. Man's tolerance to the thermal environment, and the escape time available to the aircraft occupants are among the factors considered. J M S

N79-19663# Sikorsky Aircraft, Stratford, Conn Systems Engineering Branch

CRASH SURVIVABILITY OF THE UH-60A HELICOPTER

Brian L Carnell $\mbox{\it In}$ AGARD Operational Helicopter Aviation Med Dec 1978 10 p

Avail NTIS HC A99/MF A01

The Sikorsky UH-60A or BLACK HAWK is designed to minimize the hazards found in the many accidents that occurred in the combat environment of Southeast Asia. Its crash survivability design features are discussed. These include (1) a protective shell is maintained around the occupants, the energy absorbing landing gear cushions the crash impact and the structure is designed to minimize penetration by rotor blades transmissions and engines, (2) the loads on the occupants are limited to noninjurious levels, all seats are energy attenuating, (3) major postcrash fires are prevented a complete crash survivable fuel system is installed (4) the interior is noninjurious, no hard structure is in the head strike zones. Padding and shielding in the cockpit protect the aircrew from injury and entrapment, and (5) adequate emergency escape capability is provided, jettisonable cockpit doors and cabin windows allow rapid emergency egress JMS

N79-19664# Hughes Helicopters, Culver City Calif Analysis Section

THE APPROACH TO CREW PROTECTION IN THE CRASH **ENVIRONMENT FOR THE YAH-64**

John M McDermott $\it In$ AGARD Operational Helicopter Aviation Med Dec 1978 7 p refs -

Avail NTIS HC A99/MF A01

The approach to crashworthiness in protecting the crew of the advanced attack helicopter is described. Basic requirements of crash criteria specified by the Army are presented Impact modes and impact velocities are discussed. The means used to meet these requirements using a total systems approach (i.e. landing gear, plus fuselage crushing and energy absorbing seats all in series) are presented. Crash pulses felt by the occupants during the various crash impacts are presented. Design of energy absorbing seats is discussed. Protection of the crew by use of turnover structure and by means of high load factors on heavy mass items which could penetrate the cockpit is illustrated. Maintaining living space during crash barrier impacts, and protection against blade strikes using the roll over structure are discussed.

N79-19665# Naval Training Equipment Center Orlando Fla HELICOPTER UNDERWATER ESCAPE TRAINER (9D5)

William F Cunningham /n AGARD Operational Helicopter Aviation Med Dec 1978 3 p refs

Avail NTIS HC A99/MF A01

A helicopter equivalent of the Navy Dilbert Dunker long used as an underwater escape procedures trainer is described. The same principles of of the Dilbert Dunker apply to the helicopter escape trainer. Aircrews ride the trainer from different seat positions thoroughly gaining confidence in their ability to successfully escape from anywhere in the helicopter. This training reflects the belief that successful escape from a ditched/sinking helicopter depends largely on spontaneous action achieved through repetitive drills. The results tend to prove this true. J M S

N79-19666# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany)

BAILOUT FROM AUTOROTATING HELICOPTERS

H D Melzig U Schmidt, and E A Bockemuller In AGARD Operational Helicopter Aviation Med Dec 1978 9 p refs

Avail NTIS HC A99/MF A01

Parachute jumps were conducted from an autorotating helicopter to prove the possibility of bailout with a parachute as a means of rescue in emergency cases. The tests were conducted at glide angles of 17 deg proving by their good agreement with the computed results the general applicability of the computational method to glide angles up to 90 deg. The results show that bailout from autorotating helicopters is possible for all glide angles. It is recommended, however that crew members are taught to perform the ball attitude and give a delay of 3 sec before releasing their parachute.

N79-19814*# MAN-Acoustics and Noise Inc Seattle Wash A COMMERCIAL AIRPORT NOISE ENVIRONMENT MEASUREMENT, PREDICTION AND CONTROL Final Report

J E Mabry and B U Sullivan Feb 1979 72 p refs (Contract NAS1-14404)

(NASA-CR-3107 MAN-1023-B) Avail NTIS HC A04/MF A01 CSCL 20A

The data for a commercial airport noise measurement program included approximately 1,100 calibrated tape recordings at three observer positions and some 1500 supplementary peak level measurement at ten additional measurement points. For some individual airplane categories there were substantial differences between results based on state-of-the-art noise prediction technology and those based on actual measurements. Certain takeoff procedures resulted in significant noise reductions for particular airplane types. Also, there was some evidence that specific categories of airplanes can be flown with reduced ranges of peak noise levels.

N79-19815*# United Technologies Research Center, East Hartford, Conn
AIRFRAME NOISE COMPONENT INTERACTION STUDIES

AIRFRAME NOISE COMPONENT INTERACTION STUDIES Final Report

Martin R Fink and Robert H Schlinker Mar 1979 138 p refs

(Contract NAS1 15083)

(NASA-CR-3110 R78-912996-12) Avail NTIS HC A07/MF A01 CSCL 20A

Acoustic wind tunnel tests were conducted of a two-dimensional wing section with removable high-lift leading and trailing edge devices and a removable two-wheel landing gear with open cavity. An array of far field conventional microphones and an acoustic mirror directional microphone were utilized to determine far field spectrum levels and noise source distribution. Data were obtained for the wing with components deployed separately and in various combinations. The basic wing model had 0.305 m (1.00 ft) chord, which is roughly 1/10 scale for a one-hundred passenger transport airplane. Most of the data were obtained at 70.7 and 100 m/sec (232 and 328 ft/sec) airspeeds which bracket the range of practical approach speeds for such aircraft. Data were obtained at frequence to 40 kHz so that when scaled to s typical full-airframe the frequency region which strongly influences preceived noise level would be included.

Author


SUBJECT INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Suppl 110)

JUNE 1979

A79-26537

Typical Subject Index Listing



The title is used to provide a description of the subject matter. When the title is insufficiently descriptive of the document content a title extension is added separated from the title by three hyphens. The NASA or AlAA accession number is included in each entry to assist the user in locating the abstract in the abstract section of this supplement. If applicable, a report number is also included as an aid in identifying the document.

Δ	
A-7 AIRCRAFT	
Software requirements for the A-7E aircraft [AD-A061751]	N79-18974
AC GENERATORS	N/3-103/4
Filter weight minimization for rectified	
superconducting alternator power supplies	z
for aircraft	•
201 4110144	A79-26966
Air Force applications of lightweight	
superconducting machinery in airborn	e power
sources	•
	A79-27666
ACCELERATED LIFE TESTS	
Recent General Electric engine development	testing
for improved service life	
[SAE PAPER 780990]	N79-25876
The application of a design verification s	
and accelerated mission testing to gas to	irbine
engine development	.70 05075
[SAE PAPER 780991]	A79-25877
ACCELERATION (PHYSICS)	
Some aspects of unsteady insect aerodynamic Acceleration potential methods in plane	:S:
airfoil theory, and measurements of	insteady
unsteady-periodic forces generated by the	hlowfly
unsteady periodic forces defletated by the	N79-18903
Evaluation of a wake vortex upset model bas	
simultaneous measurements of wake velocit	ies and
probe-aircraft accelerations	
[NA SA-TH-78561]	N79-18960
ACCELEROMETERS	
Evaluation of a wake vortex upset model bas	sed on
simultaneous measurements of wake velocit	ties and
probe-aircraft accelerations	
[NASA-TH-78561]	N79-18960
Statistical review of counting acceleromete	er data
for Navy and Marine fleet aircraft	
[AD-A061894]	N79-18972
ACCIDENT PREVENTION	
Parachute partial inversions	
[AIAA 79-0451]	A79-26655
Why doesn't aircraft accident investigation	1
prevent accidents	.20 0000
71t1i of 1-11t	A79-27319
Electric charging of helicopters aircra	
hazards and static dischargers for accide	3DT
prevention [BMVG-PBWT-78-7]	N79-18274
f DU 40-1 DM 1-10-1]	N/3-102/4

ACOUSTIC ATTENUATION	
Full-scale engine tests of bulk absorber ac	coustic
inlet treatment	
[AIAA PAPER 79-0600]	A79-26881
Sound absorption caused by vorticity sheddi	.ng,
demonstrated with a jet flow	.70 ocoor
[AIAA PAPER 79-0575]	A79-26905
Inside noise of C-1 cargo aircraft and the	
reduction performance by interior materia	A79-27121
ACOUSTIC DUCTS	R/3-2/121
Wave propagation in ducts using the finite	element
method for aircraft noise reduction	
[AIAA PAPER 79-0659]	A79-26879
Sound radiation from hyperboloidal inlet du	cts
[AIAA PAPER 79-0677]	A79-26885
ACOUSTIC EXCITATION	
Discrete noise spectrum generated by an	
acoustically excited jet [AINA PAPER 79-0592]	- 70 0 0 0 0 0 7
	179-26887
Turboprop interior noise studies	A79-26931
[AIAA PAPER 79-0647]	R/9-20931
ACOUSTIC MEASUREMENTS An acoustical study of the XV-15 Tilt Rotor	
Research Aircraft	
[AIAA PAPER 79-0612]	A79-26939
ACOUSTIC PROPAGATION	
The application of finite element technique	s to
acoustic transmission in lined ducts with	
[AIAA PAPER 79-0660]	A79-26893
ACOUSTIC PROPERTIES	
Investigation of the aerodynamic and acoust	10
performance of a low-pressure ratio tande	m-blade
compressor	-20 40025
ACOUSTIC SCATTERING	N79-18975
Radiation of an acoustic source near the tr	ailing
edge of a wing in forward motion	arrang
edge of a wing in forward motion [AIAA PAPER 79-0605]	A79-26940
Applications of diffraction theory to aeroa	
[NASA-TH-80053]	N79-18686
ACOUSTIC SIMULATION	
Radiation of an acoustic source near the tr	ailing
edge of a wing in forward motion	
[AIAA PAPER 79-0605]	A79-26940
ACTUATOR DISKS	
Pailure studies of a third stage fan disk f TP-30 turbine engine	rom a
[AD-A061801]	N79-19004
ACTUATORS	N73-13004
Direct drive control valve for fly-by-wire	flight
control system actuators	,
[AD-A062030]	N79-19007
ADAPTIVE CONTROL	
Redundant control systems for flight vehicl	.es
Russian book	
Russian book	.es A79-25875
Russian book	A79-25875
Russian book ADDITIVES Effect of a chromium-containing fuel additi	A79-25875
Russian book	A79-25875 ve on
Russian book ADDITIVES Effect of a chromium-containing fuel additing the corrosion	A79-25875
Russian book ADDITIVES Effect of a chromium-containing fuel additing the corrosion ADDESIVE BONDING	A79-25875 ve on A79-26546
Russian book ADDITIVES Effect of a chromium-containing fuel additing the hot corrosion ADDESIVE BONDING GASP IV simulation model for the composites	A79-25875 ve on A79-26546
Russian book ADDITIVES Effect of a chromium-containing fuel addition to corrosion ADHESIVE BONDING GASP IV simulation model for the composites bonding production facility	A79-25875 We on A79-26546 and A79-27297
Russian book ADDITIVES Effect of a chromium-containing fuel addition to corrosion ADDESIVE BONDING GASP IV simulation model for the composites bonding production facility Fracture mechanics for structural adhesive	A79-25875 We on A79-26546 and A79-27297
Russian book ADDITIVES Effect of a chromium-containing fuel addition to the corrosion ADHESIVE BONDING GASP IV simulation model for the composites bonding production facility Practure mechanics for structural adhesive part 2, phase 2	A79-25875 ve on A79-26546 and A79-27297 bonds,
Russian book ADDITIVES Effect of a chromium-containing fuel addition to corrosion ADDESIVE BONDING GASP IV simulation model for the composites bonding production facility Fracture mechanics for structural adhesive	A79-25875 We on A79-26546 and A79-27297

The U-2 story

AEROACOUSTICS SUBJECT INDEX

AEROACOUSTICS		Comparison of the aerodynamic properties of	
A comparison of linear acoustic theory with		aeroplane with the tail-first configurati	on and
experimental noise data for a small-scale hovering rotor		with the conventional configuration [BLL-RTS-11520]	N79-17794
	A79-26876	Aerodynamic properties of a flat plate with	
Measured and predicted noise of the AVCO-Ly	coming	for optical-propagation studies	-
YF-102 turbofan engine			N79-17796
	A79-26877	Stability and control characteristics of a	
A finite element subvolume technique for structural-borne interior noise predictio	n	monoplanar elliptic missile model at Mach numbers from 1.60 to 2.86	
in aircraft	ц		N79-17808
	A79-26882	Space shuttle afterbody aerodynamics/plume	1177 11000
The application of finite element technique		simulation data summary	
acoustic transmission in lined ducts with		[NASA-TP-1384]	N79-17810
	A79-26893	Rotary-wing aerodynamics. Volume 2: Perfo	rmance
Direct experimental verification of the		prediction of helicopters	
theoretical model predicting rotor noise			N79-17811
generation [AIAA PAPER 79-0658]	A79-26894	Formulation of aerodynamic prediction techn for hypersonic configuration design	rdnez
Propagation of buzz-saw noise in a nonunifo			N79-17850
contoured jet engine inlets		Aerodynamic behavior of fibres and sampling	
	A79-26896	respirable dust	
Considerations for the design of inlet flow			N79-18470
conditioners for static fan noise testing		Analysis of some aerodynamic characteristic	s due
	A79-26909	to wing-jet interaction	N79-18917
Diagnostic evaluation of jet noise suppress mechanisms	100	[NASA-CR-158349] Wings	W/3-10317
	A79-26912		N79-18921
Airframe noise measurements on a small-scal		The place of aerodynamics in the design pro	
of a supersonic transport concept in an a			N79-18933
flow facility		Investigation of the aerodynamic and acoust	ıc
	A79-26920	performance of a low-pressure ratio tande	m-blade
Noise from struts and splitters in turbofan	exit	compressor	W70 *007E
ducts [AIAA PAPER 79-0637]	A79-26923		N79-18975
Reduction of rotor-turbulence interaction n		Transonic compressors for heavy gases. Part Selections of the aero-design parameters	'•
static fan noise testing	0200 22		N79-19351
[AIAA PAPER 79-0656]	A79-26925	Transonic compressors for heavy gases. Par	t 2:
An experimental study of the influence of		Aero-mechanical considerations, testing a	nđ
flight-stream turbulence on jet mixing no		operation	
	A79-26935		N79-19352
Effects of simulated forward flight on jet :	noise,	Aerodynamic and Mechanical factors affectin surge line: Inlet flow distortion influe	
shock noise and internal noise			nces on
	174-76446	arial flow comproceors	
	A79-26936 8D	axial flow compressors	N79-19363
Flight effects on noise generated by the JT	8D	-	N79-19363
	8D A		
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel	8D Wind	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers	high
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614]	8D Wind A79-26937	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers	high A79-25247
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor	8D Wind A79-26937	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations	high A79-25247
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft	8D A wind A79-26937	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna	high A79-25247
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612]	8D A wind A79-26937	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection	high A79-25247 mlc
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft	8D wind A79-26937 A79-26939 on	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection	high A79-25247
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interactitones generated by inlet rods in the JT15	8D wind A79-26937 A79-26939 on	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNVG-PBNT-77-27] BRODYNAMIC COMPIGURATIONS Experiments on tandem diffusers with	high A79-25247 Mac N79-17814
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor	8D A wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BRVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between	high A79-25247 BlC N79-17814
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579]	8D A wind A79-26937 A79-26939 on D engine A A79-26944	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [MASA-CR-158957]	high 100 100 100 100 100 100 100 100 100 100
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of	8D A wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BHVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation	high A79-25247 mic N79-17814 N79-17803 of
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets	8D A wind A79-26937 A79-26939 on Dengine A79-26944 wakes A79-26945	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r	high A79-25247 mic R79-17814 R79-17803 of atto
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574]	8D A wind A A79-26937 A79-26939 on D engine A A79-26944 wakes A79-26945 A79-26946	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-PBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration	high A79-25247 mic R79-17814 R79-17803 of atto
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa	8D A wind A79-26937 A79-26939 on D engine A A79-26944 wakes A79-26945 A79-26946 coustics	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-PBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel	high A79-25247 nic N79-17814 N79-17803 of atio in the
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa	8D A wind A A79-26937 A79-26939 on D engine A A79-26944 wakes A79-26945 A79-26946	BRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041]	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-17871
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053]	8D A wind A79-26937 A79-26939 on D engine A79-26944 wakes A79-26945 A79-26946 coustics N79-18686	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-PBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel	high h79-25247 m1c m79-17814 m79-17803 of attio in the m79-17871 utation
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] ABRODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7	8D A wind A 79-26937 A79-26939 on D engine A 79-26944 wakes A 79-26945 A 79-26946 coustics N 79-18686	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-17871 utation tion,
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0512] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7 Technical Papers	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oggy , 1979,	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-PBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspector highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design	high h79-25247 n1c n79-17814 n79-17803 of attio in the n79-17871 utation tion, n79-18946
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TR-80053] AERODYMANIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7 Technical Papers	8D A wind A 79-26937 A79-26939 on D engine A 79-26944 wakes A 79-26945 A 79-26946 coustics N 79-18686	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro	high h79-25247 nic N79-17814 N79-17803 of atio in the N79-17871 utation tion, N79-18946
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TR-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq	high h79-25247 nic N79-17814 N79-17803 of atio in the N79-17871 utation tion, N79-18946
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0512] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISFICS Dynamics of controlled longitudinal motion	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single rohelicopter configuration. Volume 8: freq analyses of wake single film data, basic	high h79-25247 nic N79-17814 N79-17803 of atio in the N79-17871 utation tion, N79-18946
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single rohelicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-1891 tion, N79-18946 tor uency
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing	8D A wind A A79-26937 A79-26939 on Dengine A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 ogy , 1979, A79-26626 of an	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-N062013] Interactional aerodynamics of the single ro	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-17871 utation tion, N79-18946 tor uency
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYMANIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYMANIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book	8D A wind A A79-26937 A79-26939 on Dengine A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 ogy , 1979 , A79-26626 of an A79-25517 A79-26355	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A:	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18971 utation, N79-18946 tor uency
Flight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simula	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626 of an A79-25517 A79-26355 ated	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wake	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18971 utation, N79-18946 tor uency
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa- [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol- Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul- damage on the aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626 of an A79-25517 A79-26355 ated	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TH-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline	high h79-25247 nic N79-17814 N79-17803 of atio in the N79-17871 utation tion, N79-18946 tor uency N79-18956
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simulicange on the aerodynamic characteristics airplanes and missiles	8D A wind A A79-26937 A79-26939 on Dengine A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626 of an A79-25517 A79-25517 A79-26355 ated of	REODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BHYG-FBWT-77-27] ERODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994]	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18910 tion, N79-18946 tor uency N79-18956 tor e
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979 , A79-26626 of an A79-25517 A79-26355 ated of	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNVG-FDNT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18910 tion, N79-18946 tor uency N79-18956 tor e
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simulicange on the aerodynamic characteristics airplanes and missiles	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 ogy , 1979, A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of	REODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BHYG-FBWT-77-27] ERODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994]	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-1891 utation tion, N79-18946 tor uency N79-18956 tor
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe- coolant discharge from perforated turbine on their aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979 , A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of vanes	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wake single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro helicopter configuration. Volume 8-C: Frequency analyses of wake single film da hubcaps and air ejectors	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-18971 utation tion, N79-18946 tor uency N79-18956 tor e N79-18958 tor ta,
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa- [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol- Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers ABRODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe- coolant discharge from perforated turbine on their aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 ogy , 1979, A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TH-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro helicopter configuration. Volume 8-C: Frequency analyses of wake single film da hubcaps and air ejectors [AD-A061995]	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18914 tor uency N79-18956 tor e N79-18958 tor ta, N79-18959
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe coolant discharge from perforated turbine on their aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979 , A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of vanes	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BHYG-FBWT-77-27] RRODYBANIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro helicopter configuration. Volume 8-C: Frequency analyses of wake single film da hubcaps and air ejectors [AD-A061995] The aerodynamic penalties associated with t	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18914 tor uency N79-18956 tor e N79-18958 tor ta, N79-18959
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe coolant discharge from perforated turbine on their aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 A79-26945 A79-26946 coustics N79-18686 oogy , 1979 , A79-26626 of an A79-26355 ated of A79-27424 nce of vanes A79-27727	RRODYNAMIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BNG-FDNT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TR-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wake single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro helicopter configuration. Volume 8-C: Frequency analyses of wake single film da hubcaps and air ejectors [AD-A061995] The aerodynamic penalties associated with thade cooling	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-18971 tion, N79-18956 tor e N79-18958 tor ta, N79-18959 urbine
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa- [NASA-TH-80053] AERODYNABIC BRAKES Aerodynamic Decelerator and Balloon Technol- Conference, 6th, Houston, Tex., Harch 5-7 Technical Papers ABRODYNABIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe- coolant discharge from perforated turbine on their aerodynamic characteristics Influence of bypass ratio change on fan aerodynamic characteristics	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics W79-18686 ogy y, 1979, A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of vanes A79-27727 A79-27744	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TH-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single rothelicopter configuration. Volume 8: frequanalyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single rothelicopter configuration. Volume 6-A: One-third octave band spectrograms of wake single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single rothelicopter configuration. Volume 8-C: Frequency analyses of wake single film data hubcaps and air ejectors [AD-A061995] The aerodynamic penalties associated with thaled cooling	high A79-25247 nic N79-17814 N79-17803 of atio in the N79-18914 tor uency N79-18956 tor e N79-18958 tor ta, N79-18959
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe coolant discharge from perforated turbine on their aerodynamic characteristics Influence of bypass ratio change on fan aerodynamic characteristics Wing rock due to aerodynamic bysteresis	8D wind A A79-26937 A79-26939 on Dengine A A79-26944 wakes A79-26945 A79-26946 coustics W79-18686 ogy y, 1979, A79-26626 of an A79-25517 A79-26355 ated of A79-27424 nce of vanes A79-27727 A79-27744	Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BHVG-FBWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-r highly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TM-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single ro helicopter configuration. Volume 8: freq analyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single ro helicopter configuration. Volume 6-A: One-third octave band spectrograms of wak single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single ro helicopter configuration. Volume 8-C: Frequency analyses of wake single film da hubcaps and air ejectors [AD-A061995] The aerodynamic penalties associated with thlade cooling	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-18971 tion, N79-18956 tor e N79-18958 tor ta, N79-18959 urbine
Plight effects on noise generated by the JT engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot tunnel [AIAA PAPER 79-0614] An acoustical study of the XV-15 Tilt Rotor Research Aircraft [AIAA PAPER 79-0612] Analysis of radiation patterns of interacti tones generated by inlet rods in the JT15 [AIAA PAPER 79-0581] Unsteady stator response to upstream rotor [AIAA PAPER 79-0579] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] Applications of diffraction theory to aeroa [NASA-TH-80053] AERODYNAMIC BRAKES Aerodynamic Decelerator and Balloon Technol Conference, 6th, Houston, Tex., March 5-7 Technical Papers AERODYNAMIC CHARACTERISTICS Dynamics of controlled longitudinal motion airplane with a variable-geometry wing Aerodynamics of flame jets Russian book Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics airplanes and missiles Theoretical-experimental analysis of influe coolant discharge from perforated turbine on their aerodynamic characteristics Influence of bypass ratio change on fan aerodynamic characteristics Wing rock due to aerodynamic bysteresis	8D wind A A79-26937 A79-26939 on Dengine A79-26944 wakes A79-26945 A79-26946 coustics N79-18686 oogy , 1979, A79-26626 of an A79-25517 A79-25517 A79-27424 of vanes A79-27744 A79-27744 A39-27744	RRODYBANIC COEFFICIENTS Characteristic aerodynamic coefficients at Reynolds numbers Vortex models on missile configurations computer program for determining aerodyna coefficients and flow deflection [BMVG-FDWT-77-27] BRODYNAMIC CONFIGURATIONS Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Theoretical and experimental investigation ground induced effects for a low-aspect-rhighly swept arrow-wing configuration Langley V/STOL tunnel [NASA-TH-80041] Some recent progress in transonic flow comp flow distribution, numerical optimiza and airfoil design Interactional aerodynamics of the single rothelicopter configuration. Volume 8: frequanalyses of wake single film data, basic configuration wake exploration [AD-A062013] Interactional aerodynamics of the single rothelicopter configuration. Volume 6-A: One-third octave band spectrograms of wake single film data, buildup to baseline [AD-A061994] Interactional aerodynamics of the single rothelicopter configuration. Volume 8-C: Frequency analyses of wake single film data hubcaps and air ejectors [AD-A061995] The aerodynamic penalties associated with thaled cooling	high A79-25247 mic N79-17814 N79-17803 of atio in the N79-18971 tion, N79-18956 tor e N79-18958 tor ta, N79-18959 urbine

SUBJECT INDEX AGRICULTURE

Delta method, an empirical drag buildup technique [NASA-CR-151971] 879-17801	Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight
ABRODYNAMIC FORCES A first-order theory for the effects of line ties	[AIAA PAPER 79-0648] A79-26930 Master Plan for prediction of vehicle interior noise
on parachute deployment	[AIAA PAPER 79-0582] A79-26943
[AIAA 79-0450] A79-26654 The validity of the Leicester computer model for a	Airframe noise component interaction studies [NASA-CR-3110] B79-19815
parachute with fully-deployed canopy	AERODYWAHIC STALLING
[AIAA 79-0460] A79-26663 General purpose computer program for interacting	Identification of various flutter regimes and discussion of dynamic stall
supersonic configurations. User's manual	N79-19354
determining unsteady aerodynamic foreces [NASA-CR-145128] N79-17798	ARRODYNATICS Pressure measurement in air data instrumentation
AERODYNAMIC HEATING	A79-25850
Blevated-temperature effects on strain gages on the YF-12A wing A79-26400	Some aspects of unsteady insect aerodynamics: Acceleration potential methods in plane unsteady airfoil theory, and measurements of
Heat generation in cavities at high velocity flights resonance-pipe effect	unsteady-periodic forces generated by the blowfly #79-18903
[BMVG-PBWT-77-28] H79-17815 Pressure and heat-transfer distributions in a	Wings N79-18921
simulated wing-elevon cove with variable leakage	Airbreathing engines - aerodynamic aspects
at a free-stream Mach number of 6.9 [NASA-TM-74095] N79-18284	N79-18925 The place of aerodynamics in the design process
ABRODYNAMIC INTERPRENCE	N79-18933
Propeller slipstream wing interactions at Mach no. 0.8 ISAB PAPER 7809971 A79-25881	Identification of various flutter regimes and discussion of dynamic stall N79-19354
[SAE PAPER 780997] A79-25881 The influence of ballonet motions on the	ABBOBLASTICITY
longitudinal stability of tethered aerostats	Behavior of elastic systems in separated flow A79-25618
[AIAA 79-0445] A79-26649 AERODYVAHIC LOADS	Divergence of forward swept composite wings
Behavior of elastic systems in separated flow A79-25618	[AIAA 79-0722] APP-28255 Aeroelastic tailoring studies in fighter aircraft
The influence of sweep on aerodynamic loading of	design
an oscillating NACAOO12 airfoil. Volume 2:	[AIAA 79-0725] A79-28257
Data report [NASA-CR-145350] N79-17802	An aeroelastic optimization procedure for composite high aspect ratio wings
A modification to linearized theory for prediction of pressure loadings on lifting surfaces at high	[AIAA 79-0726] A79-28258 Combined strength and aeroelastic wing synthesis
supersonic Mach numbers and large angles of attack	via constraint approximation
[NASA-TP-1406] N79-17806 Interactional aerodynamics of the single rotor	[AIAA 79-0724] A79-28290 Aeroelastic addition to NASTRAN
helicopter configuration. Volume 6-A:	[NASA-CR-3094] N79-17812
One-third octave band spectrograms of wake single film data, buildup to baseline	Aeroservoelastic stability analysis of an airplane with a control augmentation system
[AD-A061994] N79-18958	N79-19006
Interactional aerodynamics of the single rotor helicopter configuration. Volume 8-C:	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing
Preguency analyses of wake single film data,	moderate deformation
hubcaps and air ejectors [AD-A061995] N79-18959	[NASA-CR-159478] N79-19414 ABRONAUTICAL ENGINEBRING
Flow modelling and aerodynamic design techniques	The application of computer aided techniques to
for centrifugal compressors N79-19386	project design for aircraft A79-26592
Application of aerodynamic design techniques to process compressor design computerized design	ABROSPACE MEDICIME US Army aviation fatigue-related accidents, 1971 -
H79-19388 Industrial Centrifugal Compressors, Volume 2	1977 N79- 1 9621
[VKI-LECTURE-SERIES-95] N79-19389	ABROTHBRHODYNAHICS
ARRODINATIC MOISE A comparison of linear acoustic theory with experimental noise data for a small-scale	Plane problems of aerothermooptics refraction in two-dimensional nonuniform medium 179-26865
hovering rotor	Method for digital computer calculation of
[AIAA PAPER 79-0608] Sound radiation from hyperboloidal inlet ducts	unsteady temperature fields in turbomachine discs A79-27746
[AIAA PAPER 79-0677] A79-26885 Discrete noise spectrum generated by an	Contribution to the development of theoretical calculations for the design and optimization of
acoustically excited jet [AIAA PAPER 79-0592] A79-26887	lifting bodies. (Solution of three-dimensional basic thermo fluid dynamics equations with
Direct experimental verification of the	strong interacting attached and separated flow
theoretical model predicting rotor noise generation	fields) [BMVG-PBWT-78-4] N79-17816
[AIAA PAPER 79-0658] A79-26894	AFTERBODIES
On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAN PAPER 79-0603] A79-26907	IR scanning camera measurements of an exhaust plume from an axisymmetric nozzle afterbody model at transonic Mach numbers
An experimental study of USB flap noise reduction	A79-28097
through mean flow modification Upper Surface Blown	AGRICULTURE Environmental factors affecting the installation
[AIAA PAPER 79-0607] A79-26908	and operation of gas turbine engines in
The effect of throttling on forward radiated fan noise	agricultural aircraft [SAE PAPER 781010] A79-25892
[AIAA PAPER 79-0640] A79-26917	Advanced system design requirements for large and
The sound power spectrum of shock-free jets [AIAA PAPER 79-0595] A79-26918	small fixed-wing aerial application systems for agriculture
Coaxial jet noise in flight	(NASA-CR-158939) N79-17848
[AIAA PAPER 79-0636] A79-26919	

AIR BREATHING ENGINES SUBJECT INDEX

AIR BREATHING ENGINES	System for the display of extracted radar data on
Airbreathing engines - aerodynamic aspects N79-18925	the basis of minicomputer-controlled display devices /DERD-MC/ for an employment in Air
AIR CARGO Cargo/Logistics Airlift System Study (CLASS),	Traffic Control
volume 1	Digital target extraction at civil air traffic
[NASA-CR-158915] N79-17822 Cargo/Logistics Airlift System Study (CLASS),	control radar installations in the Pederal Republic of Germany and possibilities for its
volume 2	further development from the point of view of
[NASA-CR-158916] N79-17823 Cargo/Logistics Airlift System Study (CLASS),	the Federal Institute of ATC A79-26753
executive summary	Concept of modular software for the stepwise
[NASA-CR-158959] N79-17824 AIR COOLING	construction of radar data processing systems with minicomputers, taking into account as
Theoretical-experimental analysis of influence of	example the Airtrack System
coolant discharge from perforated turbine wanes on their aerodynamic characteristics	A79-26759 Hardware and software structure of a coordination
179-27727	system for air traffic control on the basis of
AIR DEFENSE Strike Drone - A defense suppression concept using	flight plan data A79-26760
unmanned cruise/loster/attack vehicle	FAA air traffic control automation - Programs and
[SAE PAPER 781017] A79-25894 AIR NAVIGATION	trends A79-26871
The future of surveillance systems in civil aviation	Cockpit displays and the growing role of the pilot
A79-24800 Algorithms and logic for incorporating MLS back	in the ATC system . A79-26875
azimuth information into the NASA TCV B-737	Advanced en route air traffic control automation
airplane area navigation system [NASA-TM-80039] N79-17843	A79-27129 Operational evaluation of an Air Traffic Control
AIR POLLUTION	Radar Beacon Syste∎ open array antenna
Time degradation factors for the turbine engine exhaust emissions. Volume 1: Program	A79-27139 Alrcraft accident report: Midair collision
description and results air pollution control	involving a Palcon JET, N121GW, and a Cessna
[NREC-1238-6-VOL-1] N79-17860 Time degradation factors for the turbine engine	150M, N6423K, Memphis, Tennessee [NTSB-AAR-78-14] N79-17821
exhaust emission. Volume 2: JT8D-9 test data	Collision avoidance an annotated bibliography
air pollution control [NREC-1238-7-VOL-2] N79-17863	[PAA-NA-78-8] N79-17840 RNAV route design-terminal area design procedures
Time degradation factors for turbine engine exhaust emissions. Volume 3: JT3D-7 test data	and transition area design guidelines [FAA-RD-78-61] N79-17841
air pollution control	[FAA-RD-78-61] N79-17841 Survey of radar simulation training at ATC field
[NREC-1238-8-VOL-3] N79-17864	facilities
Time degradation factors for turbine engine exhaust emissions. Volume 4: JT3D-7 test data	[FAA-NA-78-27] N79-17877 AIR TRANSPORTATION
air pollution control [NREC-1238-9-VOL-4] N79-17865	Safety of air transport A79-25542
Time degradation factors for turbine engine	Technology for future air transports
exhaust emissions. Volume 5: JT3D-3B test data air pollution control	[AIAA PAPER 79-0529] A79-25853
[NREC-1238-10-VOL-5] N79-17866	How to get the world airborne market research and aircraft design for air transportation in
Time degradation factors for turbine engine exhaust emissions. Volume 6: JT9D-3A test data	developing countries [AIAA 79-0695] A79-27360
air pollution control	Findings of the Ottawa-Montreal STOL demonstration
[NREC-1238-11-VOL-6] N79-17867 Time degradation factors for turbine engine	service [AIAA 79-0710] A79-27369
exhaust emissions. Volume 7: RB211-22B test data	Cargo/Logistics Airlift System Study (CLASS),
air pollution control [NREC-1238-12-VOL-7] N79-17868	volume 1 [NASA-CR-158915] N79-17822
Time degradation factors for turbine engine	Cargo/Logistics Airlift System Study (CLASS),
exhaust emissions. Volume 8: C700-2D test data [NREC-1238-13-VOL-8] N79-17869	volume 2 [NASA-CR-158916] N79-17823
Airport vicinity air pollution model. Abbreviated	Cargo/Logistics Airlift System Study (CLASS),
version user's guide [FAA-RD-78-111] N79-18475	executive summary [NASA-CR-158959] N79-17824
Control of air pollution from aircraft and	AIRBORNE EQUIPMENT
aircraft engines N79-19376	An airborne reference noise source for studying airplane flyover noise propagation and measurement
AIR SAMPLING	[AIAA PAPER 79-0650] A79-26928
Comparisons of turbine engine combustor exhaust emissions measurements using three gas-sampling	New airborne armament systems multimission design requirements
probe designs	[AIAĂ 79-0697] A79-27362
[AD-A061733] N79-19005 AIR TRAFFIC	Evaluation of IFR handling qualities of helicopters using the NAE airborne V/STOL
Aviation obstructions and the particular	simulator
conditions for construction projects in the vicinity of airports	[AIAA 79-0702] A79-27365 Analysis of the functional requirements for an
A79-25372	intelligent airborne computer system
The future of surveillance systems in civil aviation	[AD-A061649] H79-18962 AIRBORNE SURVEILLANCE RADAR
A79-24800	Adaptation of a digital airborne radar for use on
FAA remote terminal system frequency assignment model	the microphysics research aircraft A79-25681
A79-25323	Design considerations for the NOAA airborne
Selective calling procedure in air traffic flight stress reduction in aircraft-ground voice	meteorological radar and data system 179-25689
communication	Technology and the new look meet the F/A-18 radar
A79-25369	reliability challenge [SAR PAPER 781024] A79-25897

SUBJECT INDEX AIRCRAFT CONTROL

AIRBORME/SPACEBORME COMPUTERS SIFT - Design and analysis of a fault-tolerant computer for aircraft control Software	Engineering analysis of crash injury in army aircraft N79-19655
Implemented Pault Tolerant systems	Assessment of the benefits of aircraft crashworthiness
A79-25718 Development of the L-1011 Plight Hanagement System	N79-19657
179-26535 PAN air traffic control automation - Programs and trends	Helicopter crashworthy fuel systems and their effectiveness in preventing thermal injury N79-19660
A79-26871 AIRCRAFT ACCIDENT INVESTIGATION	A method for selecting a crashworthy fuel system design
Why doesn't aircraft accident investigation	N79-19661
prevent accidents	AIRCRAFT ANTENNAS RCS reduction of installed aircraft antennas
Briefs of accidents involving turbine powered	Radar Cross Section prediction
aircraft, US general aviation, 1977 [NTSB-AMM-78-14] N79-17830	A79-24716 Aircraft antenna pattern measurements using near
Briefs of accidents involving rotorcraft, US general aviation, 1977	field techniques A79-24721
[NTSB-AMM-78-15] N79-17831	A proposed integrated ECM system using the
Briefs of accidents involving missing and missing later recovered aircraft, US general aviation,	constant index lens antenna A79-24726
1977 [NTSB-AMM-78-18] N79-17834	Near-field analysis of helicopter rotating blades modulation interference
Briefs of accidents involving amateur/home built	A79-25131
aircraft, US general aviation, 1977 [NTSB-AMM-78-20] N79-17836	AIRCRAFT CARRIERS Briefs of accidents involving commuter air
Briefs of accidents involving aerial application	carriers and on-demand air taxi operations, US general aviation, 1977
operations, US general aviation 1977 [NTSB-AHM-78-21] N79-17837	[NTSB-AMM-78-22] N79-17838
Briefs of accidents involving commuter air carriers and on-demand air taxi operations, US	Statistical review of counting accelerometer data for Navy and Marine fleet aircraft
general aviation, 1977	[AD-A061894] N79-18972
[NTSB-AMM-78-22] N79-17838 Arrcraft accident report: Allegheny Airlines,	Selective calling procedure in air traffic
Inc. BAC 1-11, N1550, Rochester, New York, July 9, 1978	flight stress reduction in aircraft-ground voice communication
[NTSB-AAR-79-2] N79-18961	A79-25369
AIRCRAFT ACCIDENTS Allocaft fire protection and rescue procedures	An optical communication system for aircraft A79-28034
/2nd edition/ Book A79-25750	Military fiber optics applications A79-28040
Aircraft accident report: Midair collision	Some aspects of helicopter communications N79-19647
involving a Palcon JET, N121GW, and a Cessna 150M, N6423K, Memphis, Tennessee	AIRCRAFT COMPARTMENTS
[NTSB-AAR-78-14] N79-17821 Alrcraft accident report: Continental Air lines,	A finite element subvolume technique for structural-borne interior noise prediction
Incorporated, McDonnell-Douglas DC-10-10, N68045, Los Angeles, California, March 1, 1978	in aircraft [AIAA PAPER 79-0585] A79-26882
[NTSB-AAR-79-1] N79-17826	Master Plan for prediction of vehicle interior noise
Listing of accidents/incidents by make and model, US civil aviation, 1977	[AIAA PAPER 79-0582] A79-26943 Simultaneous measurements of ozone outside and
[NTSB-AMM-78-12] N79-17828 Briefs of accidents involving midair collisions,	inside cabins of two B-747 airliners and a Gates Learjet business jet
US general aviation, 1977	179-27571
[NTSB-AMM-78-13] N79-17829 Briefs of accidents involving turbine powered	Pool fire radiation through a door in a simulated aircraft fuselage
aircraft, US general aviation, 1977 [NTSB-AMM-78-14] N79-17830	[FAA-NA-78-38] N79-17966 AIRCRAFT COMPIGURATIONS
Briefs of fatal accidents involving weather as a	Some effects of applying sonic boom minimization
cause/factor, US general aviation, 1977 [NTSB-AMM-78-16] N79-17832	to supersonic cruise aircraft design [AIAA PAPER 79-0652] A79-26927
Briefs of accidents involving alcohol as a cause/factor, US general aviation, 1977	Comparison of the aerodynamic properties of an aeroplane with the tall-first configuration and
[NTSB-ARE-78-17] N79-17833	with the conventional configuration
Briefs of accidents, involving corporate/executive aircraft, US general aviation, 1977	[BLL-RTS-11520] R79-17794 AIRCRAFT CONSTRUCTION HATERIALS
[NTSB-NMM-78-19] N79-17835 Briefs of accidents involving aerial application	Design against fatique - Current trends for aircraft structural reliability
operations, US general aviation 1977	[AIAA 79-0689] A79-27355
[NTSB-AMM-78-21] N79-17837 Overview of the carbon fiber problem	Environmental models for moisture absorption by aircraft composites
N79-18076 Probabilistic analysis of air carrier accidents	A79-27572 Structural aluminum materials for the 1980's
N79-18078	[AIAA 79-0755] A79-28270
Carbon fiber release conditions #79-18079	Fabrication and evaluation of advanced titanium structural panels for supersonic cruise aircraft
Estimation of economic losses	[NASA-CR-2744] N79-18320 AIRCRAFT COSTROL
Synthesis of national risk profile	The impact of the total lightning environment on aircraft flight control systems
US Army aviation fatigue-related accidents, 1971 -	A79-25319
1977 N79-19621	SIFT - Design and analysis of a fault-tolerant computer for aircraft control Software
Occupant injury mechanisms in civil helicopter accidents	Implemented Fault Tolerant systems A79-25718
N79-19653 Comparative injury patterns in US Army helicopters	, 30
R79-19654	

Control system time response optimization nonlinear programming approach for	
flight	
[AIAA PAPER 79-0540] Redundant control systems for flight webs	179-25859 Lcles
Russian book	
F-16 high angle of attack testing	A79-25875
Flight testing the Kfir	A79-26527
•	A79-26530
Development of the L-1011 Flight Management	ent System A79-26535
Recent developments in active control tec	
for fighter aircraft design [AIAA 79-0708]	A79-27368
IRCRAFT DESIGN	****
Fundamentals of design. I - 'Whys' and	
'wherefores' of wings	A79-25485
Technology for future air transports	R/J 25405
[AIAA PAPER 79-0529] General aviation aircraft in the 1990's	A79-25853
[AIAA PAPER 79-0560]	A79-25866
Damage-tolerance practices applied to tra	insport
aircraft structures [SAE PAPER 781021]	A79-25896
Trade-off studies with an interactive	1175 25050
engine/airframe life-cycle-cost model	- 70 05005
[SAE PAPER 781033] V/STOL aircraft engine and mechanical dri	1 79-25905
component integration	
[SAE PAPER 781038]	A79-25906
Use of radio controlled models in the con development of V/STOL aircraft	ceptual
development of V/STOL aircraft [SAE PAPER 781050]	A79-25915
F-16 high angle of attack testing	A79-26527
F-18 status report	A79-26529
The continuity factor in aircraft develop	ment
The application of computer aided techniq	A79-26536
project design for aircraft	
Theoretical lower limits of forebody drag	A79-26592
incolected lower limits of folebody dray	A79-26593
Design specifications for the capped ball	
special reference to their survival in equatorial tropopause	the
[AIAA 79-0426]	A79-26635
Development of modern airfoil sections fo	r high
subsonic cruise speeds [AIAA 79-0687]	A79-27353
Design against fatigue - Current trends -	
aircraft structural reliability	
[AIAA 79-0689] New technology in commercial aircraft des	179-27355
minimum operating cost	192 102
[AIAA 79-0690]	A79-27356
Transonic wing design for transport aircr [AIAA 79-0692]	A79-27357
Compromise between economic concerns and	
application of new technologies in the definition of a new airplane project	
[AIAA 79-0693]	A79-27358
Advanced supersonic technology and its	
<pre>implications for the future faina 79-0694]</pre>	A79-27359
How to get the world airborne market	research
and aircraft design for air transportat developing countries	ion in
[AIAA 79-0695]	A79-27360
Supersonic combat aircraft design	
[AIAA 79-0699] Future advanced technology rotorcraft	A79-27363
[AIAA 79-0705]	A79-27366
Some new approaches for wind-tunnel testa	ng
through the use of computers [AIAA 79-0707]	A79-27367
Recent developments in active control tec	
for fighter aircraft design [AIAA 79-0708]	A79-27368
Enhanced capabilities of future fighters	
result of HiMAT [AIAA 79-0698]	A79-27370
Lurum 12-0030 l	A13 41310

SDM lecture - Introduction of new SDM technology	
into production systems Structures, Dynamics and Materials technology in aircraft design	
[AIAA 79-0719] A79-28252	
Aeroelastic tailoring studies in fighter aircraft	
design [AIAA 79-0725] A79-28257	
Inverse transonic airfoil design methods including	
boundary layer and viscous interaction effects	
[NASA-CR-158136] N79-17805 Listing of accidents/incidents by make and model,	
US civil aviation, 1977	
[NTSB-AMM-78-12] N79-17828	
Advanced system design requirements for large and small fixed-wing aerial application systems for	
agriculture	
[NASA-CR-158939] N79-17848	
Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without	
laminar flow control	
[NASA-CR-159006] N79-17852	
XF4D Skyray development: Now it can be told N79-18897	
An analysis of fuel conserving operational	
procedures and design modifications for	
bomber/transport aircraft. Volume 1: Executive summary	
[AD-A061746] N79-18969	
AIRCRAPT DETECTION	
Apparatus for measuring an aircraft's speed and height	
[NASA-CASE-LAR-12275-1] N79-18296	
AIRCRAFT BEGINES	
Engine technology for production turbofan engines A79-24827	
Causes for the deterioration of splined	
connections in aircraft engines during service A79-25249	
Recording methods for steady state and transient	
signals aircraft engine tests	
NASA research on general aviation power plants	
[AIAA PAPER 79-0561] A79-25870	
Planning the development and qualification process	
for the next generation of high technology aircraft engines	
[SAE PAPER 780992] A79-25878	
Requirements and constraints in the development	
and qualification of gas turbine engines for the Navy	
[SAE PAPER 780994] A79-25879	
Life Cycle Cost in advanced technology engine	
development [SAB PAPER 781029] A79-25901	
Applying design-to-life cycle cost methods during	
engine advanced development [SAE PAPER 781030] A79-25902	
Trade-off studies with an interactive	
engine/airframe life-cycle-cost model	
[SAE PAPER 781033] A79-25905 V/STOL alreraft engine and mechanical drive	
component integration	
[SAE PAPER 781038] A79-25906	
An unstable subsynchronous critical speed solution of shaft failures in F-16 engine start system	
[SAE PAPER 781055] A79-25916	
Small fan-jet engines for business aircraft	
179-26531 The U-2 story	
179-26537	
Thermal cycling endurance problems in gas-turbine parts	
A79-26838	
A79-26838 Comparison of BTJES and TJE characteristics in	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet	
A79-26838 Comparison of BTJES and TJE characteristics in	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element A79-27742	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element A79-27742 Intensification of fuel vaporization in aircraft	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element A79-27742	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element A79-27742 Intensification of fuel vaporization in aircraft gas turbine engines by electrical forces A79-27748 A decision theory model for health monitoring of	
A79-26838 Comparison of BTJES and TJE characteristics in supersonic cruising flight Bypass Turbojet Engine A79-27740 Convective heat exchange of gas-particle stream in flow passage of throttling device with vane-type turning element A79-27742 Intensification of fuel vaporization in aircraft gas turbine engines by electrical forces A79-27748	

A79-28381

SUBJECT INDEX AIRCRAFT NOISE

S	eparation and investigation of wear partic	cles	New agents for the extinguishment of m	
	from aero-engines [BLL-RISLEY-TR-3308-(9091.9F)]	N79-17856	[AD-A061664] AIRCRAFT HYDRAULIC SYSTEMS	N79-19122
T:	ime degradation factors for the turbine e		Direct drive control valve for fly-by-	wire flight
	exhaust emissions. Volume 1: Program description and results air pollution	n sontrol	control system actuators	N79-19007
	[NREC-1238-6-VOL-1]	N79-17860	[AD-A062030] AIRCRAFT INSTRUMENTS	N13-13001
E	ngine dynamics		Overestimates of entrainment from wett	
φ.	[BMVG-PBWT-78-6] ime degradation factors for the turbine e	N79-17862	aircraft temperature sensors in clou	ad A79-25296
	exhaust emission. Volume 2: JT8D-9 test		Flight deck alarm systems	A75 25250
	air pollution control	N 70 - 1706 2	learner sections posses to entire TV	A79-25541
T	[NREC-1238-7-VOL-2] ime degradation factors for turbine engin	N 79-17863 e	Avionics systems needed to optimize V/	179-26874
	exhaust emissions. Volume 3: JT3D-7 tes		TASAR, a thinned adaptive synthetic ap	
	air pollution control [NREC-1238-8-VOL-3]	N79-17864	New airborne display concepts	A79-27135
T:	ime degradation factors for turbine engine	е		A79-27672
	exhaust emissions. Volume 4: JT3D-7 tement of the pollution control	st data	Study of the structure of an integrate flight control, navigation and displ	
	[NREC-1238-9-VOL-4]	N79-17865	ringhe control, havingation and dispi	A79-27674
T	ime degradation factors for turbine engine		Tests of an integrated piloting, navig	ation, and
	exhaust emissions. Volume 5: JT3D-3B to air pollution control	est data	display system	179-27675
_	[NREC-1238-10-VOL-5]	N79-17866	LED instrument approach instruction di	splay
T:	Lime degradation factors for turbine engine exhaust emissions. Volume 6: JT9D-3A te		[NASA-TM-78823] Evaluation of the Ryan Stormscope as a	N79-17854 Severe
	air pollution control		weather avoidance system for aircraf	t
m :	[NREC-1238-11-VOL-6] ime degradation factors for turbine engine	N79-17867	GASP-PL/I simulation of integrated avi	N79-18229
1.	exhaust emissions. Volume 7: RB211-22B		processor architectures	onic system
	air pollution control	W70 470C0	[NASA-CR-158244]	N79-18973
T:	[NREC-1238-12-VOL-7] ime degradation factors for turbine engine	N79-17868	AIRCRAFT LANDING Foam Impact Attenuation System for	RPV recovery
	exhaust emissions. Volume 8: C700-2D to	est data	[AIAA 79-0416]	A79-26627
c	[NREC-1238-13-VOL-8] ontrol of air pollution from aircraft and	N79-17869	A spectral analysis of thunderstorm tu jet transport landing performance	rruntence and
-	aircraft engines			A79-27576
ATRC	RAFT EQUIPMENT	N79-19376	The need of stick force stability for attitude-stabilized aircraft, Part 2	1
	alidation of IEMCAP using the B-52		[NLR-TR-77027-H]	ท79-17875
	Intrasystem Electro Magnetic Compatibilit	t y	AIRCRAFT MAINTENANCE	
	Analysis Program	A79-25326	Statistics of disturbances and mainten according to conditions at Interflug	
A :	ir Force applications of lightweight		Technical requirements concerning th	
	superconducting machinery in airborne sources	e bower	for the processing of disturbance da of electronic data processing	ta by means
m t	to general and maggin gotallite (ClDC1M) or	A79-27666	li- flock and foculity planning may an	A79-25371
T	he search and rescue satellite (SARSAT) sy project	ystem	Air fleet and facility planning via op control models	timai
_		N79-18115		A79-26725
P	rotection/hardening of aircraft electronic systems against the indirect effects of 1		AIRCRAFT MANEUVERS A simulator study of aircraft ground-r	un handling
		N79~18238	in the Posim Research Simulator - So	me results
	RAFT FUELS ffects of fuel properties on soot formation	on in	and experiences	A79-26498
	turbine combustion		Principles of helicopter performance	
S	[SAE PAPER 781026] bale oil - The answer to the jet fuel	A79-25899	[AD-A061671] AIRCRAFT MODELS	N79-18970
	availabılıty question		Use of radio controlled models in the	conceptual
	[SAE PAPER 781027] aser aircraft using kerosene	A79-25900	development of V/STOL aircraft [SAE PAPER 781050]	A79-25915
	ibel directate dainy kelosene	A79-26597	AIRCRAFT BOISE	E 7 2 2 3 7 1 3
Cı	ryohydrogen-fuel for tomorrow's commercial	l aircraft A79-27656	A comparison of linear acoustic theory experimental noise data for a small-	
St	tudy of hydrogen recovery systems for gas		hovering rotor	Scale
	while refueling liquid-hydrogen fueled as	ircraft	[AIAA PAPER 79-0608]	A79-26876
ATRC	[NASA-CR-158991] RAFT GUIDANCE	N79-18057	<pre>Wave propagation in ducts using the fi nethod for aircraft noise reduct</pre>	
	ardware options for gliding airdrop guida	nce	[AIAA PAPER 79-0659]	A79-26879
	systems [AIAA 79-0471]	A79-26671	Interior noise path identification in aircraft using multivariate spectral	
F	AA air traffic control automation - Progra		[AIAA PAPER 79-0644]	A79-26915
	trends	A79-26871	Airframe noise measurements on a small of a supersonic transport concept in	
AIRC	RAFT HAZARDS	A77-20071	flow facility	an anechoic
R	ecent advances in indirect lightning effect research	cts	[AIAA PAPER 79-0666] An airborne reference noise source for	A79-26920
	lesedici	A79-25313	airplane flyover noise propagation a	
El	P coupling to a composite aircraft		[AIAA PAPER 79-0650]	A79-26928
Pi	roperties of induced transients associated	A79-25321 d with	Characteristics of propeller noise on fuselage related to interior noise t	
	Em fields produced by lightning or other		[AIAA PAPER 79-0646]	A79-26932
	relatively slow rise-time PMP in airc	craft 179-25322	An acoustical study of the XV-15 Tilt Research Aircraft	Rotor
E	lectric charging of helicopters aircra	aft	[AIAA PAPER 79-0612]	A79-26939
	hazards and static dischargers for accide prevention	ent	Radiation of an acoustic source near t	he trailing
	[BEVG-PBWT-78-7]	N79-18274	edge of a wing in forward motion [AIAA PAPER 79-0605]	A79-26940

AIRCRAFT PARTS SUBJECT INDEX

Variability of annoyance response due to aircraft noise	Helicopter crashworthy fuel systems and their effectiveness in preventing thermal injury N79-19660
[NASA-TP-1335] N79-18687 Computer-aided collection of demographic data within day-night level contours: Two test cases	A method for selecting a crashworthy fuel system design
[AD-A061657] N79-19010 A commercial airport noise environment:	N79-19661 Crash survivability of the UH-60A helicopter
Measurement, prediction and control [NASA-CR-3107] N79-19814	N79-19663 The approach to crew protection in the crash
AIRCRAFT PARTS Introduction of electron beam welding in aircraft	environment for the YAH-64 N79-19664
production A79-25248	Control of the location of the center of gravity
Perspectives of technological development for helicopters [AIAA 79-0701] A79-27364	of loaded aircraft A79-25370 Dynamics of controlled longitudinal motion of an
AIRCRAFT PERFORMANCE Aircraft static charging testing	airplane with a variable-geometry wing A79-25517
[ONERA, TP NO. 1978-110] A79-26130 The Learjet Longhorn series - The first jets with winglets	The need of stick force stability for attitude-stabilized aircraft, Part 2 [NIR-TR-77027-8] N79-17875
Enhanced capabilities of future fighters as a	AIRCRAFT STRUCTURES EMP coupling to a composite aircraft
result of HiMAT	179-25321
[AIAA 79-0698] XV-15 Tilt Rotor Research Aircraft - Program report [AIAA 79-0704] A79-27371	The prediction of fatigue crack growth under flight-by-flight loading A79-25482
A spectral analysis of thunderstorm turbulence and jet transport landing performance	Analysis of longitudinal natural vibrations of deformable aircraft by the finite-element method
A79-27576	A79-25505
AIRCRAFT PILOTS Airline approach to CAT III	<pre>Damage-tolerance practices applied to transport aircraft structures</pre>
A79-26533 US Army aviation fatigue-related accidents, 1971 -	[SAE PAPER 781021] A79-25896 Aircraft static charging testing
1977 N79-19621	[ONERA, TP NO. 1978-110] A79-26130 Crashworthiness tests on model aircraft fuselage
Comparative injury patterns in US Army helicopters N79-19654 The approach to crew protection in the crash	structures [AIAA 79-0688] A79-27354 Statistical estimation of economic life for
environment for the YAH-64 N79-19664	aircraft structures [AIAA 79-0761] A79-28275
AIRCRAFT PRODUCTION Introduction of electron beam welding in aircraft	Factors affecting residual strength prediction of a cracked aircraft structure
production	A79-28380
A79-25248 GASP IV simulation model for the composites and bonding production facility	An assessment of the risks presented by the use of carbon fiber composites in commercial aviation. Volume 1: Final report. Volume 2: Supporting
The continuity factor in aircraft development	appendices [NASA-CR-158989] N79-18074
AIRCRAFT BELIABILITY Recognition of damage-tolerance in civil	An assessment of the risks presented by the use of carbon fiber composites in commercial aviation: Executive summary
alrworthiness standards [SAE PAPER 781019] A79-25895	N79-18075 Induced effects of lightning on an all composite
The analysis and identification of flux-induced voltage transients on low-loss transmission	aircraft N79-18242
lines with application to the	AIRCRAFT SURVIVABILITY
Lightning-Transient-Analysis /LTA/ problem A79-26246	Recognition of damage-tolerance in civil airworthiness standards
Crashworthiness tests on model aircraft fuselage structures [AIAA 79-0688] A79-27354	[SAE PAPER 781019] Design specifications for the capped balloons with special reference to their survival in the
AIRCRAFT SAPERY Lightning protection with segmented diverters	equatorial tropopause [AIAA 79-0426] A79-26635
for aircraft radomes and dielectric structures A79-25317	Wind-tunnel studies of the effects of simulated damage on the aerodynamic characteristics of
Safety of air transport A79-25542	airplanes and missiles
Recognition of damage-tolerance in civil airworthiness standards	Total environment survivability methodology N79-18971
[SAE PAPER 781019] A79-25895 Stable boundary layer wind shear model for	Crash survivability of the UH-60A helicopter N79-19663
aircraft flight hazard definition	AIRCRAFT WAKES
A79-27575 A new standard for lightning qualification testing of aircraft: Technical overview, definitions	An experimental study of the influence of flight-stream turbulence on jet mixing noise [AIAA PAPER 79-0617] A79-26935
and basic waveforms N79-18246	An improved system for use in conducting wake investigation for a wing in flight
Rotor fragment protection program: Statistics on	differential pressure measurements for drag
aircraft gas turbine engine rotor failures that occurred in US commercial aviation during 1976	investigations [NASA-CASE-PRC-11024-1] N79-17797
[NASA-CR-159474] N79-18977	Evaluation of a wake vortex upset model based on
Development of fire test methods for airplane interior materials	simultaneous measurements of wake velocities and probe-aircraft accelerations
[NASA-CR-160119] N79-19112 Crashworthy helicopter seats and occupant	[NASA-TM-78561] N79-18960 AIRDROPS
restraint systems N79-19658	Hardware options for gliding airdrop guidance systems
n/3-13030	[AIAA 79-0471] A79-26671

SUBJECT INDEX ARTERNA DESIGN

	•		
AIRPIELD SURFACE MOVEMENTS		AIRPORT PLANNING	
A simulator study of aircraft ground-run l	handling	Aviation obstructions and the particular	
in the Posis Research Simulator - Some :		conditions for construction projects in	the
and experiences		vicinity of airports	
•	A79-26498	* ·- * ·	A79-25372
Airfield marking paints state-of-the-art		Siting Criteria for MLS stations. II	
[PAA-BD-78-104]	N79-17876	•	A79-28184
AIRPOIL PROPILES		An offshore airport that works - Nagasaki	
Development of modern airfoil sections for	hiqh .	·	A79-28185
subsonic cruise speeds	-	AIRPORTS	
[AIAA 79-0687]	A79-27353	The Dulles International Airport wind-shear	r
Approximation concepts for numerical airfo		detection system Statistical results	
optimization			A79-27574
[NA SA-TP-1370]	ท79-18915	Airport Vicinity air pollution model. Abb	reviated
Some recent progress in transonic flow con	putation	version user's guide	
flow distribution, numerical optimiz		[PAA-RD-78-111]	N79-18475
and airfoil design	-	Computer-aided collection of demographic d	ata
·	N79-18946	within day-night level contours: Two te	st cases
AIRFOILS		[AD-A061657]	N79-19010
Numerical study of unsteady flows of visco	ous	A commercial airport noise environment:	
incompressible fluids about airfoils by		Measurement, prediction and control	
combined method of order 0/h2/ and 0/h4/	/	[NASA-CR-3107]	N79-19814
	A79-24829	AIRSHIPS	
A visual investigation of the separation a	and	The influence of ballonet motions on the	
subsequent transition near the leading of	edge of	longitudinal stability of tethered aeros	tats
airfoils		[AIAA 79-0445]	A79-26649
[AIAA PAPER 79-0552]	A79-25863	AIRSPACE	
Unsteady pressures on a NACA 64A010 airfor	11 -	RNAV route design-terminal area design pro-	cedures
Experimental and theoretical results		and transition area design guidelines	
[AIAA PAPER 79-0330]	A79-26545	[FAA-RD-78-61]	N79-17841
On sound radiation from the trailing edge	of an	AIRSPEED	
isolated airfoil in a uniform flow		Aircraft velocity and altitude measurement:	s using
[AIAA PAPER 79-0603]	A79-26907	a tunable diode laser	
The influence of sweep on aerodynamic load	ling of		A79-28139
an oscillating NACA0012 airfoil. Volume	e 2:	Apparatus for measuring an aircraft's spee	d and
Data report		height	
[NASA-CR-145350]	N 79-17802	[NA SA-CASE-LAR-12275-1]	N79-18296
Inverse transonic airfoil design methods i		ALGORITHMS	
boundary layer and viscous interaction e	effects	A shock capturing application of the finite	
[NASA-CR-158136]	N79-17805	element method to viscous compressib	le flow
Alternative turbine cooling technology		problem	
	N79-18984		A79-24771
AIRPRAME MATERIALS		ALL-WEATHER AIR WAVIGATION	
Design and fabrication of advanced titanic	1 18	Helicopter operations development plan	
structures		[PAA-RD-78-101]	ห79-18799
[AIAA 79-0757]	A79-28272	ALL-WEATHER LANDING SYSTEMS	
AIRPRAMES		Helicopter operations development plan	
Trade-off studies with an interactive		[PAA-RD-78-101]	N79-18799
engine/airframe life-cycle-cost model		ALTIMETERS	
[SAE PAPER 781033]	A79-25905	Aircraft velocity and altitude measurement:	s using
Airframe noise measurements on a small-sca		a tunable diode laser	- 70 00430
of a supersonic transport concept in an	anechoic		A79-28139
flow facility	.70 00000	ALUMINUM ALLOYS	• _
[AIAA PAPER 79-0666]	A79-26920	Structural aluminum materials for the 1980	
Environmental effects on crack growth in	107E mc	[AIAA 79-0755]	A79-28270
flight-simulation tests on 2024-T3 and 7	7075-16	AMBULANCES	
material	H70-10012	Casualty evacuation by helicopter	¥70-10616
[NLR-TR-76104-U]	N79-18012	LUMOTOTO CULENTINO	N79-19615
Airframe noise component interaction studi		AMECHOIC CHAMBERS	
[NASA-CR-3110] AIRLINE OPERATIONS	N79-19815	An acoustic problem in anechoic chambers as	LISING
		from exhaust noise testing	A79-26929
Objectives related to an enhancement of the effectivity of MALEV. I civil aircra		[AIAA PAPER 79-0649] ANGLE OF ATTACK	H / 3-20323
utilization in Hungary	11.0	P-16 high angle of attack testing	
dellization in hungary	170-25260	r-10 migh angle of actack testing	A79-26527
Statistics of disturbances and maintenance	A79-25368	Aerodynamic side-force alleviator means	R 7 3 - 20 32 7
according to conditions at Interflug. II		[NASA-CASE-LAR-12326-1]	N79-17813
Technical requirements concerning the pr		F-16 high angle of attack testing	M79-17013
for the processing of disturbance data h	TO BEARS	1-10 high angle of actack testing	N79-18886
of electronic data processing	o, medus	Vortex pattern development on the upper su	
or ercotronic data processing	A79-25371	a swept wing at high angle of attack	LIUCE OI
Airline approach to CAT III	1,3 233.1	[NASA-TH-75377]	N79-18914
to out iii	A79-26533	Design, calibration, and application of a	
Why doesn't aircraft accident investigation		for measuring time dependent angle of at	
prevent accidents		helicopter blades	ouon or
P201001 000100	A79-27319	HOLLOOPICE BIEGES	พ79-18968
Corporate aviation in the 1980's	11.5 21515	ABTEBNA ARRAYS	u / 5 / 10300
		TASAR, a thinned adaptive synthetic apertur	re radar
AIRPLANE PRODUCTION COSTS	N79-18892	and and on oliver aberra	A79-27135
	N79-18892		
		Operational evaluation of an Air Traffic Co	
Life Cycle Cost in advanced technology eng		Operational evaluation of an Air Traffic Co Radar Beacon System open array antenna	
Life Cycle Cost in advanced technology end development	jine	Operational evaluation of an Air Traffic Co Radar Beacon System open array antenna	ontrol
Life Cycle Cost in advanced technology end development [SAE PAPER 781029]	gine A79-25901		
Life Cycle Cost in advanced technology end development [SAE PAPER 781029] Life cycle cost in preliminary engine desi	gine A79-25901	Radar Beacon System open array antenna	a79-27139
Life Cycle Cost in advanced technology end development [SAE PAPER 781029] Life cycle cost in preliminary engine desi for F-15	gine A79-25901 ign	Radar Beacon System open array antenna ANTENNA DESIGN RCS reduction of installed aircraft antenna	a79-27139
Life Cycle Cost in advanced technology end development [SAE PAPER 781029] Life cycle cost in preliminary engine desi for P-15 [SAE PAPER 781032]	gine A79-25901	Radar Beacon System open array antenna	a79-27139
Life Cycle Cost in advanced technology end development [SAE PAPER 781029] Life cycle cost in preliminary engine desi for F-15	gine A79-25901 ign	Radar Beacon System open array antenna ANTENNA DESIGN RCS reduction of installed aircraft antenna	ontrol
Life Cycle Cost in advanced technology end development [SAE PAPER 781029] Life cycle cost in preliminary engine desi for P-15 [SAE PAPER 781032] Trade-off studies with an interactive	gine A79-25901 ign	Radar Beacon System open array antenna ANTENNA DESIGN RCS reduction of installed aircraft antenna Radar Cross Section prediction	ontrol

SUBJECT INDEX

ANTERNA RADIATION PATTERNS Hodeling the X-band radar augmentation sys	stem of a	Advanced en route air traffic control auto	mation A79-27129
high altitude supersonic target		AUTOHATION	
An IFF antenna with superior sidelobe and suppression characteristics	A79-24715 backlobe	PAA air traffic control automation - Progr trends	ams and A79-26871
• •	A79-24718	Advanced en route air traffic control auto	
Aircraft antenna pattern measurements usin field techniques	ig near	AUTOHOBILE ENGINES	A79-27129
<u>-</u>	A79-24721	Cold-air performance of free power turbine	
APPROACH CONTROL Two-segment approach investigation on a		designed for 112-kilowatt automotive gas engine. 2: Effects of variable	-turbine
moving-base piloted flight simulator		stator-vane-chord setting angle on turbi	пе
[VTH-LR-250] ARCHITECTURE (COMPUTERS)	N79-17880	performance [NASA-TM-78993]	₩79-17859
GASP-PL/I simulation of integrated avionic	: system	AUTOROTATION	N/3-1/033
processor architectures	#70 40073	Bailout from autorotating helicopters	-70 40444
[NASA-CR-158244] ARMED FORCES (UNITED STATES)	N79-18973	AVIONICS	N79-19666
US Army aviation fatigue-related accidents	s, 1971 -	Reliability growth planning to achieve RIW	/GMTBF
1977	N79-19621	requirements for an airborne radar	A79-24965
ARROW WINGS	175 15021	Advances in avionics emphasizing	R.7 24303
Theoretical and experimental investigation		microprocessor technology and integrated	
ground induced effects for a low-aspect- highly swept arrow-wing configuration		[AIAA PAPER 79-0562] Avionics systems needed to optimize V/STOL	A79-25862 potential
Langley V/STOL tunnel			A79-26874
[NASA-TM-80041] ARTIFICIAL INTELLIGENCE	N79-17871	Puture avionics - Keeping capability up, c	osts down A79-27093
Analysis of the functional requirements for	or an	The coming of age of digital electronics i	
intelligent airborne computer system	¥70_10060	commercial transports emphasizing si processing technology and Boeing 767 avi	
[AD-A061649] ASSURANCE	N79-18962	[AIAA 79-0686]	A79-27352
Fabrication and quality assurance procedur	e to	Future advanced technology rotorcraft	
assure a symmetrical lifting parachute [AIAA 79-0427]	A79-26636	[AIAA 79-0705] Multimode radar processor for combat a	A79-27366
ATHLETES	20030	Hardrade Fadar Processor 201 001340 F	A79-28058
Factors and tradeoffs affecting ram-air pa designed for civilian personnel applicat		Integrated Thermal Avionics Design (ITAD)	N79-17855
[AIAA 79-0457]	A79-26660	[AD-A061227] Cockpit management	879-17655
ATROSPHERIC COMPOSITION		•	N79-18890
Simultaneous measurements of ozone outside inside cabins of two B-747 airliners and		GASP-PL/I simulation of integrated avionic processor architectures	system
Learjet business jet		[NASA-CR-158244]	N79-18973
ATMOSPHERIC MOISTURE	A79-27571	Software requirements for the A-7E aircraf [AD-A061751]	t N79-18974
Environmental models for moisture absorpti	on by	AXIAL PLOW TURBINES	1175 10374
aircraft composites		TDS - A preliminary design system for turb	
ATEOSPHERIC OPTICS	A79-27572	[SAE PAPER 780999] Cold-air performance of free power turbine	A79-25882
Plane problems of aerothermooptics ref	raction	designed for 112-kilowatt automotive gas	
in two-dimensional nonuniform medium	A79-26865	engine. 2: Effects of variable stator-vane-chord setting angle on turbi	ne
ATROSPHERIC TURBULENCE		performance	
Gust load estimation using a simplified po spectral technique	Mei	[NASA-TM-78993] Time marching finite area method	N79-17859
[ARAP-362]	N79-17870	Time marching linite area method	N79-18990
ATTACK AIRCRAFT		В	
New airborne armament systems multimis design requirements	SION		
[AIAA 79-0697]	A79-27362	B-52 AIRCRAFT	
Internal cockpit reflections of external p light sources for the model YAH-64 advan		Reliability growth on B-52 FLIR system	A79-24958
attack helicopter		Validation of IEMCAP using the B-52	
The approach to crew protection in the cra	N79-19643	Intrasystem Electro Magnetic Compatibili	ty
environment for the YAH-64	.SII	Analysis Program	A79-25326
	N79-19664	BAC 111 AIRCRAFT	
ATTITUDE STABILITY The need of stick force stability for		Aircraft accident report: Allegheny Airli Inc. BAC 1-11, N1550, Rochester, New Yo	
attıtude-stabılızed aircraft, Part 2		9, 1978	
[NLR-TR-77027-H] AUTOMATIC CONTROL	N79-17875	[NTSB-AAR-79-2] BACKGROUND MOISE	N79-18961
Development and initial test results of pa	rachutes	A survey of communications in the high non-	se
with automatic inflation modulation /AIM [AIAA 79-0467]		environment of Army aircraft	N79-19646
AUTOBATIC FLIGHT CONTROL	A/9-200/3	Some aspects of helicopter communications	N79-19646
The impact of the total lightning environm	ent on		N79-19647
aircraft flight control systems	A79-25319	BAILOUT Bailout from autorotating helicopters	
Redundant control systems for flight wehic		-	N79-19666
Russian book	A79-25875	BALAUCING Ontinizing gasturbine engine flexible roto:	r
Strike Drone - A defense suppression conce		Optimizing gasturbine engine flexible roto: balancing by the LP-search method	•
unmanned cruise/loiter/attack vehicle	-		A79-27745
[SAE PAPER 781017] Development of the L-1011 Flight Managemen	179-25894 at System	BALLOON PLIGHT Development and testing of a shipboard lau	nched
•	A79~26535	balloon system	
		[AIAA 79-0420]	A79-26631

SUBJECT INDEX CARGO AIRCRAPT

Accolymanic Decelerator and Ballono Technology Technical Papers Technical Technical Technical Papers Technical Technical Technical Papers Technical Technical Technical Papers Technical Tec	BALLOOMS		BYPASSES	
Design specifications for the capped balloons with especial efficiency to their survival in the especial efficiency of the survival in the especial espe	Conference, 6th, Houston, Tex., March 5-			A79-27737
centerial tropopase fill?-90-026] Analysis of base-flow problems during powered supersonic Light FRANTES Design and development of an belicopter rotor bub GRIAN 79-0315] BETHANTES Design and development of an belicopter rotor bub GRIAN 79-0315] Development of community procession in the forest property of the second wind to the second wind to the second wind to the second wind to the second wind tunnel test of Substantial Configured whiches against processing to the second wind tunnel test of Substantial English Substantial Subs	Design specifications for the capped ballo	oons with	supersonic cruising flight Bypass Tu	rbojet
A 179-2771a BATTATO of hame-flow problems during powered and evalescencic barrials Derelopment of an helicopter rotor has and evalescencic barrials BILL HIGHT Derelopment of causalty evacuation kit for the light observation helicopter (fiva) BYFFHAGE BILE ATTER OF accidents involving alcohol as a BYFFHAGE BILE ATTER OF accidents involving alcohol as a FIRE COMPAPIES CITAL-NA-78-0] BOUT-HIS CONTINUENTONS CITAL-NA-78-0] BOUTH ATTER CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENT CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENT CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENT CONTINUENTONS CITAL-NA-78-0] FOR CONTINUENT CONTINUENTONS CONTINUENT CONTINUENTONS CITAL-NA-78-00		the	Influence of bypass ratio change on fan	179-27740
### PRAIRIES Design and development of an helicopter rotor had add slandoweric bearing ### Property ### Prope	[AIAA 79-0426]	179-26635		170-27700
Design and development of an belicopter (rote hab and elastoseric bearing (IAIA 79-015) 179-20289 (IAIA 79-015) 189-20289 (IAI		ered	•	A19-21144
Deady and development of an helicopter rotor hab Deady and development of an helicopter rotor hab CRIAIA 79-0815] (ATAN 79-0815] (BLI LICELY) Development of cancelly exacuation hit for the Light observation helicopter (fixe) BYPELENS CREATER Color of Cancelly exacuation hit for the Light observation helicopter (fixe) BYPELENS CREATER Color of Cancelly exacuation hit for the Light observation helicopter (fixe) BYPELENS CREATER Color of Separation spaces a visition, 1979 BYPELENS CREATER Color of Separation spaces CREATER AND AND AND ASSESSMENT OF THE SECONDARY COLOR OF THE SECONDARY	supersonic flight	N79-19926		
and elastoseric bearing (ILLA 70-9815) Development of cascalty evacuation has been provided and incords. The provided provided by the provided pro				
PRILITIONAL TO PROPERTY OF CASUALTY STATEMENTS BYFERRES First of Accidents importing alcaloi as From 1975 Forgress in transonic flow computations analysis of the Posts in transonic flow computations analysis of the Rock in th		otor hub		
Development of casualty executation kit for the lipid to beservation belicoptor (Kaya) N79-1961 BEVERABES BILEGES of accidents involving alcohol as a cases/factor, 193 general vialation, 1977 Fig. 193 STELLOGERIFE 2-173 Fig. 193 STELLOGERI		A79-28289		nd C-5A
BYPERANCE	Development of casualty evacuation kit for	the	[AD-A061807]	N79-19008
BIBLIOGRIPHIES COllasion avokance an annotated bibliography Collasion avokance annotation annotation annotation annotation annotation annotation annotation avokance annotation annotation annotation avokance annotation annotation avokance annotation annotation annotation avokance annotation annotation avokance annotation annotation annotation avokance annotation annotation annotation avokance annotation annotation annotation avokance annotation annotation avokance annotation annotation avokance annotation annotation avokance annotation avokance annotation avokance annotation annotation avokance annotation		N79-19616	Simultaneous measurements of ozone outside	
RESIDENCE AIRCRAFT Collision avoidance an annotated bibliography SIDINGEARIZES Collision avoidance an annotated bibliography Frogress in transonar flow computations manipuss and design methods for three-dimensional flows and design methods and vand tunnel test of the Roming ITC model WF9-1779 BORING 373 AIRCRAFT Tlying MSA's Terminal Configured Vehicle against the Ricrowave Landing System algorithms and logic for incorporating RIS back azumth information into the MASA TCV B-737 airphane area navigation system WF9-17813 BORING 373 AIRCRAFT SUBJECTION Flows azumth information into the MASA TCV B-737 airphane area navigation system WF9-17813 BORING 373 AIRCRAFT SUBJECTION Flows azumth information into the MASA TCV B-737 airphane area navigation system WF9-17813 BORING 373 AIRCRAFT SUBJECTION Flows azumth information into the MASA TCV B-737 airphane area navigation system WF9-17813 BORING 373 AIRCRAFT SUBJECTION Flows azumth information into the MASA TCV B-737 airphane area navigation system WF9-17813 BORING 373 AIRCRAFT SUBJECTION Flows SUBJECTION Flows SUBJECTION Flows SUBJECTION Flows AF9-27304 AF9-27304 AF9-27307 AIRCRAFT SUBJECTION Flows		1		a Gates
BRINGERPHIS Collasion avoidance an annotated bibliography Progress in transonic flow computations analysis and design methods for three-disensional flows TSUBMARY report of the second wind tunnel test of the Boeing ITC model NAS-T-8-03039] BORING TAP AIRCHAFT Submary Experiment and to the Pask TUT P-737 Aliquither and logic for uncorporating NS back antipline area navigation system (NAS-T-8-03039) BORING TAP AIRCHAFT Supersonic contact design Annolysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft design TAP-17930 An analysis of fuel conserving operations for bomber/transport aircraft. Toline 1: Executive far-Notified and procedures and design modifications for bomber/transport aircraft. Toline 1: Executive far-Notified (NAS-T-15957) BOURDARY LATER COUPED. Submary Layer section applied in between [NAS-T-15957] Wy9-17853 Experiment on tander diffusers with boundary-layer section applied in between [NAS-T-15957] Wy9-17854 (NAS-T-15957) Submary LATER FIGOV Lasinat boundary layer with foreign gas injection on a contacl body ATS-22203 Inverse transonic airfold design methods including boundary layer and viscous interaction effects (NAS-T-15957) BOURDARY LATER FIGOV Lasinat boundary layer with foreign gas injection on a contact lody ATS-22203 Inverse transonic airfold design methods including boundary layer and viscous interaction effects (NAS-T-15957) BOURDARY LATER FIGOV Lasinat boundary layer with foreign gas injection on a contact lody ATS-22203 Inverse transonic airfold design met			CHITRRATTEC	A79-27571
FOR A-RA-78-8] NP9-17800 BONT-HIRE CONFIGURATIONS Progress in transmone flow computations snalpys. Frogress in transmone flow computations snalpys. BORING AIMCHRY Substance of the second wind tunnel test of the flowing 1rc and in the Microwave landing System Algorithms and logic for incorporating RIS back azimuth information into the MASA TCV p-737 Algorithms are an anymation system Frogress and design for incorporating RIS back azimuth information into the MASA TCV p-737 AIRCHRY Substances reasons reastrements of ozone outside and inside cabins of two B-747 ariliners and a Gates least bankers get with substances and design and first claims for two B-747 ariliners and a Gates least bankers get with substances and design and first claims for two B-747 ariliners and a Gates least procedures and design modifications for bubber/transport aircraft. Volume 1: Executive cases. Frogress AIRCHRY Substance of landing flow control on the performance of a large spandistributed-load flying-ving (MASA-76-159056) Probabilistic analysis of air carrier accidents. Frogress AIRCHRY Substance of landing flow control on the performance of a large spandistributed-load flying-ving pendices. Frogress AIRCHRY From Figure 1 and the figures with boundary layer substance and their capabilities of fluture flythquent of a long-endurance-surveillance conserving appendices. From Figure 1 and the figure of the MASA TCV p-27230 and the figure flythquent of the figur	BIBLIOGRAPHIES		An in-place recallibration technique to ext	
Progress in transonic flow computations analysis and design subtoos for three-discustional flows are design subtoos for three-discustional flows and design subtoos for three-discustional flows are design subtoos for three-discustional flows and design subtoos for three-discustional flows are design subtoos for three-discustional flows and design subtoos for three-discustional flows are provided that such as the subtoos of the second wind tunnel test of the Social Type subtoos for the second wind tunnel test of the Social Type subtoos for the second wind tunnel test of the Social Type subtoos for the second wind tunnel test of the Social Type subtoos for the second wind tunnel test of the Social Type subtoos for the Socia				
and design methods for three-dimensional flows supercritical yungs and wing-body combinations 879-18951 BORING AIRCRAFT Summary report of the second wind tunnel test of the Booling LFC model (NSA-CR-157792) 879-17799 BORING 737 AIRCRAFT 71 lying NSA's Terminal Configured Vehicle against the microwave Landing System A79-26534 Algorithms and logic for incorporating NLS back azumuth information into the NASA TCV B-737 airplane area marylation system A79-26534 Algorithms and logic for incorporating NLS back azumuth information into the NASA TCV B-737 airplane area marylation system A79-26534 Algorithms could be second wind tunnel and facts Learlet business; Branches Shaultaneous measurements of come outside and anside cabins of two B-787 airliners and a Gates Learlet business; Branches Supersonic combat aircraft design A79-27251 AD-ANGING 17818 BOURDARY LATES CONTROL Summary layer studies of the second wind tunnel test of the Boeing LFC model (NSA-CR-155905) Frailaction of a long-endurance-surrelllance remothy-plicted whicle with and without laninar flow control on the perforance of a large span-distributed-load flying-wing cargo airplane concept A79-27203 April 1893 BOURDARY LATES STABLINT Stable boundary layer with foreign gas injection on a concal body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects BOURDARY LATES STABLINT Stable boundary layer with foreign gas injection on a concal body A79-27203 Taverse transonic airfoil design methods including boundary layer and viscous interaction effects BOURDARY LATES STABLINT Stable boundary layer with shear model for aircraft flight hazard definintion A79-27205 BOURDARY LATES STABLINT Stable boundary layer with shear model for aircraft flight hazard definintion A79-27205 BOURDARY LATES STABLINT Stable boundary layer with shear model for aircraft flight hazard definition A79-27205 BOURDARY LATES STABLINT Stable boundary layer with shear wold if or aircraft flight hazard definition A7	BODY-WING CONFIGURATIONS		[SAE PAPER 781003]	
BOILEG AIRCRAFT Summary report of the second wind tunnel test of [RISA-CH-157792] R79-17826 BOILEG AIRCRAFT SUMMARY report of the second wind tunnel test of [RISA-CH-157792] R79-17826 BOILEG 737 AIRCRAFT Flying RSA's Terminal Configured Vehicle against the microwave Landing System A79-26334 A19porithms and logic for incorporating HIS Borney Aircraft and the microwave Landing System A79-26334 A19porithms and Logic for incorporating HIS Borney Aircraft Arms Aircraft			Aircraft accident report: Continental Air	
Summary report of the second wind tunnel test of the Boeling IXC model The Boeling IXC model WF9-17799 FINING 737 AIRCRAFT SINING TATA IXCRAFT SUPErsonic combat aircraft design (MANA TAP-0699) AN analysis of fuel conserving operational properations of the second wind tunnel test of the superation of the superation superation of the superation superation superation superation superation of the superation super	supercritical wings and wing-body co			
[NASA-CR-15792] N79-17799 BORING 737 AIRCRAFT Plying NASA's Tersinal Configured Vehicle against the Microwave Landing System A79-26534 Algorithms and logic for incorporating MLS bases are used for microwave Landing System A79-26534 Algorithms and logic for incorporating MLS bases are used in formation into the MASA TOV B-737 airplane area navigation system N79-17833 BORING 737 AIRCRAFT Simultaneous measurements of ozone outside and Learjet business jet A79-27571 Supersonic combat aircraft design A79-27571 Supersonic combat aircraft design A79-27571 Manalysis of fue conserving operational Combon Meritaneous measurements of conserving operational Combon Meritaneous measurements of the Boeing INT model Type of the Boeing INT model (MASA-CR-15987) Fig. 18. 18. 18. 18. 18. 18. 18. 18. 18. 18			[NTSB-AAR-79-1]	
Flying MSA's Terminal Configured Vehicle against the Microwave Landing System A79-26534			Enhanced capabilities of future fighters a	s a
This was a serviced by the second wind tunnel test of the seco		N79~17799		A79-27370
Algorithms and logic for incorporating RIS back azimuth information into the WASA TCV B-737 airplane area navigation system [MASA-TR-18039] BOKING 747 AIRCHAFT SABOLIAGEOUS RESIDENCE TO A THERMATT SABOLIAGEOUS RESIDENCE TO STATE AND THE	Flying NASA's Terminal Configured Vehicle	against	An experimental wind-tunnel investigation	of a
azimuth information into the MASS TOV B-737 airplane area navigation system (MASS-TM-80039) BORING 747 AIRCRAFT Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 BOBBEM BATECHTP Supersonic combat aircraft design (ATAM 79-0699) An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary (AD-MOGITMG) BOUNDARY LATER COMPROI Effects of laminar flow control on the performance of a large span-distributed-load flying-ving cargo airplane concept (MASS-CM-158957) EVALUATION OF AIRCRAFT (MASS-CM-158957) INVS-CC-1579570 INVS-CC	the microwave Landing System	A79-26534		
Aarplane area navagation system [NRSA-TR-80039] NF9-17803 BORING 747 AIRCRAFT Samultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 BORDER AIRCRAFT Superious consta dicraft design An analysis of fuel conserving operational procedures and design modifications for bonber/transport aircraft. Volume 1: Executive summary [AD-061746] NF9-17892 EXPERION 1766] NF9-17899 EXPERION 1766 INFO-1767 NF9-17799 EXPERION 1766 INFO-1767 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-17800 EXPERION 1766 INFO-1766 NF9-1800 EXPERION 1766 INFO-1766				N79-17809
Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 BORBER AIRCRAFT Supersonic combat aircraft design A79-27571 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061786] R79-18969 BOUDDARK LATINE COMPROL Summary report of the second wind tunnel test of the Boeing LFC model of the Boeing L	airplane area navigation system		•	N79-18889
Inside cabins of two B-747 arrhiners and a Gates Learjet business jet N79-27571 BORBER HIRCRAFT Supersonic combat aircraft design [ATAN 79-0697] An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061786] BOUNDARY LATER COMPON Summary report of the second wind tunnel test of the Boeing LPC model [MASA-CR-157792] Experiments on tandem diffusers with modification procedure and design medical in between boundary-layer suction applied in between of a large span-distributed-load flying-wing cargo airglane concept [MASA-CR-15906] ANSA-CR-159005] SUMDARY LATER TOW Componing the second wind the second wind the second flying-wing cargo airglane concept [MASA-CR-15906] [NASA-CR-159006] INVESTIGATION OF a long-endurance-surveillance remarks of a long-endurance-surveillance remarks of the risks presented by the use of carbon fiber composites in commercial availation. Yolume 1: Planal report. Volume 2: Supporting appendices N79-18079 Overview of the carbon fiber problem N79-18079 Cargo airglane concept [MASA-CR-15906] [NASA-CR-159006] [NASA-CR-159006] INVESTIGATION OF a long-endurance-surveillance remarks of a long-endurance surveillance remarks of a long-end		N79~17843		of
Learjet business jet A79-27571 BORBER AIRCRAFT Supersonic combat aircraft design A79-27363 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] BOUNDARY LAYER COMPROL Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157972] Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158987] N79-1805 [RASA-CR-158987] Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-TR-18715] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] EVARPH LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 BOUNDARY LAYER TRANSITION Boundary layer and viscous interaction effects [NASA-CR-158136] BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the APDC aircraft flight hazard definition A79-2755 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measurements on the APDC 10 deg cone in three RAZE wind tunnels and their implications DOUBLARY LAYER TRANSITION Boundary layer transition measure				179-26628
Supersonic combat aircraft design 179-27363 [ATAA 79-0699] A79-27363 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 BOUNDARY LAYER TRANSITIOS Experiments on tandes diffusers with boundary-layer and viscous interaction effects [NASA-CR-15792] N79-17852 Braluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a connect loody a remotely-piloted vehicle with and without laminar flow control of a connect loody a connect laminar flow control of a connect loody a remotely-piloted vehicle with and without laminar flow control of a connect loody a connect laminar flow control of a connect loody a remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control design methods including boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects [NASA-CR-15836] N79-1805 BOUNDARY LAYER TRANSITIOS BOUNDARY LAYER TRANSITIOS BOUNDARY LAYER TRANSITIOS Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications A79-27575			Development and initial test results of pa	rachutes
An analysis of fiel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary summary aircraft aircraft. Volume 1: Executive summary (AD-NO61746) N79-18969 BOUDDARY LATER CONTROL Summary report of the second wind tunnel test of the Boeing LPC model (NASA-CR-157792) N79-18779 Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] N79-1803 Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept (NASA-TR-78715) Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control (NASA-CR-159006) N79-17852 BOUNDARY LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION ROUNDARY LAYER TRANSITION Roundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications are considered and the principle and the risks presented by the use of carbon fiber craposites in commercial aviation: Provide a carbon fiber craposites in commercial aviation: Carbon fiber craposites in commercial aviation: Carbon fiber craposites in	BOHBER AIRCRAFT	A/9~27571		
An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive Summary [AD-A061746] N79-18969 BOUDDARY LAYER CONTROL Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-15792] N79-17799 Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-1597792] N79-17803 Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-CR-15975] N79-17803 Eyaluation of a long-endurance-surveillance renotly-piloted wehicle with and without laminar flow control (NASA-CR-159006) N79-17852 BOUNDARY LAYER FLOW Laminar houndary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-159136) BOUNDARY LAYER TRANSITION A79-27575 BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION A79-27575 BOUNDARY LAYER TRANSITION A79-27575 BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION A79-27575 BOUNDAR		379~27363		e ase of
bomber/transport aircraft. Volume 1: Executive Submary [AD-A061746] BOUDDARY LAYER COMPROL Submary report of the second wind tunnel test of the Boeing LPC model [NASA-CR-157792] Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158987] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-CR-158987] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar boundary layer with foreign gas injection on a conical body Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) BOUDDARY LAYER TRABSITION BOUNDARY L	An analysis of fuel conserving operational	l	carbon fiber composites in commercial av	iation.
Non-Noi 1746 Non-Noi 1746 Non-Noi 1746 Non-Noi 1746 Noundary Layer court of the second wind tunnel test of the Boeing LPC model. Non-17799 Non-17799 Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] Non-17803 Non-17805 Non				porting
Summary report of the second wind tunnel test of the Boeing LPC model [NRSA-CR-157792] Experiments on tandem diffusers with boundary-layer suction applied in between [NRSA-CR-159577] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NRSA-TR-78715] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NRSA-CR-15906] N79-17852 BOUNDARY LAYER PLOW Laminar boundary layer with foreign gas injection on a conical body Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NRSA-CR-158136) BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAZ wind tunnels and their implications Carbon fiber composites in commercial aviation: Executive summary N79-18075 Overview of the carbon fiber problem N79-18076 Carbon fiber composites in commercial aviation: Executive summary N79-18075 Overview of the carbon fiber problem N79-18076 Carbon fiber composites in commercial aviation: Executive summary N79-18076 Overview of the carbon fiber problem N79-18076 Carbon fiber composites in commercial aviation: Frobablistic analysis of air carrier accidents N79-18078 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber composites in commercial aviation: N79-18076 Carbon fiber combon fiber problem N79-18078 Carbon fiber combon fiber problem N79-18078 Carbon fiber combon fiber problem N79-18078 Carbon fiber combon fiber problem N79-1808 Estimation of economic losses N79-18080 N79-18080 N79-18080 N79-18080 N79-18080 CARBON HON		N79-19969		
the Boeing LFC model [NASA-CR-157792] N79-17799 Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] N79-17803 Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TR-78715] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] N79-17852 BOUNDARY LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects [NASA-CR-18136] N79-17805 BOUNDARY LAYER STABLITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications N79-1807 Overview of the carbon fiber problem N79-18076 Carbon fiber release conditions (Carbon fiber dispersion models used for risk analysis calculations N79-18079 Carbon fiber dispersion models used for risk analysis calculations N79-18080 Estimation of economic losses N79-18080 N79-18075 Carbon fiber release conditions N79-18079 Carbon fiber dispersion models used for risk analysis calculations N79-18080 Estimation of economic losses N79-18080 N79-18075 N79-18079 Carbon fiber dispersion models used for risk analysis calculations N79-18080 Estimation of economic losses N79-18080 Nonte Carlo simulation of single accident airport N79-18080 N79-18080 N79-18080 N79-18080 N79-18080 N79-18080 Nonte Carlo simulation of single accident	BOUNDARY LAYER CONTROL		carbon fiber composites in commercial av	
Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] N79-17803 Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-CR-178715] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control (NASA-CR-159006) N79-17852 BOUNDARY LATER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) N79-17805 BOUNDARY LATER STABLISTY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LATER TRANSITION A79-27575 BOUNDARY LATER TRANSITION A79-27121 10 deg cone in three RAE wind tunnels and their implications		test of	Elecutive summary	N79-18075
boundary-layer suction applied in between [NASA-CR-159957] N79-17803 Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TR-78715] N79-17851 Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control (NASA-CR-159006) N79-17852 BOUNDARY LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications Probabilistic analysis of air carrier accidents N79-1807 Carbon fiber release conditions N79-1807 Carbon fiber of ispersion models used for risk analysis calculations N79-1808 Estimation of economic losses N79-1808 Estimation of economic losses N79-1808 Enterpretation of results N79-1808 CARBON HONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAPT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121		N79-17799	Overview of the carbon fiber problem	N79-18076
Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TH-78715] N79-17851 Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control (NASA-CR-159006) N79-17852 BOUNDARY LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications Carbon fiber dispersion models used for risk analysis calculations N79-1808 Estimation of economic losses N79-1808 Estimation of economic losses N79-1808 Synthesis of national risk profile N79-18085 Interpretation of results N79-18086 CARBON HONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAPT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121 Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials	boundary-layer suction applied in between		Probabilistic analysis of air carrier acci	dents
Carbon fiber dispersion models used for risk [NASA-TH-78715] Bvaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] BOUNDARY LAYER PLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects [NASA-CR-158136] BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications Carbon fiber dispersion models used for risk analysis calculations N79-18080 Estimation of economic losses N79-18080 Fonte Carlo simulation of single accident airport risk profile N79-18080 Synthesis of national risk profile N79-18085 Interpretation of results CARBON HONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121			Carbon fiber release conditions	N/9-180/8
[NASA-CR-159006] Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136] BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications of a long-endurance-surveillance (NASA-CR-159006) N79-1808 Estimation of economic losses N79-1808 Honte Carlo simulation of single accident airport risk profile N79-1808 Synthesis of national risk profile N79-18085 Synthesis of national risk profile N79-18085 Interpretation of results N79-18086 CARBON MONOXIDE LASERS Laser aircraft using kerosene A79-27575 Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121 A79-27121		wing	Carbon fiber dispersion models used for II	
remotely-piloted wehicle with and without laminar flow control [NASA-CR-159006] N79-17852 BOUNDARY LAYER PLOW Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects [NASA-CR-158136] N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications Figure 199-1808 N79-1808 Monte Carlo simulation of single accident airport risk profile N79-1808 Synthesis of national risk profile N79-18085 Interpretation of results N79-18086 CARBOW MONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	[NASA-TH-78715]			
[NASA-CR-159006] BOUNDARY LAYER FLOW Laminar boundary layer with foreign gas injection on a conical body Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136) BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition BOUNDARY LAYER TRANSITION BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications N79-17805 Honte Carlo simulation of single accident airport risk profile N79-1808 Synthesis of national risk profile N79-18085 CARBON MONOXIDE LASERS Laser aircraft using kerosene CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	remotely-piloted wehicle with and withou		Estimation of economic losses	
Laminar boundary layer with foreign gas injection on a conical body A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects [NASA-CR-158136] BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications N79-18085 Synthesis of national risk profile N79-18085 Interpretation of results N79-18085 CARBON MONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	[NASA-CR-159006]	N79-17852		
A79-27203 Inverse transonic airfoil design methods including boundary layer and viscous interaction effects (NASA-CR-158136] BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications N79-18085 Interpretation of results N79-18086 CARBON MONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	Laminar boundary layer with foreign gas in	jection	•	N79-18084
boundary layer and viscous interaction effects [NASA-CR-158136] N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications N79-1808 CARBON MONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	<u>-</u>		Synthesis of national risk profile	พ79-18085
[NASA-CR-158136] N79-17805 BOUNDARY LAYER STABILITY Stable boundary layer wind shear model for aircraft flight hazard definition BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications CARBON MONOXIDE LASERS Laser aircraft using kerosene A79-26597 CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121			Interpretation of results	N79-18086
Stable boundary layer wind shear model for aircraft flight hazard definition A79-26597 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications A79-27121	[NASA-CR-158136]			
aircraft flight hazard definition A79-27575 BOUNDARY LAYER TRANSITION Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications CARGO AIRCRAFT Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials A79-27121	Stable boundary layer wind shear model for	r	·	A79-26597
BOUNDARY LAYER TRANSITION reduction performance by interior materials Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their implications				noise
10 deg cone in three BAE wind tunnels and their implications				als
	10 deg cone in three RAE wind tunnels as	nd their		M13-2/121
		N79-17817		

CASCADE PLOW SUBJECT INDEX

Effects of laminar flow control on the perfo of a large span-distributed-load flying-wi		FAA remote terminal system frequency assign model	ment
cargo airplane concept [NASA-TM-78715] N CASCADE FLOW	79-17851	Objectives related to an enhancement of the	
Outlet air angle prediction for subsonic flo cascades	¥	effectivity of MALEV. I civil aircraf utilization in Hungary	A79-25368
Comparison between flows in cascades and rot the transonic range. 1: Basic considerat	10ns 179-19000	Statistics of disturbances and maintenance according to conditions at Interflug. III Technical requirements concerning the profor the processing of disturbance data by of electronic data processing	gram
the transonic range. 2: Investigation of transonic compressor cascades and comparis	two	Safety of air transport	A79-25371
with rotor data	79-19001	General aviation aircraft in the 1990's	A79-25542
Comparison between flows in cascades and rot the transonic range. 3: Comparison of experimental and theoretical results of fl		[AIAA PAPER 79-0560] Recognition of damage-tolerance in civil airworthiness standards	A79-25866
studies on blade-to-blade surfaces in an a compressor rotor			
CAST ALLOYS Advanced Turbine Engine Gas generator (ATEGG fractography of cast nickel base superallo		developing countries [AllA 79-0695] Listing of accidents/incidents by make and	A79-27360 model.
[AD-A061701] N CAUCHY INTEGRAL PORMULA	79-19149	US civil aviation, 1977 [NTSB-AMM-78-12]	N79-17828
Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A CAVITY RESONATORS	79-25869	An assessment of the risks presented by the carbon fiber composites in commercial avi Volume 1: Final report. Volume 2: Supp appendices	ation.
<pre>Heat generation in cavities at high velocity resonance-pipe effect</pre>	*	[NASA-CR-158989] Corporate aviation in the 1980's	N79-18074
[BMVG-FBWT-77-28] N CENTER OF GRAVITY	179 - 17815	CLOUDS (METEOROLOGY)	N79-18892
Control of the location of the center of gra- of loaded aircraft	vity	Overestimates of entrainment from wetting o aircraft temperature sensors in cloud	
CENTRIFUGAL COMPRESSORS	.79-25370	CLUTCHES	A79-25296
Industrial centrifugal compressors, volume 1 [VKI-LECTURE-SERIES-95] N	79-19385	Advanced overrunning clutch technology helicopter transmission application	
Flow modelling and aerodynamic design technifor centrifugal compressors		[SAE PAPER 781039] CONXIAL FLOW	A79-25907
Viscous flows in centrifugal compressors	79-19386	Coaxial jet noise in flight	A79-26919
		[AIAA PAPER 79-0636] COCKPITS Cockpit displays and the growing role of th	
	79-19388		A79-26875
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SERIES-95] A stress and strain analysis of industrial r.	79-19389	Cockpit management Advancements in helicopter cockpit technolo	n79-18890 gy
compressor impellers using the framework me finite element method and descriptive of N		Design procedure for an information transfe method CUBITS for allocating panel area f	
Development testing of stages for centrifugate process compressors		aircrew station controls and displays	N79-19631
CH-47 HELICOPTER Advanced technology applied to the CH-47D dr.	79-19392 i v e	Internal cockpit reflections of external po light sources for the model YAH-64 advanc attack helicopter	
system [SAE PAPER 781040] Structural development of the Modernized Chi	79-25908	A survey of communications in the high nois	N79-19643 e
helicopter transmission gearing	79-28260	environment of Army aircraft Some aspects of helicopter communications	N79-19646
Effect of a chromium-containing fuel additive hot corrosion	e on	Some improvements to the UK helicopter cock	N79-19647 pit N79-19659
	79-2654€	Crash survivability of the UH-60A helicopte	
The analysis and identification of flux-induction voltage transients on low-loss transmission lines with application to the	n	COLD FLOW TESTS Cold-air performance of free power turbine designed for 112-kilowatt automotive gas-	
Lightning-Transient-Analysis /LTA/ problem A' An RF compatible lightning diverter strip	79-26246	engine. 2: Effects of variable stator-vane-chord setting angle on turbin performance	e
Protection/hardening of aircraft electronic		ÎNASA-TM-78993] COLLISION AVOIDANCE	N79-17859
systems against the indirect effects of li- N' CIRCULAR CYLINDERS	ghtning 79-18238	The future of surveillance systems in civil Aviation obstructions and the particular	aviation A79-24800
Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a		conditions for construction projects in t vicinity of airports	
combined method of order 0/h2/ and 0/h4/ A CIVIL AVIATION	79-24829	FAA air traffic control automation - Progra	A79-25372 ms and
The future of surveillance systems in civil	a v 1ation 79-24800	Collision avoidance an annotated bibliograp	A79-26871 hy N79-17840

SUBJECT INDEX COMPUTATION

COMBAT	- E	Military fiber optics applications	.70 5000
Development of smart target for simulation one-on-one air-to-air combat		COMPONENT RELIABILITY	A79-28040
[AD-A056739] COMBUSTION CHAMBERS	N79-17879	Causes for the deterioration of splined connections in aircraft engines during s	
Combustion noise prediction update [AIAA PAPER 79-0588]	A79-26942	COMPOSITE MATERIALS	A79-25249
Two-frequency-range theory of unstable tur- combustion oscillations in a jet engine	bulent	GASP IV simulation model for the composite bonding production facility	
combustion chamber. II - Analysis of the characteristic equation and comparison we experiment		New technology in commercial aircraft desi minimum operating cost	A79-27297 gn for
The design and development of high perform combustors	A79-27728 ance	[AIAA 79-0690] Environmental models for moisture absorpti aircraft composites	A79-27356 on by
	N79-19380	-	A79-27572
COMBUSTION CONTROL Intensification of fuel waporization in augas turbine engines by electrical forces		Aeroelastic tailoring studies in fighter a design [AIAA 79-0725]	1rcraft 179-28257
Diffusers for gas turbine combustion system	A79-27748 ms	An aeroelastic optimization procedure for composite high aspect ratio wings	A79-28258
COMBUSTION EFFICIENCY	N79-19369	[AIAA 79-0726] An assessment of the risks presented by the	
Combustion problems in gas turbine applicative [VKI-LECTURE-SERIES-93] COMBUSTION PHYSICS	tions N79-19365	carbon fiber composites in commercial av Volume 1: Pinal report. Volume 2: Sup appendices	
Lean combustion limits of a confined		[NASA-CR-158989]	N79-18074
premixed-prevaporized propane jet [AIAA PAPER 79-0538] Aerodynamics of flame jets Russian boo	A79~25856	An assessment of the risks presented by th carbon fiber composites in commercial av Executive summary	
	A79-26355	-	N79-18075
Path in rocket technology - Selected works 1924-1946 Russian book	,	Overview of the carbon fiber problem	N79-18076
Combustion in the gas turbine, parts 1, 2,	A79-27599 3	Interpretation of results	N79-18086
COMBUSTION PRODUCTS	N79-19366	Composite seal for turbomachinery back turbine engine shrouds	ings for
Effects of fuel properties on soot formation		[NASA-CASE-LEW-12131-1] COMPOSITE STRUCTURES	N79-18318
turbine combustion [SAE PAPER 781026]	A79-25899	Thermal response of composite panels	
Development of fire test methods for airpli interior materials	ane	Divergence of forward swept composite wings	A79-25350
[NASA-CR-160119] COMBUSTION VIBRATION	N79-19112	[ATAN 79-0722] Induced effects of lightning on an all com	A79-28255
Two-frequency-range theory of unstable tur	bulent	alroraft	
combustion oscillations in a jet engine combustion chamber. II - Analysis of the		COMPRESSIBLE FLOW	N79-18242
characteristic equation and comparison w		A shock capturing application of the finit	
experiment	A79-27728	element method to viscous compressib problem	le flow
COMPORT		Claries was as commercial flow Pro-	A79-24771
Advancements in helicopter cockpit technol- COMMERCIAL AIRCRAFT	N79-19625	Slender wing in compressible flow Russ COMPRESSOR BLADES	A79-25872
The coming of age of digital electronics is		Characteristics of the wake of a lightly 1	oaded
commercial transports emphasizing si- processing technology and Boeing 767 avi-		compressor or fan rotor [AIAA PAPER 79-0550]	A79-25861
[AIAA 79-0686] New technology in commercial aircraft desi	A79-27352	Turbulence characteristics in the near wak compressor rotor blade	e of a
minimum operating cost [AIAA 79-0690]	A79-27356	[AIAA PAPER 79-0280] Interactive multi-mode blade impact analys.	A79-26544 1s
Simultaneous measurements of ozone outside	and	[NASA-CR-159462]	N79-17858
inside cabins of two B-747 airliners and Learjet business jet		Investigation of the aerodynamic and acous performance of a low-pressure ratio tand	
Cryohydrogen-fuel for tomorrow's commercia		compressor	N79-18975
An assessment of the risks presented by th		Turbine blade cooling	N79-18980
carbon fiber composites in commercial av Volume 1: Pinal report. Volume 2: Sup appendices		COMPRESSOR ROTORS Characteristics of the wake of a lightly 1 compressor or fan rotor	oaded
[NASA-CR-158989]	N79-18074	[AIAA PAPER 79-0550]	A79-25861
An assessment of the risks presented by the carbon fiber composites in commercial aversecutive summary	lation:	Comparison between flows in cascades and r the transonic range. 3: Comparison of experimental and theoretical results of	flow
Corporate aviation in the 1980's	₩79-18075	studies on blade-to-blade surfaces in an compressor rotor	
Rotor fragment protection program: Statis	N79-18892	COMPRESSORS	N79-19002
arroraft gas turbine engine rotor failur occurred in US commercial aviation durin	es that	CORPRESSORS Strain gage system evaluation program [NASA-CR-159486]	ห79-19314
[NASA-CR-159474] Occupant injury mechanisms in civil helico	N79-18977	COMPUTATION Some recent progress in transonic flow com	
accidents	pter N79-19653	flow distribution, numerical optimiz	
COMMUNICATION EQUIPMENT A proposed integrated ECM system using the constant index lens antenna	n / 7 - 1 20 3 3	and airfoil design	N79-18946

A79-24726

COMPUTER DESIGN SUBJECT INDEX

COMPUTER DESIGN SIFT - pesign and analysis of a fault-toler	ant	COMPUTERIZED SIMULATION Flight simulation of a vehicle with a two-st	age
computer for aircraft control Softwar Implemented Fault Tolerant systems	e	parachute system [AIAA 79-0448]	A79-26652
Integrated Thermal Avionics Design (ITAD)	A79-25718	The validity of the Leicester computer mode: parachute with fully-deployed canopy	l for a
[AD-A061227] COMPUTER GRAPHICS	N79-17855	[AIAA 79-0460] GASP IV simulation model for the composites	479-26663 and
Aviation wide angle visual system /AWAVS/ - system performance	Visual A79-28161		A79-27297
COMPUTER PROGRAMMING GASP-PL/I simulation of integrated avionic		Perspectives of technological development for helicopters	
processor architectures	N79-18973	[ATAA 79-0701] Survey of radar simulation training at ATC: facilities	179-27364 E1eld
COMPUTER PROGRAMS SIFT - Design and analysis of a fault-toler	ant		179-17877 of
computer for aircraft control Softwar Implemented fault Tolerant systems			779-17879
The application of computer aided technique project design for aircraft	A79-25718 s to	Monte Carlo simulation of single accident as risk profile	rport 179-18084
	A79-26592	CONCENTRATION (COMPOSITION)	
Method for digital computer calculation of		Comparisons of turbine engine combustor exha	
unsteady temperature fields in turbomachi		emissions measurements using three gas-sai	npling
	A79-27746	probe designs	.70 40005
General purpose computer program for intera supersonic configurations. User's manual		[AD-A061733] CONFERENCES	179-19005
determining unsteady aerodynamic foreces		Aerodynamic Decelerator and Balloon Technological	na 🗸
	N79-17798	Conference, 6th, Houston, Tex., March 5-7, Technical Papers	
computer program for determining aerodyna			79-26626
coefficients and flow deflection		Application of fracture mechanics to design	
	N79-17814		179-26980
Interactive multi-mode blade impact analysi		Structures, Structural Dynamics, and Materia	
Software requirements for the A-7E aircraft		Conference, 20th, St. Louis, Mo., April 4- 1979, Technical Papers on Dynamics and Los	ıds
	N79-18974		79-28251
Computer-aided collection of demographic dawithin day-night level contours: Two tes		Industrial centrifugal compressors, volume 1 [VKI-LECTURE-SERIES-95]	i 179-19385
	N79-19010	Industrial Centrifugal Compressors, Volume 2	
COMPUTER SYSTEMS DESIGN Multimode radar processor for combat as			79-19389
	A79-28058	Laminar boundary layer with foreign gas inje	ection
COMPUTER SYSTEMS PROGRAMS		on a conical body	
Concept of modular software for the stepwis			179-27203
construction of radar data processing sys		Boundary layer transition measurements on the	
with minicomputers, taking into account a	s	10 deg cone in three RAE wind tunnels and	their
example the Airtrack System	A79-26759	1mplications [ARC-R/M-3821]	779-17817
Hardware and software structure of a coordi		CONICAL NOZZLES	
<pre>system for air traffic control on the bas flight plan data</pre>	is of	The sound power spectrum of shock-free jets	79-26918
	A79-26760	CONSTRUCTION MATERIALS	203.0
Analysis of the functional requirements for	an	SDM lecture - Introduction of new SDM techno	
intelligent airborne computer system		into production systems Structures, Dy	
	N79-18962	and Materials technology in aircraft design	
COMPUTER TECHNIQUES Life Cycle Cost in advanced technology engin	пе	[AIAA 79-0719] CONTINUOUS WAVE LASERS	79-28252
development		Laser propulsion	
	A79-25901		79-26598
COMPUTERIZED DESIGN	noc	CONTROL Accorded to the state of an air	mmla
TDS - A preliminary design system for turbing [SAE PAPER 780999]	A79-25882	Aeroservoelastic stability analysis of an ai with a control augmentation system	-
Turbine engine cost reduction using Life Cyc	cle		179-19006
Cost techniques [SAE PAPER 781031]	A79-25903	CONTROL BOARDS	_
The application of computer aided techniques		Design procedure for an information transfer method CUBITS for allocating panel area for	
project design for aircraft		aircrew station controls and displays	_
	A79-26592		79-19631
Recovery system preliminary design - A simp		Visual pockets: A design parameter for heli	.copter
approach to determining drogue chute stag: timing, and altitude requirements	ing,	instrument panels	79-19641
	A79-26650	CONTROL COMPIGURED VEHICLES	175-15041
Introduction to the computer-aided design of	£	Recent developments in active control techno	logy
flight vehicles Russian book on space		for fighter aircraft design	
design	170_276h0		79-27368
Combined strength and aeroelastic wing synt	1 179-27648 hesis	CONTROL EQUIPMENT Evaluation of two inflow control devices for	
via constraint approximation	······································	flight simulation of fan noise using a JT1	
[AIAA 79-0724]	A79-28290	engine	· -
Progress in transonic flow computations anal		[AIAA PAPER 79-0654]	79-26926
and design methods for three-dimensional		Validation of MIL-F-9490D: General specific	
supercritical wings and wing-body com	Dinations N79-18951	for flight control system for piloted mili	
Application of aerodynamic design technique		aircraft. Volume 1: Summary of YF-17 and validations	C-SA
process compressor design computerized			79-19008

SUBJECT INDEX DATA REDUCTION

Validation of MIL-F-9490D: General spect for flight control system for puloted m aircraft. Volume 2: YF-17 lightweight	ılitary	CRASE LANDING Alteraft accident report: Allegheny Airli Inc. BAC 1-11, N1550, Rochester, New York	
validation	#70-10000	9, 1978	#70 10061
[AD-A062008] CONTROL STABILITY	N79-19009	[NTSB-AAR-79-2] Crash survivability of the UH-60A helicopt	ห79-18961
Plight testing the Kfir		clash sqrvivability of the on-ton helicope	N79-19663
112,20 1000223 120 112==	A79-26530	The approach to crew protection in the cra	
The Learjet Longhorn series - The first j	ets with	environment for the YAH-64	
winglets			₹79-19664
	A79-26532	CRASHES	
Development of the L-1011 Flight Manageme	A79-26535	A method for selecting a crashworthy fuel design	system
Recent developments in active control tec		uesign	N79-19661
for fighter aircraft design		CRERP BUCKLING	
[AIAA 79-0708]	A79-27368	Experimental and finite element investigat	
CONTROLLABILITY		the buckling characteristics of a beader	d skin
Evaluation of IPR handling qualities of	107	panel for a hypersonic aircraft	N79-19412
helicopters using the NAE airborne V/ST simulator	UL	CREEP PROPERTIES	N/3-13412
[AIAA 79-0702]	A79-27365	Prediction of gas-turbine alloy creep	
CONVECTIVE BEAT TRANSPER		characteristics	
Convective heat exchange of gas-particle			A79-26841
flow passage of throttling device with	vane-type	CRITICAL VELOCITY	
turning element	A79-27742	An unstable subsynchronous critical speed of shaft failures in P-16 engine st	
CONVERGENT NOZZLES	H. J. Z. 1.742	[SAE PAPER 781055]	A79-25916
Aerodynamic and acoustic comparisons of		CROSS CORRELATION	
scaled-down and actual engine jets		Separation of core noise and jet noise	
[AIAA PAPER 79-0574]	A79-26946	[AIAA PAPER 79-0589]	A79-26941
COOLING Plate Cooling		CRUCIPORM WINGS An experimental wind-tunnel investigation	of a
Turbine Blade Cooling [VKI-LECTURE-SERIES-83]	N79-18979	ram-air-spoiler roll-control device on a	
Turbine blade cooling		forward-control missile at supersonic sp	
	N79-18980	[NASA-TP-1353]	ัท79-17809
Alternative turbine cooling technology		CRYOGENIC WIND TOWNELS	
ml	N79-18984	Theoretical investigations of real gas ef	fects in
The aerodynamic penalties associated with blade cooling	carpine	cryogenic wind tunnels [DS-PB-76/50B]	N79-17820
blude cooling	N79-18986	CORVED PARELS	
CORRELATION		Experimental and finite element investigation	tion of
Delta method, an empirical drag buildup t		the buckling characteristics of a beader	l skin
[NASA-CR-151971]	N79-17801	panel for a hypersonic aircraft	N79-19412
CORROSION PREVENTION Effect of a chromium-containing fuel addi	tive on	CYCLIC LOADS	873-13412
hot corrosion		The prediction of fatigue crack growth und	der
	A79-26546	flight-by-flight loading	
COST ANALYSIS			A79-25482
		CYLINDRICAL BODIES	
Trade-off studies with an interactive		loredwareig gide-forge allegiator means	
engine/airframe life-cycle-cost model	379-25905	Aerodynamic side-force alleviator means [NASA-CASE-LAR-12326-1]	N79-17813
engine/airframe life-cycle-cost model [SAE PAPER 781033]	A79-25905	[NASA-CASE-LAR-12326-1]	ท79-17813
engine/airframe life-cycle-cost model	A79-25905		ท79-17813
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the	279-25905	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP interior noise studies [AIAA PAPER 79-0647]	N79-17813
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVEMESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project		[NASA-CASE-LAR-12326-1] CYLINDRICAL SHRLLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693]	A79-25905	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP interior noise studies [AIAA PAPER 79-0647]	
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST RFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION	A79-27358	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHRLLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645]	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693]	A79-27358	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHRLLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAN 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031]	A79-27358 Cycle A79-25903	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] DABAGE	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques	A79-27358 Cycle A79-25903 costs down	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPROP interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up,	A79-27358 Cycle A79-25903 costs down A79-27093	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards	A79-26931 A79-26933
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAN 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des	A79-27358 Cycle A79-25903 costs down A79-27093	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019]	A79-26931
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des	A79-27358 Cycle A79-25903 costs down A79-27093	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPROP interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION	A79-26931 A79-26933
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAN 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des	A79-27358 Cycle A79-25903 costs down A79-27093 dign for	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019]	A79-26931 A79-26933
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690]	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356	[MAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505]	A79-26931 A79-26933
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft	A79-27358 Cycle A79-25903 costs down A79-27093 dign for	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDOJET blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING	A79-26933 A79-26933 A79-25895 design N79-18976
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST RFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil alivorthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine eng:	A79-26933 A79-26933 A79-25895 design N79-18976
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDOJET blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING	A79-26933 A79-26933 A79-25895 design N79-18976
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST RFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR NOISE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil alivorthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine eng:	A79-26933 A79-26933 A79-25895 design N79-18976 ine A79-25845
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine engine vibration transducers Concept of modular software for the stepwiconstruction of radar data processing specific processing sp	A79-26933 A79-25895 design N79-18976 ine A79-25845
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth	A79-27358 Cycle A79-25903 costs down A79-27093 cign for A79-27356 A79-25321	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDO jet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginesis and the step wibration transducers Concept of modular software for the step with minicomputers, taking into account	A79-26933 A79-25895 design N79-18976 ine A79-25845
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST RFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Four lectures on fatigue crack growth Environmental effects on crack growth in	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine engine vibration transducers Concept of modular software for the stepwiconstruction of radar data processing specific processing sp	A79-26933 A79-25895 design N79-18976 ine A79-25845
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Future avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Four lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS Turboprop interior noise studies [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D DABAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine engine vibration transducers Concept of modular software for the stepwiconstruction of radar data processing synth minicomputers, taking into account example the Airtrack System	A79-26933 A79-25895 design N79-18976 ine A79-25845
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDO jet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginesis and the step wibration transducers Concept of modular software for the step with minicomputers, taking into account	A79-26933 A79-26933 A79-25895 design N79-18976 ine A79-25845 ise A79-26759
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NUR-TR-76104-U] CRASS HUJDRIES	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDO jet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine engineers with airmoducers Concept of modular software for the stepwinth minicomputers, taking into account example the Airtrack System DATA RECORDING	A79-26933 A79-25895 design N79-18976 ine A79-25845 Lse ystems A79-26759
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NLR-TR-76104-U]	A79-27358 Cycle A79-25903 costs down A79-27093 dign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDO jet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginetion transducers Concept of modular software for the stepwiconstruction of radar data processing synth minicomputers, taking into account example the Airtrack System DATA BECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-26933 A79-25895 design N79-18976 ine A79-25845 ise A79-26759
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NIR-TR-76104-U] CRASH INJURIES Comparative injury patterns in US Army be	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012 illcopters N79-19654	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginessing the standard of the stepwiconstruction of radar data processing symith minicomputers, taking into account example the Airtrack System DATA RECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-25895 design N79-18976 ine A79-25845 Lse ystems A79-26759
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NIC-TE-76104-U] CRASH INJURIES Comparative injury patterns in US Army he Engineering analysis of crash injury in a	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012 illcopters N79-19654	[NASA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] NOISE TRANSMISSION - TUTDOPTOP PROBLEM [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION TUTDO jet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginetion transducers Concept of modular software for the stepwiconstruction of radar data processing synth minicomputers, taking into account example the Airtrack System DATA BECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-25895 design N79-18976 ine A79-25845 lse ystems A79-26759 ansient A79-25849
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NIR-TR-76104-U] CRASH INJURIES Comparative injury patterns in US Army be	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012 illcopters N79-19654	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginessing the standard of the stepwiconstruction of radar data processing symith minicomputers, taking into account example the Airtrack System DATA RECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-25895 design N79-18976 ine A79-25845 Lse ystems A79-26759
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2029-T3 and material [NIR-TE-76104-U] CRASH INJURIES Comparative injury patterns in US Army he Engineering analysis of crash injury in a aircraft Helicopter crashworthy fuel systems and the	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012 ilicopters N79-19655 iny N79-19655	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginessing the standard of the stepwiconstruction of radar data processing symith minicomputers, taking into account example the Airtrack System DATA RECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-25895 design N79-18976 ine A79-25845 lse ystems A79-26759 ansient A79-25849
engine/airframe life-cycle-cost model [SAE PAPER 781033] COST EFFECTIVENESS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] COST REDUCTION Turbine engine cost reduction using Life Cost techniques [SAE PAPER 781031] Puture avionics - Keeping capability up, New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] COUPLING EMP coupling to a composite aircraft CRACK PROPAGATION The prediction of fatigue crack growth un flight-by-flight loading Pour lectures on fatigue crack growth Environmental effects on crack growth in flight-simulation tests on 2024-T3 and material [NLR-TB-76104-U] CRASE INJURIES Comparative injury patterns in US Army be Engineering analysis of crash injury in a aircraft	A79-27358 Cycle A79-25903 costs down A79-27093 ign for A79-27356 A79-25321 der A79-25482 A79-25484 7075-T6 N79-18012 ilicopters N79-19655 iny N79-19655	[NAŠA-CASE-LAR-12326-1] CYLINDRICAL SHELLS TUTDOPTOP INTERIOR TO THE STUDIES [AIAA PAPER 79-0647] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] D D DAMAGE Recognition of damage-tolerance in civil airworthiness standards [SAE PAPER 781019] DATA ACQUISITION Turbojet blade vibration data acquisition and feasibility testing [NASA-CR-159505] DATA PROCESSING Dynamic data analysis gas turbine enginessing the standard of the stepwiconstruction of radar data processing symith minicomputers, taking into account example the Airtrack System DATA RECORDING Recording methods for steady state and trasignals aircraft engine tests	A79-26933 A79-25895 design N79-18976 ine A79-25845 lse ystems A79-26759 ansient A79-25849

DATA SYSTEMS SUBJECT INDEX

DATA SYSTEMS	How to get the world airborne market research
Statistics of disturbances and maintenance according to conditions at Interflug. III -	and aircraft design for air transportation in developing countries
Technical requirements concerning the program	[AIAA 79-0695] A79-27360
for the processing of disturbance data by means	DEVIATION
of electronic data processing A79~25371	Worst case time-histories causing largest deviations from a desired flight path: An
DATA TRANSMISSION An optical communication system for aircraft	analytical approach [VTH-LR-267] N79-17839
DC 10 AIRCRAFT	DIFFERENTIAL PRESSURE An improved system for use in conducting wake
Aircraft accident report: Continental Air lines,	investigation for a wing in flight
Incorporated, McDonnell-Douglas DC-10-10,	differential pressure measurements for drag
N68045, Los Angeles, California, March 1, 1978 [NTSB-AAR-79-1] N79-17826	investigations [NASA-CASE-PRC-11024-1] N79-17797
[NTSB-AAR-79-1] N79-17826 DEPENSE PROGRAM	DIPPUSERS
Strike Drone - A defense suppression concept using	Experiments on tandem diffusers with
unmanned cruise/loiter/attack vehicle [SAE Paper 781017] A79-25894	boundary-layer suction applied in between [NASA-CR-158957] N79-17803
[SAE PAPER 781017] A79-25894 DEFORMATION	DIGITAL COMPUTERS
Analysis of longitudinal natural vibrations of	Redundant control systems for flight vehicles
deformable aircraft by the finite-element method A79-25505	Russian book 179-25875
DEGRADATION	Some new approaches for wind-tunnel testing
Time degradation factors for the turbine engine	through the use of computers
exhaust emissions. Volume 1: Program	[AIAA 79-0707] A79-27367 DIGITAL INTEGRATORS
description and results air pollution control [NREC-1238-6-VOL-1] N79-17860	Design of proportional-plus-integral controllers
Time degradation factors for the turbine engine	for multivariable systems
exhaust emission. Volume 2: JT8D-9 test data air pollution control	DIGITAL RADAR SYSTEMS
[NREC-1238-7-VOL-2] N79-17863	System for the display of extracted radar data on
Time degradation factors for turbine engine	the basis of minicomputer-controlled display
exhaust emissions. Volume 3: JT3D-7 test data air pollution control	devices /DERD-MC/ for an employment in Air Traffic Control
[NREC-1238-8-VOL-3] N79-17864	A79-25491
Time degradation factors for turbine engine	Adaptation of a digital airborne radar for use on
exhaust emissions. Volume 4: JT3D-7 test data air pollution control	the microphysics research aircraft A79-25681
[NREC-1238-9-VOL-4] N79-17865	Digital target extraction at civil air traffic
Time degradation factors for turbine engine	control radar installations in the Federal
exhaust emissions. Volume 5: JT3D-3B test data air pollution control	Republic of Germany and possibilities for its further development from the point of view of
[NREC-1238-10-VOL-5] N79-17866	the Federal Institute of ATC
Time degradation factors for turbine engine	A79-26753
exhaust emissions. Volume 6: JT9D-3A test data air pollution control	New approaches concerning the implementation of radar target extractors with the aid of very
[NREC-1238-11-VOL-6] N79-17867	fast microprogrammable data processors
Time degradation factors for turbine engine	A79-26754
exhaust emissions. Volume 7: RB211-22B test data air pollution control	Concept of modular software for the stepwise construction of radar data processing systems
[NREC-1238-12-VOL-7] N79-17868	with minicomputers, taking into account as
Time degradation factors for turbine engine	example the Airtrack System A79-26759
exhaust emissions. Volume 8: C700-2D test data [NREC-1238-13-VOL-8] N79-17869	Hardware and software structure of a coordination
DEGREES OF PREEDOM	system for air traffic control on the basis of
Gust load estimation using a simplified power	flight plan data A79-26760
spectral technique [ARAP-362] N79-17870	Problems of computer-aided tracking, giving
DELTA WINGS	particular attention to radar which can be
A modification to linearized theory for prediction	electronically turned
of pressure loadings on lifting surfaces at high supersonic Mach numbers and large angles of attack	DIGITAL SYSTEMS
[NASA-TP-1406] N79-17806	The coming of age of digital electronics in
A slender delta wing oscillating in surface waves fVTH-IR-2571 N79-17818	commercial transports emphasizing signal processing technology and Boeing 767 avionics
[VTH-LR-257] N79-17818 XF4D Skyray development: Now it can be told	[AIAA 79-0686] A79-27352
N79-18897	Puture advanced technology rotorcraft
Calculation of supersonic viscous flow over delta wings with sharp subsonic leading edges	[AIAA 79-0705] A79-27366 DIGITAL TECHNIQUES
wrings with sharp subsonic reading edges	Interior noise path identification in light
DESCENT TRAJECTORIES	aircraft using multivariate spectral analysis
A simple physical model of a descending parachute fataa 79-04471 A79-26651	[AIAA PAPER 79-0644] A79-26915 Multimode radar processor for combat aircraft
[AIAA 79-0447] Flight simulation of a webicle with a two-stage	A79-28058
parachute system	DISPERSING
[AIAA 79-0448] A79-26652 DESCRIPTIVE GEORETRY	Carbon fiber release conditions N79-18079
A stress and strain analysis of industrial radial	Carbon fiber dispersion models used for risk
compressor impellers using the framework method	analysis calculations
finite element method and descriptive geometry N79-19391	R79-18080 Estimation of economic losses
DEVELOPING NATIONS	Estimation of economic losses N79-18083
Air fleet and facility planning via optimal	Monte Carlo simulation of single accident airport
control models	risk profile N79-18084
£17-20123	Interpretation of results
	N79-18086

SUBJECT INDEX ELASTOMERS

DISPLAY DEVICES	DUCTED BODIES
System for the display of extracted radar data on	Propagation of buzz-saw noise in a nonuniform medium
the basis of minicomputer-controlled display devices /DERD-MC/ for an employment in Air	contoured jet engine inlets [AIAA PAPER 79-0639] A79-26896
Traffic Control	DUCTED PAN ENGINES
A79-25491 Visual simulation devices for flight training	Noise from struts and splitters in turbofan exit ducts
simulators Russian book	[AIAA PAPER 79-0637] A79-26923
A79-26354	DUCTED PARS
Flying NASA's Terminal Configured Vehicle against the Microwave Landing System	Direct experimental verification of the theoretical model predicting rotor noise
A79-26534	generation
Cockpit displays and the growing role of the pilot in the ATC system	[AIAA PAPER 79-0658] A79-26894 DUCTED FLOW
A79-26875	Sound radiation from hyperboloidal inlet ducts
New airborne display concepts	[AIAA PAPER 79-0677] A79-26885
A79-27672 Study of the structure of an integrated system of	The application of finite element techniques to acoustic transmission in lined ducts with flow
flight control, navigation and display	[AIAA PAPER 79-0660] A79-26893
A79-27674 Tests of an integrated piloting, navigation, and	Influence of bypass ratio change on fan aerodynamic characteristics
display system	A79-27744
A79-27675	DUST
A three-channel high-resolution-TV image generation system flight simulator application	<pre>Aerodynamic behavior of fibres and sampling of respirable dust</pre>
A79-28160	[BLL-RTS-11267] N79-18470
Aviation wide angle visual system /AWAVS/ - Visual system performance	DYNAMIC MODELS The validity of the Leicester computer model for a
A79-28161	parachute with fully-deployed canopy
LED instrument approach instruction display	[AIAA 79-0460] A79-26663
[NASA-TM-78823] N79-17854 Design procedure for an information transfer	DYNAMIC PRESSURE Pressure measurement in air data instrumentation
method CUBITS for allocating panel area for	A79-25850
aircrew station controls and displays N79-19631	DYNAMIC RESPONSE SDM lecture - Introduction of new SDM technology
DIVERGENCE	into production systems Structures, Dynamics
Divergence of forward swept composite wings	and Materials technology in aircraft design FAIAA 79-07191 A79-28252
[AIAA 79-0722] A79-28255 DIVERTERS	[AIAA 79-0719] A79-28252 Engine dynamics
Lightning protection with segmented diverters	[BMVG-FBWT-78-6] N79-17862
for aircraft radomes and dielectric structures A79-25317	DYNAMIC STRUCTURAL AWALYSIS Analysis of longitudinal natural vibrations of
An RF compatible lightning diverter strip	deformable aircraft by the finite-element method
N79-18237	A79-25505 Structures, Structural Dynamics, and Materials
Pool fire radiation through a door in a simulated	Conference, 20th, St. Louis, Mo., April 4-6,
aircraft fuselage	1979, Technical Papers on Dynamics and Loads
[PAA-NA-78-38] N79-17966 DOPPLER RADAR	Nonlinear equations of equilibrium for elastic
DOPPLER RADAR The Dulles International Airport wind-shear	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation
DOPPLER RADAR The Dulles International Airport wind-shear	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] DRAG CHUTES	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E BCONOMIC ANALYSIS Compromise between economic concerns and
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] DRAG CHUTES Recovery system preliminary design - A simplified	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E BCONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] A79-27358
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] A79-26650	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] **ECONOMIC ANALYSIS** Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AINA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIRA 79-0695] A79-27360
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREBERT	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AINA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPEE 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 DRAG MEASUREMENT An improved system for use in conducting wake investigation for a wing in flight	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] RECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIRA 79-0695] A79-27360 Pindings of the Ottawa-Montreal STOL demonstration service [AIRA 79-0710] Estimation of economic losses
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPEE 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 DRAG MEASUREMENT An improved system for use in conducting wake investigation for a wing in flight	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries [AIRA 79-0695] A79-27360 Findings of the Ottawa-Montreal STOL demonstration service [AIRA 79-0710] A79-27369 ESCONOMIC FACTORS Statistical estimation of economic life for
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPEE 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 DRAG MRASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag A79-26593 Transonic wing design for transport aircraft	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIRA 79-0695] Pindings of the Ottawa-Montreal STOL demonstration service [AIRA 79-0710] Estimation of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIRA 79-0761] A79-28275 ECONOMIC IMPACT
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] PRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] PRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASR-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag A79-26593 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-28275
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-1777 DRAG REDUCTION Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083 ECONOMIC PACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-28275 ECONOMIC INPACT Monte Carlo simulation of single accident airport risk profile
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] PRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 PRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASR-FRC-11024-1] N79-1777 DRAG REDUCTION Theoretical lower limits of forebody drag A79-26593 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-158349] N79-18917	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E BCONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083 BCONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] BCONOMIC INPACT Monte Carlo simulation of single accident airport risk profile N79-18084
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG HEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-1777 DRAG REDUCTION Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] RECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] ESTIMATION of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] AA9-28275 ECONOMIC IMPACT Monte Carlo simulation of single accident airport risk profile N79-18084 EIGENVALUES Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] A79-2685
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] PRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 PRAG MERSURBERET An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag A79-26593 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-158349] N79-18917 DROWB AIRCRAFT Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E ECONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIRA 79-0693] A79-27358 How to get the world airborne market research and aircraft design for air transportation in developing countries [AIRA 79-0695] A79-27360 Pindings of the Ottawa-Montreal STOL demonstration service [AIRA 79-0710] A79-27369 Estimation of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIRA 79-0761] A79-28275 ECONOMIC INPACT Monte Carlo simulation of single accident airport risk profile N79-18084 EIGENVALUES Sound radiation from hyperboloidal inlet ducts [AIRA PAPER 79-0677] A79-26885
The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPEE 79-0551] Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG BEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] WASA-CASE-FRC-11024-1] Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-158349] DROWE AIRCRAFT Strike Drone - A defense suppression concept using	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] RESCONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-28275 ECONOMIC INPACT Monte Carlo simulation of single accident airport risk profile N79-18084 EIGENVALUES Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] A79-2685
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] PRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 PRAG MEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-158349] N79-18917 DROWE AIRCRAFT Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle [SAE PAPER 781017] DROP TESTS The validity of the Leicester computer model for a	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E
The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26653 DRAG REASUREMENT An improved system for use in conducting wake investigations [NASA-CASE-FRC-11024-1] [NASA-CASE-FRC-11024-1] Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] A79-26593 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-158349] N79-18917 DRONE AIRCRAFT Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle [SAE PAPER 781017] DROP TESTS	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] E BCONONIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] ESTIMATION of economic losses N79-18083 BCONONIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-28275 BCONONIC INPACT Monte Carlo simulation of single accident airport risk profile N79-18084 BIGENVALUES Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] EIGENVECTORS Accuracy of an approximate static structural analysis technique based on stiffness matrix
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 DRAG MEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-FRS 349] DROWE AIRCRAFT Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle [SAE PAPER 781017] A79-25894 DROP TESTS The validity of the Leicester computer model for a parachute with fully-deployed canopy	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] N79-19414 E
DOPPLER RADAR The Dulles International Airport wind-shear detection system Statistical results A79-27574 DOWNWASH Lifting surface theory for skewed and swept subsonic wings [AIAA PAPER 79-0551] A79-25869 DRAG CHUTES Recovery system preliminary design - A simplified approach to determining drogue chute staging, timing, and altitude requirements [AIAA 79-0446] Parachute inflation control using an attached apex drogue [AIAA 79-0449] A79-26650 DRAG MEASUREMENT An improved system for use in conducting wake investigation for a wing in flight differential pressure measurements for drag investigations [NASA-CASE-FRC-11024-1] N79-17797 DRAG REDUCTION Theoretical lower limits of forebody drag Transonic wing design for transport aircraft [AIAA 79-0692] Analysis of some aerodynamic characteristics due to wing-jet interaction [NASA-CR-FRS 349] DROWE AIRCRAFT Strike Drone - A defense suppression concept using unmanned cruise/loiter/attack vehicle [SAE PAPER 781017] A79-25894 DROP TESTS The validity of the Leicester computer model for a parachute with fully-deployed canopy	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing moderate deformation [NASA-CR-159478] RESCONOMIC ANALYSIS Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] How to get the world airborne market research and aircraft design for air transportation in developing countries [AIAA 79-0695] Findings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] Estimation of economic losses N79-18083 ECONOMIC FACTORS Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-28275 ECONOMIC IMPACT Monte Carlo simulation of single accident airport risk profile N79-18084 EIGENVALUES Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] EIGENVECTORS Accuracy of an approximate static structural analysis technique based on stiffness matrix eigenmodes [AIAA 79-0748] ELASTOMERS

ELECTRIC CHARGE SUBJECT INDEX

BLECTRIC CHARGE		ELEVONS
Electric charging of helicopters airc		Pressure and heat-transfer distributions in a
hazards and static dischargers for accid	ient	simulated wing-elevon cove with variable leakage
prevention	W70 4007h	at a free-stream Mach number of 6.9
[BMVG-FBWT-78-7]	N79-18274	[NASA-TH-74095] N79-182
ELECTRIC FIELDS	£4	EMBRGENCIES
Intensification of fuel vaporization in a		Rescue helicopters in primary and secondary mission
gas turbine engines by electrical forces		N79-196
DI DAMBIC DITMING	A79-27748	ENERGY STORAGE
ELECTRIC FILTERS		Air Force applications of lightweight
Filter weight minimization for rectified		superconducting machinery in airborne power
superconducting alternator power supplied	es	Sources
for aircraft	170 0000	A79-276
ELECTRIC HOTORS	A79-26966	ENGINE CONTROL
	. 61	Development of the L-1011 Flight Management System
Direct drive control valve for fly-by-wire control system actuators	e rright	A79-265
	770 40007	BUGINE COOLANTS
[AD-A062030] ELECTRIC POWER SUPPLIES	N79-19007	Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes
Filter weight minimization for rectified		on their aerodynamic characteristics
superconducting alternator power supplie	ne	A79-277
for aircraft	es	ENGINE DESIGN
for afforate	A79-26966	
Air Force applications of lightweight	R 7 9 - 20 900	Engine technology for production turbofan engines A79-248
superconducting machinery in airborn	O DONOT	NASA research on general aviation power plants
sources	re boser	[AIAA PAPER 79-0561] A79-258
5042005	A79-27666	Recent General Electric engine development testing
ELECTRIC POWER TRANSMISSION	2.000	for improved service life
The analysis and identification of flux-in	nduced	[SAE PAPER 780990] A79-258
voltage transients on low-loss transmiss		The application of a design verification system
lines with application to the		and accelerated mission testing to gas turbine
Lightning-Transient-Analysis /LTA/ prob	le:	engine development
,,,,,,,,,,,,,,,,,,,,,,,	A79-26246	[SAE PAPER 780991] A79-258
ELECTRICAL MEASUREMENT		TDS - A preliminary design system for turbines
Electric charging of helicopters airci	caft	[SAE PAPER 780999] A79-2589
hazards and static dischargers for accid		Life Cycle Cost in advanced technology engine
prevention		development
[BMVG-FBWT-78-7]	N79-18274	[SAE PAPER 781029] A79-2590
ELECTRONAGNETIC COMPATIBILITY		Applying design-to-life cycle cost methods during
Validation of IEMCAP using the B-52		engine advanced development
Intrasystem Electro Magnetic Compatibil:	ity	[SAE PAPER 781030] A79-259
Analysis Program		Turbine engine cost reduction using Life Cycle
	A79-25326	Cost techniques
BLECTROMAGNETIC INTERPERENCE		[SAE PAPER 781031] A79-259
The impact of the total lightning environs	ment on	Life cycle cost in preliminary engine design
aircraft flight control systems		for F-15
		[SAE PAPER 781032] A79-259
	A79-25319	
Validation of IEMCAP using the B-52		Small fan-jet engines for business aircraft
Intrasystem Electro Magnetic Compatibil:		Small fan-jet engines for business aircraft A79-265
	ıty	Small fan-jet engines for business aircraft A79-2655 Influence of bypass ratio on jet engine weight
Intrasystem Electro Magnetic Compatibil: Analysis Program		Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277:
Intrasystem Electro Magnetic Compatibili Analysis Program ELECTROMAGNETIC POLSES	ıty	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan
Intrasystem Electro Magnetic Compatibil: Analysis Program	A79-25326	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan aerodynamic characteristics
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft	A79-25326	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan aerodynamic characteristics A79-277:
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate	A79-25326 A79-25321 ed with	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan aerodynamic characteristics A79-277: Optimizing gasturbine engine flexible rotor
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other	A79-25326 A79-25321 ad with	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan aerodynamic characteristics A79-277: Optimizing gasturbine engine flexible rotor balancing by the LP-search method
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate	A79-25326 A79-25321 ad with coraft	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air	A79-25326 A79-25321 ad with	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTROM BEAM WELDING	A79-25326 A79-25321 ad with craft A79-25322	Small fan-jet engines for business aircraft A79-265: Influence of bypass ratio on jet engine weight A79-277: Influence of bypass ratio change on fan aerodynamic characteristics A79-277: Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277: Design of proportional-plus-integral controllers for multivariable systems
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTROM BEAM WELDING Introduction of electron beam welding in a	A79-25326 A79-25321 ad with craft A79-25322	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTROM BEAM WELDING	A79-25326 A79-25321 and with coraft A79-25322	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production	A79-25326 A79-25321 ad with craft A79-25322	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects N79-189
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL	A79-25326 A79-25321 ad with craft A79-25322 aircraft A79-25248	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems Airbreathing engines - aerodynamic aspects ENGIBE IBLETS
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environm	A79-25326 A79-25321 ad with craft A79-25322 aircraft A79-25248	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects ENGINE INLETS Full-scale engine tests of bulk absorber acoustic
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL	A79-25326 A79-25321 ed with craft A79-25322 Arrcraft A79-25248 ment on	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems Arbreathing engines - aerodynamic aspects N79-1899 ENGINE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems	A79-25326 A79-25321 ad with craft A79-25322 Arreraft A79-25248 ment on A79-25319	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems Arbreathing engines - aerodynamic aspects BNGIBE IBLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, giving	A79-25326 A79-25321 ad with coraft A79-25322 Aircraft A79-25248 ment on A79-25319	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects BNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268. Sound radiation from hyperboloidal inlet ducts
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAN WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can	A79-25326 A79-25321 ad with coraft A79-25322 Aircraft A79-25248 ment on A79-25319	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] A79-268
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, giving	A79-25326 A79-25321 ad with craft A79-25322 Arreraft A79-25248 ment on A79-25319 ag be	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects ENGIBE IBLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medium
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAN WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can	A79-25326 A79-25321 ad with coraft A79-25322 Aircraft A79-25248 ment on A79-25319	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects FNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medital-
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned	A79-25326 A79-25321 ad with craft A79-25322 Arrcraft A79-25248 ment on A79-25319 ag be A79-26761	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects FNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medital-
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAR WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, giving particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES	A79-25326 A79-25321 ad with craft A79-25322 Arrcraft A79-25248 ment on A79-25319 ag be A79-26761	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects N79-189 ENGINE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] A79-2689
Intrasystem Electro Magnetic Compatibility Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associated EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, giving particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna	A79-25326 A79-25321 A79-25322 A79-25322 A79-25319 A79-26761	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BEGINE NOISE
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTREMEASURES A proposed integrated ECH system using the	A79-25326 A79-25321 A79-25322 A79-25322 A79-25319 A79-26761	Small fan-jet engines for business aircraft A79-265. Influence of bypass ratio on jet engine weight A79-277. Influence of bypass ratio change on fan aerodynamic characteristics A79-277. Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277. Design of proportional-plus-integral controllers for multivariable systems A79-282. Airbreathing engines - aerodynamic aspects FNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] A79-268: Airbreathing engines - aerodynamic aspects
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERMASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GFS /Global Positioning System/ ar electronic counter measures TACAN sy	A79-25326 A79-25321 avith craft A79-25322 aircraft A79-25248 ment on A79-25319 ig be A79-26761	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects FNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] A79-268 Airbreathing engines - aerodynamic aspects N79-1892 ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTREMMASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar	A79-25326 A79-25321 A79-25322 A1rcraft A79-25248 Ment on A79-25319 Ment on A79-26761	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BEGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689 A79-2689 A79-2689 A79-2689 A79-2689 A79-2689
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability	A79-25326 A79-25321 avith craft A79-25322 aircraft A79-25248 ment on A79-25319 ig be A79-26761	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects BNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform mediuser contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BNGIHE HOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERMASURES A proposed integrated ECH system using the constant index lens antenna Navstar/GFS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT	A79-25326 A79-25321 ad with coraft A79-25322 aircraft A79-25248 ment on A79-25319 aig be A79-26761 a79-24726 dd sstem A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects FNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268 Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] A79-268 Airbreathing engines - aerodynamic aspects N79-1892 ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2681 The effect of throttling on forward radiated fan noise
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electronic	A79-25326 A79-25321 A79-25321 A79-25322 A17Craft A79-25248 Ment on A79-25319 Ment on A79-26761 A79-24726 A79-24726 A79-24726 A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BEGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] A79-269
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERMASURES A proposed integrated ECH system using the constant index lens antenna Navstar/GFS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT	A79-25326 A79-25321 ed with craft A79-25322 aircraft A79-25248 ment on A79-25319 ig be A79-26761 e A79-24726 id stem A79-25492 ic lightning	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects BNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform mediu contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BNGIBE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERMASURES A proposed integrated ECH system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electrons systems against the indirect effects of	A79-25326 A79-25321 A79-25321 A79-25322 A17Craft A79-25248 Ment on A79-25319 Ment on A79-26761 A79-24726 A79-24726 A79-24726 A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects ENGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] Evaluation of two inflow control devices for flight simulation of fan noise using a J715D
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environ aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electrons systems against the indirect effects of	A79-25326 A79-25321 A79-25321 A79-25322 A17Craft A79-25248 Ment on A79-25319 Ment on A79-26761 A79-24726 A79-24726 A79-24726 A79-25492 A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BEGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689 Airbreathing engines - aerodynamic aspects BEGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] Bvaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electronic systems against the indirect effects of ELEVATION ANGLE ESTIMATION OF TARGET ELEVATION angle from	A79-25326 A79-25321 A79-25321 A79-25322 A17Craft A79-25248 Ment on A79-25319 Ment on A79-26761 A79-24726 A79-24726 A79-24726 A79-25492 A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects BNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medius-contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BNGIHE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689 Arbreathing engines - aerodynamic aspects N79-1899 ENGIHE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC POLSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environ aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electrons systems against the indirect effects of	A79-25326 A79-25321 ad with craft A79-25322 A1rcraft A79-25248 ment on A79-25319 Be A79-26761 A79-24726 dd stem A79-25492 cc lightning N79-18238 2-D radars	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects ENGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] Evaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine [AIAA PAPER 79-0654] Experiments concerning the anomalous behaviour of
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electronic systems against the indirect effects of ELEVATION ANGLE ESTIMATION OF TARGET ELEVATION angle from	A79-25326 A79-25321 A79-25321 A79-25322 A17Craft A79-25248 Ment on A79-25319 Ment on A79-26761 A79-24726 A79-24726 A79-24726 A79-25492 A79-25492	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268 ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] Evaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine [AIAA PAPER 79-0654] Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electronic systems against the indirect effects of ELEVATION ANGLE ESTIMATION OF TARGET ELEVATION angle from	A79-25326 A79-25321 ad with craft A79-25322 A1rcraft A79-25248 ment on A79-25319 Be A79-26761 A79-24726 dd stem A79-25492 cc lightning N79-18238 2-D radars	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects BNGIBE INLETS Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medius-contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects BNGIHE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689 Arbreathing engines of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2689 ENGIHE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0640] A79-2699 Evaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine [AIAA PAPER 79-0648] Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight [AIAA PAPER 79-0648] A79-2699
Intrasystem Electro Magnetic Compatibil: Analysis Program ELECTROMAGNETIC PULSES EMP coupling to a composite aircraft Properties of induced transients associate EM fields produced by lightning or other relatively slow rise-time EMP in air ELECTRON BEAM WELDING Introduction of electron beam welding in a production ELECTRONIC CONTROL The impact of the total lightning environs aircraft flight control systems Problems of computer-aided tracking, givin particular attention to radar which can electronically turned ELECTRONIC COUNTERNEASURES A proposed integrated ECM system using the constant index lens antenna Navstar/GPS /Global Positioning System/ ar electronic counter measures TACAN sy vulnerability ELECTRONIC EQUIPMENT Protection/hardening of aircraft electronic systems against the indirect effects of ELEVATION ANGLE ESTIMATION OF TARGET ELEVATION angle from	A79-25326 A79-25321 ad with craft A79-25322 A1rcraft A79-25248 ment on A79-25319 Be A79-26761 A79-24726 dd stem A79-25492 cc lightning N79-18238 2-D radars	Small fan-jet engines for business aircraft A79-265 Influence of bypass ratio on jet engine weight A79-277 Influence of bypass ratio change on fan aerodynamic characteristics A79-277 Optimizing gasturbine engine flexible rotor balancing by the LP-search method A79-277 Design of proportional-plus-integral controllers for multivariable systems A79-282 Airbreathing engines - aerodynamic aspects Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] Sound radiation from hyperboloidal inlet ducts [AIAA PAPER 79-0677] Propagation of buzz-saw noise in a nonuniform medit contoured jet engine inlets [AIAA PAPER 79-0639] Airbreathing engines - aerodynamic aspects ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-268 ENGINE NOISE Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] The effect of throttling on forward radiated fan noise [AIAA PAPER 79-0640] Evaluation of two inflow control devices for flight simulation of fan noise using a JT15D engine [AIAA PAPER 79-0654] Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight

SUBJECT INDEX EXHAUST NOZZLES

Effects of simulated forward flight on jet	noise,	EQUATIONS OF STATE	
Shock noise and internal noise	A79-26936	Theoretical investigations of real gas eff cryogenic wind tunnels	ects in
[AIAA PAPER 79-0615] Plight effects on noise generated by the JT		[DS-PB-76/50B]	N79-17820
engine with inverted primary/fan flow as	V	EQUATORIAL ATHOSPHERE	
measured in the NASA-Ames 40- by 80-foot	wind	Design specifications for the capped ballo	ons with
tunnel		special reference to their survival in t	he
	179-26937	equatorial tropopause	
Radiation of an acoustic source near the tra	alling	[AIAA 79-0426] BQUILIBRIUE BQUATIONS	A79-26635
edge of a wing in forward motion [AIAA PAPER 79~0605]	A79-26940	Nonlinear equations of equilibrium for ela	stic
Combustion noise prediction update	A77 20340	helicopter or wind turbine blades underg	
	A79-26942	moderate deformation	,,
Unsteady stator response to upstream rotor		[NASA-CR-159478]	N79-19410
	A79-26945	EQUIPMENT SPECIFICATIONS	
Aerodynamic and acoustic comparisons of		Validation of MIL-F-9490D: General specif	
Scaled-down and actual engine jets	170. 26046	for flight control system for piloted mi aircraft. Volume 1: Summary of YF-17 a	
[AIAA PAPER 79~0574] ENGINE PARTS	A79-26946	validations	ind C-JA
Causes for the deterioration of splined		[AD-A061807]	N79-19008
connections in aircraft engines during se	rvice	Validation of MIL-P-9490D: General specif	
	A79-25249	for flight control system for piloted mi	litary
Residual-stress formation during the thermal		aircraft. Volume 2: YF-17 lightweight	fighter
hardening of components in gas-turbine en		validation	
	A79-26828	[AD-A062008]	ท79-19009
Thermal cycling endurance problems in gas-to parts	urdine	BSCAPE (ABANDONNERT) Helicopter underwater escape trainer (9D5)	
	A79-26838	nelicopter underwater escape trainer (303)	N79-19665
Prediction of gas-turbine alloy creep	M17 20050	Barlout from autorotating helicopters	1177 13003
characteristics			N79-19666
	A79-26841	ETHYL ALCOHOL	
ENGINE STARTERS		Methanol, ethanol and jet fuel emissions	
An unstable subsynchronous critical speed so		comparison from a small gas turbine	
of shaft failures in F-16 engine star		[SAE PAPER 781013]	A79-25893
	A79-25916	EVAPORATION	nana 64
ENGINE TESTS Dynamic data analysis qas turbine enqine	_	Intensification of fuel vaporization in ai qas turbine engines by electrical forces	CLAIC
Vibration transducers	e	gas curbine engines by electrical forces	, A79-27748
	A79-25845	EXHAUST DIFFUSERS	1177 27740
Recording methods for steady state and trans		Diffusers for gas turbine combustion syste	ens
signals aircraft engine tests		•	N79-19369
	A79-25849	EXHAUST GASES	
Recent General Electric engine development	testing	Methanol, ethanol and jet fuel emissions	
for improved service life		comparison from a small gas turbine	130 25002
	A79-25876	[SAE PAPER 781013]	A79-25893
Planning the development and qualification property for the next generation of high technology		IR scanning camera measurements of an exha plume from an axisymmetric nozzle afterb	
aircraft engines	7	model at transonic Mach numbers	ouy
	A79-25878	model de clansonio ndon numbero	A79-28097
Requirements and constraints in the develop		Time degradation factors for the turbine e	
and qualification of gas turbine engines		exhaust emissions. Volume 1: Program	
Navy		description and results air pollution	
	A79-25879	[NREC-1238-6-VOL-1]	N79-17860
Operational experience with linked-blade		Time degradation factors for the turbine e	
high-output gas-turbine	A79-26830	exhaust emission. Volume 2: JT8D-9 tes	it uata
Aerodynamic and acoustic comparisons of	n/3~20030	[NREC-1238-7-VOL-2]	N79-17863
scaled-down and actual engine jets		Time degradation factors for turbine engin	
	A79-26946	exhaust emissions. Volume 3: JT3D-7 tes	
A decision theory model for health monitoring	ng of	air pollution control	
aeroengines metal particles in lubric	ating		N79-17864
Oils as wear indicator	70 00004	Time degradation factors for turbine engin	
ENTRAINMENT	A79-28381	<pre>exhaust emissions. Volume 4: JT3D-7 te air pollution control</pre>	est data
Overestimates of entrainment from wetting of	e	[NREC-1238-9-VOL-4]	N79-17865
aircraft temperature sensors in cloud	L	Time degradation factors for turbine engin	
	A79-25296	exhaust emissions. Volume 6: JT9D-3A t	
ENVIRONMENT EPPECTS		air pollution control	
Supersonic combat aircraft design		[NREC-1238-11-VOL-6]	N79-17867
	A79-27363	Time degradation factors for turbine engin	
ENVIRONMENT HODELS		exhaust emissions. Volume 7: RB211-22B	test data
Environmental models for moisture absorption	n by	air pollution control	m30 43060
aircraft composites	170_27572	[NREC-1238-12-VOL-7] Time degradation factors for turbine engin	N79-17868
ENVIRONMENT SIMULATORS	A79-27572	exhaust emissions. Volume 8: C700-2D t	
Evaluation of IPR handling qualities of		[NREC-1238-13-VOL-8]	N79-17869
helicopters using the NAE airborne V/STOL		Comparisons of turbine engine combustor ex	
simulator		emissions measurements using three gas-s	
[AIAA 79-0702]	A79-27365	probe designs	
BHVIRONHENTAL BEGINEBRING		[AD-A061733]	N79-19005
Advancements in helicopter cockpit technolog		EXHAUST NOZZLES	
	N79-19625	The influence of geometric asymmetry on the	
ENVIRONMENTAL TESTS Recent advances in indirect lightning effect	+e	downstream of row of jets discharging no into a free stream	rmarra
Recent advances in indirect lightning effect research	La	THEO & ILEC SCHOOL	A79-25065
	A79-25313	Noise from struts and splitters in turbofa	
EQUATIONS OF MOTION		ducts	
Inertial dynamics of a general purpose rotor	C	[AIAA PAPER 79-0637]	A79-26923
	N79-18916		

EXHAUST SYSTEMS SUBJECT INDEX

EXHAUST SYSTEMS	1-1	Environmental effects on crack growth in	1075 m/
An acoustic problem in anechoic chambers a from exhaust noise testing	arising	flight-simulation tests on 2024-T3 and 7 material	0/5-1e
[AIAA PAPER 79-0649]	A79-26929	[NLR-TR-76104-U]	N79-18012
EXTERNAL STORES		PREDBACK CONTROL	
New airborne armament systems multimi: design requirements	SSION	Plight testing the Kfir	A79-26530
[AIAA 79-0697]	A79-27362	Design of proportional-plus-integral contr	
EYE HOVERENTS		for multivariable systems	
Visual pockets: A design parameter for he instrument panels	ericobter	FIBER OPTICS	A79-28223
tungs and the factor	N79-19641	Military fiber optics applications	
F			A79-28040
•		FIBERS Aerodynamic behavior of fibres and samplin	of of
P-4 AIRCRAFT		respirable dust	19 01
Direct drive control valve for fly-by-wire	e flight	[BLL-RTS-11267]	N79-18470
control system actuators [AD-A062030]	N79-19007	FIGHTER AIRCRAFT The prediction of fatigue crack growth und	le r
P-15 AIRCRAPT	11.5 15007	flight-by-flight loading	
Life cycle cost in preliminary engine des	ıgn		A79-25482
for F-15 [SAE PAPER 781032]	A79-25904	Fundamentals of design. I - 'Whys' and 'wherefores' of wings	
A water tunnel flow visualization study of		wheretores of wrings	A79-25485
[NASA-CR-144878]	N79-18286	Applying design-to-life cycle cost methods	during
P-16 BIRCRAPT An unstable subsynchronous critical speed	solution	engine advanced development [SAE PAPER 781030]	A79-25902
of shaft failures in F-16 engine sta		Ski-jump - A great leap for tactical airpo	
SAE PAPER 781055]	A79-25916	V/STOL jet launching from upward-incline	
F-16 high angle of attack testing	A79-26527	[AIAA 79-0696] Supersonic combat aircraft design	A79-27361
F-16 high angle of attack testing	2002,	[AIAA 79-0699]	A79-27363
D 47 ATDODARM	N79-18886	Recent developments in active control tech	nology
F-17 AIRCRAFT Validation of MIL-F-9490D: General speci:	fication	for fighter aircraft design [AIAA 79-0708]	A79-27368
for flight control system for piloted m	ılıtary	Enhanced capabilities of future fighters a	
aircraft. Volume 1: Summary of YF-17	and C-5A	result of HiMAT	
validations [AD-A061807]	N79-19008	[AIAA 79-0698] Multimode radar processor for combat a	A79-27370
F-18 AIRCRAFT		# 120220 2-112 F-10082-1	A79-28058
F-18 status report	170 26F20	Aeroelastic tailoring studies in fighter a	ırcraft
F-102 AIRCRAFT	A79-26529	design [AIAA 79-0725]	A79-28257
Measured and predicted noise of the AVCO-	Lycoming	Engine dynamics	
YF-102 turbofan engine	170 26077	[BMVG-FBWT-78-6]	N79-17862
[AIAA PAPER 79-0641] PABRICATION	A79-26877	Development of smart target for simulation one-on-one air-to-air combat	OI
Fabrication and quality assurance procedure	re to	[AD-A056739]	N79-17879
assure a symmetrical lifting parachute	170-26626	F-18 status report	N70 . 10000
Design and fabrication of advanced titania	A79-26636	FINITE DIFFERENCE THEORY	N79-18888
structures		Numerical study of unsteady flows of visco	
[AIAA 79-0757] PACTOR AWALYSIS	A79-28272	incompressible fluids about airfoils by	
The continuity factor in aircraft develops	ment	combined method of order 0/h2/ and 0/h4/	A79-24829
	N79-18896	An alternating direction explicit method f	or
FAIL-SAFE SYSTEMS SIFT - Design and analysis of a fault-tole	arant	computing three-dimensional viscous flow in turbomachines	fields
computer for aircraft control Softwa		[SAE PAPER 781001]	A79-25884
Implemented Fault Tolerant systems		FINITE ELEMENT METHOD	
FAILURE ANALYSIS	A79-25718	A shock capturing application of the finit element method to viscous compressib	
Failure studies of a third stage fan disk	from a	problem	
TF-30 turbine engine [AD-A061801]	N70 4000"	·	A79-24771
FANS	N79-19004	Analysis of longitudinal natural vibration deformable aircraft by the finite-elemen	
Reduction of rotor-turbulence interaction	noise in	delormable director by the rinter cremen	A79-25505
static fan noise testing	170 26025	Wave propagation in ducts using the finite	element
[AIAA PAPER 79-0656] FAR PIELDS	A79-26925	method for aircraft noise reduction [AIAA PAPER 79-0659]	A79-26879
Aircraft antenna pattern measurements usin	ng near	A finite element subvolume technique for	
field techniques	A79-24721	structural-borne interior noise predicti	on
Separation of core noise and jet noise	879-24721	in aircraft [AIAA PAPER 79-0585]	A79-26882
[AIAA PAPER 79-0589]	A79-26941	Time marching finite area method	
FATIGUE (HATERIALS) Four lectures on fatigue crack growth		h chace and chrain analysis of industrial	N79-18990
1 200 1200 on Lucayac Cluck Glowin	A79-25484	A stress and strain analysis of industrial compressor impellers using the framework	
PATIGUE LIFE		finite element method and descriptiv	e geometry
Design against fatigue - Current trends aircraft structural reliability	for	Rynorimontal and finite element investigat	N79-19391
[AIAA 79-0689]	A79-27355	Experimental and finite element investigat the buckling characteristics of a beaded	
FATIGUE TESTS		panel for a hypersonic aircraft	
An unstable subsynchronous critical speed of shaft failures in F-16 engine sta		FIRE CONTROL	N79-19412
[SAE PAPER 781055]	A79-25916	Reliability growth planning to achieve PIW	/GMTBP
		requirements for an airborne radar	
			A79-24965

SUBJECT INDEX FLIGHT PLANS

SEATRACKS - A millimeter wave radar fire	control	Plying NASA's Terminal Configured Vehicle	2022054
system		the Microwave Landing System	•
Estimation of target elevation angle from	A79-27144 2-D radars	The U-2 story	A79-26534 A79-26537
FIRE EXTINGUISHERS	A79-27145	Parachute inflation control using an attac	
New agents for the extinguishment of maging [AD-A061664]	nesium fires N79-19122	(AIÁA 79-0449] Air fleet and facility planning via optima	A79-26653
FIRB FIGHTING Aircraft fire protection and rescue proce //2nd edition/ Book	edures	control models Study of the structure of an integrated sy	A79-26725
Full-scale fire modeling tests of a compa		flight control, navigation and display	A79-27674
response foam and dry chemical powder of system	. ,	Tests of an integrated piloting, navigatio display system	•
[FAA-NA-78-24] PIRE PREVENTION	ห79-17825	Configuration management and automatic con	A79-27675 strol of
Development of fire test methods for airp interior materials	plane	an augmentor wing aircraft with vectored	l thrust N79-17872
[NASA-CR-160119]	N79-19112	Development of the L-1011 flight managemen	t system
FIREBEE 2 TARGET DROWE AIRCRAFT The development of the DAST I remotely po	loted	Validation of MIL-F-9490D: General specif	N79-18895 ication
research vehicle for flight testing an flutter suppression control system		for flight control system for piloted mi aircraft. Volume 1: Summary of YF-17 a	
[NASA-CR-144881] FIRES	N79-17849	validations [AD-A061807]	N79-19008
Pool fire radiation through a door in a s aircraft fuselage		Validation of MIL-F-9490D: General specif for flight control system for piloted mi	.litary
[PAA-NA-78-38] New agents for the extinguishment of magn	N79-17966 nesium fires	aircraft. Volume 2: YF-17 lightweight validation	•
[AD-A061664] PIXED WINGS	N79-19122	[AD-A062008] FLIGHT CREWS	N79-19009
Advanced system design requirements for l small fixed-wing aerial application sys		US Army aviation fatigue-related accidents 1977	, 1971 -
agriculture [NASA-CR-158939]	N79-17848	Design procedure for an information transf	N79-19621 er
PLANE PROPAGATION Aerodynamics of flame jets Russian bo	ook	method CUBITS for allocating panel area aircrew station controls and displays	for
	A79-26355		N79-19631
Thermal response of composite panels		The approach to crew protection in the cra environment for the YAH-64	
PLAT PLATES	A79-25350	FLIGHT PATIGUE	N79-19664
Aerodynamic properties of a flat plate wi for optical-propagation studies	ith cawity	US Army aviation fatigue-related accidents	, 1971 -
[NASA-TM-78487]	N79-17796		N79-19621
The 1-4-1 system of jack movements for the	ne	PLIGHT HAZARDS Recent advances in indirect lightning effe	cts
flexible liners of supersonic wind tunn	nels A79-26594	research	A79-25313
Optimizing gasturbine engine flexible rot balancing by the LP-search method		Properties of induced transients associate 3M fields produced by lightning or other	
FLEXIBLE WINGS	A79-27745	relatively slow rise-time EMP in air	
Combined strength and aeroelastic wing sy	nthesis	Aviation obstructions and the particular	
via constraint approximation [AIAA 79-0724] FLIGHT	A79-28290	conditions for construction projects in vicinity of airports	A79-25372
Heat generation in cavities at high veloc	ity flights	Parachute partial inversions	
resonance-pipe effect [BMVG-FBWT-77-28]	N79-17815	[AIAA 79-0451] Stable boundary layer wind shear model for	A79-26655
PLIGHT ALTITUDE Apparatus for measuring an aircraft's spe	eed and	aircraft flight hazard definition	A79-27575
height [NASA-CASE-LAR-12275-1]	N79-18296	PLIGHT INSTRUMENTS Advancements in helicopter cockpit technol	.ogy
PLIGHT CHARACTERISTICS Comparison of BTJES and TJE characterists	ics in	Design procedure for an information transf	N79-19625
supersonic cruising flight Bypass T Engine		method CUBITS for allocating panel area aircrew station controls and displays	
FLIGHT CONDITIONS	A79-27740	Visual pockets: A design parameter for he	N79-19631
Coaxial jet noise in flight [AIAA PAPER 79-0636]	A79-26919	instrument panels	N79-19641
An alrhorne reference noise source for st		PLIGHT LOAD RECORDERS	179-19041
airplane flyover noise propagation and [AIAA PAPER 79-0650]	measurement A79-26928	Statistical review of counting acceleromet for Navy and Marine fleet aircraft	er data
Experiments concerning the anomalous beha aero-engine exhaust noise in flight	viour of	[AD-A061894] PLIGHT PATHS	N79-18972
[AIAA PAPER 79-0648]	A79-26930	Worst case time-histories causing largest	
PLIGHT CONTROL Control system time response optimization		deviations from a desired flight pathenalytical approach	
nonlinear programming approach for flight	aircraft	[VTH-LR-267] PLIGHT PLANS	N79~17839
[AIAA PAPER 79-0540] Plight testing the Kfir	A79-25859	Hardware and software structure of a coord system for air traffic control on the ba	
	A79-26530	flight plan data	
			A79-26760

FLIGHT SAFETY SUBJECT INDEX

FLIGHT SAFETY Control of the location of the center of gravion of loaded aircraft	ıty	The need of stick force stability for attitude-stabilized aircraft, Part 2 [NLR-TR-77027-H]	N79-17875
	9-25370	Environmental effects on crack growth in flight-simulation tests on 2024-T3 and 70	
	9-25541	material	N79-18012
	9-25542	F-18 status report	N79-18888
	9-26130	Flight testing the KFIR	N79-18889
[PAA-NA-78-8] Analysis of the functional reguirements for a	9-17840	The Learjet Longhorn series: The first jet winglets	s with
	9-18962 PI	LIGHT TRAINING	N79-18893
PLIGHT SIMULATION Recent General Electric engine development tes	sting	Visual simulation devices for flight trainis simulators Russian book	-
	9-25876 PI	IR DETECTORS	A79-26354
Simulation studies of the flight dynamics of gliding parachute systems	0 00000 77		A79-24958
A simple physical model of a descending parach		OW CHARACTERISTICS Experimental investigation of the effect of	
Flight simulation of a vehicle with a two-stage	9-26651 ge	surface discontinuity on step-backward flo	ow A79-27000
parachute system [AIAA 79-0448] A79	FI 9-26652	OW DEFLECTION The 1-4-1 system of jack movements for the	
Evaluation of two inflow control devices for flight simulation of fan noise using a JT151		flexible liners of supersonic wind tunnel	s A79-26594
engine	9-26926	Vortex models on missile configurations	
Experiments concerning the anomalous behaviour		computer program for determining aerodyna coefficients and flow deflection	
		OW DISTORTION	N79-17814
Effects of simulated forward flight on jet noi shock noise and internal noise	ıse,	Effects of inflow distortion profiles on far noise calculated using a 3-D theory	n tone
[AIAA PAPER 79-0615] Stable boundary layer wind shear model for	9-26936	[AIAA PAPER 79-0577] Aerodynamic and Mechanical factors affecting	179-26911 g the
aircraft flight hazard definition A79	9-27575	surge line: Inlet flow distortion influe axial flow compressors	
Environmental effects on crack growth in flight-simulation tests on 2024-T3 and 7075-	-T6 FL		N79-19363
material	9-18012	An alternating direction explicit method for computing three-dimensional viscous flow:	
FLIGHT SIMULATORS Visual simulation devices for flight training	10012	ın turbomachines	A79-25884
simulators Russian book	26754	An improved supersonic, three-dimensional,	479-23004
F-18 status report	9-26354		N79-17807
Airline approach to CAT III	9-26529	Analysis of some aerodynamic characteristics to wing-jet interaction	
Aviation wide angle visual system /AWAVS/ - Vi	9-26533 isual	Wings	N79-18917
	9-28161	Some recent progress in transonic flow compo	
Two-segment approach investigation on a moving-base piloted flight simulator		flow distribution, numerical optimization and airfoil design	
PLIGHT STABILITY TESTS		OW EQUATIONS	N79-18946
Aeroservoelastic stability analysis of an airp with a control augmentation system	plane	Contribution to the development of theoretic calculations for the design and optimizat:	
	9-19006	lifting bodies. (Solution of three-dimens basic thermo fluid dynamics equations with	sional
F-16 high angle of attack testing	9-26527	strong interacting attached and separated fields)	
F-18 status report	9-26529		179-17816
Flight testing the Kfir			79-19387
The Learjet Longhorn series - The first jets winglets	ith	The influence of geometric asymmetry on the downstream of row of jets discharging nor into a free stream	
The continuity factor in aircraft development	9-26532	1	A79-25065
Development and testing of a shipboard launche		OW STABILITY Axial compressor operation with radially	
	9-26631		479-27743
Flight effects on noise generated by the JT8D engine with inverted primary/fan flow as		OW VISUALIZATION A visual investigation of the separation and	
measured in the NASA-Ames 40- by 80-foot win tunnel		subsequent transition near the leading edd	-
XV-15 Tilt Rotor Research Aircraft - Program r		On sound radiation from the trailing edge of	179-25863 E an
The development of the DAST I remotely piloted	9-27371 l		79-26907
research vehicle for flight testing an activ flutter suppression control system		A water tunnel flow visualization study of t [NASA-CR-144878]	he F-15 779-18286
[NASA-CR-144881] N79) - 17849		

SUBJECT INDEX GAS GENERATORS

FLUID DYNAMICS Outlet air angle prediction for subsonic flow		Effect of a chromium-containing fuel additanted hot corrosion	
	9-18997	Intensification of fuel vaporization in air	A79-26506 craft
PLUID PILTERS	~	gas turbine engines by electrical forces	A79-27748
Separation and investigation of wear particles from aero-engines	S	PUEL CONSUMPTION	A/9-2//40
	9-17856	An analysis of fuel conserving operational	
PLUID INJECTION		procedures and design modifications for	
Instability of fluid flow in centrifugal injec		bomber/transport aircraft. Volume 1: 2:	ecutive
	9-27731	Summary	
PLOTTER		[AD-A061746]	F79-18969
The development of the DAST I remotely piloted research vehicle for flight testing an activ		FUEL INJECTION Fuel injection	
flutter suppression control system	• •	ruer injection	N79-19368
	9-17849	FUEL SYSTEMS	
Turbomachinery flutter: Introductory concepts		Helicopter crashworthy fuel systems and the	elr
	9-19353	effectiveness in preventing thermal injur	
Identification of various flutter regimes and discussion of dynamic stall		A method for selecting a crashworthy fuel s	N79-19660
	9-19354	design	,,500
PLUTTER ANALYSIS			N79-196€1
Aeroelastic addition to NASTRAN		PUEL TANKS	
	9-17812	Puel tank sealant requirements for advance	high
Investigation of torsion free wing trend flutt	ter	performance aircraft	A79-28288
models [AD~A061942] N79	9-18957	[AIAA 79-0807] FUEL TESTS	A 79-20200
PLY BY WIRE CONTROL	, 1055.	Effects of fuel properties on soot formation	on in
Flight testing the Kfir		turbine combustion	
	9-26530	[SAE PAPER 781026]	A79-25899
Direct drive control valve for fly-by-wire fli	ıght	Pvaluation of the application of some gas	
control system actuators [AD-A062030] N79	9-19007	chromatographic methods for the determina properties of synthetic fuels	tion or
POARS	3-13001	brobercies or alucuecto ruers	A79-25917
Full-scale fire modeling tests of a compact ra	apıd	FUELS	
response foam and dry chemical powder disper	nsing	Pool fire radiation through a door in a sig	ulated
system	0 17005	aircraft fuselage	W70 17066
[PAA-NA-78-24] N79 FORCE DISTRIBUTION	9-17825	[FAA-NA-78-38] FULL SCALE TESTS	N79-17966
Aerodynamic side-force alleviator means		Design criteria for and development of Kevi	lar
	9-17813	ribbon parachutes	
POREBODIES		[AIAA 79-0430]	A79-26638
Theoretical lower limits of forebody drag	0.000	Plight simulation of a vehicle with a two-s	stage
A first-order theory for the effects of line t	9-26593	parachute system [AIAA 79-0448]	A79-26652
on parachute deployment	cies	Full-scale engine tests of bulk absorber ac	
	9-26654	inlet treatment	
Aerodynamic side-force alleviator means		[AIAA PAPER 79-0600]	A79-26881
	9-17813	Coaxial jet noise in flight	170 26010
PRACTURE MECHATICS Application of fracture mechanics to design	Book	[AIAA PAPER 79-0636] XV-15 Tilt Rotor Research Aircraft - Progra	A79-26919
	9-26980		A79-27371
Fracture mechanics and fail-safe design for		Full-scale fire modeling tests of a compact	
helicopter rotor structures		response foam and dry chemical powder dis	spensing
	9-26986	system	n20 47025
Pactors affecting residual strength prediction a cracked aircraft structure	ı or	[FAA-NA-78-24] FUSELAGES	N79-17825
	9-28380	Characteristics of propeller noise on an an	rcraft
Advanced Turbine Engine Gas generator (ATEGG)		fuselage related to interior noise transi	
fractography of cast nickel base superalloys			A79-26932
	9-19149	Noise transmission - Turboprop problem	X70-26022
Practure mechanics for structural adhesive bon part 2, phase 2	ius,	[AIAA PAPER 79-0645] Crashworthiness tests on model aircraft fus	A79-26933 selage
	9-19418	structures	-
PREE PLOW		[AIAA 79-0688]	A79-27354
The influence of geometric asymmetry on the fl	Low	_	
downstream of row of jets discharging normal	lly	G	
into a free stream	9-25065	GAS CHROHATOGRAPHY	
Pressure and heat-transfer distributions in a		Evaluation of the application of some gas	
simulated wing-elevon cove with variable lea	akage	chromatographic methods for the determina	tion of
at a free-stream Mach number of 6.9		properties of synthetic fuels	
[NASA-TM-74095] N79 PRBOUENCY ASSIGNMENT	9-18284	GAS DYNAMICS	A79-25917
FAA remote terminal system frequency assignmen	nt.	Design of multistage compressors with	
model		consideration of the real behavior of gas	and
	9-25323	gas mixtures	
PREQUENCY RANGES	-	ALC BLAN	ห79-19390
Two-frequency-range theory of unstable turbule	ent	GAS PLOW	
<pre>combustion oscillations in a jet engine combustion chamber. II - Analysis of the</pre>		Plane problems of aerothermooptics refi	.uction
characteristic equation and comparison with			A79-26865
experiment		GAS GENERATORS	
	9-27728	Advanced Turbine Engine Gas generator (ATEC	
FUBL COMBUSTION Effects of fuel properties on soot formation i	1 n	fractography of cast nickel base superall [AD-A061701]	loys ท79-19149
turbine combustion	- 11	(ab Roottoi)	13143
	9-25899		

GAS INJECTION SUBJECT INDEX

GAS INJECTION	Time degradation factors for turbine engine
Laminar boundary layer with foreign gas injection	exhaust emissions. Volume 3: JT3D-7 test data
on a conical body	air pollution control [NREC-1238-8-VOL-3] N79-17864
A79-27203 GAS JETS	[NREC-1238-8-VOL-3] N79-17864 Time degradation factors for turbine engine
Aerodynamics of flame jets Russian book	exhaust emissions. Volume 4: JT3D-7 test data
A79-26355	air pollution control
GAS MIXTURES	[NREC-1238-9-VOL-4] N79-17865
Design of multistage compressors with	Time degradation factors for turbine engine
consideration of the real behavior of gas and gas mixtures	exhaust emissions. Volume 6: JT9D-3A test data air pollution control
N79-19390	[NREC-1238-11-VOL-6] N79-17867
GAS RECOVERY	Time degradation factors for turbine engine
Study of hydrogen recovery systems for gas vented	exhaust emissions. Volume 7: RB211-22B test data
while refueling liquid-bydrogen fueled aircraft [NASA-CR-158991] N79-18057	air pollution control [NREC-1238-12-VOL-7] N79-17868
GAS TURBINE ENGINES	Time degradation factors for turbine engine
Dynamic data analysis gas turbine engine	exhaust emissions. Volume 8: C700-2D test data
vibration transducers	[NREC-1238-13-VOL-8] N79-17869
A79-25845	Rotor fragment protection program: Statistics on
The application of a design verification system and accelerated mission testing to gas turbine	aircraft gas turbine engine rotor failures that occurred in US commercial aviation during 1976
engine development	[NASA-CR-159474] N79-18977
[SAE PAPER 780991] A79-25877	Comparisons of turbine engine combustor exhaust
Planning the development and qualification process	emissions measurements using three gas-sampling
for the next generation of high technology	probe designs [AD-A061733] N79-19005
aircraft engines [SAE PAPER 780992] A79-25878	Strain gage system evaluation program
Peguirements and constraints in the development	[NASA-CR-159486] N79-19314
and qualification of gas turbine engines for the	Combustion problems in gas turbine applications
Navy	[VKI-LECTURE-SERIES-93] N79-19365
[SAE PAPER 780994] TDS - A preliminary design system for turbines	Diffusers for gas turbine combustion systems N79-19369
[SAE PAPER 780999] A79-25882	Ignition in the gas turbine
Integrally cast turbine rotor for high volume	N79-19372
production	GAS_TORBINES
[SAE PAPER 781000] A79-25883	Time degradation factors for turbine engine
Environmental factors affecting the installation and operation of gas turbine engines in	exhaust emissions. Volume 5: JT3D-3B test data air pollution control
agricultural aircraft	[NREC-1238-10-VOL-5] N79-17866
[SAE PAPER 781010] A79-25892	Combustion in the gas turbine, parts 1, 2, 3
Methanol, ethanol and jet fuel emissions	N79-1936€
comparison from a small gas turbine [SAE PAPER 781013] A79-25893	GEARS Advanced technology applied to the CH-47D drive
Residual-stress formation during the thermal	system
hardening of components in gas-turbine engines	[SAE PAPER 781040] A79-25908
A79-26828	The Lynx transmission and Conformal gearing
Operational experience with linked-blade high-output gas-turbine	helicopter drive train [SAE PAPER 781041] A79-25909
A79-26830	Structural development of the Modernized Chinook
Thermal cycling endurance problems in gas-turbine	helicopter transmission gearing
parts	[AIAA 79-0728] A79-28260
A79-26838 Prediction of gas-turbine alloy creep	GENERAL AVIATION AIRCRAFT General aviation aircraft in the 1990's
characteristics	[AIAA PAPER 79-0560] A79-25866
A79-26841	NASA research on general aviation power plants
Potential uses of rapidly solidified alloys in gas	[AIAA PAPER 79-0561] A79-25870
turbine engines	Small fan-jet engines for business aircraft
A79-27313 Comparison of BTJES and TJE characteristics in	A79-26531 Briefs of accidents involving midair collisions,
supersonic cruising flight Bypass Turbojet	US general aviation, 1977
Engine	[NTSB-AMM-78-13] N79-17829
A79-27740 Optimizing gasturbine engine flexible rotor	Briefs of accidents involving rotorcraft, US general aviation, 1977
balancing by the LP-search method	[NTSB-AMM-78-15] N79-17831
A79-27745	Briefs of fatal accidents involving weather as a
Intensification of fuel vaporization in aircraft	cause/factor, US general aviation, 1977
gas turbine engines by electrical forces	[NTSB-AMM-78-16] N79-17832
A79-27748 Design of proportional-plus-integral controllers	Briefs of accidents involving alcohol as a cause/factor, US general aviation, 1977
for multivariable systems	[NTSB-AMM-78-17] N79-17833
A79-28223	Briefs of accidents involving missing and missing
Cold-air performance of free power turbine	later recovered aircraft, US general aviation,
designed for 112-kilowatt automotive gas-turbine	1977
engine. 2: Effects of variable stator-vane-chord setting angle on turbine	[NTSB-AMM-78-18] N79-17834 Briefs of accidents, involving corporate/executive
performance	aircraft, US general aviation, 1977
[NASA-TM-78993] N79-17859	[NTSB-AMM-78-19] N79-17835
Time degradation factors for the turbine engine	Briefs of accidents involving amateur/home built
exhaust emissions. Volume 1: Program description and results air pollution control	aircraft, US general aviation, 1977 [NTSB-AMM-78-20] N79-17836
[NREC-1238-6-VOL-1] N79-17860	Briefs of accidents involving commuter air
Time degradation factors for the turbine engine	carriers and on-demand air taxi operations, US
exhaust emission. Volume 2: JT8D-9 test data	general aviation, 1977
air pollution control [NREC-1238-7-VOL-2] N79-17863	[NTSB-AMM-78-22] N79-17838 Gust load estimation using a simplified power
1 1230 7 TOU 2 J H 17-17003	spectral technique
	[ARAP-362] N79-17870

SUBJECT INDEX HELICOPTERS

Occupant injury mechanisms in civil heli	copter	Advanced overrunning clutch technology	UH-60 A
accidents	W70 40453	helicopter transmission application	
GLASS	N79-19653	[SAE PAPER 781039] An investigation of model helicopter rotor	A79-25907
New agents for the extinguishment of mag	nesium fires	slap at low tip speeds	
[AD-A06 1664]	N79-19122	(AIAA PAPER 79-0613)	A79-26938
GLASS FIBER REIMFORCED PLASTICS Thermal response of composite panels		Practure mechanics and faul-safe design for helicopter rotor structures	r
12011-1 -caponac of boaponice panelo	A79-25350	acitopici ideal suractures	A79-26986
GLIDERS	_	Perspectives of technological development	for
Simulation studies of the flight dynamic gliding parachute systems	sot	helicopters [AIAA 79-0701]	A79-27364
[AIAA 79-0417]	A79-26628	Structural development of the Modernized C	
GLOBAL POSITIONING SYSTEM	_	helicopter transmission gearing	
Navstar/GPS /Global Positioning System/ electronic counter measures TACAN		[AIAA 79-0728] Structural stiffening of transmission hous	A79-28260
vulnerability	3,000	with metal matrix materials	ings
ADADETER BRANC CARRAGE CARRAGE	A79-25492	[AIAA 79-0806]	A79-28287
GRAPHITE-EPOXY COMPOSITE NATERIALS BMP coupling to a composite aircraft		Design and development of an helicopter ro- and elastomeric bearing	tor hub
and soupering to a composite affectate	A79-25321	[AIAA 79-0815]	A79-28289
GROUND EFFECT (AERODYNAMICS)		Interactional aerodynamics of the single re	otor
Theoretical and experimental investigation ground induced effects for a low-aspec		helicopter configuration. Volume 6-4: One-third octave band spectrograms of wal	ro
highly swept arrow-wing configuration		single film data, buildup to baseline	(e
Langley V/STOL tunnel		[AD-A061994]	N79-18958
[NASA-TM-80041] GROUND HANDLING	ห79-17871	Interactional aerodynamics of the single re helicopter configuration. Volume 8-C:	otor
A simulator study of aircraft ground-run	handling	Frequency analyses of wake single film da	ata,
in the Posim Research Simulator - Some		hubcaps and air ejectors	
and experiences	A79-26498	<pre>fAD-A061995] Design procedure for an information transfe</pre>	N79-18959
GROUND STATIONS	H - 3 - 20490	method CUBITS for allocating panel area:	
Siting criteria for MLS stations. II		aircrew station controls and displays	
GROUND SUPPORT EQUIPMENT	A79-28184	Comparative injury patterns in US Army hel:	N79-19631
Apparatus for measuring an aircraft's sp	eed and	comparative injury patterns in 03 army ner.	เออกเอเร พ79-19654
height		Assessment of the benefits of aircraft	
[NASA-CASE-LAR-12275~1] GUIDANCE SENSORS	N79-18296	crashworthiness	N79-19657
Air Force applications for optical rotat:	ion rate	Crashworthy helicopter seats and occupant	M79-19037
sensors		restraint systems	
GUST LOADS	A79-28122	Some improvements to the UK helicopter cocl	N79-19658
Gust load estimation using a simplified	power	pero infrarence of the ownerstree coo.	ที่79-19659
spectral technique [ARAP-362]	¥70 47070	A method for selecting a crashworthy fuel s	system
[REAL 302]	N79-17870	design	N79-19661
Н		Crash survivability of the UH-60A helicopte	er N79-19663
HANG GLIDERS		The approach to crew protection in the cras	
A new life saving application for the par		environment for the YAH-64	
[AIAA 79-0456] HARTHANN FLOW	A79-26659	Bailout from autorotating helicopters	N79-19664
Heat generation in cavities at high veloc	city flights	parroac real adoptionary herrospects	N79-19666
resonance-pipe effect	N70 17015	HELICOPTER PERFORMANCE	
[BMVG-PBWT-77-28] HEAT GENERATION	N79-17815	Rotary-wing aerodynamics. Volume 2: Perfo prediction of helicopters	огшансе
Heat generation in cavities at high veloc	city flights	[NASA-CR-3083]	N79-17811
resonance-pipe effect	N70 47045	Helicopter operations development plan	"70 40700
[BMVG-PBWT-77-28] HEAT RESISTANT ALLOYS	N79-17815	[FAA-RD-78-101] HELICOPTER PROPELLER DRIVE	N79-18799
Effect of a chromium-containing fuel add:	itive on	Advanced overrunning clutch technology	TT - 6 () 3
			Un-cua
hot corrosion		helicopter transmission application	
	A79-26546	[SAE PAPER 781039]	A79-25907
hot corrosion Potential uses of rapidly solidified alloturbine engines	A79-26546 oys in gas	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system	A79-25907 lri v e
Potential uses of rapidly solidified allo turbine engines	A79-26546 oys in gas A79-27313	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040]	A79-25907 lrive A79-25908
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A	A79-26546 oys in gas A79-27313 TEGG)	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing	A79-25907 lrive A79-25908
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base super: [AD-AO61701]	A79-26546 oys in gas A79-27313 TEGG)	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041]	A79-25907 lrive A79-25908
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (Affractography of cast nickel base superation (AD-A061701) HEAT TRANSFER	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES	A79-25907 irive A79-25908 J A79-25909
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base supers (AD-A061701) HEAT TRANSPER Pressure and heat-transfer distributions	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single re	A79-25907 drive A79-25908 g A79-25909
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base supera [AD-AO61701] HEAT TRANSPER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single round helicopter configuration. Volume 8: free analyses of wake single film data, basic	A79-25907 drive A79-25908 g A79-25909
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base super (AD-A061701) HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095]	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single rother configuration. Volume 8: free analyses of wake Single film data, basic configuration wake exploration	A79-25907 drive A79-25908 g A79-25909 otor quency
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base super (AD-AO61701) HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATERNT	A79-26546 oys in gas A79-27313 TBGG) alloys N79-19149 in a le leakage N79-18284	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single round helicopter configuration. Volume 8: free analyses of wake single film data, basic	A79-25907 drive A79-25908 g A79-25909
Potential uses of rapidly solidified allo turbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base super (AD-A061701) HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095]	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage N79-18284 rmal engines	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single rotelling to the single rotelling and single for analyses of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air	A79-25907 irive A79-25908 y A79-25909 otor quency N79-18956 craft
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (A' fractography of cast nickel base supers [AD-A061701] HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATERNT Residual-stress formation during the they hardening of components in gas-turbine	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage N79-18284	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single rote helicopter configuration. Volume 8: free analyses of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air [NASA-CASE-ARC-11045-1]	A79-25907 drive A79-25908 g A79-25909 otor quency N79-18956 craft N79-17847
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base supera [AD-AO61701] HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATRENT Residual-stress formation during the them	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage N79-18284 rmal engines	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single rotelling to the single rotelling and single for analyses of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air	A79-25907 irive A79-25908 A79-25909 ptor quency N79-18956 craft N79-17847 ift
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base supers (AD-A061701) HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATHENT Residual-stress formation during the their hardening of components in gas-turbine HELICOPTER CONTROL Evaluation of IPR handling qualities of helicopters using the NAE airborne V/S	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage N79-18284 rmal engines A79-26828	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single result of the single resu	A79-25907 irive A79-25908 y A79-25909 otor quency N79-18956 craft N79-17847 ift
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base supera [AD-A061701] HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATERNET Residual-stress formation during the their hardening of components in gas-turbine HELICOPTER CONTROL Evaluation of IPR handling qualities of helicopters using the NAE airborne V/Stamulator	A79-26546 oys in gas A79-27313 TEGG) alloys H79-19149 in a le leakage N79-18284 rmal engines A79-26828	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single rehalicopter configuration. Volume 8: free analyses of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air [NASA-CASE-ARC-11045-1] Electric charging of helicopters aircra hazards and static dischargers for accided prevention [BMYG-PBWT-78-7]	A79-25907 irive A79-25908 A79-25909 ptor quency N79-18956 craft N79-17847 ift
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base super (AD-AO61701) HEAT TRANSFER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Hach number of 6.9 [NASA-TH-74095] HEAT TREATHENT Residual-stress formation during the their hardening of components in gas-turbine hardening of IPR handling qualities of helicopters using the NAE airborne V/Standlator [AIAA 79-0702] BELICOPTER DESIGN	A79-26546 oys in gas A79-27313 TEGG) alloys N79-19149 in a le leakage N79-18284 rmal engines A79-26828	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single response of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air [NASA-CASE-ARC-11045-1] Electric charging of helicopters aircrafized and static dischargers for accidence of prevention [BMYG-PBWT-78-7] Principles of helicopter performance [AD-A061671]	A79-25907 irive A79-25908 y A79-25909 otor quency N79-18956 craft N79-17847 ift
Potential uses of rapidly solidified alloturbine engines Advanced Turbine Engine Gas generator (Afractography of cast nickel base supers (AD-A061701) HEAT TRANSPER Pressure and heat-transfer distributions simulated wing-elevon cove with variable at a free-stream Mach number of 6.9 [NASA-TM-74095] HEAT TREATENT Residual-stress formation during the their hardening of components in gas-turbine HELICOPTEE CONTROL Evaluation of IPR handling qualities of helicopters using the NAE airborne V/SS simulator [AIAA 79-0702]	A79-26546 oys in gas A79-27313 TEGG) alloys H79-19149 in a le leakage N79-18284 rmal engines A79-26828	[SAE PAPER 781039] Advanced technology applied to the CH-47D of system [SAE PAPER 781040] The Lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] HELICOPTER WAKES Interactional aerodynamics of the single received analyses of wake single film data, basic configuration wake exploration [AD-A062013] HELICOPTERS Constant life rotor for a heavier than air [NASA-CASE-ARC-11045-1] Electric charging of helicopters aircraft hazards and static dischargers for accidence prevention [BMYG-PBWT-78-7] Principles of helicopter performance	A79-25907 irrve A79-25908 J A79-25909 otor quency N79-18956 craft N79-17847 ift ent N79-18274

Advancements in helicopter cockpit technol		i	
Visual pockets: A design parameter for he	N79-19625		
instrument panels	N79-19641	IFF SYSTEMS (IDENTIFICATION) An IFF antenna with superior sidelobe and b	acklobe
Some aspects of helicopter communications	W70 40657	suppression characteristics	.70 00740
Occupant injury mechanisms in civil helico	N79-19647 Pter	IGNITION	A79-24718
docidents	N79-19653	Ignition in the gas turbine	N79-19372
HIGH ALTITUDE ENVIRONMENTS Hodeling the X-band radar augmentation sys	tem of a	IMAGE ENHANCEMENT Elimination of scale and luminance distorti	
high altitude supersonic target HIGH ASPECT RATIO	A79-24715	thermal imaging systems with a large fiel onboard aircraft	A79-27416
An aeroelastic optimization procedure for		INAGING TECHNIQUES	A/3 2/410
composite high aspect ratio wings	- 50	A three-channel high-resolution-TV image	
[AIAA 79-0726] HIGH SPEED Heat generation in cavities at high veloci	A79-28258	generation system flight simulator ap Aviation wide angle visual system /AWAVS/ -	A79-28160
resonance-pipe effect [BMVG-FBWT-77-28]	-	system performance	A79-28161
HIGH STRENGTH ALLOYS	N79-17815	IMPACT DAMAGE	A / 9-20101
Structural aluminum materials for the 1980		Engineering analysis of crash injury in arm	Y
[AIAA 79-0755] HIGH TEMPERATURE ENVIRONMENTS	A79-28270	aircraft	N79-19655
Fuel tank sealant requirements for advance performance aircraft	high	A method for selecting a crashworthy fuel s design	
[AIAA 79-0807]	A79-28288		พ79-19661
HORIZONTAL TAIL SURPACES	e	The approach to crew protection in the cras	h
Comparison of the aerodynamic properties o aeroplane with the tail-first configurat		environment for the YAH-64	N79-19664
with the conventional configuration		IMPACT LOADS	
[BLL-RTS-11520] HOT PRESSING	N79-17794		recovery A79-26627
Design and fabrication of advanced titaniu structures	m	IMPACT TESTS Crashworthiness tests on model aircraft fus	elage
[AIAA 79-0757]	A79-28272	structures	•
HOUSINGS Structural stiffening of transmission hous	nas	[AIAA 79-0688] Interactive multi-mode blade impact analysi	A79-27354
with metal matrix materials	11195		N79-17858
[AIAA 79-0806] HOVERING	A79-28287	IMPELLERS	d1
A comparison of linear acoustic theory wit	h	A stress and strain analysis of industrial compressor impellers using the framework	
experimental noise data for a small-scal		finite element method and descriptive	
hovering rotor [AIAA PAPER 79-0608]	A79-26876	IN-FLIGHT MONITORING	
HUBS	tar hub	Alrcraft velocity and altitude measurements a tunable diode laser	using
Design and development of an helicopter ro and elastomeric bearing	tor nub		A79-28139
[AIAA 79-0815]	A79-28289	An improved system for use in conducting wa	ke
HUMAN PACTORS ENGINEERING Flight deck alarm systems		<pre>investigation for a wing in flight differential pressure measurements for dr</pre>	ап
1119H GCON WIGIE Offices	A79-25541	investigations	~ y
Internal cockpit reflections of external p			พ 79-17797
light sources for the model YAH-64 advan- attack helicopter	cea	Casualty evacuation by helicopter	N79-19615
•	N79-19643	INCOMPRESSIBLE PLOW	
The annoyance of multiple noisy events	ratings	Numerical study of unsteady flows of viscou incompressible fluids about airfoils by a	
for simulated flyovers	· .	combined method of order 0/h2/ and 0/h4/	
[AIAA PAPER 79-0653] Variability of annoyance response due to a	A79-26895 ircraft	Nonsteady flow of an incompressible liquid	A79-24829 over
noise		slender permeable profiles	
[NASA-TP-1335] HYDRAULIC TEST TUNNELS	N79-18687	INDEXES (DOCUMENTATION)	A79-27062
A water tunnel flow visualization study of		Listing of accidents/incidents by make and	model,
[NASA-CR-144878] HYDRODYNAMICS	N79-18286	US civil aviation, 1977 [NTSB-AMM-78-12]	N79-17828
Thermoelastic and dynamic phenomena in sea		INERTIAL GUIDANCE	
[AD-A061754] HYDROGEN PUBLS	N79-19396	Air Force applications for optical rotation sensors	
Cryohydrogen-fuel for tomorrow's commercia	1 aircraft 1 A79-27656	INERTIAL BAVIGATION	A79-28122
HYPERBOLAS Sound radiation from hyperboloidal inlet do		Redundant control systems for flight wehicl Russian book	es
[AIAA PAPER 79-0677]	A79-26885		A79-25875
HYPERSONIC AIRCRAFT Formulation of aerodynamic prediction techn	niques	INFORMATION MANAGEMENT Development of the L-1011 Flight Management	System
for hypersonic configuration design			A79-26535
[NASA-CR-158994] Experimental and finite element investigat:	N79-17850 lon of	INFORMATION SYSTEMS New approaches concerning the implementatio	n of
the buckling characteristics of a beaded panel for a hypersonic aircraft		radar target extractors with the aid of v fast microprogrammable data processors	
	N79-19412		A79-26754
HYSTERESIS Wing rock due to aerodynamic hysteresis		INFRARED IMAGERY	
wand took are to detonlingmic ulatelesis	A79-28376	Reliability growth on B-52 PLIR system	A79-24958

SUBJECT INDEX JET ENGINES

Elimination of scale and luminance distortion		Ski-jump - A great leap for tactical airpow	
thermal imaging systems with a large field onboard aircraft	of View	V/STOL jet launching from upward-inclined [AIAA 79-0696]	1 ramp A79-27361
	179-27416	JET AIRCRAPT NOISE	R79-27301
INFRARED SCANNERS	_	Measured and predicted noise of the AVCO-Ly	coming
IR scanning camera measurements of an exhaus plume from an axisymmetric nozzle afterboo		YP-102 turbofan engine [AIAA PAPER 79-0641]	A79-26877
model at transonic Mach numbers	•1	The application of finite element technique	
	79-28097	acoustic transmission in lined ducts with	
INJECTORS Instability of fluid flow in centrifugal in	lector	[AIAA PAPER 79-0660] The annoyance of multiple noisy events	A79-26893
	79-27731	for simulated flyovers	2402495
INLET PLOW		[AIAA PAPER 79-0653]	A79-26895
Considerations for the design of inlet flow conditioners for static fan noise testing		Propagation of buzz-saw noise in a nonunifo	orm medium
	79-26909		A79-26896
Effects of inflow distortion profiles on far	tome	An experimental study of USB flap noise red	
noise calculated using a 3-D theory	79-26911	through mean flow modification Upper Blown	Surface
[AIAA PAPER 79-0577] Evaluation of two inflow control devices for		[AIAA PAPER 79-0607]	A79-26908
flight simulation of fan noise using a JT1		Considerations for the design of inlet flow	
engine	70-26026	conditioners for static fan noise testing	A79-26909
[AIAA PAPER 79-0654] Axial compressor operation with radially	179-26926	[AIAA PAPER 79-0657] Effects of inflow distortion profiles on fa	
nonuniform inflow		noise calculated using a 3-D theory	\$
	79-27743	[AIAA PAPER 79-0577]	A79-26911
Aerodynamic and Mechanical factors affecting surge line: Inlet flow distortion influen		Diagnostic evaluation of jet noise suppress mechanisms	sion
axial flow compressors	ices on	[AIAA PAPER 79-0674]	A79-26912
X	179-19363	The sound power spectrum of shock-free jets	
INLET NOZZLES		[AIAA PAPER 79-0595] Coaxial jet noise in flight	A79-26918
Analysis of radiation patterns of interaction tones generated by inlet rods in the JT151		[AIAA PAPER 79-0636]	A79-26919
[AIAA PAPER 79-0581] A	79-26944	Noise from struts and splitters in turbofar	
INSECTS		ducts	170-26022
Some aspects of unsteady insect aerodynamics Acceleration potential methods in plane un		[AIAA PAPER 79-0637] Twin jet shielding for aircraft noise r	A79-26923 eduction
airfoil theory, and measurements of	2	[AIAA PAPER 79-0671]	A79-2692ª
unsteady-periodic forces generated by the		Some effects of applying sonic boom minimiz	zation
INSTRUMENT PLIGHT RULES	179-18903	to supersonic cruise aircraft design [AIAA PAPER 79-0652]	A79-26927
Evaluation of IPR handling qualities of		An acoustic problem in anechoic chambers ar	
helicopters using the NAE airborne V/STOL		from exhaust noise testing	170-26020
Simulator [AIAA 79-0702]	79~27365	[AIAA PAPER 79-0649] An experimental study of the influence of	A79-26929
LED instrument approach instruction display	2.303	flight-stream turbulence on jet mixing no	oise
	179~ 17854	[AIAA PAPER 79-0617]	179-26935
INTEGRATED CIRCUITS Advances in avionics emphasizing		Effects of simulated forward flight on jet shock noise and internal noise	noise,
microprocessor technology and integrated of	circuits	[AIAA PAPER 79-0615]	A79-26936
	179-25862	Flight effects on noise generated by the J1	18D
Path in rocket technology - Selected works,		engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot	wind
1924-1946 Russian book		tunnel	
	79-27599		A79-26937
Quasi-natural numerical methods for the		Separation of core noise and jet noise [AIAA PAPER 79-0589]	A79-26941
computation of inviscid potential or rotat	ional	Analysis of radiation patterns of interacti	
transonic flows		tones generated by inlet rods in the JI15	
	179-26487	[AIAA PAPER 79-0581] Unsteady stator response to upstream rotor	A79-26944
An improved supersonic, three-dimensional, external, inviscid flow field code			A79-26945
[NASA-CR-3108]	179-17807	Inside noise of C-1 cargo aircraft and the	
Contribution to the development of theoretic	· - 1	reduction performance by interior materia	115 179-27121
Contribution to the development of theoretic calculations for the design and optimizati		JET CONTROL	27121
lifting bodies. (Solution of three-dimens	nonal	Aerodynamics of flame jets Russian book	
basic thermo fluid dynamics equations with strong interacting attached and separated		JET ENGINE PUBLS	A79-26355
fields)	110	Methanol, ethanol and jet fuel emissions	
[BMVG-FBWT-78-4]	179-17816	comparison from a small gas turbine	
1		[SAE PAPER 781013] Shale oil - The answer to the jet fuel	A79~25893
J		availability question	
J-57 EBGINE			A79-25900
The U-2 story	79-26537	JET ENGINES Small fan-jet engines for business airc	F+
JACKS (LIFTS)	113-20331		A79-26531
The 1-4-1 system of jack movements for the		Aerodynamic and acoustic comparisons of	
flexible liners of supersonic wind tunnels		scaled-down and actual engine jets	A79-26946
JAPAH	79-26594	[AIAA PAPER 79-0574] Two-frequency-range theory of unstable turb	
An offshore airport that works - Nagasaki		combustion oscillations in a jet engine	
	79-28185	combustion chamber. II - Analysis of the	**
JET AIRCRAFT The continuity factor in aircraft developmen	ıt	characteristic equation and comparison wi experiment	LLI
	79-26536		A79-27728
		Small fan-jet engines	N79-18891
			10071

JET EXHAUST SUBJECT INDEX

JET EXHAUST	LANDING GEAR
Discrete noise spectrum generated by an	Aircraft accident report: Continental Air lines,
acoustically excited jet	Incorporated, McDonnell-Douglas DC-10-10,
[AIAA PAPER 79-0592] A79-26887	N68045, Los Angeles, California, March 1, 1978
Experiments concerning the anomalous behaviour of aero-engine exhaust noise in flight	[NTSB-AAR-79-1] N79-17826 All frame noise component interaction studies
[AIAA PAPER 79-0648] A79-26930	[NASA-CR-3110] N79-19815
JET FLAPS	LARGE SCALE INTEGRATION
Analysis of some aerodynamic characteristics due	Multimode radar processor for combat aircraft
to wing-jet interaction	A79-28058
[NASA-CR-158349] N79-18917	LASER APPLICATIONS
JET FLOW	Laser aircraft using kerosene
The influence of geometric asymmetry on the flow downstream of row of jets discharging normally	A79-26597 Laser propulsion
into a free stream	A79-26598
A79-25065	LASER DOPPLER VELOCIMETERS
Lean combustion limits of a confined	Aircraft velocity and altitude measurements using
premixed-prevaporized propane jet	a tunable diode laser
[AIAA PAPER 79-0538] A79-25856	A79-28139
Sound absorption caused by vorticity shedding, demonstrated with a jet flow	LATERAL CONTROL An experimental wind-tunnel investigation of a
(AIAA PAPER 79-0575) A79-26905	ram-air-spoiler roll-control device on a
JET MIXING PLOW	forward-control missile at supersonic speeds
The sound power spectrum of shock-free jets	[NASA-TP-1353] N79-17809
[AIR IREE 15.0333] A73-20310	LAUNCHING PADS
An experimental study of the influence of flight-stream turbulence on jet mixing noise	Ski-jump - A great leap for tactical airpower V/STOL jet launching from upward-inclined ramp
[AIAA PAPER 79-0617] A79-26935	[AIAA 79-0696] A79-27361
Interaction of the supersonic flow below a wing	LC CIRCUITS
and a supersonic free jet (two-dimensional	Filter weight minimization for rectified
situation)	superconducting alternator power supplies
[VTH-LR-268] N79-17819	for aircraft
JOINTS (JUNCTIONS) Fracture mechanics for structural adhesive bonds,	A79-26966 LEADING EDGES
part 2, phase 2	A visual investigation of the separation and
[AD-A061805] N79-19418	subsequent transition near the leading edge of
JP-5 JET PUEL	airfoils
Effects of fuel properties on soot formation in	[AIAA PAPER 79-0552] A79-25863
turbine combustion	Airframe noise component interaction studies
[SAE PAPER 781026] A79-25899 Evaluation of the application of some gas	[NASA-CR-3110] N79-19815 LEAR JET AIRCRAFT
chromatographic methods for the determination of	The Learjet Longhorn series - The first jets with
properties of synthetic fuels	winglets
A79-25917	A79-26532
	Simultaneous measurements of ozone outside and
K	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates
KEROSENE	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet
KEROSENE Laser alrcraft using kerosene	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571
KEROSENE Laser alrcraft using kerosene A79-26597	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK)	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTERWAS
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AUTEWHAS A proposed integrated ECM system using the
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTERWAS
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] A79-26638 Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] A79-26641	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEBS ABTENHAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] A79-25901
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEBS ABTERNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] A79-25902
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faina 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AINA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AINA PAPER 79-0600] A79-26881	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-26881 L-1011 AIRCRAFT	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L L-1011 AIRCRAFT Development of the L-1011 Plight Management System	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENHAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faina 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AINA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AINA PAPER 79-0600] L L-1011 AIRCRAFT Development of the L-1011 Plight Management System A79-26535	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L L-1011 AIRCRAFT Development of the L-1011 Plight Management System	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS ANTENHAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-26881 L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEHARK) Design criteria for and development of Kevlar ribbon parachutes faiha 79-0430 } Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433 } Pull-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIHAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTEWNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEHARK) Design criteria for and development of Kevlar ribbon parachutes fAIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIMAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] A79-25905
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faina 79-0430	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-26881 L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIMAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] A79-25905
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faina 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AINA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AINA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] N79-17799	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [ATAA 79-0633] A79-27358
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faila 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] Integrated Thermal Avionics Design (ITAD)
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2681 L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIMAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781039] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AITAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] N79-17855
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [ATAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] LIFT AUGHENTATION
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2681 L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIMAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] LIFT AUGMENTATION Development of modern airfoil sections for high
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Pull-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Fffects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] N79-17851	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [ATAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] LIFT AUGHENTATION
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TN-78715] LAMINAR PLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AITAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] N79-17855 LIFT AUGMENTATION Development of modern airfoil sections for high subsonic cruise speeds
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2681 L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHIMAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] LAHIMAR PLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] A79-25904 Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AITAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] N79-17855 LIFT AUGENTATION Development of modern airfoil sections for high subsonic cruise speeds [AITAA 79-0687] LIFT FAMS V/STOL aircraft engine and mechanical drive
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] LAHINAR PLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] N79-17852	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AIAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-0461227] LIPT AUGHENTATION Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] LIFT FARS V/STOL aircraft engine and mechanical drive component integration
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes faina 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [Aina 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [Aina Paper 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAHINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Fifects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] LAHINAR FLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] N79-17852 LAHINATES	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [ATAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] LIFT AUGENTATION Development of modern airfoil sections for high subsonic cruise speeds [ATAA 79-0687] LIFT FANS V/STOL aircraft engine and mechanical drive component integration [SAE PAPER 781038] A79-25906
KEROSENE Laser aircraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] L-1011 AIRCRAFT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] LAHINAR PLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] N79-17852	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIFE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781039] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781032] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [AITA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] N79-17855 LIFT AUGHENTATION Development of modern airfoil sections for high subsonic cruise speeds [AITA 79-0687] LIFT FANS V/STOL aircraft engine and mechanical drive component integration [SAE PAPER 781038] A79-25906 LIFTING BODIES
KEROSENE Laser alrcraft using kerosene A79-26597 KEVLAR (TRADEMARK) Design criteria for and development of Kevlar ribbon parachutes [AIAA 79-0430] Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute [AIAA 79-0433] Full-scale engine tests of bulk absorber acoustic inlet treatment [AIAA PAPER 79-0600] A79-2681 L-1011 AIRCRAPT Development of the L-1011 Flight Management System A79-26535 Development of the L-1011 flight management system N79-18895 LAMINAR BOUNDARY LAYER Laminar boundary layer with foreign gas injection on a conical body A79-27203 Summary report of the second wind tunnel test of the Boeing LFC model [NASA-CR-157792] Effects of laminar flow control on the performance of a large span-distributed-load flying-wing cargo airplane concept [NASA-TM-78715] LAMINAR PLOW Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] N79-17852 LAHINATES Design and development of an helicopter rotor hub	Simultaneous measurements of ozone outside and inside cabins of two B-747 airliners and a Gates Learjet business jet A79-27571 The Learjet Longhorn series: The first jets with winglets N79-18893 LEWS AWTENNAS A proposed integrated ECM system using the constant index lens antenna A79-24726 LIPE CYCLE COSTS Life Cycle Cost in advanced technology engine development [SAE PAPER 781029] Applying design-to-life cycle cost methods during engine advanced development [SAE PAPER 781030] Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25902 Turbine engine cost reduction using Life Cycle Cost techniques [SAE PAPER 781031] A79-25903 Life cycle cost in preliminary engine design for F-15 [SAE PAPER 781032] Trade-off studies with an interactive engine/airframe life-cycle-cost model [SAE PAPER 781033] Compromise between economic concerns and application of new technologies in the definition of a new airplane project [ATAA 79-0693] Integrated Thermal Avionics Design (ITAD) [AD-A061227] LIFT AUGENTATION Development of modern airfoil sections for high subsonic cruise speeds [ATAA 79-0687] LIFT FANS V/STOL aircraft engine and mechanical drive component integration [SAE PAPER 781038] A79-25906

SUBJECT INDEX MARKET BESEARCH

Contribution to the development of theoretical	LONGITUDINAL CONTROL
calculations for the design and optimization of lifting bodies. (Solution of three-dimensional	Dynamics of controlled longitudinal motion of an airplane with a variable-geometry wing
basic thermo fluid dynamics equations with strong interacting attached and separated flow	LONGITUDINAL STABILITY
fields)	The influence of ballonet motions on the
[BMVG-FBWT-78-4] N79-17816 LIGHT (VISIBLE BADIATION)	longitudinal stability of tethered aerostats [AIAA 79-0445] A79-26649
Internal cockpit reflections of external point	A simple physical model of a descending parachute
light sources for the model YAH-64 advanced	[AIAA 79-0447] A79-26651
attack helicopter N79-19643	Longitudinal oscillation damping for fully-inflated parachute canopies
LIGHT AIRCRAFT	[AIAA 79-04591 A79-26662
Adaptation of a digital airborne radar for use on	LONGITUDINAL WAVES
the microphysics research aircraft A79-25681	Analysis of longitudinal natural vibrations of deformable aircraft by the finite-element method
General aviation aircraft in the 1990's [AIAA PAPER 79-0560] A79-25866	LOW ASPECT RATIO
Small fan-jet engines for business aircraft	Theoretical and experimental investigation of
A79-26531	ground induced effects for a low-aspect-ratio
Interior noise path identification in light aircraft using multivariate spectral analysis	highly swept arrow-wing configuration in the Langley V/STOL tunnel
[AIAA PAPER 79-0644] A79-26915	[NASA-TM-80041] N79-17871
Characteristics of propeller noise on an aircraft fuselage related to interior noise transmission	LOW ASPECT RATIO WINGS
[AIAA PAPER 79-0646] A79-26932	XP4D Skyray development: Now it can be told N79-18897
Short Range Terminal Radar (SRTR) definition study	LOW SPEED WIND TUNNELS
[FAA-RD-78-64] N79-18156 Development of casualty evacuation kit for the	Some new approaches for wind-tunnel testing through the use of computers
light observation helicopter (Kiwa)	[AIAA 79-0707] A79-27367
พ79-19616	LUBRICATING OILS
LIGHT BRAMS Plane problems of aerothermooptics refraction	A decision theory model for health monitoring of aeroengines metal particles in lubricating
in two-dimensional nonuniform medium	oils as wear indicator
A79-26865	A79-28381
LED instrument approach instruction display	Separation and investigation of wear particles from aero-engines
[NASA-TM-78823] N79-17854	[BLL-RISLEY-TR-3308-(9091.9F)] N79-17856
An optical communication system for aircraft	**
A79-28034	M
LIGHTNING Begant advances in indirect lightning offerts	MACHINE TOOLS
	CICD IN cimplation model for the compaction and
Recent advances in indirect lightning effects research	GASP IV simulation model for the composites and bonding production facility
research A79-25313	bonding production facility A79-27297
research A79-25313 Lightning protection with segmented diverters	bonding production facility A79-27297 HAGNESIUM
research A79-25313	bonding production facility A79-27297
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on	bonding production facility A79-27297 **BAGHESIUM** Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317	bonding production facility A79-27297 **HAGNESIUM** Structural stiffening of transmission housings with metal matrix materials
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDROUTHABIC GENERATORS
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] MAGHETOHYDRODYMAMIC GENERATORS Air Force applications of lightweight
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDROUTHABIC GENERATORS
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYNAMIC GENERATORS Air Porce applications of lightweight superconducting machinery in airborne power sources A79-27666
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission	bonding production facility A79-27297 HAGNESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGNETOHYDRODYNAMIC GENERATORS Air Porce applications of lightweight superconducting machinery in airborne power sources A79-27666
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYMAHIC GENERATORS Air Porce applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUNCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYNAMIC GENERATORS Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUHCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] HAN HACHINE SYSTEHS
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYMAHIC GENERATORS Air Porce applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUNCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip Protection/hardening of aircraft electronic	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYNAMIC GENERATORS Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUHCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 HAN HACHINE SYSTEMS FAA remote terminal system frequency assignment model A79-25323
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip Protection/hardening of aircraft electronic systems against the indirect effects of lightning	bonding production facility A79-27297 **HAGHESIUM** Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 **HAGRETOHYDRODYNAMIC GENERATORS** Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 **HALPUNCTIONS** Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 **HAM HACHINE SYSTEMS** FAA remote terminal system frequency assignment model A79-25323 Flight deck alarm systems
research A79-25313 Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip Protection/hardening of aircraft electronic	bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGHETOHYDRODYNAMIC GENERATORS Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUHCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 HAN HACHINE SYSTEMS FAA remote terminal system frequency assignment model A79-25323
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft	bonding production facility A79-27297 **HAGHESIUM** Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 **HAGRETOHYDRODYNAMIC GENERATORS** Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 **HALPUNCTIONS** Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 **HAM HACHINE SYSTEMS** FAA remote terminal system frequency assignment model A79-25323 **Flight deck alarm systems** A79-25541 **TDS - A preliminary design system for turbines [SAE PAPER 780999] A79-25882
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft	Bonding production facility A79-27297 HAGHESIUM Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 HAGBETOHYDRODYMAHIC GENERATORS Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 HALPUNCTIONS Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 HAN HACHINE SYSTEMS PAA remote terminal system frequency assignment model A79-25323 Flight deck alarm systems A79-25541 TDS - A preliminary design system for turbines [SAE PAPER 780999] A79-25882
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft N79-18242 A new standard for lightning qualification testing of aircraft. Technical overview, definitions	Bonding production facility A79-27297 **HAGHESIUM** Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 **HAGRETOHYDRODYNAMIC GENERATORS** Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 **HALPUNCTIONS** Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 **HAM MACHINE SYSTEMS** FAA remote terminal system frequency assignment model A79-25323 **Flight deck alarm systems** TDS - A preliminary design system for turbines [SAE PAPER 780999] A79-25882 **HANAGEMENT PLANNING** Air fleet and facility planning via optimal control models
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft N79-18242 A new standard for lightning qualification testing of aircraft: Technical overview, definitions and basic waveforms	### Bonding production facility ###################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft N79-18242 A new standard for lightning qualification testing of aircraft. Technical overview, definitions	Bonding production facility A79-27297 **HAGHESIUM** Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 **HAGRETOHYDRODYNAMIC GENERATORS** Air Force applications of lightweight superconducting machinery in airborne power sources A79-27666 **HALPUNCTIONS** Commercial parachutes from safety standpoint [AIAA 79-0458] A79-26661 **HAM MACHINE SYSTEMS** FAA remote terminal system frequency assignment model A79-25323 **Flight deck alarm systems** TDS - A preliminary design system for turbines [SAE PAPER 780999] A79-25882 **HANAGEMENT PLANNING** Air fleet and facility planning via optimal control models
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18237 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the	### Bonding production facility ###################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft N79-18242 A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBITES The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels	### Bonding production facility ###################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to	### Bonding production facility ###################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft N79-18242 A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LININGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow	### Bonding production facility #### A79-27297 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to	### Bonding production facility #### A79-27297 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow (AIAA PAPER 79-0660) LIQUID ATOHIZATION Puel injection	### Bonding production facility ### A79-27297 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LININGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow (AIAA PAPER 79-0660) LIQUID ATOMIZATION Fuel injection N79-19368	### Bonding production facility #### Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow (AIAA PAPER 79-0660) LIQUID ATOHIZATION Puel injection	### Bonding production facility ### A79-27297 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LININGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow (AIAA PAPER 79-0660) LIQUID ATOMIZATION Fuel injection N79-19368 LIQUID HYDROGEN Cryohydrogen-fuel for tomorrow's commercial aircraft A79-27656	### Bonding production facility ### Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 #################################
Lightning protection with segmented diverters for aircraft radomes and dielectric structures A79-25317 The impact of the total lightning environment on aircraft flight control systems A79-25319 Properties of induced transients associated with EM fields produced by lightning or other relatively slow rise-time EMP in aircraft A79-25322 The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 An RF compatible lightning diverter strip N79-18237 Protection/hardening of aircraft electronic systems against the indirect effects of lightning N79-18238 Induced effects of lightning on an all composite aircraft A new standard for lightning qualification testing of aircraft Technical overview, definitions and basic waveforms N79-18246 LIBIEGS The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunnels A79-26594 The application of finite element techniques to acoustic transmission in lined ducts with flow (AIAA PAPER 79-0660) A79-26893 LIQUID ATOHIZATION Puel injection N79-19368 LIQUID HYDROGEM Cryohydrogen-fuel for tomorrow's commercial aircraft	### Bonding production facility ### Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] A79-28287 New agents for the extinguishment of magnesium fires [AD-A061664] N79-19122 #################################

MARKING SUBJECT INDEX

Corgo (Logistias livité Erston Stude (CLIS		NUMBER ATTORNEY
Cargo/Logistics Airlift System Study (CLAS executive summary	55),	METHYL ALCOHOLS Methanol, ethanol and jet fuel emissions
[NASA-CR-158959]	N79-17824	comparison from a small gas turbine
HARKING		[SAE PAPER 781013] A79-25893
Airfield marking paints state-of-the-art		HICROPROCESSORS
[FAA-RD-78-104]	N79-17876	Advances in avionics emphasizing
MATHEMATICAL HODELS Quasi-natural numerical methods for the		microprocessor technology and integrated circuits [AIAA PAPER 79-0562] A79-25862
computation of inviscid potential or rot	tational	New approaches concerning the implementation of
transonic flows		radar target extractors with the aid of very
	A79-26487	fast microprogrammable data processors
Noise transmission - Turboprop problem		A79-26754
[AIAA PAPER 79-0645]	A79-26933	MICROWAVE LANDING SYSTEMS
Perspectives of technological development helicopters	101	Flying NASA's Terminal Configured Vehicle against the Microwave Landing System
[AIAA 79-0701]	A79-27364	A79-26534
Carbon fiber dispersion models used for ri	ıs k	Siting criteria for MLS stations. II
analysis calculations		A79-2818 th
Airport vicinity air pollution model. Abb	N79-18080	Algorithms and logic for incorporating MLS back azimuth information into the PASA TCV B-737
version user's guide	or eardred	airplane area navigation system
[FAA-RD-78-111]	N79-18475	[NASA-TM-80039] N79-17843
Investigation of torsion free wing trend f	flutter	Plying NASA's terminal configured vehicle against
models	w70 40057	the microwave landing system
[AD-A061942] Flow modelling and aerodynamic design tech	N79-18957	N79-18894
for centrifugal compressors	iniques	Aircraft accident report: Midair collision
	ห79-19386	involving a Falcon JET, W121GW, and a Cessna
Application of aerodynamic design technique		150M, N6423K, Memphis, Tennessee
process compressor design computer12		[NTSB-AAR-78-14] N79-17821
MEASURING INSTRUMENTS	N79-19388	Briefs of accidents involving midair collisions, US general aviation, 1977
An in-place recalibration technique to ext	tend the	[NTSB-AMM-78-13] N79-17829
temperature capability of capacitance-se		HILITARY AIR PACILITIES
rotor-blade-tip-clearance measurement sy		Air fleet and facility planning via optimal
[SAE PAPER 781003]	A79-25885	control models
Runway surface condition sensor [AC-150/5220-13]	N79-17878	A79-26725
BECHANICAL DRIVES	1175 170 0	Strike Drone - A defense suppression concept using
Advanced technology applied to the CH-47D	drive	unmanned cruise/loiter/attack vehicle
system		[SAE PAPER 781017] A79-25894
[SAE PAPER 781040] HECHANICAL PROPERTIES	A79-25908	Shale oil - The answer to the jet fuel
Transonic compressors for heavy gases. Pa	rt 2:	availability question [SAE PAPER 781027] A79-25900
Aero-mechanical considerations, testing		Avionics systems needed to optimize V/STOL potential
operation		A79-26874
	N79-19352	New airborne armament systems multimission
Aerodynamic and Mechanical factors affecti		design requirements [AIAA 79-0697] A79-27362
surge line: Inlet flow distortion influ axial flow compressors	iences on	[AIAA 79-0697] A79-27362 A survey of communications in the high noise
daldi ilow complessors	N79-19363	environment of Army alreraft
MEDICAL SERVICES		N79-19646
Rescue helicopters in primary and secondar		MILITARY HELICOPTERS
TO_60% MPDPURC b.+	N79-19606	The Lynx transmission and Conformal gearing
UH-60A MEDEVAC kit	N79-19614	helicopter drive train [SAE PAPER 781041] A79-25909
Casualty evacuation by helicopter		Internal cockpit reflections of external point
	N79-19615	light sources for the model YAH-64 advanced
METAL BONDING		attack helicopter
Design and development of an helicopter ro and elastomeric bearing	otor hub	N79-19643 Comparative injury patterns in US Army helicopters
(AIAA 79-0815)	A79-28289	N79-19654
METAL PATIGUE		Engineering analysis of crash injury in army
The prediction of fatigue crack growth und	ler	aircraft
flight-by-flight loading	A79-25482	N79-19655 Assessment of the benefits of aircraft
HETAL HATRIX COMPOSITES	A13-23402	crashworthiness
Structural stiffening of transmission hous	ings	N79-19657
with metal matrix materials	•	Helicopter crashworthy fuel systems and their
[AIAA 79-0806]	A79-28287	effectiveness in preventing thermal injury
METAL PARTICLES A decision theory model for health monitor	and of	N79-19660 The approach to crew protection in the crash
aeroengines metal particles in lubri		environment for the YAH-64
oils as wear indicator	,	N79-19664
	A79-28381	Helicopter underwater escape trainer (9D5)
METAL SHEETS	_	N79-19665
Design and fabrication of advanced titaniu structures	1 10	HILITARY TECHNOLOGY Technology and the new look meet the F/A-18 radar
[AIAA 79-0757]	A79-28272	reliability challenge
METEOROLOGICAL RADAR		[SAE PAPER 781024] A79-25897
Adaptation of a digital airborne radar for	use on	Future avionics - Reeping capability up, costs down
the microphysics research aircraft	170-25601	A79-27093
Design considerations for the NOAA airborn	A79-25681	Enhanced capabilities of future fighters as a result of HiMAT
meteorological radar and data system		[AIAA 79-0698] A79-27370
	A79-25689	Air Force applications of lightweight
		superconducting machinery in airborne power
		sources A79-27666
		A/3-2/000

SUBJECT INDEX NOISE BEASUREMENT

Military fiber optics applications	WAVIGATION AIDS Navstar/GPS /Global Positioning System/ and
Total environment survivability methodology [AD-A061888] N79~18971	electronic counter measures TACAN system vulnerability
HILLIMETER WAVES SEATRACKS - A millimeter wave radar fire control	A79-25492 How to add satellite navigational accuracy and
system A79-27144	stability to existing offshore MAV Systems A79-27388
MINICOMPUTERS SIFT - Design and analysis of a fault-tolerant	NAVIGATION INSTRUMENTS Study of the structure of an integrated system of
computer for aircraft control Software Implemented Pault Tolerant systems	flight control, navigation and display A79-27674
A79-25718	Tests of an integrated piloting, navigation, and
Concept of modular software for the stepwise construction of radar data processing systems	display system A79-27675
with minicomputers, taking into account as example the Airtrack System	NAVSTAR SATELLITES Navstar/GPS /Global Positioning System/ and
HIRAGE 3 AIRCRAFT	electronic counter measures TACAN system vulnerability
Flight testing the KPIR N79-18889	NAVY
HISSILE COMPONENTS Wings	Requirements and constraints in the development and qualification of gas turbine engines for the
N79-18921	Navy [SAE PAPER 780994] A79-25874
Vortex models on missile configurations computer program for determining aerodynamic	Statistical review of counting accelerometer data for Navy and Marine fleet aircraft
coefficients and flow deflection	[AD-A061894] N79-18972
[BNVG-FBWT-77-27] N79-17814 HISSILE CONTROL	WEAR FIRLDS Alrcraft antenna pattern measurements using near
Stability and control characteristics of a monoplanar elliptic missile model at Mach	field techniques A79-24721
numbers from 1.60 to 2.86 [NASA-TP-1352] N79-17808	Near-field analysis of helicopter rotating blades modulation interference
MISSILE DESIGN The place of aerodynamics in the design process	MEAR WAKES
N79-18933	Characteristics of the wake of a lightly loaded compressor or fan rotor
Wind-tunnel studies of the effects of simulated damage on the aerodynamic characteristics of	[ATAA PAPER 79-0550] A79-25861 Turbulence characteristics in the near wake of a
airplanes and missiles	compressor rotor blade
A79-27424 Analysis of base-flow problems during powered	HICKEL ALLOYS
supersonic flight N79-18926	Prediction of gas-turbine alloy creep characteristics
MTBP Reliability growth on B-52 PLIR system	A79-26841 Potential uses of rapidly solidified alloys in gas
A79-24958 Reliability growth planning to achieve RIW/GMTBF	turbine engines A79-27313
requirements for an airborne radar A79-24965	Advanced Turbine Engine Gas generator (ATRGG) fractography of cast nickel base superalloys
N	[AD-A061701] N79-19149 NOISE GENERATORS
NASA PROGRAMS	An airborne reference noise source for studying
Engine technology for production turbofan engines	airplane flyover noise propagation and measurement [AIAA PAPER 79-0650] A79-26928
A79-24827 NASA research on general aviation power plants	Analysis of radiation patterns of interaction tones generated by inlet rods in the J?15D engine
[AIAA PAPER 79-0561] Prop-fan propulsion - Its status and potential	[AIAA PAPER 79-0581] A79-26944 NOISE INTENSITY
[SAE PAPER 780995] A79-25880 An acoustical study of the XV-15 Tilt Rotor	Turboprop interior noise studies [AIAA PAPER 79-0647] A79-26931
Research Aircraft [AIAA PAPER 79-0612] A79-26939	Combustion noise prediction update [AIAA PAPER 79-0588] A79-26942
Advanced supersonic technology and its implications for the future	A survey of communications in the high noise environment of Army aircraft
(AIAA 79-0694) A79-27359 Enhanced capabilities of future fighters as a	N79-19646 Some aspects of helicopter communications
result of HIMAT	N79-19647
[AIAA 79-0698] Algorithms and logic for incorporating MIS back	MOISE MEASUREMENT A comparison of linear acoustic theory with
azimuth information into the NASA TCV B-737 airplane area navigation system	experimental noise data for a small-scale hovering rotor
[NASA-TM-80039] N79-17843 Flying NASA's terminal configured vehicle against	[AIAA PAPER 79-0608] A79-26876 Heasured and predicted noise of the AVCO-Lycoming
the microwave landing system N79-18894	YF-102 turbofan engine [AIAA PAPER 79-0641] A79-26877
WASTRAN Aeroelastic addition to NASTRAN	Pull-scale engine tests of bulk absorber acoustic inlet treatment
[NASA-CR-3094] N79-17812 NAVIER-STOKES EQUATION	[ATAA PAPER 79-0600] A79-26881 Direct experimental verification of the
Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a	theoretical model predicting rotor noise
combined method of order O/h2/ and O/h4/	generation [AIAA PAPER 79-0658] A79-26894
A79-24829	Airframe noise measurements on a small-scale model of a supersonic transport concept in an anechoic
	flow facility [AIAA PAPER 79-0666] A79-26920

NOISE POLLUTION SUBJECT INDEX

Feduction of rotor-turbulence interaction noise in	Separation of core noise and jet noise
static fan noise testing	[AIAA PAPER 79-0589] A79-26941
[AIAA PAPER 79-0656] A79-26925	Combustion noise prediction update [ATAA PAPER 79-0588] A79-26942
An airborne reference noise source for studying airplane flyover noise propagation and measurement	[AIAA PAPER 79-0588] A79-26942 Inside noise of C-1 cargo aircraft and the noise
[AIAA PAPER 79-0650] A79-26928	reduction performance by interior materials
An acoustic problem in anechoic chambers arising	A79-27121
from exhaust noise testing	NOISE THRESHOLD
[AIAA PAPER 79-0649] A79-26929	Variability of annoyance response due to aircraft
A commercial airport noise environment:	NOISE NO 12252
Measurement, prediction and control [NASA-CR-3107] N79-19814	[NASA-TP-1335] N79-18687 NOISE TOLERANCE
[NASA-CR-3107] N79-19814 All	The annoyance of multiple noisy events ratings
[NASA-CR-3110] N79-19815	for simulated flyovers
NOISE POLLUTION	[AIAA PAPER 79-0653] A79-26895
Twin jet shielding for aircraft noise reduction	NONLINEAR EQUATIONS
[AIAA PAPER 79-0671] A79-26924	Nonlinear equations of equilibrium for elastic
NOISE PROPAGATION	helicopter or wind turbine blades undergoing
A finite element subvolume technique for structural-borne interior noise prediction	moderate deformation [NASA-CR-159478] N79-19414
in aircraft	NONLINEAR PROGRAMMING
[AIAA PAPER 79-0585] A79-26882	Control system time response optimization - A
Propagation of buzz-saw noise in a nonuniform medium	nonlinear programming approach for aircraft
contoured jet engine inlets	flight
[AIAA PAPER 79-0639] A79-26896	[AIAA PAPER 79-0540] A79-25859
An airborne reference noise source for studying airplane flyover noise propagation and measurement	NONUMIFORM FLOW
[AIAA PAPER 79-0650] A79-26928	Axial compressor operation with radially nonuniform inflow
Characteristics of propeller noise on an aircraft	A79-27743
fuselage related to interior noise transmission	NOZZLE PLOW
[AIAA PAPER 79-0646] A79-26932	Quasi-natural numerical methods for the
NOISE REDUCTION	computation of inviscid potential or rotational
<pre>Wave propagation in ducts using the finite element method for aircraft noise reduction</pre>	transonic flows A79-26487
[AIAA PAPER 79-0659] A79-26879	Discrete noise spectrum generated by an
An experimental study of USB flap noise reduction	acoustically excited jet
through mean flow modification Upper Surface	[AIAA PAPER 79-0592] A79-26887
Blown	Sound absorption caused by vorticity shedding,
[AIAA PAPER 79-0607] A79-26908	demonstrated with a jet flow
Considerations for the design of inlet flow conditioners for static fan noise testing	[AIAA PAPER 79-0575] A79-26905
[AIAA PAPER 79-0657] A79-26909	An experimental study of USB flap noise reduction through mean flow modification Upper Surface
Diagnostic evaluation of jet noise suppression	Blown
mechanisms	[AIAA PAPER 79-0607] A79-26908
[AIAA PAPER 79-0674] A79-26912	NUMBRICAL ANALYSIS
Twin jet shielding for aircraft noise reduction	Worst case time-histories causing largest
[AIAA PAPER 79-0671] A79-26924	deviations from a desired flight path: An
Reduction of rotor-turbulence interaction noise in static fan noise testing	analytical approach [VTH-LR-267] N79-17839
[AIAA PAPER 79-0656] A79-26925	[VTH-LR-267] N79-17839 Approximation concepts for numerical airfoil
Some effects of applying somic boom minimization	optimization
to supersonic cruise aircraft design	[NASA-TP-1370] N79-18915
[AIAA PAPER 79-0652] A79-26927	Some recent progress in transonic flow computation
Experiments concerning the anomalous behaviour of	flow distribution, numerical optimization,
aero-engine exhaust noise in flight [AIAA PAPER 79-0648] A79-26930	and airfoil design N79-18946
Effects of simulated forward flight on jet noise,	Industrial centrifugal compressors, volume 1
shock noise and internal noise	[VKI-LECTURE-SERIES-95] N79-19385
[AIAA PAPER 79-0615] A79-26936	Plow modelling and aerodynamic design techniques
Master Plan for prediction of vehicle interior noise	for centrifugal compressors
[AIAA PAPER 79-0582] A79-26943	N79-19386
Inside noise of C-1 cargo aircraft and the noise reduction performance by interior materials	Viscous flows in centrifugal compressors N79-19387
A79-27121	NUMERICAL FLOW VISUALIZATION
Advanced supersonic technology and its	Numerical study of unsteady flows of viscous
implications for the future	incompressible fluids about airfoils by a
[AIAA 79-0694] A79-27359	combined method of order 0/h2/ and 0/h4/
Structural stiffening of transmission housings	A79-24829
with metal matrix materials [AIAA 79-0806] A79-28287	Progress in transonic flow computations analysis and design methods for three-dimensional flows
A commercial airport noise environment:	supercritical wings and wing-body combinations
Measurement, prediction and control	N79-18951
[NASA-CR-3107] N79-19814	NYLON (TRADEMARK)
HOISE SPECTRA	Design and development of the 24-foot diameter
Discrete noise spectrum generated by an	hybrid Kevlar-29/nylon ribbon parachute
acoustically excited jet [AIAA PAPER 79-0592] A79-26887	[AIAA 79-0433] A79-26641
Interior noise path identification in light	lack
aircraft using multivariate spectral analysis	U
[AIAA PAPER 79-0644] A79-26915	OBLIQUE SHOCK WAVES
The effect of throttling on forward radiated fan	A shock capturing application of the finite
noise	element method to viscous compressible flow
[AIAA PAPER 79-0640] A79-26917	problem
The sound power spectrum of shock-free jets [AIAA PAPER 79-0595] A79-26918	A79-24771 OBSERVATION AIRCRAPT
Characteristics of propeller noise on an aircraft	
Characteristics of propeller noise on an aircraft fuselage related to interior noise transmission [AINA PAPER 79-0646] A79-26932	Development of casualty evacuation kit for the light observation helicopter (Kiwa)

SUBJECT INDEX PERFORMANCE TESTS

OFFSHORE PLATFORES		Recovery system preliminary design - A si	mplified
An offshore airport that works - Nagasaki		approach to determining drogue chute st	aging,
OBBOARD EQUIPMENT	A79-28185	timing, and altitude requirements [AIAA 79-0446]	A79-26650
UH-60A MEDEVAC kit		A simple physical model of a descending page 1	
	N79-19614	[AIAA 79-0447]	A79-26651
Development of casualty evacuation kit for	the	Plight simulation of a vehicle with a two	-stage
light observation helicopter (Kiwa)	N79-19616	parachute system [AIAA 79-0448]	A79-26652
OPERATIONAL PROBLEMS		Parachute inflation control using an atta-	
Environmental factors affecting the install	lation	drogue [AIAA 79-0449]	A79-26653
and operation of gas turbine engines in agricultural aircraft		A first-order theory for the effects of 1:	
[SAE PAPER 781010]	A79-25892	on parachute deployment	
OPERATIONS RESEARCH Helicopter operations development plan		[AIAA 79-0450] Parachute partial inversions	A79-26654
[PAN-RD-78-101]	₦79-18799	[AIAA 79-0451]	A79-26655
OPTICAL COMMUNICATION	<u>.</u> .	Longitudinal oscillation damping for	
An optical communication system for aircra	11 179-28034	fully-inflated parachute canopies [AIAA 79-0459]	A79-26662
Military fiber optics applications	#15 E0054	The validity of the Leicester computer mo-	
	A79-28040	parachute with fully-deployed canopy	
OPTICAL GYROSCOPES Air Force applications for optical rotation	n rate	[AIAA 79-0460] Hardware options for gliding airdrop guid	A79-26663
sensors	n race	systems	u noc
ADMIGN. 01 WT GREEN	A79-28122	[AIAA 79-0471]	A79-26671
OPTICAL WAVEGUIDES Plane problems of aerothermooptics refi	raction	Bailout from autorotating helicopters	N79-19666
in two-dimensional nonuniform medium		PARACHUTE FABRICS	
	A79-26865	Design criteria for and development of Ke	vlar
OPTIMAL CONTROL Control system time response optimization	- 1	ribbon parachutes [AIAA 79-0430]	A79-26638
nonlinear programming approach for a		Development and initial test results of p	
flight		with automatic inflation modulation /AI	
[AIAA PAPER 79-0540] Air fleet and facility planning via optima:	479-25859	[AIAA 79-0467] PARACHUTES	A79-26673
control models	•	Aerodynamic Decelerator and Balloon Techno	ology
	A79-26725	Conference, 6th, Houston, Tex., March 5	-7, 1979,
Approximation concepts for numerical airfor optimization	11	Technical Papers	A79-26626
[NASA-TP-1370]	N79-18915	Fabrication and quality assurance procedu	
OPTIMIZATION	11	assure a symmetrical lifting parachute	170 26626
Development of modern airfoil sections for subsonic cruise speeds	urdu	[AIAA 79-0427] A new life saving application for the para	A79-26636 achute
[AIAA 79-0687]	A79-27353	[AIAA 79-0456]	A79-26659
Optimizing gasturbine engine flexible rotor balancing by the LP-search method	r	Factors and tradeoffs affecting ram-air page designed for civilian personnel applica	
balancing by the br-search method	A79-27745	[AIAA 79-0457]	A79-26660
An aeroelastic optimization procedure for		Commercial parachutes from safety star	
composite high aspect ratio wings [AIAA 79-0726]	A79-28258	[AIAA 79-0458] PARAGLIDERS	A79-26661
Combined strength and aeroelastic wing syn-		Hardware options for gliding airdrop guide	ance
via constraint approximation	-70 00000	systems	•20 0667•
[AIAA 79-0724] Turbocharger design and development tea	A79-28290	[AIAA 79-0471] PARTICLES	A79-26671
assessment and design optimization		Separation and investigation of wear part	ıcles
OCCITIANTED BY OR	N79-19393	from aero-engines	N70 17056
OSCILLATING PLOW A slender delta wing oscillating in surface	e waves	[BLL-RISLEY-TR-3308-(9091.9F)] PASSENGER AIRCRAFT	N79-1785€
[VTH-LR-257]	N79-17818	Findings of the Ottawa-Montreal STOI demon	nstration
OSCILLATIONS		Service	170-27360
Wing rock due to aerodynamic hysteresis	A79-28376	[AIAA 79-0710] PERFORMANCE PREDICTION	A79-27369
OUTLET PLOW		RCS reduction of installed aircraft anten	nas
Outlet air angle prediction for subsonic fi	low	Radar Cross Section prediction	170-20716
cascades	N79-18997	Radar system design for track-while-scan	A79-24716
OZOBOHETRY	_		A79-25139
Simultaneous measurements of ozone outside inside cabins of two B-747 airliners and		Prediction of gas-turbine alloy creep characteristics	
Learjet business jet	a dates	Characteristics	A79-26841
•	A79-27571	Rotary-wing aerodynamics. Volume 2: Per:	formance
n		prediction of helicopters [NASA-CR-3083]	พ79-17811
Р		Formulation of aerodynamic prediction tec	
PAINTS		for hypersonic configuration design	
Airfield marking paints state-of-the-art [PAA-RD-78-104]	N79-17876	[NASA-CR-158994] PERFORMANCE TESTS	N79-17850
PANELS	,,,,,,	P-18 status report	
Thermal response of composite panels	170-25250	Toole of an integrated mileting co-	179-26529
Noise transmission - Turboprop problem	A79-25350	Tests of an integrated piloting, navigation display system	ou, and
[AIAA PAPER 79-0645]	A79-26933		A79-27675
PARACHUTE DESCRIT	of	P-16 high angle of attack testing	N70-1000
Simulation studies of the flight dynamics of gliding parachute systems	01	Principles of helicopter performance	N79-18886
[AIAA 79-0417]	A79-26628	[AD-A061671]	N79-18970

PERIODICALS SUBJECT INDEX

PERIODICALS		POLLUTION MONITORING	
Briefs of accidents involving turbine powers	eđ	Comparisons of turbine engine combustor exi	haust
aircraft, US general aviation, 1977		emissions measurements using three gas-sa	ampling
	N79-17830	probe designs	
Briefs of accidents involving aerial applica	ation	[AD-A061733]	N79-19005
operations, US general aviation 1977		POLYURETHANE FOAM	
	N79~17837	Foam Impact Attenuation System for RPV	
PERTURBATION THEORY		[AIAA 79-0416]	A79-26627
Slender wing in compressible flow Russia		POROUS WALLS	
	A79-25872	Nonsteady flow of an incompressible liquid	Over
PILOT ERROR Why doesn't aircraft accident investigation		slender permeable profiles	A79-27062
prevent accidents		POSITION (LOCATION)	R/3"2/002
	A79-27319	The search and rescue satellite (SARSAT) sy	vstem
Alrcraft accident report: Allegheny Airline		project	,
Inc. BAC 1-11, N1550, Rochester, New York		project	N79-18115
9, 1978	.,1	POTENTIAL PLOW	
	N79-18961	Quasi-natural numerical methods for the	
PILOT PERFORMANCE		computation of inviscid potential or rota	ational
Cockpit displays and the growing role of the	e pilot	transonic flows	
in the ATC system			A79-26487
	A79-26875	Theoretical lower limits of forebody drag	
Two-segment approach investigation on a			179-26593
moving-base piloted flight simulator	n70 17000	POWDER (PARTICLES)	
	N79-17880	Full-scale fire modeling tests of a compact response foam and dry chemical powder dis	
Visual pockets: A design parameter for heli instrument panels	rcobter	system	spensing
	179-19641	[FAA-NA-78-24]	N79-17825
PILOT TRAINING	175 15041	POWDER HETALLURGY	1177 11023
Visual simulation devices for flight training	n or	Potential uses of rapidly solidified alloys	s in das
simulators Russian book	•9	turbine engines	· ,
	179-26354	our value	A79-27313
Airline approach to CAT III		POWER CONDITIONING	
	179-26533	Filter weight minimization for rectified	
PIPE PLOW		superconducting alternator power supplies	3
The influence of geometric asymmetry on the	flow	for aircraft	
downstream of row of jets discharging norm	nally		A79-26966
into a free stream		POWER SPECTRA	
	A79-25065	The sound power spectrum of shock-free jets	
Heat generation in cavities at high velocity	y flights	[AIAA PAPER 79-0595]	A79-26918
resonance-pipe effect		Gust load estimation using a simplified por	ier
	8 79-1781 5	spectral technique	W70 47070
PL/1		[ARAP-362]	N79-17870
GASP-PL/I simulation of integrated avionic s	system	POWERED LIFT AIRCRAFT	rol of
processor architectures [NASA-CR-158244]	179-18973	Configuration management and automatic cont an augmentor wing aircraft with vectored	
PLASTIC DEPORMATION	175-10573	[NASA-TP-1222]	N79-17872
Four lectures on fatigue crack growth		PREDICTION ANALYSIS TECHNIQUES	1175 17072
	179-25484	Reliability growth planning to achieve RIW	/GETBF
PLUMES		requirements for an airborne radar	
Space shuttle afterbody aerodynamics/plume		• • • • • • • • • • • • • • • • • • • •	A79-24965
simulation data summary		Validation of IEMCAP using the B-52	
[NASA-TP-1384]	779-17810	Intrasystem Electro Magnetic Compatibilit	t y
POLLUTION CONTROL		Analysis Program	
Time degradation factors for the turbine eng	jine		A79-25326
exhaust emissions. Volume 1: Program		Life Cycle Cost in advanced technology engi	rne
description and results air pollution		development	
	179-17860	[SAE PAPER 781029]	A79-25901
Time degradation factors for the turbine eng		A finite element subvolume technique for	·-
exhaust emission. Volume 2: JT8D-9 test air pollution control	aata	structural-borne interior noise prediction)II
	8 79-1 7863	in aircraft [AIAA PAPER 79-0585]	A79-26882
Time degradation factors for turbine engine	173-17003	Diagnostic evaluation of jet noise suppress	
exhaust emissions. Volume 3: JT3D-7 test	data	nechanisms	
air pollution control	4404	[AIAA PAPER 79-0674]	A79-26912
	779-17864	Master Plan for prediction of vehicle inter	
Time degradation factors for turbine engine		[AIAA PAPER 79-0582]	A79-26943
exhaust emissions. Volume 4: JT3D-7 test	t data	Factors affecting residual strength predict	tion of
air pollution control		a cracked aircraft structure	
[NREC-1238-9-VOL-4]	979-17865		A79-28380
Time degradation factors for turbine engine		PREMIXED PLANES	
exhaust emissions. Volume 5: JT3D-3B tes	st data	Lean combustion limits of a confined	
air pollution control		premixed-prevaporized propane jet	
	179-17866	[AIAA PAPER 79-0538]	A79-25856
Time degradation factors for turbine engine		PRESSURE DISTRIBUTION	
exhaust emissions. Volume 6: JT9D-3A tes	st data	Experimental studies on the effects of a st	
	179-17867	support on the pressure distribution arou	ини а
Time degradation factors for turbine engine	1/3-1/00/	spherical object [NASA-CR-158127]	N79-17800
exhaust emissions. Volume 7: RB211-228 t	tost data	A modification to linearized theory for pre	
air pollution control	cost duta	of pressure loadings on lifting surfaces	
	779-17868	supersonic mach numbers and large angles	
Time degradation factors for turbine engine	,,,,,,,,	[NASA-TP-1406]	N79-17806
exhaust emissions. Volume 8: C700-2D tes	st data	Pressure and heat-transfer distributions in	
	779-17869	simulated wing-elevon cove with variable	
Control of air pollution from aircraft and	-	at a free-stream Mach number of 6.9	-
aircraft engines		[NASA-TM-74095]	N79-18284
N	179-19376		

SUBJECT INDEX RADAR TARGETS

PRESSURE DRAG Theoretical lower limits of forebody drag A79-26593	PROTECTION Alreraft fire protection and rescue procedures /2nd edition/ Book
PRESSURE GAGES Pressure measurement in air data instrumentation	PSYCHOACOUSTICS A79-25750
PRESSURE BEASUBERBRTS	The annoyance of multiple noisy events ratings for simulated flyorers
Pressure measurement in air data instrumentation A79-25850	[AIAA PAPER 79-0653] A79-26895 PULSE DOPPLER RADAR
An improved system for use in conducting wake investigation for a wing in flight	Near-field analysis of helicopter rotating blades modulation interference
differential pressure measurements for drag 11vestigations	PULSE DURATION HODULATION
[NASA-CASE-PEC-11024-1] N79-17797 PRESSURE OSCILLATIONS	An optical communication system for aircraft A79-28034
Unsteady pressures on a NACA 64A010 airfoil - Experimental and theoretical results [AIAA PAPER 79-0330] A79-26545	PULSED LASERS Laser propulsion A79-26598
PRESSURE SENSORS Pressure measurement in air data instrumentation	Ω
The Dulles International Airport wind-shear	QUALITY CONTROL
detection system Statistical results A79-27574 PROBABILITY THEORY	Fabrication and quality assurance procedure to assure a symmetrical lifting parachute [AIAA 79-0427] A79-26636
Probabilistic analysis of air carrier accidents N79-18078	A new standard for lightning qualification testing of aircraft: Technical overview, definitions
PRODUCT DEVELOPMENT The continuity factor in aircraft development	and basic waveforms
PRODUCTION ENGINEERING	QUIET ENGINE PROGRAM Neasured and predicted noise of the AVCO-Lycoming
Turbine engine cost reduction using Life Cycle Cost techniques	YF-102 turbofan engine [AIAA PAPER 79-0641] A79-26877
[SAR PAPER 781031] A79-25903 GASP IV simulation model for the composites and	R
bonding production facility A79-27297	BADAR ANTENNAS
PRODUCTION MANAGEMENT Cockpit management N79-18890	Modeling the X-band radar augmentation system of a high altitude supersonic target A79-24715
PROJECT PLANNING The application of computer aided techniques to	RCS reduction of installed aircraft antennas Radar Cross Section prediction
project design for aircraft A79-26592	RADAR BEACONS
F-18 status report W79-18888	Operational evaluation of an Air Traffic Control Radar Beacon System open array antenna
PROPANE Lean combustion limits of a confined	RADAR CROSS SECTIONS
premixed-prevaporized propane jet [AIAA PAPER 79-0538] A79-25856	RCS reduction of installed aircraft antennas Radar Cross Section prediction
PROPELLER DRIVE V/STOL aircraft engine and mechanical drive	A79-24716 RADAR DATA
COmponent integration [SAR PAPER 781038] A79-25906	Concept of modular software for the stepwise construction of radar data processing systems
PROPELLER FARS Prop-fan propulsion - Its status and potential	with minicomputers, taking into account as example the Airtrack System
[SAE PAPER 780995] A79-25880 PROPELLER SLIPSTREAMS	RADAR DETECTION
Propeller slipstream wing interactions at Mach no. 0.8	Digital target extraction at civil air traffic control radar installations in the Federal
[SAE PAPER 780997] A79-25881 PROPELLERS	Republic of Germany and possibilities for its further development from the point of view of
Characteristics of propeller noise on an aircraft fuselage related to interior noise transmission	the Federal Institute of ATC A79-26753
[AIAA PAPER 79-0646] A79-26932 PROPORTIONAL CONTROL	BADAR EQUIPMENT Reliability growth planning to achieve RIW/GMTHP requirements for an airborne radar
Design of proportional-plus-integral controllers for multivariable systems A79-28223	A79-20965 Multimode radar processor for combat aircraft
PROPULSION SYSTEM CONFIGURATIONS Prop-fan propulsion - Its status and potential	A79-28058
[SAB PAPER 780995] A79-25880 V/STOL arcraft engine and mechanical drive	System for the display of extracted radar data on the basis of minicomputer-controlled display
COmponent integration [SAR PAPER 781038] A79-25906	devices /DERD-MC/ for an employment in Air Traffic Control
Laser propulsion A79-26598	RADAR REFLECTORS
Twin jet shielding for aircraft noise reduction [Alah PAPER 79-0671] A79-26924	TASAR, a thinned adaptive synthetic aperture radar A79-27135
PROPULSION SYSTEM PERFORMANCE Planning the development and qualification process for the next generation of high technology	RADAR SCANNING Radar system design for track-while-scan A79-25139
alteraft engines [SAE PAPER 780992] A79-25878	RADAR TARGETS New approaches concerning the implementation of
PROPULSIVE EFFICIENCY Prop-fan propulsion - Its status and potential	radar target extractors with the aid of very fast microprogrammable data processors
[SAE PAPER 780995] A79-25880	A79-26754

RADAR TRACKING SUBJECT INDEX

Estimation of target elevation angle from for shipboard fire control	2-D radars	RANGE AND RANGE RATE TRACKING Short Range Terminal Radar (SRTR) definition [PAA-RD-78-64]	n study N79+18156
Survey of radar simulation training at AT facilities		RAPID QUENCHING (HETALLURGY) Potential uses of rapidly solidified alloys	
[FAA-NA-78-27] RADAR TRACKING	N79-17877	turbine engines	A79-27313
Radar system design for track-while-scan	A79-25139	REAL GASES Theoretical investigations of real gas effe	
Problems of computer-aided tracking, givi particular attention to radar which can	ng	cryogenic wind tunnels [DS-FB-76/50B]	N79-17820
electronically turned	A79-26761	RECORDING INSTRUMENTS Recording methods for steady state and tran	SIONT
SEATRACKS - A millimeter wave radar fire system		signals aircraft engine tests	A79-25849
	A79-27144	RECOVERY PARACHUTES	
Estimation of target elevation angle from for shipboard fire control	2-D radars A79-27145	Recovery system preliminary design - A simp approach to determining drogue chute stag timing, and altitude requirements	
Short Range Terminal Radar (SRTR) definit	lon study N79-18156		A79-26650
RADIAL PLOW Axial compressor operation with radially		Redundant control systems for flight vehicl Russian book	les
nonuniform inflow			A79-25875
Industrial contribusal commessars volum	179-27743	REFLECTION	
Industrial centrifugal compressors, volum [VKI-LECTURE-SERIES-95] A stress and strain analysis of industrial	N79-19385 l radial	Internal cockpit reflections of external po- light sources for the model YAH-64 advanc attack helicopter	
compressor impellers using the framewor finite element method and descripti		REFRACTION	175-15045
RADIATION EPPECTS	ห79-19391	Plane problems of aerothermooptics refr in two-dimensional nonuniform medium	action
Induced effects of lightning on an all co	mposite		A79-26865
aircraft	N70 10000	RELEASING Carbon fiber dispersion models used for ris	. .
RADIATION HARDENING	N79-18242	analysis calculations	· K
Protection/hardening of aircraft electron	10		N79-18080
systems against the indirect effects of		RELIABILITY AWALYSIS	
RADIATIVE HEAT TRANSFER	N79-18238	Reliability growth on B-52 FLIR system	A79-24958
Pool fire radiation through a door in a s aircraft fuselage	amulated	RELIABILITY ENGINEERING Reliability growth planning to achieve RIW/	
[FAA-NA-78-38]	N79-17966	requirements for an airborne radar	
RADIO COMMUNICATION A proposed integrated ECM system using the	_		A79-24965
	е	Technology and the new look meet the F/A-18 reliability challenge	Laual
constant index lens antenna	e A79-24726	reliability challenge [SAE PAPER 781024]	A79-25897
	A79-24726	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus	A79-25897
constant index lens antenna	A79-24726	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures	A79-25897
Constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the con-	A79-24726 N79-19647	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends	A79-25897 selage A79-27354
constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft	A79-24726 N79-19647 Ceptual	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability	A79-25897 selage A79-27354
constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050]	A79-24726 N79-19647 Ceptual A79-25915	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689]	A79-25897 selage A79-27354
Constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidensystems	A79-24726 N79-19647 Ceptual A79-25915	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability	A79-25897 relage A79-27354 for A79-27355
constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidsystems [ATAA 79-0471]	A79-24726 N79-19647 Ceptual A79-25915	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES PAA remote terminal system frequency assign model	A79-25897 selage A79-27354 for A79-27355
Constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidensystems	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES PAA remote terminal system frequency assign model	A79-25897 relage A79-27354 for A79-27355
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guids systems [AIAA 79-0471] RADIO FREQUENCIES An RF compatible lightning diverter strip	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV	A79-25897 relage A79-27354 for A79-27355 ment A79-25323 recovery
Constant index lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidence systems [AIAA 79-0471] RADIO PREQUENCIES	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV	A79-25897 lelage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidsystems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES FOAM IMPACT Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an acc	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guids systems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REBOTE CONSOLES PAA remote terminal system frequency assign model REBOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidence systems [ATAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110]	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely piloresearch vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance	A79-25897 selage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 tied tive
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT)	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidence systems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COHSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006]	A79-25897 selage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 tied tive
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) project	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidensystems [ATAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in search and rescue satellite (SARSAT)	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted rtive N79-17849
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) project	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely piloresearch vehicle for flight testing an actifuter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedu	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 ires A79-25750
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidensystems [ATAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project	A79-24726 N79-19647 Ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedurance flow application for the parace [AIAA 79-0456]	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 chute A79-26659
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidence systems [AIAA 79-0471] RADIO FREQUENCIES An RF compatible lightning diverter strip RADIO FREQUENCY INTERFERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedu /2nd edition/ Book A new life saving application for the parac [AIAA 79-0456] The search and rescue satellite (SARSAT) sy	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 chute A79-26659
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guidensystems [ATAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedurance flow application for the parace [AIAA 79-0456]	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 chute A79-26659
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guident systems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADOMES Lightning protection with segmented divertion aircraft radomes and dielectric strip RADIET BISSILES	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an ac flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedu /2nd edition/ Book A new life saving application for the parac [AIAA 79-0456] The search and rescue satellite (SARSAT) sy	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 teld tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115 missions
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO BELAY SYSTERS The search and rescue satellite (SARSAT) project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) project RADOMES Lightning protection with segmented diverfor aircraft radomes and dielectric str RAMJET HISSILES An experimental wind-tunnel investigation	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilor research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERRITONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RP compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The static charging testing project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS An experimental wind-tunnel investigation ram-air-spoiler roll-control device on interpretation of the project of the projec	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilor research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedured edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115 MISSIONS N79-19606
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO BELAY SYSTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satel	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE COMSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Poam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilor research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERRITONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 ored N79-17849 N79-17852 tres A79-25750 chute A79-26659 rytelage N79-18115 vm15-19606 N79-19614
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotatin modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS An experimental wind-tunnel investigation ram-air-spoiler roll-control device on forward-control missile at supersonic s [NASA-TP-1353] RAMPS (STRUCTURES)	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a peeds N79-17809	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES PAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilor research vehicle for flight testing an act flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary UH-60A MEDEVAC kit Casualty evacuation by helicopter	A79-25897 telage A79-27354 for A79-27355 tment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115 missions N79-19606 N79-19614 N79-19615
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft (SAE PAPER 781050) Hardware options for gliding airdrop guident systems (ATAA 79-0471) RADIO FREQUENCIES An RF compatible lightning diverter strip RADIO FREQUENCY INTERFERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS An experimental wind-tunnel investigation ram-air-spoiler roll-control device on forward-control missile at supersonic sinksa-TP-1353] RAMPS (STRUCTURES) Ski-jump - A great leap for tactical airpe	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a peeds N79-17809	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES FOAM Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an actifuter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERRIONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary UH-60A MEDEVAC kit Casualty evacuation by helicopter	A79-25897 telage A79-27354 for A79-27355 tment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115 missions N79-19606 N79-19614 N79-19615
CONSTANT INDEX LENS ANTENNA Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guident systems [AIAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO RELAY SYSTEMS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSHITTERS The search and rescue satellite (SARSAT) in project RADOMES Lightning protection with segmented divertion aircraft radomes and dielectric str RAMJET MISSILES An experimental wind-tunnel investigation ram-air-spoiler roll-control device on forward-control missile at supersonic s [NASA-TP-1353] RAMPS (STRUCTURES) Ski-jump - A great leap for tactical airpentation of the proposed	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a peeds N79-17809	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES Foam Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an acc flutter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERATIONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the paracc [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary UH-60A MEDEVAC kit Casualty evacuation by helicopter Development of casualty evacuation kit for light observation helicopter (Kiwa)	A79-25897 telage A79-27354 for A79-27355 tment A79-25323 recovery A79-26627 ted tive N79-17849 N79-17852 tres A79-25750 thute A79-26659 stem N79-18115 missions N79-19606 N79-19614 N79-19615
CONSTANT INDEX lens antenna Some aspects of helicopter communications RADIO CONTROL Use of radio controlled models in the condevelopment of V/STOL aircraft [SAE PAPER 781050] Hardware options for gliding airdrop guid systems [AITAA 79-0471] RADIO PREQUENCIES An RF compatible lightning diverter strip RADIO PREQUENCY INTERPERENCE Near-field analysis of helicopter rotation modulation interference Aircraft static charging testing [ONERA, TP NO. 1978-110] RADIO BELAY SYSTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS The search and rescue satellite (SARSAT) in project RADIO TRANSMITTERS Lightning protection with segmented divertion aircraft radomes and dielectric str RADIET BISSILES An experimental wind-tunnel investigation ram-air-spoiler roll-control device on forward-control missile at supersonic s [NASA-TP-1353] RAMPS (STRUCTURES) Ski-jump - A great leap for tactical airpov/STOL jet launching from upward-inclin	A79-24726 N79-19647 ceptual A79-25915 ance A79-26671 N79-18237 g blades A79-25131 A79-26130 system N79-18115 system N79-18115 ters uctures A79-25317 of a a peeds N79-17809 ower ed ramp	reliability challenge [SAE PAPER 781024] Crashworthiness tests on model aircraft fus structures [AIAA 79-0688] Design against fatigue - Current trends aircraft structural reliability [AIAA 79-0689] REMOTE CONSOLES FAA remote terminal system frequency assign model REMOTELY PILOTED VEHICLES FOAM Impact Attenuation System for RPV [AIAA 79-0416] The development of the DAST I remotely pilo research vehicle for flight testing an actifuter suppression control system [NASA-CR-144881] Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] RESCUE OPERRIONS Aircraft fire protection and rescue procedu/2nd edition/ Book A new life saving application for the parace [AIAA 79-0456] The search and rescue satellite (SARSAT) sy project Rescue helicopters in primary and secondary UH-60A MEDEVAC kit Casualty evacuation by helicopter	A79-25897 telage A79-27354 for A79-27355 ment A79-25323 recovery A79-26627 teld tive N79-17849 N79-17852 tres A79-25750 chute A79-26659 retwith a a a a a a a a a a a a a a a a a a a

BSEARCH AND DEVELOPMENT	Interactional aerodynamics of the single rotor
NASA research on general aviation power plants	helicopter configuration. Volume 8. frequency
[AIAA PAPER 79-0561] A79-25870	analyses of wake single film data, basic configuration wake exploration
Planning the development and qualification process for the next generation of high technology	[AD-A062013] N79-18956
aircraft engines	Interactional aerodynamics of the single rotor
[SAE PAPER 780992] A79-25878	helicopter configuration. Volume 6-A:
Requirements and constraints in the development and qualification of gas turbine engines for the	One-third octave band spectrograms of wake single film data, buildup to baseline
Navy	[AD-A061994] N79-18958
[SAE PAPER 780994] A79-25879	Interactional aerodynamics of the single rotor
The continuity factor in aircraft development A79-26536	helicopter configuration. Volume 8-C
Development and initial test results of parachutes	Prequency analyses of wake single film data, hubcaps and air ejectors
with automatic inflation modulation /AIM/	[AD-A061995] N79-18959
[AIAA 79-0467] A79-26673	Design, calibration, and application of a sensor
ESBARCH HAFAGEHERT Total environment survivability methodology	for measuring time dependent angle of attack of helicopter blades
[AD-A061888] N79-18971	N79-18968
ESI DUAL STRESS	Principles of helicopter performance
Residual-stress formation during the thermal hardening of components in gas-turbine engines	[AD-A061671] N79-18970
A79-26828	Nonlinear equations of equilibrium for elastic helicopter or wind turbine blades undergoing
ESPONSE TIME (COMPUTERS)	moderate deformation
FAA remote terminal system frequency assignment	[NASA-CR-159478] N79-19414
model A79-25323	ROTATING FLUIDS Quasi-natural numerical methods for the
EYBOLDS NUMBER	computation of inviscid potential or rotational
Characteristic aerodynamic coefficients at high	transonic flows
Reynolds numbers A79-25247	ROTATION A79-26487
Experiments on tandem diffusers with	Air Force applications for optical rotation rate
boundary-layer suction applied in between	sensors
[NASA-CR-158957] N79-17803 IBBON PARACHUTES	ROTOR AERODYNAMICS
Design criteria for and development of Kevlar	Characteristics of the wake of a lightly loaded
ribbon parachutes	compressor or fan rotor
[AIAA 79-0430] A79-26638	[AIAA PAPER 79-0550] A79-25861
Design and development of the 24-foot diameter hybrid Kevlar-29/nylon ribbon parachute	A comparison of linear acoustic theory with experimental noise data for a small-scale
[AIAA 79-0433] A79-26641	hovering rotor
ISK	[AIAA PAPER 79-0608] A79-26876
An assessment of the risks presented by the use of carbon fiber composites in commercial aviation.	Unsteady stator response to upstream rotor wakes [AIAA PAPER 79-0579] A79-26945
Volume 1: Final report. Volume 2: Supporting	Optimizing gasturbine engine flexible rotor
appendices	balancing by the LP-search method
[NASA-CR-158989] N79-18074 An assessment of the risks presented by the use of	A79-27745
carbon fiber composites in commercial aviation:	Interactional aerodynamics of the single rotor helicopter configuration. Volume 6-A:
Executive summary	One-third octave band spectrograms of wake
N79-18075	single film data, buildup to baseline N79-18958
Overview of the carbon fiber problem N79-18076	[AD-A061994] N79-18958 Interactional aerodynamics of the single rotor
Synthesis of national risk profile	helicopter configuration. Volume 8-C:
N79-18085	Prequency analyses of wake single film data,
Interpretation of results	hubcaps and air ejectors [AD-A061995] N79-18959
OCKET ENGINE DESIGN	ROTOR BLADES
Path in rocket technology - Selected works,	Wear-field analysis of helicopter rotating blades
1924-1946 Russian book A79-27599	modulation interference A79-25131
OCKET THRUST	An in-place recalibration technique to extend the
Laser propulsion	temperature capability of capacitance-sensing,
DTARY WINGS	rotor-blade-tip-clearance measurement systems [SAE PAPER 781003] A79-25885
Near-field analysis of helicopter rotating blades	An investigation of model helicopter rotor blade
modulation interference	slap at low tip speeds
A79-25131 Helicopter rotor radius optimization	[AIAA PAPER 79-0613] A79-26938 ROTOR BLADES (TURBONACHINERY)
[AIAA PAPER 79-0554] A79-25865	Characteristics of the wake of a lightly loaded
Lifting surface theory for skewed and swept	compressor or fan rotor
subsonic wings [AIAA PAPER 79-0551] A79-25869	[AIAA PAPER 79-0550] A79-25861
[AIAA PAPER 79-0551] A79-25869 An investigation of model helicopter rotor blade	Integrally cast turbine rotor for high volume production
slap at low tip speeds	[SAE PAPER 781000] A79-25883
[AIAA PAPER 79-0613] A79-26938	Turbulence characteristics in the near wake of a
Practure mechanics and fail-safe design for helicopter rotor structures	compressor rotor blade [AIAA PAPER 79-0280] A79-26544
A79-26986	Operational experience with linked-blade
Design and development of an helicopter rotor hub	high-output gas-turbine
and elastomeric bearing [AIAA 79-0815] A79-28289	A79-26830 Direct experimental verification of the
Rotary-wing aerodynamics. Volume 2: Performance	theoretical model predicting rotor noise
prediction of helicopters	generation
[NASA-CR-3083] N79-17811	The effect of throttling on forward radiated fan
Inertial dynamics of a general purpose rotor [NASA-TH-78557] N79-18916	The effect of throttling on forward radiated fan noise
	[AIAA PAPER 79-0640] A79-26917

ROTOR LIFT SUBJECT INDEX

Strain gage system englustion program		CRIDCE DINID	
Strain gage system evaluation program [NASA-CR-159486]	N79-19314	SEARCH RADAR Radar system design for track-while-scan	
ROTOR LIFT		•	A79-25139
Constant life rotor for a heavier than air		SEATS	
[NASA-CASE-ARC-11045-1] ROTOR SYSTEMS RESEARCH AIRCRAFT	N79-17847	Crashworthy helicopter seats and occupant restraint systems	
Inertial dynamics of a general purpose roto			N79-19658
	N79-18916	Some improvements to the UK helicopter cock	
ROTORCRAFT AIRCRAFT		SECONDARY RADAR	N79-19659
Future advanced technology rotorcraft [AIAA 79-0705]	A79-27366	Operational evaluation of an Air Traffic Co	ntrol
Briefs of accidents involving rotorcraft, U		Radar Beacon System open array antenna	
general aviation, 1977			A79-27139
[NTSB-AMM-78-15] Constant life rotor for a heavier than air	N79-17831	SEMICOMDUCTOR LASERS Aircraft velocity and altitude measurements	neina
	N79-17847	a tunable diode laser	using
ROTORS			A79-28139
Rotor fragment protection program: Statist		SEPARATED PLOW	
aircraft gas turbine engine rotor failure occurred in US commercial aviation during		Behavior of elastic systems in separated fl	.ow 179-25618
	N 79-18977	A visual investigation of the separation an	
Comparison between flows in cascades and ro		subsequent transition near the leading ed	ge of
the transonic range. 1: Basic considera	tions N79-19000	airfoils	170 DEGC 1
Comparison between flows in cascades and ro		[AIAA PAPER 79-0552] Experimental investigation of the effect of	A79-25863
the transonic range. 2: Investigation o		surface discontinuity on step-backward fl	
transonic compressor cascades and compari			A79-27000
with rotor data	พ79-19001	Contribution to the development of theoreti	
RUNWAY CONDITIONS	M /9-19001	calculations for the design and optimizat lifting bodies. (Solution of three-dimen	
Environmental models for moisture absorptio	n by	basic thermo fluid dynamics equations wit	
aircraft composites		strong interacting attached and separated	flow
RUNWAYS	A79-27572	fields)	N79-17816
Runway surface condition sensor		[BMVG-PBWT-78-4] Analysis of base-flow problems during power	
	N79-17878	supersonic flight	
_			N79-18926
S		SERVICE LIFE Causes for the deterioration of splined	
SAPETY DEVICES		connections in aircraft engines during se	rvice
Lightning protection with segmented diverte			A79-25249
for aircraft radomes and dielectric struc	tures A79-25317	Recent General Electric engine development for improved service life	testing
Commercial parachutes from safety stand			A79-2587€
	POTHE	DAL PAPER /OUPPU	AIJ-ZJOIC
	A79-26661	[SAE PAPER 780990] Requirements and constraints in the develop	
[AIAA 79-0458] Crashworthy helicopter seats and occupant		Requirements and constraints in the develop and qualification of gas turbine engines	ment
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems	Ā79−266€1	Requirements and constraints in the develop and qualification of gas turbine engines Navy	ment for the
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems	A79-26661 N79-19658	Requirements and constraints in the develop and qualification of gas turbine engines Navy	ment for the
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock	A79-26661 N79-19658	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15	ment for the 1179-25879 n
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY HAWAGEBERT	Ā79-266€1 N79-19658 pit	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032]	ment for the A79-25879 n
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport	Ā79-266€1 N79-19658 pit	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15	ment for the A79-25879 n
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu	Ā79-26661 N79-19658 pit N79-19659 A79-25542	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761]	ment for the A79-25879 n
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book	Ā79-26661 N79-19658 pit N79-19659 Ā79-25542 res	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE ELEMENTS)	ment for the A79-25879 n A79-25904 A79-28275
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY HANAGEBENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book	Ā79-26661 N79-19658 pit N79-19659 A79-25542	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE BLEMENTS) An unstable subsynchronous critical speed s	ment for the 100 A 79-25879 101 A 79-25904 101 A 79-28275 101 Only 101
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan	Ā79-26661 N79-19658 pit N79-19659 Ā79-25542 res	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055]	ment for the 100 A 79-25879 101 A 79-25904 101 A 79-28275 101 Only 101
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE BLEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL	ment for the A79-25879 n A79-25904 A79-28275 olution t system
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY HANAGEBERT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additi	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel	ment for the A79-25879 n A79-25904 A79-28275 olution t system
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY HANAGEBERT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SAIT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (HACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY HANAGEBERT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SAIT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY BANAGEBERT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additiont corrosion SANDWICH STRUCTURES Thermal response of composite panels	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900 delta
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY BANAGEBERT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additiont corrosion SANDWICH STRUCTURES Thermal response of composite panels	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sypicolect	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (HACHINE BLEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHAMP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900 delta
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) syproject	Ā79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHABP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically executed jet	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900 delta N79-18909
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing the hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) syproject SCALE MODELS	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592]	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25900 delta
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) syproject SCALE MODELS A simple physical model of a descending par [AIAA 79-0447]	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHABP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically executed jet	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-25900 delta N79-18909 A79-26887
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSHISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671]	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-25900 delta N79-18909 A79-26887
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an acceptance of the search of the search of a supersonic transport concept in an acceptance of the supersonic transport concept in a supersonic transport concept in an acceptance of the supersonic transport concept in a supersonic transport concept in an acceptance of the supersonic transport concept in a supersonic transport concept in an acceptance of the supersonic transport	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671]	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26924 A79-26924
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an airflow facility	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671]	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26924 A79-26924
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSHISSION The search and rescue satellite (SARSAT) syproject SCALE HODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an aflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Tuin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25900 delta N79-18909 A79-26887 eduction A79-26924 ntrol A79-27144
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additine hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an afflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic A79-26920	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE BLEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING BDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LATERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25900 delta N79-18909 A79-26887 eduction A79-26924 ntrol A79-27144
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAFETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [FAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) syproject SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an aflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574]	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHABP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING TVIN jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25916 A79-26887 eduction A79-26924 ntrol A79-27144 -D radars
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an afflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] SEALS (STOPPERS) Fuel tank sealant requirements for advance	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-26546 A79-26651 e model nechoic A79-26920 A79-26946	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE BLEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26887 eduction A79-26824 ntrol A79-27144 -D radars A79-27145 and
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sympoject SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an afflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] SEALS (STOPPERS) Fuel tank sealant requirements for advance performance aircraft	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic A79-26920 A79-26946 high	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHABP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING TVIN jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control How to add satellite navigational accuracy stability to existing offshore NAV System	ment for the A79-25879 n A79-25904 A79-28275 olution t system A79-25916 A79-25916 A79-26887 eduction A79-26924 ntrol A79-27144 and S
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSHISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an aflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] SEALS (STOPPERS) Fuel tank sealant requirements for advance performance aircraft [AIAA 79-08071]	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-26546 A79-26651 e model nechoic A79-26920 A79-26946 high A79-28288	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control How to add satellite navigational accuracy stability to existing offshore NAV System	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26887 eduction A79-26824 ntrol A79-27144 -D radars A79-27145 and
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sympoject SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an afflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] SEALS (STOPPERS) Fuel tank sealant requirements for advance performance aircraft	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-26546 A79-26651 e model nechoic A79-26920 A79-26946 high A79-28288	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE BLEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control How to add satellite navigational accuracy stability to existing offshore NAV System	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26887 eduction A79-26924 ntrol A79-27144 -D radars A79-27145 and s A79-27388
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSHISSION The search and rescue satellite (SARSAT) sy project SCALE HODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an aflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] SEALS (STOPPERS) Fuel tank sealant requirements for advance performance aircraft [AIAA 79-0807] Composite seal for turbomachinery backiturbine engine shrouds [NASA-CASE-LEW-12131-1]	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic A79-26920 A79-26946 high A79-28288 ngs for N79-18318	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAFTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027] SHARP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING Twin jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control How to add satellite navigational accuracy stability to existing offshore NAV System SHOCK ABSORBERS Foam Impact Attenuation System for RPV: [AIAA 79-0416]	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26887 eduction A79-26924 ntrol A79-27144 -D radars A79-27145 and s A79-27388
[AIAA 79-0458] Crashworthy helicopter seats and occupant restraint systems Some improvements to the UK helicopter cock SAPETY MANAGEMENT Safety of air transport Aircraft fire protection and rescue procedu /2nd edition/ Book Helicopter operations development plan [PAA-RD-78-101] SALT SPRAY TESTS Effect of a chromium-containing fuel additing hot corrosion SANDWICH STRUCTURES Thermal response of composite panels SATELLITE TRANSMISSION The search and rescue satellite (SARSAT) sy project SCALE MODELS A simple physical model of a descending par [AIAA 79-0447] Airframe noise measurements on a small-scal of a supersonic transport concept in an aflow facility [AIAA PAPER 79-0666] Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA 79-0807] SEALS (STOPPERS) Fuel tank sealant requirements for advance performance aircraft [AIAA 79-0807] Composite seal for turbomachinery backing [NASA-CASE-LEW-12131-1] Thermoelastic and dynamic phenomena in seal	A79-26661 N79-19658 pit N79-19659 A79-25542 res A79-25750 N79-18799 ve on A79-26546 A79-25350 stem N79-18115 achute A79-26651 e model nechoic A79-26920 A79-26946 high A79-28288 ngs for N79-18318	Requirements and constraints in the develop and qualification of gas turbine engines Navy [SAE PAPER 780994] Life cycle cost in preliminary engine desig for P-15 [SAE PAPER 781032] Statistical estimation of economic life for aircraft structures [AIAA 79-0761] SHAPTS (MACHINE ELEMENTS) An unstable subsynchronous critical speed s of shaft failures in P-16 engine star [SAE PAPER 781055] SHALE OIL Shale oil - The answer to the jet fuel availability guestion [SAE PAPER 781027] SHABP LEADING EDGES Calculation of supersonic viscous flow over wings with sharp subsonic leading edges SHEAR LAYERS Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592] SHIELDING TVIN jet shielding for aircraft noise r [AIAA PAPER 79-0671] SHIPS SEATRACKS - A millimeter wave radar fire co system Estimation of target elevation angle from 2 for shipboard fire control How to add satellite navigational accuracy stability to existing offshore NAV System SHOCK ABSORBERS Foam Impact Attenuation System for RPV	ment for the A79-25879 n A79-25904 A79-25916 A79-25916 A79-25916 A79-26887 eduction A79-26924 ntrol A79-27144 -D radars A79-27145 and SA79-27388 recovery

SUBJECT INDEX STATISTICAL ABALYSIS

COARS CLURATE LENGTHER		GOOTE TANKS
SHORT TAKEOFF AIRCRAFT Findings of the Ottawa-Montreal STOL demon	stration	Applications of diffraction theory to aeroacoustics
service [AIAA 79-0710]	A79-27369	[NASA-TM-80053] N79-18686 SPACE SHOTTLES
SHROUDED TURBINES	RIJ EISOJ	Space shuttle afterbody aerodynamics/plume
Operational experience with linked-blade		simulation data summary
high-output gas-turbine	.70 0000	[NASA-TP-1384] N79-17810
Composite seal for turbomachinery back	A79-26830	SPACECRAFT DESIGN Introduction to the computer-aided design of
turbine engine shrouds	ings for	flight wehicles Russian book on spacecraft
[NASA-CASE-LEW-12131-1]	N79-18318	design
SHROUDS		A79-27648
Composite seal for turbomachinery back turbine engine shrouds	ings for	Path in rocket technology - Selected works,
[NASA-CASE-LEW-12131-1]	N79-18318	1924-1946 Russian book
SIDELOBE REDUCTION		A79-27599
An IFF antenna with superior sidelobe and	backlobe	SPANLOADER AIRCRAFT
suppression characteristics	A79-24718	Effects of laminar flow control on the performance of a large span-distributed-load flying-wing
SIGNAL HEASUREMENT	11.5 247.15	cargo airplane concept
Aircraft antenna pattern measurements usin	g near	[NASA-TM-78715] N79-17851
field techniques	170 26721	SPECTRAL CORRELATION
SIGNAL PROCESSING	A79-24721	Separation of core noise and jet noise [AIAA PAPER 79-0589] A79-26941
Recording methods for steady state and tra	insient	SPECTRUM ANALYSIS
signals aircraft engine tests		Interior noise path identification in light
The coming of age of digital electronics i	A79-25849	aircraft using multivariate spectral analysis [AIAA PAPER 79-0644] A79-26915
commercial transports emphasizing si		[AIAA PAPER 79-0644] A spectral analysis of thunderstorm turbulence and
processing technology and Boeing 767 avi		jet transport landing performance
[AIAA 79-0686]	A79-27352	₽79-27576
Multimode radar processor for combat a	A79-28058	SPHERICAL SHELLS Experimental studies on the effects of a sting
SIMULATORS	A73 20030	support on the pressure distribution around a
A simulator study of aircraft ground-run h		spherical object
in the Posim Research Simulator - Some r	esults	[NASA-CR-158127] N79-17800
and experiences	A79-26498	SPHINX Laser aircraft using kerosene
SITES		A79-26597
Siting criteria for MLS stations. II		SPLINES
SKIN RESISTANCE	A79-28184	Causes for the deterioration of splined connections in aircraft engines during service
EMP coupling to a composite aircraft		A79-25249
	479-25321	SPOILERS
SLENDER WINGS		An experimental wind-tunnel investigation of a
Slender wing in compressible flow Russ	A79-25872	<pre>ram-air-spoiler roll-control device on a forward-control missile at supersonic speeds</pre>
Accuracy of an approximate static structur		[NASA-TP-1353] N79-17809
analysis technique based on stiffness ma	trix	STANDARDS
eigenmodes [AIAA 79-0748]	A79-28263	A new standard for lightning qualification testing of aircraft: Technical overview, definitions
SLOT ANTENNAS		and basic waveforms
An IFF antenna with superior sidelobe and	backlobe	N79-18246
suppression characteristics	A79-24718	STATE VECTORS Design of proportional-plus-integral controllers
SHALL PERTURBATION FLOW	M79-24710	for multivariable systems
Slender wing in compressible flow Russ		A79-28223
CONTA DOORS	A79-25872	STATIC DISCHARGERS
SONIC BOOMS Some effects of applying sonic boom minimi	Zat 10D	Aircraft static charging testing [ONERA, TP NO. 1978-110] A79-26130
to supersonic cruise aircraft design	2412011	Electric charging of helicopters aircraft
[AIAA PAPER 79-0652]	A79-26927	hazards and static dischargers for accident
Effects of simulated forward flight on jet shock noise and internal noise	noise,	prevention [BMVG-PBWT-78-7] N79-18274
[AIAA PAPER 79-0615]	A79-26936	STATIC TESTS
SOUND PIELDS		Reduction of rotor-turbulence interaction noise in
Effects of inflow distortion profiles on f noise calculated using a 3-D theory	an tone	static fan noise testing
[AIAA PAPER 79-0577]	A79-26911	[AIAA PAPER 79-0656] A79-26925 STATISTICAL ANALYSIS
SOUND PRESSURE		Statistical estimation of economic life for
Separation of core noise and jet noise	.70 06004	aircraft structures
[AIAA PAPER 79-0589] SOURD PROPAGATION	A79-26941	[AIAA 79-0761] Briefs of accidents involving missing and missing
Analysis of radiation patterns of interact	10n	later recovered aircraft, US general aviation,
tones generated by inlet rods in the JT1		1977
[AIAA PAPER 79-0581] SOUND TRANSMISSION	A79-26944	[NTSB-AMM-78-18] N79-17834
Sound absorption caused by worticity shedd	1 ng.	Briefs of accidents, involving corporate/executive aircraft, US general aviation, 1977
demonstrated with a jet flow	•	[NTSB-AMM-78-19] N79-17835
[AIAA PAPER 79-0575]	A79-26905	Briefs of accidents involving amateur/home built
Interior noise path identification in ligh aircraft using multivariate spectral ana		aircraft, US general aviation, 1977 [NTSB-AMM-78-20] N79-17836
(AIAA PAPER 79-0644)	A79-26915	Probabilistic analysis of air carrier accidents
Turboprop interior noise studies		N79-18078
[AIAA PAPER 79-0647] Noise transmission - Turboprop problem	A79-26931	
[AIAA PAPER 79-0645]	A79-26933	
(uzum runner in reine)		

STATORS SUBJECT INDEX

STATORS			
		Damage-tolerance practices applied to transport	
Cold-air performance of free power turbine		aircraft structures	
designed for 112-kilowatt automotive gas		[SAE PAPER 781021] A79-258	396
engine. 2: Effects of variable		Fracture mechanics and fail-safe design for	
stator-vane-chord setting angle on turbi	ne	helicopter rotor structures	
performance		A79-269	986
[NA SA-TM-78993]	N79-17859	Transonic compressors for heavy gases. Part 1:	
STIFFENING	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Selections of the aero-design parameters	
Structural stiffening of transmission hous	1 Das	N79-193	351
with metal matrix materials	11193	Transonic compressors for heavy gases. Part 2:	
[AIAA 79-0806]	A79-28287	Aero-mechanical considerations, testing and	
STIPFNESS MATRIX	R /9-20201		
	-1	operation N79-193	252
Accuracy of an approximate static structur			332
analysis technique based on stiffness ma	tr1X	Plow modelling and aerodynamic design techniques	
eigenmodes		for centrifugal compressors	
[AIAA 79-0748]	A79-28263	N79-193	386
STORMS (METEOROLOGY)		Application of aerodynamic design techniques to	
Evaluation of the Ryan Stormscope as a sev	ere	process compressor design computerized design	Jn
weather avoidance system for aircraft		N79-193	388
	N79-18229	Development testing of stages for centrifugal	
STRAIN GAGES		process compressors	
Elevated-temperature effects on strain gag	es on	N79-193	392
the YF-12A wing		Turbocharger design and development technology	
one ii tan wing	A79-26400	assessment and design optimization	•
Strain dago system ovaluation program	A79-20400	N79-193	303
Strain gage system evaluation program	W70-1024#		,,,
[NASA-CR-159486]	N79-19314	STRUCTURAL MEMBERS	
STRESS CONCENTRATION		Airframe noise component interaction studies	
A stress and strain analysis of industrial		[NASA-CR-3110] N79-198	315
compressor impellers using the framework		STRUCTURAL RELIABILITY	
finite element method and descriptive		Commercial parachutes from safety standpoint	
L	N79-19391	[AIAA 79-0458] A79-266	5 6 1
STRESS MEASUREMENT		Fracture mechanics and fail-safe design for	
Strain gage system evaluation program		helicopter rotor structures	
[NASA-CR-159486]	N79-19314	A79-269	386
STRIP TRANSMISSION LINES	475 75514	Crashworthiness tests on model aircraft fuselage	
An IFF antenna with superior sidelobe and	haaklaha	structures	
	nacklone		154
suppression characteristics	170 01740	[AIAA 79-0688] A79-273)) 4
annaannii 15	A79-24718	Design against fatigue - Current trends for	
STRUCTURAL ANALYSIS		aircraft structural reliability	
Divergence of forward swept composite wing		[AIAA 79-0689] A79-273	355
[AIAA 79-0722]	A79-28255	Factors affecting residual strength prediction of	
Accuracy of an approximate static structure	al	a cracked aircraft structure	
analysis technique based on stiffness ma-	trix	A79-283	380
eigenmodes		STRUCTURAL VIBRATION	
[AIAA 79-0748]	A79-28263	A finite element subvolume technique for	
Turbomachinery flutter: Introductory conc		structural-borne interior noise prediction	
randamence, reactors restaurately cons	N79-19353	in aircraft	
Industrial Contribusal Compressors Wolamo			202
Industrial Centrifugal Compressors, Volume			002
[VKI-LECTURE-SERIES-95]	N79-19389	STRUCTURAL WEIGHT	
STRUCTURAL DESIGN		Influence of bypass ratio on jet engine weight	
Application of fracture mechanics to design		A79-277	31
	A79-26980	STROTS	
Structures, Structural Dynamics, and Mater	ıals	Noise from struts and splitters in turbofan exit	
Structures, Structural Dynamics, and Mater. Conference, 20th, St. Louis, Mo., April	ıals	Noise from struts and splitters in turbofan exit ducts	
Conference, 20th, St. Louis, No., April	ials 4-6,		123
	ials 4-6,	ducts	123
Conference, 20th, St. Louis, Mo., April 1979, Technical Papers on Dynamics and Lo	1als 4-6, 0ads A79-28251	ducts [AIAA PAPER 79-0637] A79-269 SUBHERGED BODIES)23
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis a	1als 4+6, oads A79-28251 nology	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5)	
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis a	ials 4-6, oads A79-28251 nology Dynamics	ducts [AIAA PAPER 79-0637] A79-269 SUBMERGED BODIES Helicopter underwater escape trainer (9D5) N79-196	
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis and Louis and Louis are also production of new SDM techninto production systems Structures, and Materials technology in aircraft des	nals 4-6, oads A79-28251 nology Dynamics 1gn	ducts [AIAA PAPER 79-0637] A79-269 SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT	
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft des. [AIAA 79-0719]	1als 4-6, oads A79-28251 nology Dynamics 1gn A79-28252	ducts [AIAA PAPER 79-0637] A79-269 SUBHREGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports	565
Conference, 20th, St. Louis, No., April 979, Technical Papers on Dynamics and Louis and Louis and Louis and Louis and Louis and Papers of new SDM techninto production systems Structures, and Materials technology in aircraft design and Materials technology in aircraft design and Materials technology in aircraft design. Aeroelastic tailoring studies in fighter and state of the	1als 4-6, oads A79-28251 nology Dynamics 1gn A79-28252	ducts [AIAA PAPER 79-0637] A79-269 SUBMERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] A79-258	565
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Los DM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft des. [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design	1als 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high	565
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft des. [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725]	1als 4-6, oads A79-28251 nology Dynamics 1gn A79-28252	ducts [AIAA PAPER 79-0637] SUBHREGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds	565 353
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft designation of AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for	1als 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] A79-273	565 353
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis Papers of Dynamics and Louis Papers of Dynamics and Louis Papers of November 1970, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and Materials to the Dynamics of Papers P	141s 4-6, 0ads 179-28251 nology Dynamics 1gn 179-28252 1rcraft	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's	565 353 353
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter aidesign [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726]	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1rcraft A79-28257	ducts [AIAA PAPER 79-0637] SUBHREGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282	565 353 353
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM technito production systems Structures, and Materials technology in aircraft designation of the Modern and Materials and Studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized C.	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's	565 353 353
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter aidesign [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726]	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980 s [AIAA 79-0755] A79-282 SUBSOBIC PLOW	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM technito production systems Structures, and Materials technology in aircraft designation of the Modern and Materials and Studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized C.	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook	ducts [AIAA PAPER 79-0637] SUBHREGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis Papers Pape	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260	ducts [AIAA PAPER 79-0637] SUBHBRGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM technito production systems Structures, and Materials technology in aircraft designates and Lecture 1970 and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCEAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] A79-258	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Louis Papers Pape	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM technito production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757]	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM technito production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing syn	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSONIC AIRCHAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC PLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSONIC WIED TUNNELS	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724]	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSOBIC WIED TUNNELS A visual investigation of the separation and	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation	1415 4-6, 00ads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts	ducts [AIAA PAPER 79-0637] SUBHBRGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSOBIC WIED TURNELS A visual investigation of the separation and subsequent transition near the leading edge of	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentration of structures [AIAA 79-0724]	141s 4-6, 0ads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils	665 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synthal via constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concerns	141s 4-6, 0ads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353	ducts [AIAA PAPER 79-0637] SUBHBRGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSOBIC WIED TURNELS A visual investigation of the separation and subsequent transition near the leading edge of	665 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentration of structures [AIAA 79-0724]	141s 4-6, 0ads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils	665 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synthal via constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concerns	141s 4-6, 0ads A79-28251 nology Dynamics 1gn A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSONIC WIED TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-258	665 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synthal via constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concerns	1415 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28257 A79-28260 A79-28272 thesis A79-28290 epts N79-19353 ance	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] SUCTION Experiments on tandem diffusers with	665 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentration and development of high performacements of multistage compressors with	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentric design and development of high performations of multistage compressors with consideration of the real behavior of gas	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380	ducts [AIAA PAPER 79-0637] SUBHBRGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCHAPT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-273 SUBSONIC PLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-258 SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] N79-178	353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentration and development of high performacements of multistage compressors with	141s 4-6, oads A79-28251 nology Dynamics 1gh A79-28252 1FCTaft A79-28257 A79-28258 hinook A79-28260 A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380 s and	ducts [AIAA PAPER 79-0637] SUBHERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades N79-189 SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] SUPERCHARGERS	565 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synval constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concentration of multistage compressors with consideration of the real behavior of gas gas mixtures	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1rcraft A79-28257 A79-28258 hinook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSOBIC WIED TURNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] SUPERCHARGERS Turbocharger design and development technology	565 353 353 270
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concerns design and development of high performations of multistage compressors with consideration of the real behavior of gas gas mixtures	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCFaft A79-28257 A79-28258 hlnook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380 s and N79-19390	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-258 SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] TUPBOCHARGERS Turbocharger design and development technology assessment and design optimization	353 353 353 270 381 3997
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synval constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concombustors Design of multistage compressors with consideration of the real behavior of gas gas mixtures STRUCTURAL DESIGN CRITERIA Integrally cast turbine rotor for high vol	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCFaft A79-28257 A79-28258 hlnook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380 s and N79-19390	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] SUBSOBIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSOBIC WIED TURNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] SUPERCHARGERS Turbocharger design and development technology	353 353 353 270 381 3997
Conference, 20th, St. Louis, No., April 1979, Technical Papers on Dynamics and Le SDM lecture - Introduction of new SDM techninto production systems Structures, and Materials technology in aircraft design [AIAA 79-0719] Aeroelastic tailoring studies in fighter and design [AIAA 79-0725] An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] Structural development of the Modernized Chelicopter transmission gearing [AIAA 79-0728] Design and fabrication of advanced titanium structures [AIAA 79-0757] Combined strength and aeroelastic wing synvia constraint approximation [AIAA 79-0724] Turbomachinery flutter: Introductory concerns design and development of high performations of multistage compressors with consideration of the real behavior of gas gas mixtures	141s 4-6, oads A79-28251 nology Dynamics 1gn A79-28252 1FCFaft A79-28257 A79-28258 hlnook A79-28260 m A79-28272 thesis A79-28290 epts N79-19353 ance N79-19380 s and N79-19390	ducts [AIAA PAPER 79-0637] SUBBERGED BODIES Helicopter underwater escape trainer (9D5) SUBSOBIC AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Development of modern airfoil sections for high subsonic cruise speeds [AIAA 79-0687] Structural aluminum materials for the 1980's [AIAA 79-0755] A79-282 SUBSONIC FLOW Propeller slipstream wing interactions at Mach no. 0.8 [SAE PAPER 780997] Outlet air angle prediction for subsonic flow cascades SUBSONIC WIND TUNNELS A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-258 SUCTION Experiments on tandem diffusers with boundary-layer suction applied in between [NASA-CR-158957] TUPBOCHARGERS Turbocharger design and development technology assessment and design optimization	353 353 353 270 381 3997

SUBJECT INDEX SYNTHETIC FUELS

SUPERCONDUCTING MAGNETS	:	SUPERSONIC HOZZLES	
Air Porce applications of lightweight		Convective heat exchange of gas-particle st	
superconducting machinery in airborne powe	er .	flow passage of throttling device with va	ne-type
sources A79-2	7666	turning element	A79-2774
SUPERCONDUCTORS		SUPERSONIC SPEEDS	A /9-2//4
Pilter weight minimization for rectified	•	An experimental wind-tunnel investigation o	£ a
superconducting alternator power supplies		ram-air-spoiler roll-control device on a	
for aircraft		forward-control missile at supersonic spe	
A79-2			N79-1780
SUPERCRITICAL WINGS		SUPERSONIC TRANSPORTS	
Propeller slipstream wing interactions at Mach n 0.8	10.	Airframe noise measurements on a small-scal	
[SAE PAPER 780997] A79-2	5991	of a supersonic transport concept in an a flow facility	necnoic
Delta method, an empirical drag buildup techniqu			A79-2692
[NASA-CR-151971] N79-1		SUPERSONIC WIND TUNNELS	2032
Progress in transonic flow computations analysis		The 1-4-1 system of jack movements for the	
and design methods for three-dimensional flows	3	flexible liners of supersonic wind tunnel	
supercritical wings and wing-body combinat			A79-2659
N79-1	18951 5	SURFACE DISTORTION	
SUPERBIGE PERQUENCIES		Experimental investigation of the effect of	
Modeling the X-band radar augmentation system of high altitude supersonic target	: a.	surface discontinuity on step-backward fl	ow A79−2700:
A79-2	24715 S	SURPACE GEOMETRY	K73-2700
SUPERPLASTICITY		Vortex pattern development on the upper sur	face of
Design and fabrication of advanced titanium		a swept wing at high angle of attack	
structures			N79-1891
[AIAA 79-0757] A79-2	8272	SURPACE NAVIGATION	
SUPERSONIC AIRCRAFT		How to add satellite navigational accuracy	
Some effects of applying sonic boom minimization	1	stability to existing offshore NAV System	
to supersonic cruise aircraft design [AIAA PAPER 79-0652] A79-2	26027	SURPACE PROPERTIES	A79-2738
Transonic wing design for transport aircraft	.0721	Runway surface condition sensor	
[AIAA 79-0692] A79-2	7357		N79-1787
Supersonic combat aircraft design		SURPACE WAVES	
[AIAA 79-0699] A79-2		A slender delta wing oscillating in surface	waves
Structural aluminum materials for the 1980's		[VTH-LR-257]	N79-1781
[AIAA 79-0755] A79-2	28270	SURGES	
Fuel tank sealant requirements for advance high		Properties of induced transients associated	With
performance aircraft [AIAA 79-0807] A79-2	0000	EM fields produced by lightning or other relatively slow rise-time EMP in airc	ra ft
SUPERSONIC AIRPOILS	20200		A 79-2532:
General purpose computer program for interacting	1 5	SURVEILLANCE RADAR	LUJE.
supersonic configurations. User's manual	_	The future of surveillance systems in civil	aviation
determining unsteady aerodynamic foreces			A79-2480
[NASA-CR-145128] N79-1	17798	Operational evaluation of an Air Traffic Co	ntrol
SUPERSONIC CRUISE AIRCRAFT RESEARCH		Radar Beacon System open array antenna	
Advanced supersonic technology and its			179-2713
implications for the future [AIAA 79-0694] A79-2		SURVIVAL Damage-tolerance practices applied to trans	nort
Fabrication and evaluation of advanced titanium	1333	aircraft structures	POLC
structural panels for supersonic cruise aircra	ft		A79-25896
[NASA-CR-2744] N79-1		Assessment of the benefits of aircraft	
SUPERSONIC FLIGHT		crashworthiness	
modeling the X-band radar augmentation system of	a		N79 -1 965
high altitude supersonic target		SWEEP EFFECT	_
A79-2	24715	The influence of sweep on aerodynamic loading	
F-16 high angle of attack testing	16527	an oscillating NACA0012 airfoil. Volume	2:
A79-2 Comparison of BTJES and TJE characteristics in	20321	Data report [NASA-CR-145350]	N79-1780
supersonic cruising flight Bypass Turbojet		SWEPT FORWARD WINGS	1700.
Engine	•	Divergence of forward swept composite wings	
A79-2	7740		A79-2825
Analysis of base-flow problems during powered	5	SWEPT WINGS	
supersonic flight		Lifting surface theory for skewed and swept	
N79-1	18926	subsonic wings	
SUPBRSONIC PLOW			A79-2586
Laminar boundary layer with foreign gas injection	n	Wind-tunnel investigation of the thrust aug	
on a conical body A79-2	7202	performance of a large-scale swept wing m in the Ames 40 by 80 foot wind tunnel	odei
An improved supersonic, three-dimensional,	27203		N79-1780
external, inviscid flow field code		Vortex pattern development on the upper sur	
[NASA-CR-3108] N79-1	7807	a swept wing at high angle of attack	
Interaction of the supersonic flow below a wing			N 79-1891
and a supersonic free jet (two-dimensional	5	SWIRLING	
situation)		Instability of fluid flow in centrifugal in	
[VTH-LR-268] N79-1			79-2773
Calculation of supersonic viscous flow over delta	a S	SYNTHETIC APERTURE RADAR	
wings with Sharp subsonic leading edges	18909	TASAR, a thinned adaptive synthetic aperture	e radar 479-2713:
N79-1: SUPERSONIC HEAT TRANSPER		SYNTHETIC PUBLS	17-2113
Elevated-temperature effects on strain gages on	•	Effects of fuel properties on soot formation	n in
the YP-12A wing		turbine combustion	
A79-2	6400		A79-25899
SUPERSONIC JET PLOW		Shale oil - The answer to the jet fuel	
The sound power spectrum of shock-free jets		availability question	
[AIAA PAPER 79-0595] A79-2	26918	[SAE PAPER 781027]	A79-2590(

SYSTEM EFFECTIVENESS SUBJECT INDEX

Evaluation of the application of some gas		Advanced overrunning clutch technology	UH-60A
chromatographic methods for the determin	nation of	helicopter transmission application [SAE PAPER 781039]	A79-2590
properties of synthetic fuels	A79-25917	The continuity factor in aircraft developm	
SYSTEM EFFECTIVENESS			A79-2653
Objectives related to an enhancement of the effectivity of MALEV. I civil aircra		Design against fatigue - Current trends aircraft structural reliability	- ior
utilization in Hungary	31.0	[AIAA 79-0689]	A79-2735
	A79-25368	Perspectives of technological development	
Future avionics - Keeping capability up, o		helicopters	170-2726
SYSTEMS ENGINEERING	A79-27093	[AIAA 79-0701] Recent developments in active control tech	A79-2736
Radar system design for track-while-scan		for fighter aircraft design	
n	A79-25139	[AIAA 79-0708]	A79-2736
Design considerations for the NOAA airborn meteorological radar and data system	ie	Alternative turbine cooling technology	N79-1898
	A79-25689	Industrial centrifugal compressors, volume	
Study of the structure of an integrated sy	ystem of	[VKI-LECTURE-SERIES-95]	N79-1938
flight control, navigation and display	A79-27674	Turbocharger design and development te assessment and design optimization	chhology
Tests of an integrated piloting, navigation			N79-1939
display system	170 2767E	TECHNOLOGY UTILIZATION	an for
An optical communication system for aircra	A79-27675	New technology in commercial aircraft desi minimum operating cost	.gn TOL
	A79-28034	[AIAA 79-0690]	A79-2735
Software requirements for the A-7E aircraf	Et N79-18974	Compromise between economic concerns and application of new technologies in the	
Turbojet blade vibration data acquisition		definition of a new airplane project	
and feasibility testing	-	[AIAA 79-0693]	A79-2735
[NASA-CR-159505]	N79-18976	Enhanced capabilities of future fighters a result of HiMAT	s a
т		[AIAA 79-0698]	A79-2737
		TELEVISION CAMERAS	
TACAN Navstar/GPS /Global Positioning System/ an	.a	A three-channel high-resolution-TV image generation system flight simulator a	nnlicatio
electronic counter measures TACAN sy		generation by beam tright branched a	A79-2816
vulnerability		TELEVISION SYSTEMS	
TAIL ASSEMBLIES	A79-25492	Elimination of scale and luminance distort thermal imaging systems with a large fie	
Comparison of the aerodynamic properties of		onboard aircraft	
aeroplane with the tail-first configurat	tion and	t throo-shappol high-resolution-MV image	A79-2741
with the conventional configuration [BLL-RTS-11520]	N79-17794	A three-channel high-resolution-TV image generation system flight simulator a	pplicatio
Experimental studies on the effects of a s			A79-2816
support on the pressure distribution are spherical object	ound a	Aviation wide angle visual system /AWAVS/ system performance	- Visual
[NASA-CR-158127]	N79-17800	System periormance	A79-2816
TANDEM ROTOR HELICOPTERS		TEMPERATURE DISTRIBUTION	
Investigation of the aerodynamic and acous performance of a low-pressure ratio tand		Method for digital computer calculation of unsteady temperature fields in turbomach	
compressor			A79-2774
TARGET ACQUISITION	ท79-18975	TEMPERATURE EPPECTS Elevated-temperature effects on strain gag	os on
New approaches concerning the implementati	on of	the YF-12A wing	es on
radar target extractors with the aid of			A79-2640
fast microprogrammable data processors	A79-26754	TEMPERATURE PROBES An in-place recallbration technique to ext	and the
TARGET RECOGNITION	A75 20754	temperature capability of capacitance-se	
Modeling the X-band radar augmentation sys	stem of a	rotor-blade-tip-clearance measurement sy	
high altitude supersonic target	A79-24715	[SAE PAPER 781003] TEMPERATURE SENSORS	A79-2588
TARGET SIMULATORS	1177 21710	Overestimates of entrainment from wetting	of
Development of smart target for simulation	of	aircraft temperature sensors in cloud	A79-2529
one-on-one air-to-air combat [AD-A056739]	N79-17879	TREESSEE	A 13-2323
TECHNOLOGICAL FORECASTING		Aircraft accident report: Midair collisio	
Technology for future air transports	170-25952	involving a Falcon JET, N121GW, and a Ce	ssna
[AIAA PAPER 79-0529] General aviation aircraft in the 1990's	A79-25853	150m, N6423K, Hemphis, Tennessee	ห79-1782
[AIAA PAPER 79-0560]	A79-25866	TERMINAL CONFIGURED VEHICLE PROGRAM	_
The coming of age of digital electronics in commercial transports emphasizing si		Flying NASA's Terminal Configured Vehicle the Microwave Landing System	against
processing technology and Boeing 767 avi		the nicrosave landing System	A79-2653
[AIAA 79-0686]	A79-27352	Algorithms and logic for incorporating BLS	
Advanced supersonic technology and its implications for the future		azımuth information into the NASA TCV B- airplane area navigation system	131
[AIAA 79-0694]	A79-27359	[NASA-TH-80039]	N79-1784
Future advanced technology rotorcraft	170 27266	Plying NASA's terminal configured vehicle	agaınst
[AIAA 79-0705] Total environment survivability methodolog	A79-27366	the microwave landing system	N79-1889
[AD-A061888]	ที่ 79-18971	TERMINAL FACILITIES	_
TECHNOLOGY ASSESSEENT		Short Range Terminal Radar (SRTR) definiti	
Advances in avionics emphasizing microprocessor technology and integrated	circuits	[FAA-RD-78-64] TERMINAL GUIDANCE	₩79-1815
[AIAA PAPER 79-0562]	A79-25862	RNAV route design-terminal area design pro	cedures
Prop-fan propulsion - Its status and poten [SAE PAPER 780995]	ntial A79-25880	and transition area design guidelines	N79-1784
		1488 40 70 011	

SUBJECT INDEX TOLERANCES (MECHANICS)

TEST EQUIPMENT		THRUST AUGMENTATION	
Development testing of stages for centrifu	gal	Wind-tunnel investigation of the thrust augments	or.
process compressors	พ79 ~ 19392	performance of a large-scale swept wing model in the Ames 40 by 80 foot wind tunnel	
TEST PACILITIES		[NASA-TH-X-73239] N79-1	17804
Recent advances in indirect lightning efferences	cts	THRUST-WEIGHT RATIO Influence of bypass ratio on jet engine weight	
	A79-25313	À79-2	27737
Small fan-jet engines	w70 40004	THUMDERSTORMS	
TETHERED BALLOOPS	ท79-18891	A spectral analysis of thunderstorm turbulence a jet transport landing performance	i na
The influence of ballonet motions on the		A79-2	27576
longitudinal stability of tethered aeros [AIAA 79-0445]	tats A79-26649	TILT ROTOR RESEARCH AIRCRAFT PROGRAM XV-15 Tilt Rotor Research Aircraft - Program rep	
THERNAL CYCLING TESTS	A/3-20043	[AIAA 79-0704] A79-2	
Effect of a chromium-containing fuel addit	ive on	TIME DEPENDENCE	
hot corrosion	A79-26546	Time degradation factors for the turbine engine exhaust emissions. Volume 1: Program	
Thermal cycling endurance problems in gas-		description and results air pollution cont	rol
parts	170 26020	[NREC-1238-6-VOL-1] N79-1	17860
THERMAL ENVIRONMENTS	A79-26838	Time degradation factors for the turbine engine exhaust emission. Volume 2: JT8D-9 test data	1
Integrated Thermal Avionics Design (ITAD)		air pollution control	
[AD-A061227]	N79-17855	[NREC-1238-7-VOL-2] N79-1 Time degradation factors for turbine engine	17863
THERMOCHEMICAL PROPERTIES Thermal response of composite panels		exhaust emissions. Volume 3: JT3D-7 test data	1
	A79-25350	air pollution control	
THERMODYNAMIC EPPICIENCY The aerodynamic penalties associated with	+n=h. no	[NREC-1238-8-VOL-3] N79-1 Time degradation factors for turbine engine	17864
blade cooling	cdibine	exhaust emissions. Volume 4: JT3D-7 test dat	:a
•	N79-18986	air pollution control	
THERMODYNAMIC PROPERTIES Design of multistage compressors with		[NREC-1238-9-VOL-4] N79-1 Time degradation factors for turbine engine	17865
consideration of the real behavior of ga	s and	exhaust emissions. Volume 5. JT3D-3B test da	ıta
gas mixtures		air pollution control	
THERMOBLASTICITY	N79-19390	[NREC-1238-10-VOL-5] N79-1 Time degradation factors for turbine engine	1/800
Thermoelastic and dynamic phenomena in sea	ls	exhaust emissions. Volume 6: JT9D-3A test da	ata
[AD-A061754]	N79-19396	air pollution control	17067
THIN AIRFOILS Behavior of elastic systems in separated f	lov	[NREC-1238-11-VOL-6] N79-1 Time degradation factors for turbine engine	1/00/
	A79-25618	exhaust emissions. Volume 7: RP211-22B test	đata
Nonsteady flow of an incompressible liquid	ower	air pollution control [NREC-1238-12-VOL-7] N79-1	17868
slender permeable profiles	A79-27062	Time degradation factors for turbine engine	17000
THIN WALLS	_	exhaust emissions. Volume 8: C700-2D test da	
Accuracy of an approximate static structure analysis technique based on stiffness ma		[NREC-1238-13-VOL-8] N79-1 Design, calibration, and application of a sensor	
eigenmodes		for measuring time dependent angle of attack of	
[AIAA 79-0748] THIN WINGS	A79-28263	helicopter blades N79-1	10060
Lifting surface theory for skewed and swep	t	Time marching finite area method	.0300
subsonic wings		N79-1	18990
[AIAA PAPER 79-0551] Slender wing in compressible flow Russ	A79-25869 1an book	TIME RESPONSE Control system time response optimization - A	
	A79-25872	nonlinear programming approach for aircraft	Et
THREE DIMENSIONAL PLOW		flight [AINA PAPER 79-0540] A79-2	55850
An alternating direction explicit method f computing three-dimensional viscous flow		TIME SERIES ANALYSIS	23037
in turbomachines		Worst case time-histories causing largest	
[SAE PAPER 781001] Effects of inflow distortion profiles on f	A79-25884	deviations from a desired flight path: An analytical approach	
noise calculated using a 3-D theory	un conc	[VTH-LR-267] N79-1	17839
[AIAA PAPER 79-0577]	A79-26911	TIP DRIVEN BOTORS	
An improved supersonic, three-dimensional, external, inviscid flow field code		An in-place recalibration technique to extend the temperature capability of capacitance-sensing,	
[NASA-CR-3108]	ห79-17807	rotor-blade-tip-clearance measurement systems	
Contribution to the development of theoret			25885
calculations for the design and optimiza lifting bodies. (Solution of three-dime		TIP SPEED An investigation of model helicopter rotor blade	•
basic thermo fluid dynamics equations wi	th	slap at low tip speeds	
strong interacting attached and separate fields)	d flow	[AIAA PAPER 79-0613] A79-2 TITANIUM ALLOYS	26938
[BMVG-FBWT-78-4]	N79-17816	Design and fabrication of advanced titanium	
Progress in transonic flow computations an	alysıs	structures	
and design methods for three-dimensional supercritical wings and wing-body co		[AIAA 79-0757] A79-2 Fabrication and evaluation of advanced titanium	28272
Supererrear wrings and wring-body co	N79-18951	structural panels for supersonic cruise aircra	aft
THROTTLING		[NASA-CR-2744] N79-1	18320
The effect of throttling on forward radiate	ed fan	Failure studies of a third stage fan disk from a TF-30 turbine engine	1
[AIAA PAPER 79-0640]	A79-26917	[AD-A061801] N79-1	19004
Convective heat exchange of gas-particle s		TOLBRANCES (MECHANICS)	
flow passage of throttling device with vitaring element	апе-туре	Recognition of damage-tolerance in civil airworthiness standards	
	A79-27742	[SAE PAPER 781019] A79-2	25895

TOWERS SUBJECT INDEX

TOWERS Aviation obstructions and the particular	Transonic compressors for heavy gases. Part 2: Aero-mechanical considerations, testing and
conditions for construction projects in the	operation N79-19352
vicinity of airports A79-25372	TRANSONIC PLOW
TRACKING RADAR Problems of computer-aided tracking, giving particular attention to radar which can be	Quasi-natural numerical methods for the computation of inviscid potential or rotational transonic flows
electronically turned A79-26761	A79-26487
TRAILING EDGES	boundary layer and viscous interaction effects
On sound radiation from the trailing edge of an isolated airfoil in a uniform flow	[NASA-CR-158136] N79-17805 Some recent progress in transonic flow computation
[AIAA PAPER 79-0603] A79-26907 Radiation of an acoustic source near the trailing edge of a wing in forward motion	flow distribution, numerical optimization, and airfoil design N79-18946
[Alah PAPER 79-0605] A79-26940 Pormation of a trailing wortex	
TRAILING-EDGE PLAPS	supercritical wings and wing-body combinations N79-18951
An experimental study of USB flap noise reduction	Time marching finite area method
through mean flow modification Upper Surface Blown	Comparison between flows in cascades and rotors in
[AIAA PAPER 79-0607] A79-26908 Airframe noise component interaction studies	the transonic range. 1: Basic considerations N79-19000
[NASA-CR-3110] N79-19815 TRAINING SIMULATORS	Comparison between flows in cascades and rotors in the transonic range. 2: Investigation of two
Visual simulation devices for flight training	transonic compressor cascades and comparison
simulators Russian book A79-26354	with rotor data N79-19001
Survey of radar simulation training at ATC field facilities	Comparison between flows in cascades and rotors in the transonic range. 3: Comparison of
[FAA-NA-78-27] N79-17877	experimental and theoretical results of flow
Helicopter underwater escape trainer (9D5) N79-19665	studies on blade-to-blade surfaces in an axial compressor rotor
TRAJECTORY CONTROL Configuration management and automatic control of	TRANSONIC WIND TUNNELS
an augmentor wing aircraft with vectored thrust	Unsteady pressures on a NACA 64AJ10 airfoil -
TRANSDUCERS	Experimental and theoretical results [AIAA PAPER 79-0330] A79-26545
Dynamic data analysis gas turbine engine vibration transducers	IR scanning camera measurements of an exhaust plume from an axisymmetric nozzle afterbody
A79-25845	model at transonic Mach numbers
TRANSIENT OSCILLATIONS The impact of the total lightning environment on	TRANSPORT AIRCRAFT
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and	TRANSPORT AIRCRAFT Technology for future air transports [Ala Paper 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE Paper 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [Ala 79-0686] A79-27352 Transonic wing design for transport aircraft
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Findings of the Ottawa-Montreal STOL demonstration
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems TRANSITION PLOW A visual investigation of the separation and	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Hontreal STOL demonstration service [AIAA 79-0710] A79-27369
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] An analysis of fuel conserving operational
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863	TRANSPORT AIRCRAFT Technology for future air transports [Alaa Paper 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE Paper 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [Alaa 79-0686] A79-27352 Transonic wing design for transport aircraft [Alaa 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [Alaa 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSHISSION LINES The analysis and identification of flux-induced	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [ATAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission	TRANSPORT AIRCRAFT Technology for future air transports [Alah PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [Alah 79-0686] A79-27352 Transonic wing design for transport aircraft [Alah 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [Alah 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (HACHINE ELEMENTS)	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Transient-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] A79-25907	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION PLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] Structural stiffening of transmission housings	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] STRUCTURAL STIFFENINGS NOT HELEMENTS NOT HEL	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] N79-18976
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION PLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] TRANSONIC COMPRESSORS	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] N79-18976 Turbine Blade Cooling [VKI-LECTURE-SERIES-83] N79-18979
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] A79-25909 Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] TRANSONIC COMPRESSORS Comparison between flows in cascades and rotors in the transonic range. 2: Investigation of two	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] Turbine Blade Cooling [VKI-LECTURE-SERIES-83] N79-18979 Turbine blade cooling N79-18980
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] A79-25909 Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] TRANSONIC COMPRESSORS Comparison between flows in cascades and rotors in the transonic cange. 2: Investigation of two transonic compressor cascades and comparison with rotor data	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] N79-18976 Turbine Blade Cooling [VKI-LECTURE-SERIES-83] N79-18979 Turbine blade cooling
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] A79-25909 Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] TRANSONIC COMPRESSORS Comparison between flows in cascades and rotors in the transonic compressor cascades and comparison with rotor data N79-19001	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] Turbine Blade Cooling [VKI-LECTURE-SERIES-83] N79-18979 Turbine blade cooling N79-18980 Alternative turbine cooling technology N79-18980 The aerodynamic penalties associated with turbine
The impact of the total lightning environment on aircraft flight control systems A79-25319 TRANSIENT RESPONSE The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSIT SATELLITES How to add satellite navigational accuracy and stability to existing offshore NAV Systems A79-27388 TRANSITION FLOW A visual investigation of the separation and subsequent transition near the leading edge of airfoils [AIAA PAPER 79-0552] A79-25863 TRANSMISSION LINES The analysis and identification of flux-induced voltage transients on low-loss transmission lines with application to the Lightning-Translent-Analysis /LTA/ problem A79-26246 TRANSMISSIONS (MACHINE ELEMENTS) Advanced overrunning clutch technology UH-60A helicopter transmission application [SAE PAPER 781039] The lynx transmission and Conformal gearing helicopter drive train [SAE PAPER 781041] A79-25909 Structural stiffening of transmission housings with metal matrix materials [AIAA 79-0806] TRANSONIC COMPRESSORS Comparison between flows in cascades and rotors in the transonic cange. 2: Investigation of two transonic compressor cascades and comparison with rotor data	TRANSPORT AIRCRAFT Technology for future air transports [AIAA PAPER 79-0529] A79-25853 Damage-tolerance practices applied to transport aircraft structures [SAE PAPER 781021] A79-25896 The coming of age of digital electronics in commercial transports emphasizing signal processing technology and Boeing 767 avionics [AIAA 79-0686] A79-27352 Transonic wing design for transport aircraft [AIAA 79-0692] A79-27357 Pindings of the Ottawa-Montreal STOL demonstration service [AIAA 79-0710] A79-27369 An analysis of fuel conserving operational procedures and design modifications for bomber/transport aircraft. Volume 1: Executive summary [AD-A061746] N79-18969 TROPOPAUSE Design specifications for the capped balloons with special reference to their survival in the equatorial tropopause [AIAA 79-0426] A79-26635 TURBINE BLADES Theoretical-experimental analysis of influence of coolant discharge from perforated turbine vanes on their aerodynamic characteristics A79-27727 Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] N79-18976 Turbine Blade Cooling [VKI-LECTURE-SERIES-83] N79-18979 Turbine blade cooling N79-18980 Alternative turbine cooling technology

Nonlinear equations of equilibrium for elastic		Considerations for the design of inlet flow	
helicopter or wind turbine blades undergoing moderate deformation		conditioners for static fan noise testing	
	- 19414	[AIAA PAPER 79-0657] Effects of inflow distortion profiles on fa	A79-26909
TORBINE ENGINES	.,,,,,	noise calculated using a 3-D theory	n cone
Applying design-to-life cycle cost methods duri	ing	[AIAA PAPER 79-0577]	A79-26911
engine advanced development		Noise from struts and splitters in turbofan	exit
	-25902	ducts	.70 2/022
Turbine engine cost reduction using Life Cycle Cost techniques		[AIAA PAPER 79-0637] Evaluation of two inflow control devices fo	A79-26923
	-25903	flight simulation of fan noise using a JT	
Briefs of accidents involving turbine powered		engine	
aircraft, US general aviation, 1977			A79-26926
	-17830	Flight effects on noise generated by the JT	8 D
Cold-air performance of free power turbine designed for 112-kilowatt automotive gas-turk	hano	engine with inverted primary/fan flow as measured in the WASA-Ames 40- by 80-foot	wind
engine. 2: Effects of variable	2116	tunnel	• Inu
stator-vane-chord setting angle on turbine			A79-26937
performance		Combustion noise prediction update	
	-17859		A79-26942
Composite seal for turbomachinery backings turbine engine shrouds	IOL	Analysis of radiation patterns of interactitions generated by inlet rods in the JT15	
	-18318		A79-26944
Failure studies of a third stage fan disk from		Unsteady stator response to upstream rotor	
TF-30 turbine engine			A79-26945
	- 19004	Influence of bypass ratio change on fan	
Advanced Turbine Engine Gas generator (ATEGG) fractography of cast nickel base superalloys		aerodynamic characteristics	A79-27744
	- 19149	Small fan-jet engines	RIJ 21144
TURBINE EXHAUST NOZZLES			N79-18891
IR scanning camera measurements of an exhaust	T	JRBOFANS	
plume from an axisymmetric nozzle afterbody		The effect of throttling on forward radiate	d fan
model at transonic Mach numbers	-28097	noise [AIAA PAPER 79-0640]	A79-26917
TURBINE INSTRUMENTS		JRBOJET ENGINES	R/J 20517
Dynamic data analysis gas turbine engine		Recent General Electric engine development	testing
vibration transducers		for improved service life	
TURBINE WHEELS	- 25845		A79-2587€
Integrally cast turbine rotor for high volume		Life cycle cost in preliminary engine desig for F-15	n
production			A79-25904
	-25883	Experiments concerning the anomalous behavi	
Method for digital computer calculation of		aero-engine exhaust noise in flight	
unsteady temperature fields in turbomachine d			179-26930
TURBINES	-27746	Influence of bypass ratio on jet engine wei	gnt A79-27737
Alternative turbine cooling technology		Comparison of BTJES and TJE characteristics	
	- 18984	supersonic cruising flight Bypass Tur	bojet
TURBOCOMPRESSORS		Engine	. 70 07700
Turbulence characteristics in the near wake of compressor rotor blade	a	Turbojet blade vibration data acquisition d	A79-27740
	-26544	and feasibility testing	corgn
Axial compressor operation with radially			N79-18976
nonuniform inflow		JRBOMACHINE BLADES	
Comparison between flows in cascades and rotors	-27743	Turbine Blade Cooling	N79-18979
the transonic range. 3: Comparison of		[VKI-LECTURE-SERIES-83] DRBOMACHINERY	N/9-109/9
experimental and theoretical results of flow		An alternating direction explicit method fo	r
studies on blade-to-blade surfaces in an axia	al	computing three-dimensional viscous flow	
compressor rotor		in turbomachines	
	-19002		A79-25884
Aerodynamic and Mechanical factors affecting the surge line: Inlet flow distortion influences		Turbomachinery flutter: Introductory conce	N79-19353
axial flow compressors			
w70_		Identification of various flutter regimes a	nd
	-19363	discussion of dynamic stall	
Industrial Centrifugal Compressors, Volume 2		discussion of dynamic stall	nd N79-19354
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SERIES-95] N79-		discussion of dynamic stall URBOPROP AIRCRAFT	N79-19354
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with	-19389 TO	discussion of dynamic stall JRBOPROP AIRCRAPT Prop-fan propulsion - Its status and potent	N79-19354 1al
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SERIES-95] N79-	-19389 TO	discussion of dynamic stall JRBOPROP AIRCRAPT Prop-fan propulsion - Its status and potent [SAE PAPER 780995]	N79-19354
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79-	-19389 TU d -19390	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645]	N79-19354 1al
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal	-19389 TU d -19390	discussion of dynamic stall JRBOPROP AIRCRAPT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES	N79-19354 1al A79-25880
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors	-19389 TO d -19390 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies	N79-19354 1al A79-25880 A79-26933
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79-	-19389 TO d -19390 TO -19392	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies	N79-19354 1al A79-25880
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization	-19389 TU d -19390 TU -19392 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOJEBECE EPPECTS An experimental study of the influence of	N79-19354 1al A79-25880 A79-26933 A79-26931
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79-	-19389 TO d -19390 TO -19392	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOILENCE EFFECTS An experimental study of the influence of flight-stream turbulence on jet mixing no	N79-19354 1al A79-25880 A79-26933 A79-26931
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES	-19389 TO d -19390 TO -19392 logy TO -19393	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOLEBCE EPPECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617]	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engin	-19389 TO d -19390 TO -19392 logy TO -19393	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOLEBCE EPPECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engin	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOILENCE EPPECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation)	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 Wing 1
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engin A79- Neasured and predicted noise of the AVCO-Lycomi	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBULENCE BFFECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268]	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engin N79- Neasured and predicted noise of the AVCO-Lycomi YF-102 turbofan engine [AIAA PAPER 79-0641]	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng -26877 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOLLENCE EFFECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268] JRBULENT BOUNDARY LAYER	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 W11 N79-17819
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN BNGINES Engine technology for production turbofan engin A79- Neasured and predicted noise of the AVCO-Lycom YF-102 turbofan engine [AIAA PAPER 79-0641] Pull-scale engine tests of bulk absorber acoust	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng -26877 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMCINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOLLENCE EPPECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268] JRBULENT BOUNDARY LAYER On sound radiation from the trailing edge o	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 W11 N79-17819
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engin A79- Neasured and predicted noise of the AVCO-Lycomi YF-102 turbofan engine [AIAA PAPER 79-0641] A79- Full-scale engine tests of bulk absorber acoust inlet treatment	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng -26877 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBULENCE BFFECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268] JRBULENT BOUNDARY LAYER On sound radiation from the trailing edge o isolated airfoil in a uniform flow	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 W11 N79-17819
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN BNGINES Engine technology for production turbofan engin YF-102 turbofan engine [AIAA PAPER 79-0641] Pull-scale engine tests of bulk absorber acoust inlet treatment [AIAA PAPER 79-0600] The application of finite element techniques to	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng -26877 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP EMGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBOILENCE EPPECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268] JRBULENT BOUNDARY LAYER On sound radiation from the trailing edge o isolated airfoil in a uniform flow [AIAA PAPER 79-0603] Reduction of rotor-turbulence interaction in	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 N79-17819 f an A79-26907
Industrial Centrifugal Compressors, Volume 2 [VKI-LECTURE-SBRIES-95] N79- Design of multistage compressors with consideration of the real behavior of gas and gas mixtures N79- Development testing of stages for centrifugal process compressors N79- Turbocharger design and development technol assessment and design optimization N79- TURBOFAN ENGINES Engine technology for production turbofan engine N79- Measured and predicted noise of the AVCO-Lycom YF-102 turbofan engine [NIAN PAPER 79-0641] Pull-scale engine tests of bulk absorber acoust inlet treatment [NIAN PAPER 79-0600] The application of finite element techniques to acoustic transmission in lined ducts with fice	-19389 TO d -19390 TO -19392 logy TO -19393 nes -24827 lng -26877 TO	discussion of dynamic stall JRBOPROP AIRCRAFT Prop-fan propulsion - Its status and potent [SAE PAPER 780995] Noise transmission - Turboprop problem [AIAA PAPER 79-0645] JRBOPROP ENGINES Turboprop interior noise studies [AIAA PAPER 79-0647] JRBULENCE BFFECTS An experimental study of the influence of flight-stream turbulence on jet mixing no [AIAA PAPER 79-0617] Interaction of the supersonic flow below a and a supersonic free jet (two-dimensiona situation) [VTH-LR-268] JRBULENT BOUNDARY LAYER On sound radiation from the trailing edge o isolated airfoil in a uniform flow [AIAA PAPER 79-0603] Reduction of rotor-turbulence interaction in static fan noise testing	N79-19354 1a1 A79-25880 A79-26933 A79-26931 1se A79-26935 N79-17819 f an A79-26907

TURBULENT FLOW SUBJECT INDEX

TURBULENT PLOW		UPPER SURFACE BLOWN FLAPS	
Experimental investigation of the effect	of	An experimental study of USB flap noise reduct.	10n
surface discontinuity on step-backward		through mean flow modification Upper Sur	
• •	A79-27000	Blown	
Two-frequency-range theory of unstable to	ırbulent		-26908
combustion oscillations in a jet engine		Analysis of some aerodynamic characteristics d	1e
combustion chamber. II - Analysis of the		to wing-jet interaction	10047
characteristic equation and comparison	With		-18917
experiment	A79-27728	USER MANUALS (COMPUTER PROGRAMS)	D.07
Contribution to the development of theore		General purpose computer program for interaction supersonic configurations. User's manual	ug
calculations for the design and optimiz		determining unsteady aerodynamic foreces	
lifting bodies. (Solution of three-dim			-17798
basic thermo fluid dynamics equations w		Airport vicinity air pollution model. Abbrevi	ated
strong interacting attached and separat	ed flow	version user's guide	
fields)		[FAA-RD-78-111] N79	-18475
[BMVG-FEWT-78-4]	พ79- 17816	UTILITY AIRCRAPT	
TORBULENT JETS		Environmental factors affecting the installati	on
Aerodynamics of flame jets Russian bo	A79-26355	and operation of gas turbine engines in	
Sound absorption caused by vorticity shed		agricultural alccraft [SAE PAPER 781010] A79	-25892
demonstrated with a jet flow	ning,	[SAB FAFBE 701010]	23072
[AIAA PAPER 79-0575]	A79-26905	V	
An experimental study of USB flap noise i		V	
through mean flow modification Uppe		V/STOL AIRCRAFT	
Blown		V/STOL aircraft engine and mechanical drive	
[AIAA PAPER 79-0607]	A79-26908	component integration	
TURBULENT HIXING			-25906
Interaction of the supersonic flow below		Use of radio controlled models in the conceptua	11
and a supersonic free jet (two-dimension	ona 1	development of V/STOL aircraft	25.045
Situation)	W70 17010		-25915
[VTH-LR-268] TORBOLENT WAKES	N79-17819	Avionics systems needed to optimize V/STOL potential	-26874
Turbulence characteristics in the near wa	ke of a	Ski-jump - A great leap for tactical airpower	
compressor rotor blade	ive of a	V/STOL jet launching from upward-inclined ra	
[AIAA PAPER 79-0280]	A79-26544		-27361
An experimental study of the influence of		Evaluation of IFR handling qualities of	
flight-stream turbulence on jet mixing		helicopters using the NAE airborne V/STOL	
[AIAA PAPER 79-0617]	A79-26935	simulator	
Unsteady stator response to upstream roto	r wakes	[AIAA 79-0702] A79-	-27365
[AIAA PAPER 79-0579]	A79-26945	Configuration management and automatic control	of
TWO DIMENSIONAL BOUNDARY LAYER		an augmentor wing aircraft with vectored thre	
Interaction of the supersonic flow below			-17872
and a supersonic free jet (two-dimension	na 1	VALUE ENGINEERING	
situation)	770 17010	The application of computer aided techniques to)
[VTH-LR-268] TWO PHASE FLOW	N79-17819	project design for aircraft	-26592
Convective heat exchange of gas-particle	Stream in	VARIABILITY	-20332
flow passage of throttling device with		Variability of annoyance response due to aircra	ıft
turning element	21 -	nolse	
	A79-27742	[NASA-TP-1335] N79	-18687
		VARIABLE SWEEP WINGS	
U		Dynamics of controlled longitudinal motion of	an
U-2 17000100		airplane with a variable-geometry wing	25547
U-2 AIRCRAFT The U-2 story		VELOCITY DISTRIBUTION	-25517
The U-Z Story	A79-26537	Characteristics of the wake of a lightly loaded	
UH-1 HELICOPTER			1
		COMPRESSOR OF TAB TOTOR	i
	rv missions	compressor or fan rotor [AIAA PAPER 79-0550] A79-	
Rescue helicopters in primary and seconda	ry missions N79-19606		1 -25861
		[AIAA PAPER 79-0550] A79-	-25861
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology	N79-19606	[AIĀA PAPER 79-0550] A79- VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser	-25861 Lng
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application	N79-19606	[AIĀA PAPER 79-0550] A79- VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79-	-25861 ing -28139
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039]	N79-19606	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of	-25861 ing -28139 on
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application	N79-19606 - UH-60A A79-25907	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities	-25861 ing -28139 on
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit	N79-19606 - UH-60A A79-25907 N79-19614	[AIĀĀ PĀPĒR 79-0550] A79- VELOCITY HEASURBENT Aircraft velocity and altitude measurements us a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations	-25861 ing -28139 on and
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039]	N79-19606 UH-60A A79-25907 N79-19614	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] N79-	-25861 ing -28139 on
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop	N79-19606 - UH-60A A79-25907 N79-19614	[AIĀA PAPER 79-0550] A79- VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] N79- VIBRATION DAMPING	-25861 ing -28139 on and -18960
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop	N79-19606 - UH-60A A79-25907 N79-19614 oter N79-19663	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79 Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior	-25861 ing -28139 on and -18960 noise
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop	N79-19606 - UH-60A A79-25907 N79-19614 oter N79-19663	[AIÀA PAPER 79-0550] VELOCITY MEASUREMENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior (AIAA PAPER 79-0582] A79-	-25861 ing -28139 on and -18960
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow	N79-19606 - UH-60A A79-25907 N79-19614 oter N79-19663	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79 Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior	-25861 ing -28139 on and -18960 noise -26943
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA	N79-19606 - UH-60A A79-25907 N79-19614 N79-19663	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted	-25861 ing -28139 on and -18960 noise -26943
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [ATAA PAPER 79-0603]	N79-19606 - UH-60A A79-25907 N79-19614 N79-19663 of an A79-26907	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-184881]	-25861 ing -28139 on and -18960 noise -26943
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile	N79-19606 - UH-60A A79-25907 N79-19614 N79-19663	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION HEASUREMENT	-25861 lng -28139 on and -18960 noise -26943 e
Rescue helicopters in primary and seconda UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW	N79-19606 UH-60A A79-25907 N79-19614 oter N79-19663 of an A79-26907 N79-18085	[AIĀA PAPER 79-0550] VELOCITY MEASUREMENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition design	-25861 lng -28139 on and -18960 noise -26943 e
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc	N79-19606 - UH-60A A79-25907 N79-19614 Def an A79-26907 N79-18085	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION HEASUREMENT Turbojet blade vibration data acquisition designant feasibility testing	-25861 ing -28139 on and -18960 noise -26943 e -17849
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by	N79-19606 - UH-60A A79-25907 N79-19614 ster N79-19663 of an A79-26907 N79-18085	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79 Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-184881] VIBRATION HEASUREMENT Turbojet blade vibration data acquisition designed feasibility testing [NASA-CR-159505] N79-	-25861 lng -28139 on and -18960 noise -26943 e
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc	N79-19606 UH-60A A79-25907 N79-19614 oter N79-19663 of an A79-26907 N79-18085	[AIĀA PAPER 79-0550] VELOCITY MEASUREMENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] VIBRATION HETERS	-25861 ing -28139 on and -18960 noise -26943 e -17849
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by combined method of order O/h2/ and O/h4	N79-19606 - UH-60A A79-25907 N79-19614 Def an A79-26907 N79-18085 Cous A79-24829	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an activity flutter suppression control system [NASA-CR-144881] VIBRATION HEASUREMENT Turbojet blade vibration data acquisition designed and feasibility testing [NASA-CR-159505] VIBRATION HETERS Dynamic data analysis gas turbine engine	-25861 ing -28139 on and -18960 noise -26943 e -17849
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF ABERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by combined method of order 0/h2/ and 0/hu Nonsteady flow of an incompressible liqui	N79-19606 - UH-60A A79-25907 N79-19614 Def an A79-26907 N79-18085 Cous A79-24829	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] VIBRATION HETERS Dynamic data analysis gas turbine engine vibration transducers	-25861 Lng -28139 n and -18960 noise -26943 -17849 gn -18976
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by combined method of order O/h2/ and O/h4	N79-19606 UH-60A A79-25907 N79-19614 oter N79-19663 of an A79-26907 N79-18085	[AIĀA PAPER 79-0550] VELOCITY MEASUREMENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TM-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior (AIĀA PAPER 79-0582) The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] VIBRATION METERS Dynamic data analysis gas turbine engine vibration transducers A79-	-25861 ing -28139 on and -18960 noise -26943 e -17849
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF ABERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by combined method of order 0/h2/ and 0/hu Nonsteady flow of an incompressible liqui	N79-19606 UH-60A A79-25907 N79-19614 Outer N79-19663 Cof an A79-26907 N79-18085 Cous (a A79-24829 dover A79-27062	[AIĀA PAPER 79-0550] VELOCITY HEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based of simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an active flutter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition design and feasibility testing [NASA-CR-159505] VIBRATION HETERS Dynamic data analysis gas turbine engine vibration transducers	-25861 Lng -28139 n and -18960 noise -26943 -17849 gn -18976
Rescue helicopters in primary and secondar UH-60A HELICOPTER Advanced overrunning clutch technology helicopter transmission application [SAE PAPER 781039] UH-60A MEDEVAC kit Crash survivability of the UH-60A helicop UNIFORM FLOW On sound radiation from the trailing edge isolated airfoil in a uniform flow [AIAA PAPER 79-0603] UNITED STATES OF AMERICA Synthesis of national risk profile UNSTEADY FLOW Numerical study of unsteady flows of visc incompressible fluids about airfoils by combined method of order O/h2/ and O/h4 Nonsteady flow of an incompressible liqui slender permeable profiles	N79-19606 UH-60A A79-25907 N79-19614 Outer N79-19663 Cof an A79-26907 N79-18085 Cous (a A79-24829 dover A79-27062	[AIĀA PAPER 79-0550] VELOCITY MEASUREBENT Aircraft velocity and altitude measurements us: a tunable diode laser A79- Evaluation of a wake vortex upset model based simultaneous measurements of wake velocities probe-aircraft accelerations [NASA-TH-78561] VIBRATION DAMPING Master Plan for prediction of vehicle interior [AIĀA PAPER 79-0582] The development of the DAST I remotely piloted research vehicle for flight testing an activitiuter suppression control system [NASA-CR-144881] VIBRATION MEASUREMENT Turbojet blade vibration data acquisition designed from the passibility testing [NASA-CR-159505] VIBRATION HETERS Dynamic data analysis gas turbine engine vibration transducers A79- VIBRATION MODE	-25861 ing -28139 on and -18960 noise -26943 -17849 gn -18976

SUBJECT INDEX WIND TUNNEL TESTS

VISCOUS PLOW A shock capturing application of the finit element method to viscous compressib problem	le flow	WEAPON SYSTEMS Strike Drone - A defense suppression concepunaanned cruise/loiter/attack vehicle [SAR PAPER 781017]	A79-25894
Numerical study of unsteady flows of visco incompressible fluids about airfoils by		New airborne armament systems multimiss design requirements [ATAA 79-0697]	A79-27362
combined method of order 0/h2/ and 0/h4/		WEAR	_
An alternating direction explicit method f	479-24829 or fields	A decision theory model for health monitors aeroengines metal particles in lubric oils as wear indicator	ating
in turbomachines [SAE PAPER 781001]	A79-25884	Separation and investigation of wear partic	A79-28381
Inverse transonic airfoil design methods i		from aero-engines	163
boundary layer and viscous interaction e		[BLL-RISLEY-TR-3308-(9091.9F)]	N79-17856
[NASA-CR-158136]	N79-17805	WEATHER	
Calculation of supersonic viscous flow ove	r delta	Briefs of fatal accidents involving weather	asa
wings with sharp subsonic leading edges	N79-18909	cause/factor, US general aviation, 1977 [NTSB-AMM-78-16]	N79-17832
Viscous flows in centrifugal compressors		WEATHER DATA RECORDERS	
	N79-19387	Evaluation of the Ryan Stormscope as a seve	re
VISIBILITY		weather avoidance system for aircraft	ท79-18229
Advancements in helicopter cockpit technol	09y №79-19625	WEATHER RECONNAISSANCE AIRCRAFT	N /9= 10229
VISUAL PERCEPTION	1175 15025	Design considerations for the WOAA airborne	!
Visual pockets: A design parameter for he	licopter	meteorological radar and data system	
instrument panels			A79-25689
VOICE COMMUNICATION	N79-19641	WEIGHT REDUCTION Filter weight minimization for rectified	
Selective calling procedure in air traffic flight stress reduction in aircraft-grou communication		superconducting alternator power supplies for aircraft	A79-26966
COMMUNICATION	A79-25369	Influence of bypass ratio on jet engine wei	
A survey of communications in the high noi			A79-27737
environment of Army aircraft		Combined strength and aeroelastic wing synt	hesis
TARMAY CORPURA	N79-1964€	via constraint approximation	.70 70700
VORTEX STREETS Sound absorption caused by vorticity shedd	100	[AIAA 79-0724]	A79-28290
demonstrated with a jet flow	-149,	Overestimates of entrainment from wetting of	of
[AIAA PAPER 79-0575]	A79-26905	aircraft temperature sensors in cloud	
VORTICES			A79-25296
Pormation of a trailing wortex	A79-28377	WHITHAM RULE Propagation of buzz-saw noise in a nonuniform	mn medium
Vortex models on missile configurations		contoured jet engine inlets	IL MEGICAL
computer program for determining aerodyn		[AIAA PAPER 79-0639]	A79-26896
coefficients and flow deflection	W70 47045	WIENER PILTERING	
[BMVG-FBWT-77-27] Vortex pattern development on the upper su	N79-17814	Radar system design for track-while-scan	A79-25139
a swept wing at high angle of attack	riace or	WIND HEASUREMENT	R/J 23133
[NASA-TM-75377]	N79-18914	The Dulles International Airport wind-shear	•
Evaluation of a wake vortex upset model ba		detection system Statistical results	.70 07570
simultaneous measurements of wake veloci probe-aircraft accelerations	ties and	WIND SHEAR	A79-27574
[NASA-TH-78561]	N79-18960	The Dulles International Airport wind-shear	:
VULNERABILITY		detection system Statistical results	
Total environment survivability methodolog		gr.t1. t	A79-27574
[AD-A061888]	ห79-18971	Stable boundary layer wind shear model for aircraft flight hazard definition	
W		disciple light hazard delinition	A79-27575
₩ •		A spectral analysis of thunderstorm turbule	ence and
WARBS		jet transport landing performance	07576
Interactional aerodynamics of the single r helicopter configuration. Volume 6-A:	otor	WIND TUNNEL HODELS	A79-27576
One-third octave band spectrograms of wa	ke	Summary report of the second wind tunnel te	st of
single film data, buildur to baseline		the Boeing LPC model	
[AD-A061994]	N79-18958	[NASA-CR-157792]	N79-17799
Interactional aerodynamics of the single r helicopter configuration. Volume 8-C:	otor	WIND TUNNEL STABILITY TESTS	24.04
Prequency analyses of wake single film d	ata.	Wind-tunnel studies of the effects of simul damage on the aerodynamic characteristics	
hubcaps and air ejectors	u cu ,	airplanes and missiles	. 01
[AD-A061995]	N79-18959	•	A79-27424
WARNING SYSTEMS		WIND TUNNEL TESTS	
Flight deck alarm systems	A79-25541	Propeller slipstream wing interactions at # 0.8	ach no.
Evaluation of the Ryan Stormscope as a sev		[SAE PAPER 780997]	A79-25881
weather avoidance system for aircraft		Plight effects on noise generated by the J	
	N79-18229	engine with inverted primary/fan flow as	5
Applications of diffraction theory to aero	aconstics	measured in the NASA-Ames 40- by 80-foot tunnel	wind
[NASA-TH-80053]	N79-18686	[AIAA PAPER 79-0614]	A79-26937
WAVE PROPAGATION		An investigation of model helicopter rotor	
Wave propagation in ducts using the finite	element	slap at low tip speeds	
method for aircraft noise reduction	170-26 970	[AIAA PAPER 79-0613]	A79-26938
[AIAA PAPER 79-0659] WAVEFORMS	A79-26879	Transonic wing design for transport aircraf	:t 179-27357
A new standard for lightning qualification		Some new approaches for wind-tunnel testing	
of aircraft: Technical overview, defini		through the use of computers	
and basic waveforms		[AIAA 79-0707]	A79-27367

N79-18246

WIND TUNNELS SUBJECT INDEX

XV-15 Tilt Rotor Research Aircraft - Program report	
[AIAA 79-0704] A79-27371	
Influence of bypass ratio change on fan aerodynamic characteristics	
A79-27744	
Aerodynamic properties of a flat plate with cavity	
for optical-propagation studies [NASA-TM-78487] N79-17796	
Summary report of the second wind tunnel test of	
the Boeing LPC model	
[NASA-CR-157792] N79-17799	
Wind-tunnel investigation of the thrust augmentor performance of a large-scale swept wing model	
in the Ames 40 by 80 foot wind tunnel	
[NASA-TM-X-73239] N79-17804	
An experimental wind-tunnel investigation of a ram-air-spoiler roll-control device on a	
forward-control missile at supersonic speeds	
[NASA-TP-1353] N79-17809	
Space shuttle afterbody aerodynamics/plume simulation data summary	
[NASA-TP-1384] N79-17810	
Boundary layer transition measurements on the AEDC 10 deg cone in three RAE wind tunnels and their	
10 deg come in three RAE wind tunnels and their	
implications [ARC-R/M-3821] N79-17817	
Theoretical and experimental investigation of	
ground induced effects for a low-aspect-ratio	
highly swept arrow-wing configuration in the Langley V/STOL tunnel	
[NASA-TM-80041] N79-17871	
VIND TUNNELS	
Experimental investigation of the effect of surface discontinuity on step-backward flow	
A79-27000	
VING FLOW METHOD TESTS	
Characteristic aerodynamic coefficients at high Reynolds numbers	
A79-25247	
FING LOADING	
Elevated-temperature effects on strain gages on the YF-12A wing	
A79-26400	
Effects of laminar flow control on the performance	
of a large span-distributed-load flying-wing	
cargo airplane concept [NASA-TM-78715] N79-17851	
VING OSCILLATIONS	
A slender delta wing oscillating in surface waves	
[VTH-LR-257] N79-17818 Investigation of torsion free wing trend flutter	
models	
[AD-A061942] N79-18957	
Fabrication and evaluation of advanced titanium	
structural panels for supersonic cruise aircraft	
[NASA-CR-2744] N79-18320	
ING PLANFORMS Fundamentals of design. I - 'Whys' and	
'wherefores' of wings	
A79-25485	
Helicopter rotor radius optimization [AIAA PAPER 79-0554] A79-25865	
Investigation of torsion free wing trend flutter	
models	
[AD-A061942] N79-18957	
VING PROFILES Transonic wing design for transport aircraft	
[AIAA 79-0692] A79-27357	
An improved system for use in conducting wake	
investigation for a wing in flight	
differential pressure measurements for drag	
[NAS4-CASE-FRC-11024-1] N79-17797	
Interaction of the supersonic flow below a wing	
and a supersonic free jet (two-dimensional situation)	
[VIH-LR-268] N79-17819	
ING SPAN	
Effects of laminar flow control on the performance of a large span-distributed-load flying-wing	
cargo airplane concept	
[NASA-TM-78715] N79-17851	
INGLETS	
The Learjet Longhorn series - The first jets with winglets	
179-26532	

The Learjet Longhorn series: The first jets with winglets N79-18893 WINGS An aeroelastic optimization procedure for composite high aspect ratio wings [AIAA 79-0726] A79-28258 Wing rock due to aerodynamic hysteresis A79-28376 Formation of a trailing wortex A79-28377 N79-18921 Turbomachinery flutter: Introductory concepts N79-19353 WORKLOADS (PSYCHOPHYSIOLOGY) Selective calling procedure in air traffic --flight stress reduction in aircraft-ground voice communication A79~25369 Two-segment approach investigation on a moving-base piloted flight simulator [VTH-LR-250] N79-17880 Advancements in helicopter cockpit technology N79-19625 X XV-15 AIRCRAFT An acoustical study of the XV-15 Tilt Rotor An acoustical study of the XV-15 Tilt Rotor
Research Aircraft
[ATIAN PAPER 79-0612]

XV-15 Tilt Rotor Research Aircraft - Program report
[AIAA 79-0704]

A79-27371 Y YP-12 AIRCRAFT

Elevated-temperature effects on strain gages on the YF-12A wing


PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Suppl 110)

JUNE 1979

A79-25139

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g. NASA report translation NASA contractor report). The accession number is located beneath and to the right of the title e.g. N79-11001. Under any one author's name the accession numbers are arranged in sequence with the IAA accession numbers appearing first.

name the accession numbers are arranged in sequence with the IA.	A accession
numbers appearing first	
Δ	
A	
ADAMSON, W. H.	
Prop-fan propulsion - Its status and poten	
[SAE PAPER 780995]	A79-25880
ADDY, A. L. Analysis of base-flow problems during power	rod
supersonic flight	Leu
	N79-18926
AGACHEV, R. S.	
Theoretical-experimental analysis of influence	
coolant discharge from perforated turbing	e vanes
on their aerodynamic characteristics	A79-27727
AGGARWAL, R.	A13-21121
An analysis of fuel conserving operational	
procedures and design modifications for	
bomber/transport aircraft. Volume 1: Ex	recutive
sunnary	
[AD-A061746]	N79-18969
Helicopter rotor radius optimization	
[AIAA PAPER 79-0554]	A79-25865
AHUJA, K. K.	22005
Effects of simulated forward flight on jet	noise,
shock noise and internal noise	
[AIAA PAPER 79-0615]	A79-26936
AHUHADA, A., JR.	
The annoyance of multiple noisy events [AIAA PAPER 79-0653]	A79-26895
ALBARES, D. J.	R 7 20033
Hilitary fiber optics applications	
•	A79-28040
ALBRECHT, C. O.	
Structural development of the Modernized Cl	hinook
helicopter transmission gearing [AIAA 79-0728]	A79-28260
ALEXANDER, A.	A79-20200
Interactive multi-mode blade impact analysis	is
[NASA-CR-159462]	N79-17858
ALLEHOUD, P.	
Helicopter crashworthy fuel systems and the	
effectiveness in preventing thermal injur	ry N79-19660
ANDERSON, R. S.	475-15000
Adaptation of a digital airborne radar for	use on
the microphysics research aircraft	
	A79-25681
ANGELLO, L. C.	
Shale oil - The answer to the jet fuel availability question	
[SAE PAPER 781027]	A79-25900
form ruran . A. i.a 1	23700

ANIUTIN, A. N.	
ANIUTIE, A. W. Axial compressor operation with radially nonuniform inflow	
HOUGHING THILOW	A79-27743
ANTOINE, A. C.	
Evaluation of the application of some gas chromatographic methods for the determina properties of synthetic fuels	ation of
• •	A79-25917
APEL, J. R. Applying design-to-life cycle cost methods	during
engine advanced development [SAE PAPER 781030]	A79-25902
ARBNA, A. V.	
A visual investigation of the separation as subsequent transition near the leading earth.	ige of
airfoils	A79-25863
[AIAA PAPER 79-0552] ARMSTRONG, N. A.	A/9-25003
The Learjet Longhorn series - The first jet	ts with
winglets The Learjet Longhorn series: The first jet	A79-26532
winglets	
ARVIE, J. R.	N79-18893
Integrally cast turbine rotor for high volu	1 B e
production [SAE PAPER 781000]	A79-25883
ASLANOV, S. K.	
Two-frequency-range theory of unstable turse combustion oscillations in a jet engine	oulent
combustion chamber. II - Analysis of the	
characteristic equation and comparison was	Lth
•	A79-27728
ASTLEY, R. J. The application of finite element technique	es to
acoustic transmission in lined ducts with	flow
[AIAA PAPER 79-0660] ATENCIO, A., JR.	A79-26893
Flight effects on noise generated by the J'	T8D
engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot	wand
tunnel	
[AIAA PAPER 79-0614]	A79-26937
В	
BAARSPUL, M.	
Two-segment approach investigation on a	
moving-base piloted flight simulator [VTH-LR-250]	N79-17880
BABENKO, V. S.	
Visual simulation devices for flight train: simulators	ing
Simulators	A79-2635
BAILEY, R. W. Visual pockets: A design parameter for hel	Liconter
instrument panels	
DAMED C D	N79-19641
BAKER, C. R. Study of hydrogen recovery systems for gas while refueling liquid-hydrogen fueled as	vented
There returns reques "Jacoyen recess as	
[NASA-CR-158991] BALLHAUS, W. P.	N79-18057
Some recent progress in transonic flow comp	N79-18946
BALMFORD, D. E. H. Puture advanced technology rotorcraft	
[AIAA 79-0705]	A79-27366
BARKER, P.	

BARNA, P. S. PERSOHAL AUTHOR INDEX

BARNA, P. S.		BITER, C. J.	
Experimental studies on the effects of a s support on the pressure distribution are		Overestimates of entrainment from wetting aircraft temperature sensors in cloud	
spherical object [NASA-CR-158127]	N79-17800	BLACKWELL, K. L.	A79-25296
Experiments on tandem diffusers with boundary-layer suction applied in between	en.	Space shuttle afterbody aerodynamics/plume simulation data summary	
[NASA-CR-158957]	N79-17803	[NA SA-TP-1384]	N79-17810
BARRANGER, J. An in-place recallbration technique to ext temperature capability of capacitance-se		BLAIR, A. B., JR. An experimental wind-tunnel investigation ram-air-spoiler roll-control device on a	
rotor-blade-tip-clearance measurement sy [SAE PAPER 781003]	ystems A79-25885	forward-control missile at supersonic sp [NASA-TP-1353]	eeds N79-17809
BARRY, B. The aerodynamic penalties associated with	turbine	BLANCHARD, D. K. A shock capturing application of the finit	e
blade cooling	N79-18986	element method	A79-24771
BARTLETT, W. Pressure and heat-transfer distributions i	in a	BLASZCZYK, J. Analysis of longitudinal natural vibration	sof
simulated wing-elevon cove with variable at a free-stream Mach number of 6.9	e leakage	deformable aircraft by the finite-elemen	
[NASA-TM-74095] BARTON, C. K.	N79-18284	BLICK, B. P. A spectral analysis of thunderstorm turbul	ence and
Characteristics of propeller noise on an a fuselage related to interior noise trans		jet transport landing performance	A79-27576
[AIAA PAPER 79-0646]	A79-26932	BOCKEHULLER, B. A.	11.7 2.3.0
BAUM, R. K. Evaluation of the Ryan Stormscope as a set	vere	Bailout from autorotating helicopters	N79-19666
weather avoidance system for aircraft	พ79-18229	BOGDANOV, A. S. Influence of bypass ratio on jet engine we	
BEAM, P. E., JR. V/STOL aircraft engine and mechanical driv	7e	BONDAR, V. A.	A79-27737
component integration [SAE PAPER 781038]	A79-25906	Intensification of fuel vaporization in al gas turbine engines by electrical forces	
BECHERT, D. W. Sound absorption caused by vorticity shedd	ling.	BOYLES, R. Q., JR.	A79-27748
demonstrated with a jet flow [AIAA PAPER 79-0575]	A79-26905	Advanced system design requirements for la small fixed-wing aerial application syst	
BEDARD, A. J., JR. The Dulles International Airport wind-shea	ır	agriculture [NASA-CR-158939]	N79-17848
detection system Statistical results	A79-27574	Computer-aided collection of demographic d	
EEKEBREDE, G. Two-segment approach investigation on a		<pre>within day-night level contours: Two te [AD-A061657]</pre>	N79-19010
<pre>moving-base piloted flight simulator [VTH-LR-250]</pre>	N79-17880	BREKHOV, A. P. Axial compressor operation with radially	
BELLINGER, B. D.		nonuniform inflow	. 70 077#3
Aeroelastic addition to NASTRAN [NASA-CR-3094]	N79-17812	BRENT, G. A.	A79-27743
Propeller slipstream wing interactions at	Mach no.	GASP-PL/I simulation of integrated avionic processor architectures	_
0.8 [SAE PAPER 780997]	A79-25881	[NASA-CR-158244] BREWER, G. D.	N79-18973
BENSCH, R. R. A spectral analysis of thunderstorm turbul	ence and	Cryohydrogen-fuel for tomorrow's commercia	1 aircraft A79-27656
jet transport landing performance		BRIEHL, D.	
BENVENUTI, B. Transonic compressors for heavy gases. Par	A79-27576	Simultaneous measurements of ozone outside inside cabins of two B-747 airliners and Learjet business jet	
Selections of the aero-design parameters	5		A79-27571
Transonic compressors for heavy gases. Pa Aero-mechanical considerations, testing		BROBK, D. The prediction of fatigue crack growth und flight-by-flight loading	er
operation		•	A79-25482
Development testing of stages for centrifu	N79-19352 Igal	BRUSSAT, T. R. Fracture mechanics for structural adhesive	bonds,
process compressors	N79-19392	part 2, phase 2 [AD-A061805]	N79-19418
BERKOWITZ, R. S. TASAR, a thinned adaptive synthetic apertu		BRYCE, W. D. Experiments concerning the anomalous behav	lour of
BEZIAC, G.	A79-27135	aero-engine exhaust noise in flight [AIAA PAPER 79-0648]	A79-26930
Perspectives of technological development helicopters	for	BRYSON, R. J. Comparisons of turbine engine combustor ex	hanst
[AIAA 79-0701] BIKLE, P. F.	A79-27364	emissions measurements using three gas-s probe designs	
An improved system for use in conducting w investigation for a wing in flight	rake	[AD-A061733]	₦79-19005
[NASA-CASE-PRC-11024-1]	N79-17797	BUCHSTALLER, H. Engine dynamics	
BILL, R. C. Composite seal for turbomachinery		[BMVG-PBWT-78-6] BUCKHOLZ, R. H.	N79-17862
[NASA-CASE-LEW+12131-1]	N79-18318	Some aspects of unsteady insect aerodynami	
BINDER, S. Advanced technology applied to the CH-47D	drive	Acceleration potential methods in plane airfoil theory, and measurements of	
system [SAE PAPER 781040]	A79-25908	unsteady-periodic forces generated by th	e blowfly N79-18903

PERSONAL AUTHOR INDEX CORNERY, G.

BUELL, D. A.		CHURCH, G. W.	
Aerodynamic properties of a flat plate wit for optical-propagation studies	th Cavity	Advances in avionics [AIAA PAPER 79-0562]	A79-25862
[NASA-TE-78487]	N79-17796	CHURCHILL, A. V.	
BULFORD, D. E. Collision avoidance an annotated bibliogra	phy	Shale oil - The answer to the jet fuel availability question	
[FAA-NA-78-8]	N79-17840	[SAE PAPER 7810271	A79-25900
BULYGIN, I. P. Prediction of gas-turbine alloy creep		CICCI, P. Crashworthiness tests on model aircraft fus	selage
Characteristics		structures	
BURKE, J. J.	A79-26841	[AIAA 79-0688] CICOLANI, L. S.	A79-27354
Application of fracture mechanics to design		Configuration management and automatic confi	
BURNS, B. R. A.	A79-26980	an augmentor wing aircraft with vectored [NASA-TP-1222]	hrust N79-17872
Pundamentals of design. I - 'Whys' and		CLARK, B. J.	
'wherefores' of wings	A79-25485	Measured and predicted noise of the AVCO-Ly YF-102 turbofan engine	ycoming
Supersonic combat aircraft design		[AIAA PAPER 79-0641]	A79-26877
[AIAA 79-0699] BURTON, R. A.	A79-27363	CLIFFORD, D. W. The impact of the total lightning environments	ent on
Thermoelastic and dynamic phenomena in sea		aircraft flight control systems	
[AD-A061754] SURTON, R. V., JR.	N79-19396	CLINE, J.	A79-25319
Puel tank sealant requirements for advance	e high	An RP compatible lightning diverter strip	
performance aircraft [AIAA 79-0807]	A79-28288	CLOOS, B.	N79-18237
		Digital target extraction at civil air train	
C		control radar installations in the Federa Republic of Germany and possibilities for	
CALKINS, R. B.		further development from the point of vie	
Parachute partial inversions [AIAA 79-0451]	A79-26655	the Federal Institute of ATC	A79-26753
CAMP, D. W.		COCKRELL, D. J.	
Stable boundary layer wind shear model for aircraft flight hazard definition	:	A simple physical model of a descending par [AIAA 79-0447]	A79-26651
•	A79-27575	longitudinal oscillation damping for	
CAMPION, B. S. New technology in commercial aircraft desi	lgn for	fully-inflated parachute canopies [AIAA 79-0459]	A79-26662
minimum operating cost		The validity of the Leicester computer mode	el for a
TAIAA 79-0690] CARLSON, H. W.	A79-27356	parachute with fully-deployed canopy [AIAA 79-0460]	A79-26663
A modification to linearized theory for proof pressure loadings on lifting surfaces		COB, P. L., JR. Theoretical and experimental investigation	of
supersonic Mach numbers and large angles		ground induced effects for a low-aspect-	
[NASA-TP-1406]	N79-17806	highly swept arrow-wing configuration [NASA-TM-80041]	N79-17871
CARLSON, L. A. Inverse transonic airfoil design methods i	including	COEBE, R.	1175-17071
boundary layer and viscous interaction e [NASA-CR-158136]	effects N79-17805	A slender delta wing oscillating in surface [VTH-LR-257]	waves N79-17818
CARNELL, B. L.		COLLINS, W. G.	
Crash survivability of the UH-60A helicopt	er N79-19663	Operational evaluation of an Air Traffic Co Radar Beacon System open array antenna	ontrol
CARTA, F. O.		•	A79-27139
The influence of sweep on aerodynamic load an oscillating NACA0012 airfoil. Volume		COLPIN, J. Aerodynamic and Mechanical factors affecting	ng the
Data report		surge line: Inlet flow distortion influe axial flow compressors	ences on
[NASA-CR-145350] Turbomachinery flutter: Introductory cond	N79~17802 cepts	dilai ilow complessors	N79-19363
Identification of various flutter regimes	N79~19353	COMEY, D. H. Trade-off studies with an interactive	
Identification of various flutter regimes discussion of dynamic stall		engine/airframe life-cycle-cost model	
CASSIDY, J. B.	N79-19354	[SAE PAPER 781033] CONLEY, L. A.	A79-25905
Trade-off studies with an interactive		Airport vicinity air pollution model. Abbi	re v lated
engine/airframe life-cycle-cost model [SAE PAPER 781033]	A79-25905	version user's guide [FAA-RD-78-111]	N79-18475
CAWTBORN, J. M.		COOK, R.	
Variability of annoyance response due to a noise	iliciait	Induced effects of lightning on an all compaircraft	posite
[NASA-TP-1335]	N79~18687	COOF D D	N79-18242
CHANG, M. T. Noise transmission - Turboprop problem		COOK, R. B. EMP coupling to a composite aircraft	
TAIAA PAPER 79-0645]	A79-26933	COOKE, C. H.	A79-25321
Applications of diffraction theory to aero	acoustics	A shock capturing application of the finite	e
[NASA-TM-80053] CHERNG, J. G. J.	N79-18E86	element method	A79-24771
Investigation of the aerodynamic and acous		CORBIN, J. C., JR.	
performance of a low-pressure ratio tand compressor	lem-blade	Protection/hardening of aircraft electronic systems against the indirect effects of 1	
•	พ79-18975	-	N79-18238
CHIO, S. T. Fracture mechanics for structural adhesive	bonds.	CORMERY, G. Compromise between economic concerns and	
part 2, phase 2	-	application of new technologies in the	
[AD-A061805] CHO, Y. C.	N79-19418	definition of a new airplane project [AIAA 79-0693]	A79-27358
Sound radiation from hyperboloidal inlet d		-	
[AIAA PAPER 79-0677]	A79-26885		

CORNELL, R. W. PERSONAL AUTHOR INDEX

CORNELL, R. W.		DAVIS, J. A.	
Interactive multi-mode blade impact analy: [NASA-CR-159462]	sis N79-17858	Unsteady pressures on a NACA 64A010 airfoi Experimental and theoretical results	
COUSSEDIERE, M. New airborne display concepts	. 70 07 (70	[AIAA PAPER 79-0330] DEADHORE, D. L.	A79-26545
COUSTON, H.	A79-27672	Effect of a chromium-containing fuel addit hot corrosion	1ve on
Time marching finite area method	N79-18990	DEJONG, P. J. P.	A79-26546
COX, A. R. Potential uses of rapidly solidified allog		Interaction of the supersonic flow below a and a supersonic free jet (two-dimension	
turbine engines	A79-27313	situation) [VTH-LR-268]	N79-17819
COX, R. H.		DELANEY, C. L.	
Siting criteria for MLS stations. II CRABB, D.	A79-28184	Shale oil - The answer to the jet fuel availability question [SAE PAPER 781027]	A79-25900
The influence of geometric asymmetry on the downstream of row of jets discharging no		DELAURIER, J. The influence of ballonet motions on the	
into a free stream	A79-25065	longitudinal stability of tethered aeros [AIAA 79-0445]	tats 179-26649
CRAM, C. FAA remote terminal system frequency assignments	mment	DELL, M. E. Requirements and constraints in the develo	
model	A79-25323	and qualification of gas turbine engines	
CRILL, W.	R19-23323	Navy [SAE PAPER 780994]	A79-25879
General purpose computer program for inter		DELUCIA, R. A.	****
supersonic configurations. User's manual [NASA-CR-145128] CROUCH, R. K.	ห79-17798	Rotor fragment protection program: Statis aircraft gas turbine engine rotor failur occurred in US commercial aviation durin	es that
LED instrument approach instruction displa [NASA-TM-78823]	ny N79-17854	[NASA-CR-159474] DEMPSEY, T. K.	N79-18977
CROWDER, J. P. Propeller slipstream wing interactions at	Mach no.	Variability of annoyance response due to a noise	ırcraft
0.8		[NASA-TP-1335]	N79-18687
[SAE PAPER 780997] CUFFEL, R. F.	A79-25881	DESJARDIES, S. P. Crashworthy helicopter seats and occupant	
Twin jet shielding [AIAA PAPER 79-0671]	A79-26924	restraint systems	N79-19658
Separation of core noise and jet noise		DEVEIKIS, W. D.	
[AIAA PAPER 79-0589] CULLEN, W. H. Failure studies of a third stage fan disk	A79-26941 from a	Pressure and heat-transfer distributions i simulated wing-elevon cove with variable at a free-stream Mach number of 6.9	leakage
TF-30 turbine engine [AD-A061801]	N 79-19004	[NASA-TM-74095] DOBOS-BUBNO, S.	ห79-18284
CULY, D. G. Trade-off studies with an interactive engine/airframe life-cycle-cost model		Validation of MIL-F-9490D: General specif for flight control system for piloted mi	litary
[SAE PAPER 781033]	A79-25905	aircraft. Volume 1: Summary of YF-17 a validations	
CUNNINGHAM, W. P. Helicopter underwater escape trainer (9D5)		[AD-A061807] Validation of MIL-F-9490D: General specif	N79-19008 ication
CURRAN, P. M.	N79-19665	for flight control system for piloted mi aircraft. Volume 2: YF-17 lightweight	
Design procedure for an information transf method CUBITS for allocating panel area		validation [AD-A062008]	ห79-19009
aircrew station controls and displays		DOLBEARE, R. T.	117 17005
CURRY, C. E. Turbine engine cost reduction using Life C	N79-19631	Integrated Thermal Avionics Design (ITAD) [AD-A061227] DOLLERIS, G. W.	N79-17855
Cost techniques	_	Strain gage system evaluation program	
[SAE PAPER 781031] CURRY, W. H.	A79-25903	[NASA-CR-159486] DONGUY, P.	N79-19314
Plight simulation of a vehicle with a two- parachute system	stage	Design and development of an helicopter ro and elastomeric bearing	tor hub
[AIAA 79-0448]	A79-26652	[AIAA 79-0815] DOUGHERTY, J. E.	A79-28289
D		Recognition of damage-tolerance in civil airworthiness standards	
DALE, B. General purpose computer program for inter		[SAE PAPER 781019]	A79-25895
supersonic configurations. User's manual		DOWELL, E. H. Turboprop interior noise studies	
[NASA-CR-145128] DALLY, J. W.	N79-17798	[AIAA PAPER 79-0647] Master Plan for prediction of vehicle inte	A79-26931
Failure studies of a third stage fan disk	from a	[AIAA PAPER 79-0582]	A79-26943
TF-30 turbine engine [AD-A061801] DARDEN, C. H.	N79-19004	DOYLE, V. L. Combustion noise prediction update [AIAA PAPER 79-0588]	A79-26942
Some effects of applying sonic boom minimi	zation	DRISKO, R. W.	
to supersonic cruise aircraft design [AIAA PAPER 79-0652] DAUBE, O.	A79-26927	Airfield marking paints state-of-the-art [PAA-RD-78-104] DRIVER, C.	N79-17876
Numerical study of unsteady flows of visco incompressible fluids about airfoils by		Advanced supersonic technology and its implications for the future	
combined method of order O/h2/ and O/h4/		[AÍAA 79-0694] DROBIAZKO, B. S.	A79-27359
DAVIDSON, S. A. Validation of IEMCAP using the B-52	27047	Instability of fluid flow in centrifugal in	
rarraction of theore using the B-52	A79-25326		A79-27731

PERSONAL AUTHOR INDEX PINK, M. R.

DU PEU, A. W.			
		ERUST, D.	
Pressure measurement in air data instrumen	tation	Navstar/GPS /Global Positioning System/ and	đ
	A79-25850	electronic counter measures	
DUCHENIN, J. H.		TROUGH T W	A79-25492
Application of aerodynamic design technique process compressor design	ies to	ERSHOV, V. M. Axial compressor operation with radially	
process compressor design	N79-19388	nonuniform inflow	
DUGAN, J. P., JR.	173 13000		A79-27743
Prop-fan propulsion - Its status and poten	tial	Influence of bypass ratio change on fan	
[SAE PAPER 780995]	A79-25880	aerodynamic characteristics	
DUNKER, R.			A79-27744
Comparison between flows in cascades and me the transonic range. 3: Comparison of	otors in	ESSERS, J. A.	
experimental and theoretical results of	flow	Quasi-natural numerical methods for the computation of inviscid potential or rot	a+10na1
studies on blade-to-blade surfaces in an		transonic flows	acionai
compressor rotor			A79-26487
•	N79-19002	ETTINGER, R. C.	
DONN, J.		F-16 high angle of attack testing	
An RF compatible lightning diverter strip	w20 40037	- 46 1 1 2 6 11 1 1	A79-2€527
DOUBLE D. U.	N79-18237	F-16 high angle of attack testing	N79-1888£
DUVAL, R. W. Inertial dynamics of a general purpose rot	·0.F	EVANS, J. C.	N / 3 - 1000 C
[NASA-TM-78557]	N79-18916	Reliability growth on B-52 FLIP system	
DVOSKIN, N. D.	****		A79-24958
Environmental models for moisture absorpti	on by	EVANS, R. J.	
aircraft composites		Radar system design for track-while-scan	
DWD 7 7	A79-27572	THE COLUMN TO	A79-25139
DYE, J. E. Overestimates of entrainment from wetting	of	The application of finite element technique	as to
aircraft temperature sensors in cloud	O.L	acoustic transmission in lined ducts wit	
director conformation bolloons in order	A79-25296	[AIAA PAPER 79-0660]	A79-26893
DZYGADLO, Z.		,	
Analysis of longitudinal natural vibration		r	
deformable aircraft by the finite-elemen		F	
Decompose of sentential length decol	A79-25505	PAIR, G.	
Dynamics of controlled longitudinal motion airplane with a variable-geometry wing	or an	Enhanced capabilities of future fighters a result of HiMAT	s a
displace with a variable-deometry wind	A79-25517	[AIAA 79-0698]	A79-27370
		PALARSKI, M. D.	
E		Wind-tunnel investigation of the thrust au	
_		performance of a large-scale swept wing	
EARLE, R. V.		[NA SA-TM-X-73239]	N79-17804
Turbine engine cost reduction using Life C	Acre	FARASSAT, F.	L
Cost techniques [SAE PAPER 781031]	A79-25903	A comparison of linear acoustic theory wit experimental noise data for a small-scal	
EATON, J. A.	A77 23703	howering rotor	•
A simple physical model of a descending pa	rachute		A79-26876
[AIAA 79-0447]	A79-26651	PARRELL, C. P.	
Longitudinal oscillation damping for		Technology and the new look meet the F/A-1	8 radar
fully-inflated parachute canopies	- 70 00000	reliability challenge	
[AIAA 79-0459]	A79-26662	[SAE PAPER 781024]	A79-25897
		FEAGIN, R. C. Delta method, an empirical drag buildup te	
The validity of the Leicester computer mod			chnique
parachute with fully-deployed canopy			chnigue N79-17801
	A79-26663	[NASA-CR-151971] PEW, J. D.	N79-17801
parachute with fully-deployed canopy [AIAA 79-0460]	A79-26663	[NASA-CR-151971] FEW, J. D. Comparisons of turbine engine combustor ex	N79-17801 haust
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Plight deck alarm systems		[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s	N79-17801 haust
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I.	A79-26663 A79-25541	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs	N79-17801 haust ampling
parachute with fully-deployed canopy [AIDA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid	A79-26663 A79-25541	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733]	N79-17801 haust
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I.	A79-26663 A79-25541	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A.	N79-17801 haust ampling N79-19005
parachute with fully-deployed canopy [AIDA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid	A79-26663 A79-25541	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733]	N79-17801 haust ampling N79-19005
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Plight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles	A79-26663 A79-25541 OVER A79-27062	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing	N79-17801 haust ampling N79-19005
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Plight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds	A79-26663 A79-25541 over A79-27062 high	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O.	N79-17801 haust ampling N79-19005 es on A79-26400
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687]	A79-26663 A79-25541 OVER A79-27062	[NASA-CR-151971] FEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW	N79-17801 haust ampling N79-19005 es on A79-26400
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I.	A79-26663 A79-25541 Over A79-27062 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O.	N79-17801 haust ampling N79-19005 es on A79-26400
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si	A79-26663 A79-25541 Over A79-27062 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar	N79-17801 haust ampling N79-19005 es on A79-26400
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage	A79-26663 A79-25541 Over A79-27062 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIESEL, J.	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si	A79-26663 A79-25541 over A79-27062 high A79-27353 mulated	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing PIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar PIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H.	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of iation. porting
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989]	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for electrons.	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 officer A79-27000	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIN, V. A.	N79-17801 haust ampling N79-19005 es on A79-26400 /GHTBF A79-24965 e use of lation. porting N79-18074
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for the surface discontinuity on step-backward for the province of modern airfoil sections for the province of the province of modern airfoil sections for the province of	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 officer A79-27000	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for electrons.	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 officer A79-27000	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIENI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIN, V. A.	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELIAA, G.	A79-26663 A79-25541 over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing PIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] BL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELFSTROM, G. M. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] BLIANS, G. Aerodynamic and acoustic comparisons of	A79-26663 A79-25541 over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLMAR, G. L.	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELITAN, G. B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILLWA, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLWAR, G. L. Analysis of some aerodynamic characteristic	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574]	A79-26663 A79-25541 over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing PIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av Volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLMAN, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742 cs due
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELFSTROM, G. B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] ELLINGTON, J. E.	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLMAH, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction [NASA-CR-158349]	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574]	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar PIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILLIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLHAR, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction [NASA-CR-158349] FIEM, W. R.	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742 cs due
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. B. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELFSTROM, G. B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] ELLINGTON, J. E.	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off low A79-27000 high A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLMAH, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction [NASA-CR-158349]	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742 cs due
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREMOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] EL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELISTROM, G. H. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] ELIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] ELLINGTON, J. E. Airline approach to CAT III	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off ilow A79-27000 high A79-27353 A79-26946 A79-26533	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar PIKSEL, J. An assessment of the risks presented by th carbon fiber composites in commercial av volume 1: Final report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle s flow passage of throttling device with v turning element FILLHAR, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction [NASA-CR-158349] FIEK, W. R. Noise from struts and splitters in turbofa ducts [ATAA PAPER 79-0637]	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742 cs due N79-18917 n exit A79-26923
parachute with fully-deployed canopy [AIAA 79-0460] EDWARDS, E. Flight deck alarm systems EFREBOV, I. I. Nonsteady flow of an incompressible liquid slender permeable profiles EGGLESTON, B. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] EKLUND, T. I. Pool fire radiation through a door in a si aircraft fuselage [FAA-NA-78-38] BL-TAHER, R. H. Experimental investigation of the effect of surface discontinuity on step-backward for subsonic cruise speeds [AIAA 79-0687] ELISTROM, G. M. Development of modern airfoil sections for subsonic cruise speeds [AIAA 79-0687] BLIAS, G. Aerodynamic and acoustic comparisons of scaled-down and actual engine jets [AIAA PAPER 79-0574] ELLINGTON, J. E. Airline approach to CAT III	A79-26663 A79-25541 Over A79-27062 high A79-27353 mulated N79-17966 off A79-27000 high A79-27353 A79-27353	[NASA-CR-151971] PEW, J. D. Comparisons of turbine engine combustor ex emissions measurements using three gas-s probe designs [AD-A061733] FIELD, R. A. Elevated-temperature effects on strain gag the YF-12A wing FIEWI, D. O. Reliability growth planning to achieve RIW requirements for an airborne radar FIRSEL, J. An assessment of the risks presented by the carbon fiber composites in commercial av volume 1: Pinal report. Volume 2: Sup appendices [NASA-CR-158989] FILIM, V. A. Convective heat exchange of gas-particle sellow passage of throttling device with verning element FILLHAM, G. L. Analysis of some aerodynamic characteristic to wing-jet interaction [NASA-CR-158349] FIMM, M. R. Noise from struts and splitters in turbofa ducts	N79-17801 haust ampling N79-19005 es on A79-26400 /GMTBF A79-24965 e use of lation. porting N79-18074 tream in ane-type A79-27742 cs due N79-18917 n exit A79-26923

FISCHER, H. J. PERSONAL AUTHOR INDEX

FISCHER, H. J.		GEYER, G. B.	
Electric charging of helicopters [BMVG-FBWT-78-7]	N79-18274	Full-scale fire modeling tests of a compact response foam and dry chemical powder di	
PISHBEIN, B. D.		system	-
Comparison of BTJES and TJE characteristic	s in	[FAA-NA-78-24]	N79-17825
supersonic cruising flight	A79-27740	GHAZY, H. A. Experimental investigation of the effect of	of
PISTER, W.		surface discontinuity on step-backward i	
A stress and strain analysis of industrial compressor impellers using the framework		GILEWICZ, A. B.	A79-27000
	N79-19391	Assessment of the benefits of aircraft	
PLETCHER, J.		crashworthiness	N79-19657
Supersonic combat aircraft design [AIAA 79-0699]	A79-27363	GILWEE, W. J., JR.	N/3-1363/
PORSYTH, P. J. E.		Thermal response of composite panels	
Design against fatigue - Current trends [AIAA 79-0689]	A79-27355	GIMMESTAD, D.	A79-25350
FOZARD, J. W.	R/J-2/333	An aeroelastic optimization procedure for	
Ski-jump + A great leap for tactical airport		composite high aspect ratio wings	. 20 00050
[AIAA 79-0696] FRANCIS, H. S.	A79-27361	[AIAA 79-0726] GINDER, R. B.	A79-28258
Formation of a trailing vortex		Considerations for the design of inlet flo) W
PRINCOTC I	A79-28377	conditioners for static fan noise testin	
FRANCOIS, J. Turbine blade cooling		[AINA PAPER 79-0657] GLEIZER, A. I.	A79-26909
	N79-18980	Optimizing gasturbine engine flexible roto	or
FRANKE, G. F. Unsteady stator response to upstream rotor	wakee	balancing by the LP-search method	A79-27745
[AIAA PAPER 79-0579]	A79-26945	GLICK, D. D.	R73-27743
PRAREY, J. L.	3	Visual pockets: A design parameter for he	licopter
Turbojet blade vibration data acquisition of and feasibility testing	aesign	instrument panels	N79-19€41
[NASA-CR-159505]	N79-18976	GLIDEWELL, R.	
PRENCH, K. E. A first-order theory for the effects of li	no +10c	IR scanning camera measurements of an exha plume from an axisymmetric nozzle afterb	
on parachute deployment	ne cles	model at transonic Mach numbers	,ou,
[AIAA 79-0450]	A79-26654	avenue n a	A79-28097
PREY, G. Rescue helicopters in primary and secondary	v missions	GLIEBE, P. R. Diagnostic evaluation of jet noise suppres	ssion
	N79-19606	mechanisms	
PRIEDMANN, P. P. Nonlinear equations of equilibrium for ela:	etic	[AIAA PAPER 79-0674] The effect of throttling on forward radiat	A79-26912
helicopter or wind turbine blades undergo		noise	eu lun
moderate deformation		[AIAA PAPER 79-0640]	A79-26917
[NASA-CR-159478] FRINK, N. T.	N79-19414	GLOECKNER, B. Control of the location of the center of o	ravity
Lifting surface theory for skewed and swept	t	of loaded aircraft	
subsonic wings [AIAA PAPER 79-0551]	A79-25869	GLUSHKO, V. P.	A79-25370
FROST, W.	117 25005	Path in rocket technology - Selected works	,
Stable boundary layer wind shear model for		1924-1946	A79-27599
aircraft flight hazard definition	A79-27575	GOEBEL, J.	A79-27393
FUJIWARA, O.		Turbocharger design and development	ท79-19393
Inside noise of C-1 cargo aircraft and the reduction performance by interior materia		GOEDE, R. H.	M/9-19393
-	A79-27121	Development of casualty evacuation kit for	the
•		light observation helicopter (Kiwa)	N79-19616
G		GOKHALE, G. S.	
GALICH, N. E. Plane problems of aerothermooptics		Design specifications for the capped ballo special reference to their survival in t	
	A79-26865	equatorial tropopause	
GANN, R. G.	sino fino	[AIAA 79-0426]	A79-26635
New agents for the extinguishment of magnes [AD-A061664]	81um fires N79-19122	GOLDBERG, J. SIFT - Design and analysis of a fault-tole	rant
GARDNER, F. K.		computer for aircraft control	
Validation of IBMCAP using the B-52	A79-25326	GOLDSTEIN, L. F.	A79-25718
GASKILL, J. R., JR.		Multimode radar processor	
Multimode radar processor	170-20050	COLUBOACALL B D	A79-28058
GATZEN, B. S.	A79-28058	Prediction of gas-turbine alloy creep	
Prop-fan propulsion - Its status and potent		characteristics	
[SAE PAPER 780995] GEORGE-FALVY, D.	A79-25880	GOODRICK, T. F.	A79-26841
Summary report of the second wind tunnel to	est of	Simulation studies of the flight dynamics	of
the Boeing LFC model [NASA-CR-157792]	N79-17799	gliding parachute systems	170_26620
GEORGE, H. P., JR.	u / J = / / J J	[AIAA 79-0417] Hardware options for gliding airdrop guida	A79-26628
Fuel tank sealant requirements for advance	high	systems	
performance alrcraft [AINA 79-0807]	A79-28288	[AIAA 79-0471] GORGASS, B.	A79-26671
GERASINENKO, V. P.		Rescue helicopters in primary and secondar	
Influence of bypass ratio change on fan aerodynamic characteristics		GREEN, M. W.	N79-19606
-	A79-27744	SIFT - Design and analysis of a fault-tole	rant

PERSONAL AUTHOR INDEX HOGG, G. M.

GREGORIOU, G.	HAWKIES, W. H.		
Vortex models on missile configurations [BMVG-PBWT-77-27] N79-1		the world airborne	79-27360
GROENEWEG, J. F.	HAWORTH, J. I.	J695 J	17-2/300
Effects of inflow distortion profiles on fan ton noise calculated using a 3-D theory		f aerodynamics in the design proc ${\tt F}$	cess 879-18933
[AIAA PAPER 79-0577] A79-2			
GROSE, D. L. The development of the DAST I remotely piloted	Full-scale 1nlet tre	engine tests of bulk absorber acc	oustic
research vehicle for flight testing an active	[AIAA PAP		79-26881
flutter suppression control system [NASA-CR-144881] N79-1	BEIDERICH, H.	3 -4	
[NASA-CR-144881] N79-1 GROUTAGE, P. D.		d strain analysis of industrial r r impellers using the framework m	
Strike Drone - A defense suppression concept usi	3	N	779-19391
unmanned cruise/loiter/attack vehicle [SAE PAPER 781017] A79-2	HEIDHANN, M. P Analysis of	 radiation patterns of interactic 	วท
GORSS, H. K.		erated by inlet rods in the JT15D	
Structural aluminum materials for the 1980's			179-26944
[AIAA 79-0755] A79-2 GULIARY, V. V.		o. tics Airlift System Study (CLASS)	
Behavior of elastic systems in separated flow	volume 1	-	
A79-2 GUTHAN, G. N.		158915] tics Airlift System Study (CLASS)	179-17822
Residual-stress formation during the thermal	volume 2	ties allier sistem seedi (chass)	,
hardening of components in gas-turbine engines A79-2	[NASA-CR-		779-17823
R 79-2	executive	tics Airlift System Study (CLASS) summary	•
H	[NASA-CR-	158959 j	779-17824
HADCOCK, R. H.	HENDERSON, R. Insteady st	E. ator response to upstream rotor was a second or se	rakes
SDM lecture - Introduction of new SDM technology	[AIAA PAP	ER 79-0579] A	79-26945
into production systems [AIAA 79-0719] A79-2	HENINGER, K. L	• quirements for the A-7E aircraft	
HAIR, L. M.	[AD-A0617		79-18974
Space shuttle afterbody aerodynamics/plume	HENSLER, T.		
simulation data summary [NASA-TP-1384] N79-1		terminal system frequency assignm	lent
HAJELA, P.		2	179-25323
Accuracy of an approximate static structural analysis technique based on stiffness matrix	HERTZBERG, A. Laser alrcr	aft	
eigenmodes		,	79-26597
[AIAA 79-0748] A79-2 HALVERSON, A. G.		ade vibration data acquisition de	esion
RNAV route design-terminal area design procedure	and feasi	bility testing	
and transition area design guidelines [PAA-RD-78-61] N79-1	[NASA-CR- B41 HESS, R. F.	159505] N	179−1897€
HANSEN, J. S.		of induced transients associated	with
Crashworthiness tests on model aircraft fuselage		produced by lightning or other	
structures [AIAA 79-0688] A79-2		y slow rise-time EMP A	79-25322
HARDER, R. L.	HEWETT, C. R.		
Aeroelastic addition to NASTRAN [NASA-CR-3094] N79-1		m design for track-while-scan A	79-25139
HARDING, E.	HEYMSPIELD, A.	J.	
An unstable subsynchronous critical speed soluti [SAE PAPER 781055] A79-2		es of entrainment from wetting of temperature sensors in cloud	
HARNED, H. S.			179-25296
General aviation aircraft in the 1990's [AIAA PAPER 79-0560] A79-2	HICKS, J. B.	analysis of crash injury in army	•
HARP, J. L., JR.	aircraft	analysis of class injuty in army	
An alternating direction explicit method for	DICCING N D	N	179-19655
computing three-dimensional viscous flow field in turbomachines	HIGGINS, H. W. Recovery sy:	stem preliminary design - A simpl	lified
[SAE PAPER 781001] A79-2	384 approach	to determining drogue chute stagi	
HARPER, H. P. Advancements in helicopter cockpit technology	falaa 79-	nd altitude requirements 04461 — A	79-26650
์ ที่วี9-1	25 Factors and	tradeoffs affecting ram-air para	chutes
HARRIS, W. L. An investigation of model helicopter rotor blade	designed : [AIAA 79-	for civilian personnel applicatio	ons 179-26660
slap at low tip speeds	HINELY, J. T.,		.,, 20000
[AIAA PAPER 79-0613] A79-2 HARTSOOK, L. B.		stem design requirements for larg	
Validation of MIL-F-9490D: General specificatio	agricultu	ed-wing aerial application system re	is IOI
for flight control system for piloted military	[NASA-CR-	158939] N	179-17848
aircraft. Volume 1: Summary of YF-17 and C-5 validations	HIRAI, H. An offshore	airport that works - Nagasaki	
[AD-A061807] N79-1	008		79-28185
Validation of MIL-F-9490D: General specification for flight control system for piloted military	HO, P. Y.	noise prediction update	
aircraft. Volume 2: YF-17 lightweight fighte	[AIAA PAP:		79-26942
validation [AD-A062008] N79-1	HOGAN, D.	control valve for fly-by-wire f	-11ah+
HARZ BECKER, E.		ystem actuators	LIGHT
Aviation obstructions and the particular	[AD-A0620]		79-19007
conditions for construction projects in the vicinity of airports	HOGG, G. H. Environment:	al factors affecting the installa	tion .
179-2	372 and opera	tion of gas turbine engines in	
	agricultu: [SAE PAPE:	ral aircraft R 7810101 A	79-25892
	,	•	

HOGSTEDT, C. R.		IOANNOU, H.	
An airborne reference noise source for st		Crashworthiness tests on model aircraft fu	ıselage
airplane flyover noise propagation and in [AIAA PAPER 79-0650]	A79-26928	structures [AIAA 79-0688]	A79-27354
HOLMES, R. E.		•	
A three-channel high-resolution-TV image generation system		J	
	A79-28160	JACOBS, P. A.	
HOMYAK, L. Heasured and predicted noise of the AVCO-	Lycoming	Environmental effects on crack growth in flight-simulation tests on 2024-T3 and 7	075-T6
YP-102 turbofan engine		naterial	
[AIAA PAPER 79-0641] Full-scale engine tests of bulk absorber a	A79-26877 acoustic	[NLR-TR-76104-U] JACOBSEN, R. A.	N79-18012
inlet treatment		Evaluation of a wake vortex upset model ba	
[AIAA PAPER 79-0600] Evaluation of two inflow control devices:	A79-26881 for	simultaneous measurements of wake velocuprobe-aircraft accelerations	ties and
flight simulation of fan noise using a		[NASA-TH-78561]	N79-18960
engine [AIAA PAPER 79-0654]	A79-26926	JANTZEN, E. Separation and investigation of wear parti	cles
HONE, H. T.		from aero-engines	n70 47056
UH-60A MEDEVAC kit	N79-19614	[BLL-RISLEY-TR-3308-(9091.9F)] JAPIKSE, D.	N79-17856
HOOTS, L. C.		Alternative turbine cooling technology	¥70 4000#
Lightning protection with segmented diver-	A79-25317	Turbocharger design and development	N79-18984
HOROWITZ, B. H.	•		N79-19393
Advanced en route air traffic control auto	A79-27129	JEHL, J. Application of aerodynamic design technique	ies to
HOVIS, J. B.		process compressor design	
Reliability growth planning to achieve RIV requirements for an airborne radar	/GMTBP	JENKINS, J. H.	N79-19388
	A79-24965	Elevated-temperature effects on strain gag	jes on
HOWE, D. The application of computer aided technique.	ies to	the TF-12A wing	A79-26400
project design		JERNELL, L. S.	
HOWELL, G. P.	A79-26592	Effects of laminar flow control on the per of a large span-distributed-load flying-	
The sound power spectrum of shock-free jet		cargo airplane concept	*
[AIAA PAPER 79-0595] HUBBARD, J. B., JR.	A79-26918	[NASA-TM-78715] JOHNSTON, A. H.	N79-17851
An investigation of model helicopter rotor	blade	The continuity factor in aircraft developm	
slap at low tip speeds [AIAA PAPER 79-0613]	A79-26938	The continuity factor in aircraft developm	A79-26536 ent
HUCK, K. L.			N79-18896
Lean combustion limits of a confined premixed-prevaporized propane jet		JONES, D. J. Development of modern airfoil sections for	high
[AIAA PAPER 79-0538]	A79-25856	subsonic cruise speeds	-
HUDSON, S. M. Planning the development and qualification	process	[AIAA 79-0687] JONES, E. N.	A79-27353
for the next generation of high technological		Recording methods for steady state and tra	nsient
aircraft engines [SAE PAPER 780992]	A79+25878	signals	A79-25849
V/STOL aircraft engine and mechanical driv		JONES, W. L.	
component integration [SAE PAPER 781038]	A79-25906	Evaluation of two inflow control devices f flight simulation of fan noise using a J	
HUNGENBERG, H. G.		engine	
Comparison between flows in cascades and the transonic range. 3: Comparison of	cotors in	[AIAA PAPER 79-0654] JONES, W. S.	A79-2692€
experimental and theoretical results of		Laser aircraft	. 70 06 507
studies on blade-to-blade surfaces in an compressor rotor	axiai	JONES, Y. P.	A79-26597
TWY MON D 3	N79-19002	US Army aviation fatigue-related accidents	, 1971 -
HYLTON, R. J. Validation of MIL-F-9490D: General specif	ication	1977	N79-19621
for flight control system for piloted mi	llitary	JORDAN, V.	
aircraft. Volume 1: Summary of YF-17 avalidations	ING C-SA	Environmental models for moisture absorpti aircraft composites	on by
[AD-A061807]	N79-19008	·	A79-27572
•		JOSHI, M. C. On sound radiation from the trailing edge	of an
		isolated airfoil in a uniform flow	
IAKSHIN, A. A. Convective heat exchange of gas-particle s	tream in	[AIAA PAPER 79-0603] An experimental study of USB flap noise re	A79-26907
flow passage of throttling device with v		through mean flow modification	
turning element	A79-27742	[AIAA PAPER 79-0607] JOSHI, M. N.	A79-26908
IARIM, L. P.		Design specifications for the capped ballo	
Aerodynamics of flame jets	A79-26355	special reference to their survival in t equatorial tropopause	пе
ICENBICE, P. J., JR.	, and	[AIAA 79-0426]	A79-26635
How to add satellite navigational accuracy stability to existing offshore NAV System		JUNGCLAUS, G. Alrbreathing engines - aerodynamic aspects	
	A79-27388		N79-18925
IDIATULLIN, N. S. Convective heat exchange of gas-particle s		JUNOD, L. A. Integrally cast turbine rotor for high vol	ume
flow passage of throttling device with w		production	
turning element		[SAE PAPER 781000]	A79-25883

	-
	•
1	`

PERSONAL AUTHOR INDEX

KALELKAR, A. S.	
An assessment of the risks presented by the carbon fiber composites in commercial av	e use of
Volume 1: Final report. Volume 2: Sup	lation.
appendices	porcing
[NASA-CR-158989]	N79-18074
KALLANDER, J. W.	
Software requirements for the A-7E aircraft [AD-A061751]	ท79-18974
KAWISS, A. H.	
Statistical review of counting acceleromet	er data
for Navy and Marine fleet aircraft [AD-A061894]	N79-18972
KARTOLA, R. A.	_
Reduction of rotor-turbulence interaction is static fan noise testing	noise in
Static fan noise testing [AIAA PAPER 79-0656]	A79-26925
KAPP, E. J.	R/7 20323
Multimode radar processor	
KARGER, I.	A79-28058
Rescue helicopters in primary and secondary	missions
	N79-19606
KARNEY, D. H. Helicopter crashworthy fuel systems and the	215
effectiveness in preventing thermal injur	T Y
	N79-19660
KAROVIC, S. Survey of radar simulation training at ATC	field
facilities	22024
[FAA-NA-78-27]	N79-17877
KASHORK, E. P. Avlation wide angle visual system /AWAVS/	. Vienal
system performance	V15441
	A79-28161
KAWAHURA, R. Laminar boundary layer with foreign gas in	iection
on a conical body	
77DTD +	A79-27203
KEEFE, 1. Interior noise path identification in light	•
aircraft using multivariate spectral anal	L y sış
[AIAA PAPER 79-0644]	A79-26915
KERLEY, D. T. Corporate aviation in the 1980's	
-	N79-18892
KELLY, W. L., IV LED instrument approach instruction display	
[NASA-TM-78823]	N79-17854
KEMP, N. H.	
Laser propulsion	A79-26598
KENISON, R. C.	A73 20336
Considerations for the design of inlet flow conditioners for static fan noise testing	,
[AIAA PAPER 79-0657]	3 A79-26909
KENNEDY, D. A.	R/3 20303
Pormation of a trailing vortex	
KERELIUK, S.	A79-28377
Evaluation of IFR handling qualities of	
helicopters using the NAE airborne V/STO	=
helicopters using the NAR airborne V/STO Simulator	
helicopters using the NAE airborne V/STO	A79-27365
helicopters using the NAR airborne V/STO simulator [AIAA 79-0702] KERSHISNIK, H. An unstable subsynchronous critical speed:	A79-27365
helicopters using the NAE airborne V/STOI simulator (AIAA 79-0702) KEBSHISHIK, H. An unstable subsynchronous critical speed : (SAE PAPER 781055)	A79-27365
helicopters using the NAE airborne V/STOI Simulator [AIAA 79-0702] KERSHISHIK, M. An unstable subsynchronous critical speed : [SAE PAPER 781055] KEYS, C. H. Rotary-wing aerodynamics. Volume 2: Perfo	A79-27365 solution A79-25916
helicopters using the NAE airborne V/STOI Simulator (AIAA 79-0702) KERSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. H. Botary-wing aerodynamics. Volume 2: Perfo prediction of helicopters	A79-27365 solution A79-25916 ormance
helicopters using the NAE airborne V/STOI simulator [AIAA 79-0702] KERSHISNIK, M. An unstable subsynchronous critical speed: [SAE PAPER 781055] KEYS, C. N. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters [NASA-CR-3083]	A79-27365 solution A79-25916
helicopters using the NAE airborne V/STOI Simulator (AIAA 79-0702) KERSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. H. Botary-wing aerodynamics. Volume 2: Perfo prediction of helicopters	A79-27365 solution A79-25916 ormance N79-17811 2-D radars
helicopters using the NAE airborne V/STOI SIMUlator (AIAA 79-0702] KERSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. W. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters (NASA-CR-3003) KHOURY, B. W. Estimation of target elevation angle from 2	A79-27365 solution A79-25916 ormance N79-17811
helicopters using the NAE airborne V/STOI SIMUlator (AIAA 79-0702) KEBSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KETS, C. H. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters [NASA-CR-3083] KHOURY, E. H. Estimation of target elevation angle from 2 KIBENS, V. Discrete noise spectrum generated by an	A79-27365 solution A79-25916 ormance N79-17811 2-D radars
helicopters using the NAE airborne V/STOI SIMUlator (AIAA 79-0702) KEBSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KETS, C. H. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters [NASA-CR-3083] KHOURY, E. H. Estimation of target elevation angle from 2 KIBENS, V. Discrete noise spectrum generated by an	A79-27365 solution A79-25916 ormance N79-17811 2-D radars A79-27145
helicopters using the NAE airborne V/STOI simulator [AIAA 79-0702] KERSHISNIK, M. An unstable subsynchronous critical speed: [SAE PAPER 781055] KEYS, C. N. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters [NASA-CR-3083] KHOURY, B. N. Estimation of target elevation angle from 1 KIBENS, V. Discrete noise spectrum generated by an acoustically excited jet [AIAA PAPER 79-0592]	A79-27365 solution A79-25916 ormance N79-17811 2-D radars
helicopters using the NAE airborne V/STOI SINULATOR (AIAA 79-0702) KERSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. H. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters (NASA-CR-3083) KHOURY, E. H. Estimation of target elevation angle from 2 KIBENS, V. Discrete noise spectrum generated by an acoustically excited jet (AIAA PAPER 79-0592) KIRKBY, W. T.	A79-27365 solution A79-25916 ormance N79-17811 2-D radars A79-27145
helicopters using the NAE airborne V/STOI simulator (AIAA 79-0702] KERSHISNIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. N. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters (NASA-CR-3083) KHOURY, B. N. Estimation of target elevation angle from 2 KIBEMS, V. Discrete noise spectrum generated by an acoustically excited jet (AIAA PAPER 79-0592) KIRKBY, W. T. Design against fatigue - Current trends (AIAA 79-0689)	A79-27365 solution A79-25916 ormance N79-17811 2-D radars A79-27145
helicopters using the NAE airborne V/STOI Simulator (AIAA 79-0702) KERSHISHIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. H. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters (NASA-CR-3083) KHOURY, E. H. Estimation of target elevation angle from 2 KIBENS, V. Discrete noise spectrum generated by an acoustically excited jet (AIAA PAPER 79-0592) KIRKBY, H. T. Design against fatigue - Current trends (AIAA 79-0689) KISH, J. G.	A79-27365 solution A79-25916 ormance N79-17811 2-D radars A79-27145
helicopters using the NAE airborne V/STOI simulator (AIAA 79-0702] KERSHISNIK, M. An unstable subsynchronous critical speed: (SAE PAPER 781055) KEYS, C. N. Rotary-wing aerodynamics. Volume 2: Performediction of helicopters (NASA-CR-3083) KHOURY, B. N. Estimation of target elevation angle from 2 KIBEMS, V. Discrete noise spectrum generated by an acoustically excited jet (AIAA PAPER 79-0592) KIRKBY, W. T. Design against fatigue - Current trends (AIAA 79-0689)	A79-27365 solution A79-25916 ormance N79-17811 2-D radars A79-27145

KLINEBERG, J. M.	
Technology for future air transports [AIAA PAPER 79-0529]	A79-25853
KLOCHROVA, V. G. Elimination of scale and luminance distort: thermal imaging systems with a large fie.	
KLOPPSTEIN, A.	A79-27416
Tests of an integrated piloting, navigation display system	
KWAPP, S. C. Helicopter crashworthy fuel systems and the	A79-27675
effectiveness in preventing thermal injur	
KNOX, C. B. Algorithms and logic for incorporating MLS azimuth information into the NASA TCV B-	
airplane area navigation system [NASA-TM-80039]	N79-17843
NO. W. L. Modeling the X-band radar augmentation syst	tem of a
high altitude supersonic target KOBAYSHI, H.	A79-24715
Effects of inflow distortion profiles on fa noise calculated using a 3-D theory	an tone
[AIAA PAPER 79-0577] KOCH, P.	A79-26911
An improved supersonic, three-dimensional, external, inviscid flow field code	
[NASA-CR-3108]	N79-17807
Wind-tunnel investigation of the thrust aug	
performance of a large-scale swept wing s [NASA-TM-X-73239]	nodel N79-1780
KOPSKEY, M. G. Cold-air performance of free power turbine	
designed for 112-kilowatt automotive gasengine. 2: Effects of variable	turbine-
stator-wane-chord setting angle on turbing	ıe
performance [NASA-TM-78993]	N79-17859
KOKIN, A. S. Intensification of fuel vaporization in all	craft
gas turbine engines by electrical forces	A79-27748
KOKOSZKA, E., JR.	R/3-2//40
Strain gage system evaluation program [NASA-CR-159486]	N70 1034#
	N79-19314
KOLB, E. F. Siting criteria for MLS stations. II	A79-28184
KOLB, E. F. Siting Criteria for MLS stations. II KOSTINA, G. N.	A79-28184
NOLB, E. P. Siting criteria for MLS stations. II ROSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine en	A79-28184
NOLB, E. F. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the therma	A79-28184 al agines
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan	A79-28184 al agines A79-26828
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the therminardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics	A79-28184 al agines A79-26828
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan	A79-28184 al agines A79-26828 A79-25350
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine end KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine	A79-28184 al agines A79-26828 A79-25350
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAFPT, J. H. Failure studies of a third stage fan disk in	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine ex KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. H. Failure studies of a third stage fan disk of the property of	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the therms hardening of components in gas-turbine ex KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAFPT, J. M. Failure studies of a third stage fan disk in TF-30 turbine engine	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830 from a
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. H. Failure studies of a third stage fan disk in TF-30 turbine engine [AD-A061801] KRASILSHCHIKOVA, B. A.	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830 From a N79-19004 A79-25872 Lons in
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. W. Residual-stress formation during the thermal hardening of components in gas-turbine enders. KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. M. Failure studies of a third stage fan disk in TP-30 turbine engine [AD-A061801] KRASILSHCHIKOVA, B. A. Slender wing in compressible flow KRASBIKOV, D. W. Elimination of scale and luminance distort: thermal imaging systems with a large field KRAVCHENKO, B. A.	A79-28184 all agines A79-26828 A79-25350 A79-2774 A79-26830 from a N79-19004 A79-25872 Lons in ld of view A79-27416
KOLB, E. P. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the therma hardening of components in gas-turbine ex KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. N. Failure studies of a third stage fan disk in TF-30 turbine engine [AD-A061801] KRASILSHCHIKOVA, B. A. Slender wing in compressible flow KRASHIKOV, D. N. Elimination of scale and luminance distort: thermal imaging systems with a large field KRAVCHENKO, B. A. Residual-stress formation during the thermal hardening of components in gas-turbine en	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830 From a N79-19004 A79-25872 Lons in ld of view A79-27416
KOLB, E. F. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the therma hardening of components in gas-turbine en KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. M. Failure studies of a third stage fan disk in TP-30 turbine engine [AD-A061801] KRASILSHCHIKOVA, B. A. Slender wing in compressible flow KRASHIKOV, D. H. Elimination of scale and luminance distort: thermal imaging systems with a large field KRAVCHENKO, B. A. Residual-stress formation during the thermal hardening of components in gas-turbine en KREBS, C. J. Total environment survivability methodology [AD-A061888]	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830 From a N79-19004 A79-25872 Lons in ld of view A79-27416 all agines A79-26828
KOLB, E. F. Siting criteria for MLS stations. II KOSTINA, G. N. Residual-stress formation during the thermal hardening of components in gas-turbine enders. KOURTIDES, D. A. Thermal response of composite panels KOVAL, V. A. Influence of bypass ratio change on fan aerodynamic characteristics KOVALEV, A. A. Operational experience with linked-blade high-output gas-turbine KRAPPT, J. H. Failure studies of a third stage fan disk in TF-30 turbine engine [AD-A061801] KRASILSHCHIKOVA, B. A. Slender wing in compressible flow KRASHIKOV, D. H. Elimination of scale and luminance distort: thermal imaging systems with a large field KRAVCHENKO, B. A. Residual-stress formation during the thermal hardening of components in gas-turbine enderses, C. J. Total environment survivability methodology	A79-28184 all agines A79-26828 A79-25350 A79-27744 A79-26830 From a N79-19004 A79-25872 Lons in ld of view A79-27416 all agines A79-26828

KRESS, R. W.		Diffusers for gas turbine combustion system	18
Use of radio controlled models in the cond	eptual	bilidaela lot das talbine compastion siste	N79-19369
development of V/STOL allcraft	170 25045	Ignition in the gas turbine	n70 10272
[SAE PAPER 781050] KRINGS, J. B.	A79-25915	Control of air pollution from aircraft and	N79-19372
F-18 status report		arcraft engines	
P-18 status report	A79-26529	TPDDUDD C	N79~19376
F-18 status report	N79-18888	LEFEVER, G. The future of surveillance systems in civil	l aviation
KRUEGER, G. P.			A79-24800
US Army aviation fatigue-related accidents 1977	s , 1971 -	LEGREID, S. I. Reliability growth on B-52 FLIR system	
1377	N79-19621	nerrability growen on base rain system	A79-24958
KUBBAT, W.	• •	LENSKI, J. W., JR.	
Recent developments in active control tech [AIAA 79-0708]	MO109 y A79-27368	Structural stiffening of transmission hous with metal matrix materials	ıngs
KUGLER, G.		[AIAA 79-0806]	A79-28287
Rescue helicopters in primary and secondar	y missions N79-19606	LEUTHAUSER, D. A. Development of smart target for simulation	o. f
KUMIROV, B. A.	1175-15000	one-on-one air-to-air combat	OI.
Theoretical-experimental analysis of influ		[AD-A056739]	N79-17879
coolant discharge from perforated turbin on their aerodynamic characteristics	e vanes	LEVITT, E. R. Integrated Thermal Avionics Design (ITAD)	
-	A79-27727	[AD-A061227]	N79-17855
KUNHIKRISHNAN, K. V.		LEVITT, K. N.	
A decision theory model for health monitor aeroengines	ing or	SIFT - Design and analysis of a fault-tole computer for aircraft control	ant
	A79-28381	-	A79-25718
KUZNETSOV, N. D. Thermal cycling endurance problems in gas-	turbina	LEWY, S. Direct experimental verification of the	
parts parts	CULDING	theoretical model predicting rotor noise	
	A79-26838	generation	170 2000
1		[AIAA PAPER 79-0658] LIBBELT, G. A.	A79-26894
L		Concept of modular software for the stepwi:	
LAKSHMINARAYANA, B. Turbulence characteristics in the near wak	e of a	construction of radar data processing sys	
compressor rotor blade	e or u	example the Airtrack System	13
[AIAA PAPER 79-0280] LAMBOURION, J.	A79-26544	TTRCC T	A79-26759
Direct experimental verification of the		LIBSS, J. Statistics of disturbances and maintenance	
theoretical model predicting rotor noise	!	according to conditions at Interflug. II:	
generation [AIAA PAPER 79-0658]	A79-26894	Technical requirements concerning the pro- for the processing of disturbance data by	
LAMEKIN, N. S.		of electronic data processing	
Influence of bypass ratio on jet engine we	ight 179-27737	LINDBERG, A. W.	A79-25371
LAMPORT, L.		A survey of communications in the high nois	se .
SIFT - Design and analysis of a fault-tole	rant	environment of Army aircraft	W70 10606
computer for aircraft control	A79-25718	LIU, C. Y.	N79-19646
LAN, C. B.		An alternating direction explicit method for	
Analysis of some aerodynamic characteristi to wing-jet interaction	cs due	computing three-dimensional viscous flow in turbomachines	ileias
[NASA-CR-158349]	N79-18917	[SAE PAPER 781001]	A79-25884
LANDER, H. R. Shale oil - The answer to the jet fuel		LIU, W. H. Design, calibration, and application of a s	ensor
availability question		for measuring time dependent angle of at	
[SAE PAPER 781027]	A79-25900	helicopter blades	
LANSING, D. L.		nerroopeer breach	N70-10069
Applications of diffraction theory to aero		•	N79-18968
Applications of diffraction theory to aero [NASA-TM-80053]		LOC, T. P. Numerical study of unsteady flows of viscou	ıs
[NASA-TM-80053] LAUGHLIN, J. W.	acoustics N79-18686	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a	ıs
[NA SA-TM-80053]	acoustics N79-18686 ures	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/	ıs
[NASA-TH-80053] LAUGHLIN, J. W. Aircraft fire protection and rescue proced /2nd edition/	acoustics N79-18686	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I.	ıs
[NASA-TH-80053] LAUGHLIW, J. W. Alreraft fire protection and rescue proced	acoustics N79-18686 ures A79-25750	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/	as A79-24829
[NASA-TH-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664]	acoustics N79-18686 ures A79-25750	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order 0/h2/ and 0/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach:	as A79-24829
[NASA-TM-80053] LAUGHLIN, J. W. Aircraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne	acoustics N79-18686 ures A79-25750 sium fires N79-19122	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order 0/h2/ and 0/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y.	as A79-24829 .ne discs
[NASA-TH-80053] LAUGHLIN, J. W. Alroraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E.	acoustics N79-18686 ures A79-25750 sium fires N79-19122	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227]	as A79-24829 .ne discs
[NASA-TH-80053] LAUGHLIN, J. W. Alroraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYHAN, G. E. SEATRACKS - A millimeter wave radar fire c system	acoustics N79-18686 ures A79-25750 sium fires N79-19122	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J.	A79-24829 ne discs A79-27746 N79-17855
[NASA-TM-80053] LAUGHLIN, J. W. Aircraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto	acoustics N79-18686 Ures A79-25750 Sium fires N79-19122 Ontrol	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878]	A79-24829 ne discs A79-27746 N79-17855
[NASA-TH-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYHAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A.	A79-24829 .ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TM-80053] LAUGHLIN, J. W. Alreraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [AIAA PAPER 79-0612] LEE, K.	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted wehicle with and without	A79-24829 ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TM-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [ATAA PAPER 79-0612] LEE, K. Induced effects of lightning on an all com	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control	A79-24829 ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TM-80053] LAUGHLIN, J. W. Alreraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [AIAA PAPER 79-0612] LEE, K.	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006]	A79-24829 ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TH-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYHAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [ATAA PAPER 79-0612] LEE, K. Induced effects of lightning on an all com aircraft LEE, K. B.	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144 r A79-26939	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control	A79-24829 ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TM-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An accustical study of the XV-15 Tilt Roto Research Aircraft [ATAA PAPER 79-0612] LEE, K. Induced effects of lightning on an all com aircraft	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144 r A79-26939 posite N79-18242	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] LOVESEY, E. J. Some aspects of helicopter communications	A79-24829 ne discs A79-27746 N79-17855 the F-15 N79-18286
[NASA-TH-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYHAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [ATAA PAPER 79-0612] LEE, K. Induced effects of lightning on an all com aircraft LEE, K. B. EMP coupling to a composite aircraft LEFEBYRE, A. H.	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144 r A79-26939 posite N79-18242 A79-25321	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] LOVESEY, E. J.	A79-24829 The discs A79-27746 N79-17855 The F-15 N79-18286 N79-17852
[NASA-TM-80053] LAUGHLIN, J. W. Alrcraft fire protection and rescue proced /2nd edition/ LAWRENCE, K. D. New agents for the extinguishment of magne [AD-A061664] LAYMAN, G. E. SEATRACKS - A millimeter wave radar fire c system LEE, A. An acoustical study of the XV-15 Tilt Roto Research Aircraft [ATAA PAPER 79-0612] LEE, K. Induced effects of lightning on an all com aircraft LEE, K. H. EMP coupling to a composite aircraft	acoustics N79-18686 ures A79-25750 sium fires N79-19122 ontrol A79-27144 r A79-26939 posite N79-18242 A79-25321	LOC, T. P. Numerical study of unsteady flows of viscous incompressible fluids about airfoils by a combined method of order O/h2/ and O/h4/ LOKAI, V. I. Method for digital computer calculation of unsteady temperature fields in turbomach: LORD, Y. Integrated Thermal Avionics Design (ITAD) [AD-A061227] LORINCZ, D. J. A water tunnel flow visualization study of [NASA-CR-144878] LOVELL, W. A. Evaluation of a long-endurance-surveillance remotely-piloted vehicle with and without laminar flow control [NASA-CR-159006] LOVESEY, E. J. Some aspects of helicopter communications LOWDER, B. M.	A79-24829 The discs A79-27746 N79-17855 The F-15 N79-18286 N79-17852 N79-19647 Tying

N79-19368

PERSONAL AUTHOR INDEX HELZIG, H. D.

LOWBIL, C. B. Effect of a chromium-containing fuel addit	146 OD	MAIWELL, B. D. J. Design against fatigue - Current trends	.70 07355
hot corrosion	A79-26546	[AIAA 79-0689] MATER, H. S.	≱79-2735 5
LOWSON, M. V.		A survey of communications in the high nor	ıse
Puture advanced technology rotorcraft [AIAA 79-0705]	A79-27366	environment of Army aircraft	N79-19646
LODWIG, L. P.	A.7 27300	MAYS, J. A.	
Composite seal for turbomachinery	-70 40340	A three-channel high-resolution-TV image	
[HASA-CASE-LEW-12131-1] LUSCHNITZ, W.	ท79-18318	generation system	A79-28160
New approaches concerning the implementati		HAZOR, H. J.	
radar target extractors with the aid of fast microprogrammable data processors	very	Strain gage system evaluation program [NASA-CR-159486]	พ79-19314
last microprogrammable data processors	A79-26754	HCADORY, R. W.	875 15514
LUTHANDER, S.		Air Force applications for optical rotation	on rate
A simulator study of aircraft ground-run h in the Posim Research Simulator ~ Some r		sensors	A79-28122
and experiences		MCARDLE, J. G.	
LYBAN, E. G.	A79-26498	Measured and predicted noise of the AVCO-I YF-102 turbofan engine	Lycoming
Cockpit displays and the growing role of t	he pilot	[AIAA PAPER 79-0641]	A79-26877
in the ATC system	.70 00075	Evaluation of two inflow control devices in	
	A79-26875	flight simulation of fan noise using a dengine	עכוינ
M		[AIAA PAPER 79-0654]	A79-26926
MARRY, D. G.		Analysis of radiation patterns of interact tones generated by inlet rods in the J ^{m1}	
Boundary layer transition measurements on	the AEDC	[AIAA PAPER 79-0581]	A79-26944
10 deg cone in three RAE wind tunnels an	d their	MCCARTHY, J.	longo and
implications [ARC-R/M-3821]	N79-17817	A spectral analysis of thunderstorm turbul jet transport landing performance	rence and
MABRY, J. E.			A79-27576
A commercial airport noise environment: Measurement, prediction and control		RCCONKEY, B. D. RNAV route design-terminal area design pro	cedures
[NASA-CR-3107]	N79-19814	and transition area design guidelines	
MACEY, P. C.	c \	[PAA-RD-78-61] MCCORNICK, W. S.	ท79-17841
Cargo/Logistics Airlift System Study (CLAS volume 1	3),	The analysis and identification of flux-in	nduced
[NASA-CR-158915]	N79-17822	voltage transients on low-loss transmiss	10n
Cargo/Logistics Airlift System Study (CLAS volume 2	5),	lines with application to the Lightning-Transient-Analysis /LTA/ probl	lem
[NASA-CR-158916]	N79-17823		A79-26246
Cargo/Logistics Airlift System Study (CLAS executive summary	S) ,	MCDERMOTT, J. M. The approach to crew protection in the cra	sh
[NASA-CR-158959]	N79-17824	environment for the YAH-64	
MACK, J. C.	drimo	MCDOMBELL, B. J.	N79-19664
Advanced technology applied to the CH-47D system	di i ve	The application of a design verification s	system
[SAE PAPER 781040]	A79-25908	and accelerated mission testing to gas t	urbine
MACK, R. J. Some effects of applying sonic boom minimi	zation	engine development [SAE PAPER 780991]	A79-25877
to supersonic cruise aircraft design		MCINTIRE, W. L.	
[AIAA PAPER 79-0652] MAGEE, J. P.	A79-26927	Planning the development and qualification for the next generation of high technology	
XV-15 Tilt Rotor Research Aircraft - Progr		aircraft engines	•-
(AIAA 79-0704) HAJJIGI, R. K.	A79-27371	[SAE PAPER 780992] RCINTOSH, A. C.	A79-25878
Wave propagation in ducts using the finite	element	The 1-4-1 system of jack movements for the	•
method	.70 26270	flexible liners of supersonic wind tunne	els #79-26594
[AIAA PAPER 79-0659] MALARHEY, C.	A79-26879	ECLALLIN, K. L.	#19-20394
Direct experimental verification of the		Cold-air performance of free power turbine	
theoretical model predicting rotor noise generation	1	designed for 112-kilowatt automotive gas engine. 2: Effects of variable	s-turbine
[AIAA PAPER 79-0658]	A79-26894	stator-vane-chord setting angle on turb	ıne
MARCONI, P.		performance	N79-17859
An improved supersonic, three-dimensional, external, inviscid flow field code		[NASA-TH-78993] MCWHA, J.	1179-17033
[NASA-CR-3108]	N79-17807	The coming of age of digital electronics i	Ln
Mariszkikuicz, J. Dynamics of controlled longitudinal motion	of an	commercial transports [AIAA 79-0686]	A79-27352
airplane with a variable-geometry wing	01 411	HEAD, B. D.	
ilecton h p	A79-25517	Requirements and constraints in the develor and qualification of gas turbine engines	
MASSIER, P. P. Twin jet shielding		Navy	. TOL CHE
[AIAA PAPEB 79-0671]	A79-26924	[SAE PAPER 780994]	A79-25879
Separation of core noise and jet noise [AIAA PAPER 79-0589]	A79-26941	MEHAPPIE, S. R. Poam Impact Attenuation System	
MATSUNO, K.		[AIAA 79-0416]	A79-26627
Laminar boundary layer with foreign gas in	ject10n	MELLIAR-SHITH, P. H.	rant
on a conical body	A79-27203	SIPT - Design and analysis of a fault-tole computer for aircraft control	:Lanc
MAXWELL, K. J.	_4_		A79-25718
Recent advances in indirect lightning efferesearch	CTS	BELZIG, H. D. Bailout from autorotating helicopters	

N79-19666

MEREDITH, B. D.		HOSTOVOY, S.	
LED instrument approach instruction displ		Fracture mechanics for structural adhesive	bonds,
[NASA-TM-78823]	N79-17854	part 2, phase 2	770 40540
HESSENS, W.		[AD-A061805]	N79-19418
Casualty evacuation by helicopter	N79-19615	MURHLEISEN, R. Electric charging of helicopters	
messler, R. W., Jr.	117 17013	[BHVG-PBWT-78-7]	N79-18274
Design and fabrication of advanced titani	u m	MURHIN, A. A.	
structures		Operational experience with linked-blade	
[AIAA 79-0757]	A79-28272	high-output gas-turbine	
MEYER, G.	ntrol of	MULTUR 1 10	A79-26830
Configuration management and automatic co an augmentor wing aircraft with vectore		MULLEN, J., JR. Combined strength and aeroelastic wing syn	thesis
[NASA-TP-1222]	N79-17872	via constraint approximation	
HILLER, C. A.		[AIAA 79-0724]	A79-28290
Operational evaluation of an Air Traffic	Control	MUROTA, N.	
Radar Beacon System open array antenna	.70 07430	Inside noise of C-1 cargo aircraft and the	
MIRANDE, J.	A79-27139	reduction performance by interior materi	A79-27121
Vortex pattern development on the upper s	urface of	MYERS, B. B.	H/3-2/121
a swept wing at high angle of attack		Findings of the Ottawa-Montreal STOL demon	stration
[NASA-TH-75377]	N79-18914	service	
HISHIN, V. P.	_	[AIAA 79-0710]	A79-27369
Introduction to the computer-aided design	of		
flight vehicles	A79-27648	N	
HITTRA, R.	R73-27040	BADIROV, H. A.	
Modeling the X-band radar augmentation sy	stem of a	Convective heat exchange of gas-particle s	tream in
high altitude supersonic target		flow passage of throttling device with v	ane-type
	A79-24715	turning element	
MIXSON, J. S.	armen of t	## PCDT B C #	A79-27742
Characteristics of propeller noise on an fuselage related to interior noise tran		WARGELE, G. M. Adaptation of a digital airborne radar for	use on
[AIAA PAPER 79-0646]	A79-26932	the microphysics research aircraft	
HOAVENI, M. K.			A79-25681
Near-field analysis of helicopter rotatin	g blades	NAEGELI, D. W.	
modulation interference	170 25121	Effects of fuel properties on soot formati	on in
MORSERI, H.	A79-25131	turbine combustion [SAE PAPER 781026]	A79-25899
Near-field analysis of helicopter rotatin	q blades	NAGEL, D. C.	R77 25055
modulation interference	,	The annoyance of multiple noisy events	
	A79-25131	[AIAA PAPER 79-0653]	A79-26895
HONTOYA, L. C.		NELSON, P. B.	
An improved system for use in conducting	wake	Technology and the new look meet the F/A-1	8 radar
investigation for a wing in flight [MASA-CASE-FRC-11024-1]	N79-17797	reliability challenge [SAE PAPER 781024]	A79-25897
HOOIJ, H. A.	4.5 1.757	MERI, L. H.	n., 230).
The need of stick force stability for		Full-scale fire modeling tests of a compac	t rapid
attitude-stabilized aircraft, Part 2		response foam and dry chemical powder di	spensing
[NLR-TR-77027-H]	ห79-17875	system	w20 4200F
MOOR, D. A. Development of the L-1011 Flight Manageme	nt System	[FAR-NA-78-24] BIROLITSCH, D.	N79-17825
pero-op-one of the five fixing hundyone	A79-26535	Vortex models on missile configurations	
Development of the L-1011 flight manageme		[BMVG-FBWT-77-27]	N79-17814
	ห79-18895	HORMAN, J. M.	
HOORE, R. L.		Cargo/Logistics Airlift System Study (CLAS	s) ,
Aeroservoelastic stability analysis of an with a control augmentation system	girbiane	volume 1	N79-17822
with a concion addmentation placem	N79-19006	[NASA-CR-158915] Cargo/Logistics Airlift System Study (CLAS	
MOREL, T.		volume 2	-,,
Theoretical lower limits of forebody drag		[NASA-CR-158916]	พ79-17823
	A79-26593	Cargo/Logistics Airlift System Study (CLAS	S),
MORFEY, C. L. The sound power spectrum of shock-free je	t e	executive summary [NASA-CR-158959]	N79-17824
[AIAA PAPER 79-0595]	A79-26918	HORSTER, E. R.	N /9-1/024
HORGAN, C. J.	11.3 203.0	Time degradation factors for the turbine e	nqine
Longitudinal oscillation damping for		exhaust emissions. Volume 1: Program	•
fully-inflated parachute canopies		description and results	
[AIAA 79-0459]	A79-26662	[NREC-1238-6-VOL-1]	N79-17860
HORISHIGE, R. I.		NORUM, T. D.	
MORISHIGE, R. I. Analysis of the functional requirements for		NORUM, T. D. Applications of diffraction theory to aero	acoustics
HORISHIGE, R. I.		NORUM, T. D.	
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR.	or an N79-18962	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit	acoustics N79-18686
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory vi	or an N79-18962 th	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal	acoustics N79-18686
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory viewperimental noise data for a small-sca	or an N79-18962 th	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system (AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor	or an N79-18962 th	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal	acoustics N79-18686
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory viewperimental noise data for a small-sca	or an	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to	or an N79-18962 th le A79-26876 echnique	NORUM, T. D. Applications of diffraction theory to aero [NASA-TM-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale howering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971]	or an N79-18962 th le A79-26876	NORUH, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROH, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. E.	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scal hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A.	or an N79-18962 th le A79-26876 echnique N79-17801	NORUM, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. B. Air Force applications of lightweight	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A. Effects of fuel properties on soot format	or an N79-18962 th le A79-26876 echnique N79-17801	NORUH, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROH, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. E.	acoustics 1879-18686 h e 1879-26876
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A.	or an N79-18962 th le A79-26876 echnique N79-17801	NORUM, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. B. Air Porce applications of lightweight superconducting machinery	acoustics N79-18686 h e
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A. Effects of fuel properties on soot format turbine combustion [SAE PAPER 781026] MOSHER, H.	or an N79-18962 th le A79-26876 echnique N79-17801 lon in A79-25899	NORUM, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. B. Air Force applications of lightweight	acoustics N79-18686 h e A79-26876
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A. Effects of fuel properties on soot format turbine combustion [SAE PAPER 781026] MOSHER, H. An acoustical study of the XV-15 Tilt Rote	or an N79-18962 th le A79-26876 echnique N79-17801 lon in A79-25899	NORUM, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROM, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal howering rotor [AIAA PAPER 79-0608] OBERLY, C. E. Air Force applications of lightweight superconducting machinery OESTRICHER, P. P. F-16 high angle of attack testing	acoustics 1879-18686 h e 1879-26876
MORISHIGE, R. I. Analysis of the functional requirements for intelligent airborne computer system [AD-A061649] MORRIS, C. B. K., JR. A comparison of linear acoustic theory will experimental noise data for a small-scale hovering rotor [AIAA PAPER 79-0608] MORRISON, W. D. Delta method, an empirical drag buildup to [NASA-CR-151971] MOSES, C. A. Effects of fuel properties on soot format turbine combustion [SAE PAPER 781026] MOSHER, H.	or an N79-18962 th le A79-26876 echnique N79-17801 lon in A79-25899	NORUH, T. D. Applications of diffraction theory to aero [NASA-TR-80053] NYSTROH, P. A. A comparison of linear acoustic theory wit experimental noise data for a small-scal hovering rotor [AIAA PAPER 79-0608] OBERLY, C. B. Air Porce applications of lightweight superconducting machinery OESTRICHER, P. F.	acoustics N79-18686 h e A79-26876

PERSONAL AUTHOR INDEX QUARTERO, C. B.

OSBOEW, J. D. Alrcraft antenna pattern measurements usin field techniques		PETERSEN, N. J. Turbojet blade vibration data acquisition and feasibility testing	-
OSIN, H. I.	A79-24721	[NASA-CR-159505] PETRIB, S. L.	n79-18976
Introduction to the computer-aided design flight wehicles	A79-27648	Unsteady pressures on a NACA 64A010 airfor Experimental and theoretical results [AIAA PAPER 79-0330]	.1 - 479-26545
P	175 27040	PIERSOL, A. G. Characteristics of propeller noise on an a	
•		fuselage related to interior noise trans	mission
PABZ, C. Design and fabrication of advanced titaniu	10	[AIAA PAPER 79-0646] PIKE, J.	A79-2€932
structures [AIAA 79-0757] PAPALLIOU, K. D.	A79-28272	The 1-4-1 system of jack movements for the flexible liners of supersonic wind tunne	
Viscous flows in centrifugal compressors	N79-19387	PINNELL, W. R. Design criteria for and development of Rev	lar
PARKER, G. B. Why doesn't arroraft accident investigation prevent accidents	n	ribbon parachutes [AIAA 79-0430] PIRRI, A. N.	A79-26638
PARKER, J. A.	A79-27319	Laser propulsion	A79-26598
Thermal response of composite panels		PLATT, H.	nvy Zesyo
PARWAS, D. L.	A79-25350	Time degradation factors for the turbine e exhaust emissions. Volume 1: Program	engine
Software requirements for the A-7E aircraf	:t N79-18974	description and results [NREC-1238-6-VOL-1]	ท79-17860
PARTHASARATHY, S. P.	N73-10374	PLUBER, J. A.	W73-17000
Twin jet shielding [AIAA PAPER 79-0671]	A79-26924	Lightning protection with segmented divert	ers 179-25317
Separation of core noise and jet noise	170 2004	A new standard for lightning qualification	
[AIAA PAPER 79-0589] PAVLENKO, G. V. Influence of bypass ratio change on fan	A79-26941	of aircraft: Technical overview, defini and basic waveforms	N79-18246
aerodynamic characteristics		POISSON-QUINTON, P.	N73-10240
PAVLOVSKII, V. P.	A79-27744	Some new approaches for wind-tunnel testin through the use of computers	-
Instability of fluid flow in centrifugal i	njector A79-27731	[AIAA 79-0707] PONOHAREV, A. T.	A79-27367
PAYNE, L. Fabrication and evaluation of advanced tit	anlum	Behavior of elastic systems in separated f	low A79-25618
structural panels for supersonic cruise		POPOV, B. G.	
[NASA-CR-2744] PEARSON, D. S.	N79-18320	Intensification of fuel vaporization in ai gas turbine engines by electrical forces	5
Dynamic data analysis	A79-25845	PORITZKY, S. B.	A79-27748
PEDERSEN, G. H. Turbine engine cost reduction using Life C		FAA air traffic control automation - Progr trends	ams and
Cost techniques			A79-26871
[SAE PAPER 781031]	A79-25903	PORTER, R. P.	
PEER, Y. Flight testing the Kfir		Integrated Thermal Avionics Design (ITAD) [AD-A061227]	N79-17855
	A79-26530	POULIOT, M. R.	
Flight testing the KFIR	พ79-18899	Control system time response optimization nonlinear programming approach	
PEPPER, W. B., JR. Design and development of the 24-foot diam	eter	[AIAA PAPER 79-0540] POWERS, B. N.	A79-25859
hybrid Kevlar-29/nylon ribbon parachute		TASAR, a thinned adaptive synthetic apertu	
[AIAA 79-0433]	A79-26641	DDRICCDD I C	A79-27135
PERALA, R. A. EMP coupling to a composite aircraft		PREISSER, J. S. Airframe noise measurements on a small-sca	le model
Induced effects of lightning on an all com	A79-25321 posite	of a supersonic transport concept in an flow facility	
aircraft	N79-18242	TAIAA PAPER 79-0666] PRINCE, J. B.	A79-26920
PERKINS, P. J.		Evaluation of a long-endurance-surveillance	
Simultaneous measurements of ozone outside inside cabins of two B-747 airliners and		remotely-piloted wehicle with and withou laminar flow control	
Learjet business jet	A79-27571	[NASA-CR-159006] PROKOPOVICH, V. G.	ท79-17852
PERSON, L. H., JR.	R/J 2/3/1	Axial compressor operation with radially	
Plying NASA's Terminal Configured Vehicle the Microwave Landing System	-	nonuniform inflow	A79-27743
Pluma Wacata terminal configure 4 1-	A79-26534	PULLMAN, J. B.	
Flying NASA's terminal configured vehicle the microwave landing system		Methanol, ethanol and jet fuel emissions comparison from a small gas turbine	A79-25893
PERULLI, H.	N79-18894	[SAE PAPER 781013]	A 13-23093
Direct experimental verification of the theoretical model predicting rotor noise		Q	
generation		QUARTERO, C. B.	
[AIAA PAPER 79~0658] PETERSEN, D. A.	A79-26894	Evaluation of a long-endurance-surveillanc remotely-piloted vehicle with and withou	
Avionics systems needed to optimize V/STOL	. potential A79-26874	laminar flow control [NASA-CR-159006]	N79-17852

н	ì

RAI																						
	ı,	E.	1	в.																		
		re	C.	t							v ei											
		th ge						1	mod	el	pre	dic	t1r	ıg ı	CO.	tor	n	01	se			
								R	79-	06	58]									A79	-2689	4
RAE								. .						. ,				_				
RAJ					-	-	' (1e	4 61	.op	ment	::	NOW	1 11	τ.	can	D	e	tol		-1889	7
RAU							en 1	Ł (o£	th	егі	sks	pr	ese	en'	ted	b	y	the	us	e of	
								ŗ	CO	mp	osit	es	in	COI	m m	erc	1a				e of	
		Vo ap						r.	ına	1 1	cepo	et.	٧	011	a m	e 2	:	S	upp	ort:	ing	
		f٦	A S	5A	-c	R-	19	8	989	1										ห79.	-1807	4
RAN						a	ná		fac	. 1	ity	n1 a	חחו	na		ia	٥,	+ i	ma 1			
		co	n	tr	οl		00	le	ls		,	Pro		.ug	•		υp		ma.			
		4.				_					. 4 . 1	£.,	1	1						A79	-2672	5
	М	ae							OL y	ш	Juer	. 10		iea.	10		011	1.	OLI	пу	,,	
																				A79.	-2838	1
RAN					o m	рa	tı	ıb:	Le	110	ghto	ing	dı	.vei	cto	er	st	rı	ď			
						•						•								Ŋ79-	- 18 23	7
RAC					a m	10		. 1 é	le-	for	се	a11	P V 1	ato	ъr	me	an	s				
		[N.	A S	SA.	-c	AS					326-				_			_		N 79-	-1781	3
RAO		J.					· i (61 6	a+	101	ns f	OF	t he	. c	וחי	neđ	ħ	a I	100	ne s	#1th	
	-	sp	ė	:1	a Ì	r	eí	e:	ren	се	to	the										
		eq [A								opa	ause	!								. 70	-2663	_
RAS	HE								, 1											K / J-	-2003	,
	Εx	pe	r	LDE	en	ta	1	11	ı ve	st:	ıgat	10h	of	tl	he	ef	fe	ct	of			
		su		La	ce	u	13	sec	Juc	TH	11 t y	On	St	.ep-	- D:	1CK	wa	Lq			-27000	0
RAT											.							- 3			_	
											t st				191	сn	ÞΓ	eq	ıct	10n	OI	
																				A79-	- 28 380	0
RBA							eı	ıeı	nts	to	th	e U	K h	eli	ic	opt	er	С	ock	pıt		
		_			_											-				ท79-	19659	9
RED							1f	10	cat	101	ns f	ОТ	t he	Cá	nı	seđ	h	a 7	1	nc 1	/1th	
	νe																	a 7	700	40 1		
		sp	e	:18	1	r	ei	eı	cen	сe	to	the										
		sp eq	e c	:1a	al or	r 1a	ei 1	eı tı	cen	сe		the							th	е	2663!	5
R BI	P,	sp eq [A	e c u a I !	ti A G	al or 7	r 1a 9-	e i 1 04	t:	cen cop	ce opa	to luse	the	1.	su	.∀:	iva	1	1 D	th	е		5
	F, To	sp eq [A B	e c u a I !	ti AA G	1 7	r 1a 9-	e i 1 04 or	ti ti 26	cen cop	ce opa	to	the	1.	su	.∀:	iva	1	1 D	th ogy	e A79-		
REU	F, To	sp eq [A ta [A	e d I l I	G.	7 . v 06 D	r 1a 9- 1r 18	e1 04 01 88	ti 126	ren rop 5] ent	ce opa	to luse	the	1.	su	.∀:	iva	1	1 D	th ogy	e A79-	- 26 6 3 !	
REU	F, To	sp eq [A ta [A	e d 1	G.	10F 7 00F 00F D	r 1a 9- 1r 18	e i 0 4 0 8 8 8	ti ti 26	ren rop 5] ent	ce opa	to luse	the	1.	su	.∀:	iva	1	1 D	th ogy	e A 79- N 79-	- 26 6 3 !	1
REU R ey	F, To TE	sp eq [A ta [A mm	e d 1	GA G	10 7 . v 0 6 . D 10 7 . B.	r 9- 1r 18	ei 1 04 or 88 pa	ti ti 20	ren rop 5] ent ach	ce opa si	to nuse irvi	the √ab	11 111	su:	m e	i v a eth	1 ođ	ın ol	th ogy	e A79- N79- A79-	- 2663! - 1897 - 2666	1
REU R ey	F, To TE Co	sp eq [A ta [A mm [A LD	ecuii 10 eii 10 eii	G. A. I.	107 .v.06 Da 7 B. ces	r 9- 118 1 9- e so	ei 1 04 01 88 pa 04 cl	ti 126	ent cop ent ch	ce opa su ute	to nuse irvi es	the vab	11 111	su:	m e	i v a eth	1 ođ	ın ol	th ogy	e A 79- N 79-	- 2663! - 1897 - 2666	1
REU	F, To TE Co	specific control contr	edil 1 Dellar 1 Della	G. A.	7 . v 6 D a 7 . a 2 P	r 1a 9- 17 18 1 9- e so	ei 1 04 01 88 Pa 04 cl	ti 126	ent cop ent ch	ce opa su ute	to nuse irvi	the vab	11 111	su:	m e	i v a eth	1 ođ	ın ol	th ogy ake	e A79- N79- A79- of	- 2663! - 1897 - 2666	1
RET RET	F, To TE Co	specification of the control of the	edil 1 Della Sulla	G. G. A. I. C. C. I. A. A. I. C. C. I. A. I. C. C. I. A. I. C. I. A. I. C. I. A. I.	107 000 000 000 000 000 000 000 000 000	r 14 9- 18 19- e so AP	ei 1 04 or 88 pa 04 cl	ti ti 26 ime 3]	ren rop i] ent ich ich ich ich	ce ope su ute ter 1028	to nuse irvi es cist olad	vab	111 111	.ty	me	iva eth	ođ ar	ol V	th ogy ake	e A79- N79- A79- Of A79-	- 2663! - 1897 - 2666 a - 26544	1
RET RET	F, TO TEO TU	specification of the control of the	edi. 1 Della	G. G. A. I.	107 . v 6 D a 7 . e 8 .	ra 9- 118 1 9- e so AP 150	eff 04 off 88 pa 04 ch	triber resident resid	ren rop [5] ent ach oto 79-	ce opa su ute ter 1028 f H	to nuse irvi es cist olad 30]	the vab	111 111	.ty	me	iva eth	ođ ar	ol V	th ogy ake	e 1479- 1479- 1479- 1479- 141-	- 2663! - 1897 - 2666 - a - 2654!	1
REU REY	F, TO TE Tu	speq [A tale tale tale tale tale tale tale tale	edil 10 ellani 15 ellani	GAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	21 7 . v 6 D a 7 . c 8 .	ra 9 - 1 1 8 1 9 - e sap D 1 5 0 A P	ei 04 08 08 04 cl EF	triber resident resid	ren rop [5] ent ach 3] rac oto	ce opa su ute ter 1028 f H	to nuse irvi es cist olad 30]	the vab	111 111	.ty	me	iva eth	ođ ar	ol V	th ogy ake	e 1479- 1479- 1479- 1479- 141-	- 2663! - 1897 - 2666 a - 26544	1
REY REY	P, TO TEO TO NO.	spequent in the control of the contr	edille in the same of the same	G. A.	or or or or or or or or or or	ra- 9- 18- 19- esoAPD soAPT et	ei 04 08 pa 04 cl EF	to the second se	ren rop i] ent ach 3] rac oto 79-	ce opa su ute ter 1 028 f 1 an 055	to nuse irvi es cist olad 30] the rot	ics e wak	lr ili in	ty the	me	iva eth ne	1 ođ ar ht	1 n 0 l v	th ogy ake	e 1479- 1479- 1479- 1479- 141-	- 2663 - 1897 - 2666 - a - 2654 I	1
REY REY	P, TO TEO TO NO.	specification (A)	edille in the same of the same	G. A.	or or or or or or or or or or	ra- 9- 18- 19- esoAPD soAPT et	ei 04 08 pa 04 cl EF	to the second se	ren rop i] ent ach 3] rac oto 79-	ce opa su ute ter 1 028 f 1 an 055	to nuse irvi es cist olad 30] the rot	ics e wak	lr ili in	ty the	me	iva eth ne	1 ođ ar ht	1 n 0 l v	th ogy ake lo jet	e A79- N79- A79- of A79- aded	- 2663 - 1897 - 2666 a - 2654 I - 2586	1 1 1
REY REY	F, TCO TU NCh NCh	spe [H a l A l A l A l A l A l A l A l A l A l	edii 10 eii 15 eiii 15 eiii 15 eiii 16 eiii 16 eiii 16 eiii 17 eiii 18	CITAL ALL CONTRACTOR	alco of the second of the seco	ra- 118 1- esapp sappet et	ef 04 08 pa 04 cl EF ti	to the second se	ren rop 5] ent 1ch 13] rac oto 79-	ce opa su ute ter 028 f in 055	to nuse urvi es cist olad 80] the rot 50]	ics e wak	ir ili in	ty the Th	me ne	iva eth ne	ođ ar ht	ol v ly	th ogy ake lo jet	e A79- N79- A79- of A79- aded	- 2663 - 1897 - 2666 a - 2654 l - 2586 - th	1 1 1
REY REY	F, TCO TU NCh NCh	special tale tale tale tale tale tale tale ta	edii 10 eii 15 eiii 15 eiii 15 eiii 16 eiii 16 eiii 16 eiii 17 eiii 18	CITAL ALL CONTRACTOR	alco of the second of the seco	ra- 19 18 1- esapps apper	ef 04 08 pa 04 cl EF ti	to the second se	ren rop 5] ent 1ch 13] rac oto 79-	ce opa su ute ter 028 f in 055	to nuse urvi es cist olad 80] the rot 50]	ics e wak	ir ili in	ty the Th	me ne	iva eth ne	ođ ar ht	ol v ly	th ogy ake lo jet	e A79- N79- A79- Of A79- A79- A79- A79-	- 2663! -1897 -2666 -2654! -2586 -th	1 1 1 2
REY REY REY	F,O TEO MU OC NO Th	speq [A tail [A mm [A tail [A mm [A tail [A ta	edil elsumisamisamisamisamisamisamisamisamisamisa	CITAL G. A.	al room and a room a room and a room and a room and a room a room and a room a room and a room and a room and a room a room a room and a room a r	ra- 19 18 1- esapp 150 Pts et s	ef 104 04 08 04 ch EF • ti	entition (continue) (c	centrop ich ich ich ich ich ich ich ic	ce ope su ute ter 1028 f H an 055 orr	to nuse urvi es cist olad 80] the rot 50]	ics e wak	ir ili in	ty the Th	me ne	iva eth ne	ođ ar ht	ol v ly	th ogy ake lo jet	e A79- N79- A79- Of A79- A79- A79- A79-	- 2663 - 1897 - 2666 a - 2654 l - 2586 - th	1 1 1 2
REY REY REY	F,O TEO MU OC NO Th	speq [A tail [A mm [A tail [A mm [A tail [A ta	edil elsumisamisamisamisamisamisamisamisamisamisa	CITAL G. A.	al room and a room a room and a room and a room and a room and a room a room and a room a room and a room and a room a room a room and a room and a room a room a room and a room a room a room a room a room and a room a ro	ra- 19 18 1- esapp 150 Pts et s	ef 104 04 08 04 ch EF • ti	entition (continue) (c	ren rop 5] ent 1ch 13] rac oto 79-	ce ope su ute ter 1028 f H an 055 orr	to nuse urvi es cist olad 80] the rot 50]	ics e wak	ir ili in	ty the Th	me ne	iva eth ne	ođ ar ht	ol v ly	th ogy ake lo jet	e N79- N79- Of N79- aded A79- S WI N79-	- 26639 - 1897 - 2666 - a - 26544 - 2586 - th - 26532 - th	1 1 1 2 3
REY REY REY	FT TC NT NC NT T BC H,	specification of the control of the	edi. 1 D. elisumisamisamisamisamisamisamisamisamisamisa	CITAL A COLA A C	alro 1 Blospes Prit in . m	ra- 118 - esappison es an	efi 04 08 pa 04 cl EF tr EF	entition 26	rent ich ich ich ich ich ich ich ich ich ich	ce opa su ute ter 028 fan 055 orr	to nuse pristolad 80] the rot 50]	ics e wak or	ir ili e o s -	ty the Th	me ne	iva eth ne fi	od ar ht	ol W	th ogy ake lo jet	e N79- N79- Of N79- aded A79- S WI N79-	- 2663! -1897 -2666 -2654! -2586 -th	1 1 1 2 3
REY REY REY	P.O EO OU ON ON T BC HF	spequent and the control of the cont	eul.lD.elsumisamisaec.e.e.e.e.e.e.e.e.e.e.e.e.e.e.e.e.e.e.	CITAL OF A LEGICAL A LEGIC	alro . v6 Da7csp.rsp.jt jt . m	ra- r8 - coppsoprt es es an me	efi 04 08 04 04 cr Efi cr Efi 1	entition 26 to 126 to 1	rent op ont ach ont 79- sof 79- nigh	ce ope st ute term occion occi	to nuse rist class rist rist class rist rist class rist rist rist rist rist rist rist ri	ics e wak or rie	11 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ty th	me ne	iva eth ne fi	od ar ht	ol W	th ogy ake lo jet	e N79- N79- Of N79- aded A79- S WI N79-	- 26639 - 1897 - 2666 - a - 26544 - 2586 - th - 26532 - th	1 1 1 2 3
REY REY REY	P.O EO OU Oh Oh T BC HF	special tale in the control of the c	ecall to the state of the state	CITAL GENERAL	alro o o o o o o o o o o o o o o o o o o	ra- r8 - csAPDsOPTt an mee	efi 104 088 pa 04 ch EF • I	entition 26 to 126 to 1	rent op ont ach ont 79- sof 79- nigh	ce ope st ute term occion occi	to nuse pristolad 80] the rot 50]	ics e wak or rie	11 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ty th	me ne	iva eth ne fi	od ar ht	ol W	th ogy ake lo jet jet	e A79- N79- A79- Of A79- A79- S WJ	- 26639 - 1897 - 2666 - a - 26544 - 2586 - th - 26532 - th	1 1 2 3 0
REY REY REY	P.O EO OU Oh Oh h BC H.T HA	special tanger of the control of the	ecallilities and the state of t	CITAL OF A LOCAL DICE A LOCAL D	alro voo barse Berse Prit it in sep R.	ra- ra- 19 esappsoprat a mee B	efication of the state of the s	entition in the second	rent ich ich ich ich ich ich	ter ter 028 f dan 055 orr	to nuse sist old	vab ics e wak or rie falctu	ir ili e o s - s:	ty the The The The	me ne ne	iva eth ne fi	od ar ht rs	ol W	th ogy ake lo jet jet	e A79- N79- A79- Of A79- A79- S WJ	- 2663: -1897: -2666: a - 2654! I - 2586: -1889:	1 1 2 3 0
REY REY REY	FT TC NT NC NT T BC HF HP	special tale in the contract of the contract o	ecolii eliii e	TALLE STATE OF THE	alco . ve Back Back Projet in the Back Back Projet in the Back Back Back Back Back Back Back Back	ra- r8 - csappsoprt es es a mee B	efi 104 018 108 108 108 108 108 108 108 108 108	entition of the second of the	rent ich ich ich ich ich ich	ter ter 028 f dan 055 orr	to nuse rist class rist rist class rist rist class rist rist rist rist rist rist rist ri	vab ics e wak or rie falctu	ir ili e o s - s:	ty the The The The	me ne ne	iva eth ne fi	od ar ht rs	ol W	th ogy ake lo jet jet	e A79- N79- A79- Of A79- A479- S W1 N79- N79-	- 2663: -1897: -2666: a - 2654! I - 2586: -1889:	1 1 2 3 0 5
REU REY REY RIC RIC RIC	FT TC NT NC NT T BC HF HP D	special transfer of the control of t	ecoli il construction of the construction of t	TA G. A.	alro 100 ba 100	ra- r8 - opposite es a met 816	ef1 04 018 018 018 018 018 018 018 018 018 018	to the second se	rentrope of the second of the	ce ope st ute term occi financi correct series	to nuse sistering to the rot of t	ics e wak or rie fai	ir ili in e o s - s: l-ss	ty the fa	me ne	iva eth ne lig fi fi	od ar ht rs	ol W ly t	th ogy ake lo jet jet	e A79- N79- A79- A79- A79- A79- A79- N79-	-2663: -18977 -2666 -2654 -2586 -18970 -18890 -26986 -18970	1 1 2 3 0 5
REU REY REY RIC RIC RIC	FT TC NU Oh Oh D T EC HF HP DD	speq [Ha A Fa Fa Fa Fa Fa Fa Fa	ectall the control of	A CA	arr v6Da7.csp.rsp.jt jt m .ep Re6.rl	ra- r8 - osapusoput es es a met s16 vs	eflowers and the second of the	to the state of th	centrope of acordon of the control o	teritorio ori	to nuse sistering to the rot of t	ics e wak or rie fal ctu	ir ili in e o s - s:	ty the fa	me ne	iva eth ne lig fi fi	od ar ht rs	ol W ly t	th ogy ake lo jet for	e A79- N79- A79- Of A79- A79- A79- N79- N79-	- 2663: -1897: -2666: a - 2654! -2586: -1889: -1889: -26986: -18970	1 1 2 3 0 5 0
REY REY REY REY	FT TC NO ON ON T BC BF HP DD	seq A H L A L A L A L A L A L A L A L A L A	ectal to the control of the control	TALL STATE OF A COLOR	alor 7. vo 06 Da 07. vo 06 Da 0	ra- r8 - osapusoput es es a met s16 vs	eflowers and the second of the	to the state of th	centrope of acordon of the control o	teritorio ori	to t	ics e wak or rie fal ctu	ir ili in e o s - s:	ty the fa	me ne	iva eth ne lig fi fi	od ar ht rs	ol W ly t	th ogy ake lo jet for	e A79- N79- A79- Of A79- A79- A79- N79- N79-	-2663: -18977 -2666 -2654 -2586 -18970 -18890 -26986 -18970	1 1 2 3 0 5 0
REV REY REY RIC RIC RIC	PT TC NT NC NT T BC HF HP DD GT	sequent to the sequent of the sequent to the sequen	ectal little control c	A Control of the cont	allor 7. ve no	ra- r8 - opposert t a met 81 vs0 r	eflus	en meet de la communication de la communicatio	centrop in the second of the	ute term of term of terms of t	to t	vab ics e vak or rie faictu r p	ir ili in e o s - s: fo	ty the	me ne ne ne ne	iva eth ne lig fi fi des	od ar ht rs	ın ol ly t	th ogy ake lo jet jet for	e A79- N79- A79- A79- A79- A79- A79- A79- N79- N79-	- 2663: -1897: -2666: a - 2654! -2586: -1889: -1889: -26986: -18970	11 11 11 11 11 11 11 11 11 11 11 11 11

ROBB, J. An RF compatible lightning diverter strip	N79-18237
ROBERTS, B. W. Parachute inflation control using an attac	hed apex
drogue [AIAA 79-0449]	A79-26653
ROBERTSON, S. H.	
A method for selecting a crashworthy fuel design	system
ROBIESON, M. R.	N79-19661
Enhanced capabilities of future fighters a result of Himar	s a
[AIAA 79-0698]	A79-27370
RODDEN, W. P. Aeroelastic addition to NASTRAN	
[NASA-CR-3094] RODGERS, T. N.	พ79-17812
An optical communication system for aircra	ft A79-28034
ROOD, G. H.	R73-20034
Some aspects of helicopter communications	N79-19647
ROQUEFEUIL, C. Study of the structure of an integrated sy	stem of
flight control, navigation and display	A79-27674
ROSER, A.	
Nonlinear equations of equilibrium for ela- helicopter or wind turbine blades underg	
moderate deformation [NASA-CR-159478]	N79-19414
ROSEMFIELD, D. B.	
An assessment of the risks presented by the carbon fiber composites in commercial av	e use or lation.
Volume 1: Final report. Volume 2: Sup appendices	porting
[NASA-CR-158989] ROTE, D. M.	N79-18074
Airport vicinity air pollution model. Abb:	reviated
<pre>version user's guide [FAA-RD-78-111]</pre>	N79-18475
ROUSTAN, H. Application of aerodynamic design technique	es to
process compressor design	ห79-19388
ROUX, J. A. IR scanning camera measurements of an exha-	
plume from an axisymmetric nozzle afterb	
model at transonic Mach numbers	A79-28097
RUDD, H. J. Aircraft velocity and altitude measurement:	
	s using
a tunable diode laser	
a tunable diode laser RUMDALL, T.	A79-28139
a tunable diode laser RUMDALL, T. Survey of radar simulation training at ATC facilities	A79-28139
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RYCHBOVSKY, R. E.	A79-28139 field N79-17877
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RYCHBOVSKY, R. E.	A79-28139 field N79-17877
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [FAA-NA-78-27]	A79-28139 field N79-17877
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAA-NA-78-27] RYCHBOVSKY, R. E. Fabrication and quality assurance procedur assure a symmetrical lifting parachute	A79-28139 field N79-17877
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RICHBOYSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO. J. T.	A79-28139 field N79-17877 e to A79-26636
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAA-NA-78-27] RYCHBOYSKI, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427]	A79-28139 field N79-17877 e to A79-26636
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RYCHBOVSKY, R. B. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVIBO, J. T. Rotor fragment protection program: Statissaircraft gas turbine engine rotor failuroccurred in US commercial aviation during	A79-28139 field N79-17877 e to A79-26636 tics on es that
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAA-NA-78-27] RYCHBOYSKI, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D.	A79-28139 field N79-17877 e to A79-26636 tics on es that g 1976 N79-18977
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAA-NA-78-27] RYCHBOVSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army help	A79-28139 field N79-17877 e to A79-26636 tics on es that g 1976 N79-18977
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RYCHBOYSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army helps SANFORD, R. J. Failure studies of a third stage fan disk	A79-28139 field N79-17877 e to A79-26636 tics on es that g 1976 N79-18977 copters N79-19654
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [FAA-NA-78-27] RYCHBOYSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army helications.	A79-28139 field N79-17877 e to A79-26636 tics on es that g 1976 N79-18977 copters N79-19654
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [FAA-NA-78-27] RYCHBOVSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army helication for the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the state of a third stage fan disk in the stage f	A79-28139 field M79-17877 e to A79-26636 tics on es that g 1976 M79-18977 acopters M79-19654 from a
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [FAA-NA-78-27] RYCHBOYSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failure occurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army helication for the state of a third stage fan disk fraction from the state of a third stage fan disk fraction for the state of a monoplanar elliptic missile model at faction factors.	A79-28139 field M79-17877 e to A79-26636 tics on es that g 1976 M79-18977 acopters M79-19654 from a W79-19004
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAA-NA-78-27] RYCHBOVSKY, R. E. Fabrication and quality assurance procedur assure a symmetrical lifting parachute [AIAA 79-0427] SALVIBO, J. T. Rotor fragment protection program: Statis: aircraft gas turbine engine rotor failur occurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army hell SAMFORD, R. J. Failure studies of a third stage fan disk: TP-30 turbine engine [AD-A061801] SANGIORGIO, G. Stability and control characteristics of a monoplanar elliptic missile model at Macinumbers from 1.60 to 2.86 [NASA-TP-1352]	A79-28139 field M79-17877 e to A79-26636 tics on es that g 1976 M79-18977 acopters M79-19654 from a W79-19004
a tunable diode laser RUNDALL, T. Survey of radar simulation training at ATC facilities [PAN-NA-78-27] RYCHBOYSKY, R. E. Fabrication and quality assurance procedurassure a symmetrical lifting parachute [AIAA 79-0427] SALVINO, J. T. Rotor fragment protection program: Statistaircraft gas turbine engine rotor failuroccurred in US commercial aviation during [NASA-CR-159474] SAND, L. D. Comparative injury patterns in US Army helication for the state of a third stage fan disk in Tr-30 turbine engine [AD-A061801] SANGIORGIO, G. Stability and control characteristics of a monoplanar elliptic missile model at Machanish from 1.60 to 2.86	A79-28139 field M79-17877 e to A79-26636 tics on es that g 1976 M79-18977 acopters M79-19654 from a W79-19004

A decision theory model for health monitor	ring of	SHABELIN, J. P.	
aeroengines	A79-28381	Multimode radar processor	A79-28058
SAULE, A. V.		SHCHUKIN, V. K.	
Analysis of radiation patterns of interactiones generated by inlet rods in the JT		Convective heat exchange of gas-particle s flow passage of throttling device with v	
[AIAA PAPER 79-0581]	A79-26944	turning element	dhe cipe
SAWYER, W. C.		GUDDIDA D. 7	A79-27742
Stability and control characteristics of a monoplanar elliptic missile model at Mac		SHERIDAN, P. F. Interactional aerodynamics of the single r	otor
numbers from 1.60 to 2.86		helicopter configuration. Volume 8: fre	quency
[NASA-TP-1352] SCHAEPER, B. E.	₦ 79- 17808	analyses of wake single film data, basic configuration wake exploration	
System for the display of extracted radar	data on	[AD-A062013]	N79-18956
the basis of minicomputer-controlled dis	splay	Interactional aerodynamics of the single r	otor
<pre>devices /DERD-MC/ for an employment in i Traffic Control</pre>	A1r	helicopter configuration. Volume 6-A: One-third octave band spectrograms of wa	ke
	A79-25491	single film data, buildup to baseline	
SCHABLLIG, R. Heat generation in Cavities at high veloci	ta flighte	[AD-A061994] Interactional aerodynamics of the single r	N79-18958
[BMVG-FBWT-77-28]	N79-17815	helicopter configuration. Volume 8-C:	otor
SCHATZLE, P. R.		Prequency analyses of wake single film d	ata,
Flight simulation of a vehicle with a two- parachute system	-stage	hubcaps and air ejectors [AD-A061995]	N79-18959
[AIAA 79-0448]	A79-26652	SHOBBAKER, W. W.	
SCHIJVE, J. Four lectures on fatigue crack growth		Life Cycle Cost in advanced technology eng development	ıne
rout lectures on fatigue crack growth	A79-25484	[SAE PAPER 781029]	A79-25901
Environmental effects on crack growth in		SHORE, J. E.	
flight-simulation tests on 2024-T3 and 7 material	/075-T6	Software requirements for the A-7E aircraf [AD-A061751]	ะ พ79-18974
[NLR-TR-76104-U]	N79-18012	SHORT, B. J.	
SCHLINKER, R. H. Allframe noise component interaction stud:	105	Evaluation of a wake vortex upset model ba simultaneous measurements of wake veloci	
[NASA-CR-3110]	₩79~19815	probe-aircraft accelerations	cres and
SCHHIDT, C.		[NASA-TM-78561]	N79-18960
Aerodynamic and acoustic comparisons of scaled-down and actual engine jets		SHOSTAK, R. E. SIFT - Design and analysis of a fault-tole	rant
(AIAA PAPER 79-0574)	A79-26946	computer for alreraft control	
SCHHIDT, L. V. Wing rock due to aerodynamic hysteresis		SHOTTER, B. A.	A79-25718
wing rook and to derodynamic hysteresis	A79-28376	The Lynx transmission and Conformal gearin	
SCHHIDT, U.		[SAE PAPER 781041]	A79-25909
Bailout from autorotating helicopters	N79-19666	SIEGEL, W. H. Experimental and finite element investigat	ion of
SCHHIDT, W.		the buckling characteristics of a beaded	
Theoretical investigations of real gas efficiency openic wind tunnels	fects in	panel for a hypersonic aircraft	N79-19412
[DS-FB-76/50B]	N79-17820	SIEVERS, G. K.	
Progress in transonic flow computations an and design methods for three-dimensional		NASA research on general aviation power pl [AIAA PAPER 79-0561]	ants A79-25870
and design methods for three-dimensional	N79-18951	SIGHAN, R. K.	R79-23070
SCHHITT, V.		Wave propagation in ducts using the finite	element
Vortex pattern development on the upper so a swept wing at high angle of attack	irrace or	method [AIAA PAPER 79-0659]	A79-26879
[NASA-TM-75377]	N79-18914	SIMAKOV, A. A.	
SCHNEIDER, J. G. Recent advances in indirect lightning effe	acts	Operational experience with linked-blade high-output gas-turbine	
research	ec es	nigh output gas-tarbine	A79-26830
COUNTRY BE	A79-25313	SIMENZ, R. P.	• -
SCHREIBER, H. A. Comparison between flows in cascades and i	cotors in	Structural aluminum materials for the 1980 [AIAA 79-0755]	A79-28270
the transonic range. 2: Investigation	of two	SINCLAIR, M.	
transonic compressor cascades and compai with rotor data	rison	Evaluation of IPR handling qualities of helicopters using the NAE airborne V/STO	т.
#101 10001 audu	N79-19001	simulator	-
SEPIC, W. J.		[AIAA 79-0702]	A79-27365
Elevated-temperature effects on strain gagethe YF-12A wing	jes on	SINGLEY, G. T., III Crashworthy helicopter seats and occupant	
-	A79-26400	restraint systems	
SEIDHAN, B. Computer-aided collection of demographic (lata	SLAZAK, H.	ห79-19658
within day-night level contours: Two to	est cases	Noise transmission - Turboprop problem	
[AD-A061657] SENSBURG, O.	N79-19010	[AIAA PAPER 79-0645]	A79-26933
Recent developments in active control tech	nology	SMITH, A. D. Considerations for the design of inlet flo	
[AIAA 79-0708]	A79-27368	conditioners for static fan noise testin	g
SERAJI, H. Design of proportional-plus-integral conti	collers	[AIAA PAPER 79-0657] SHITH, L. R.	A79-26909
for multivariable systems		The coming of age of digital electronics i	n
SERRANO, A. V.	A79-28223	commercial transports [AIAA 79-0686]	A79-27352
Recent advances in indirect lightning effe	ects	SHITH, R. C.	A13-21332
research		Propeller slipstream wing interactions at	Mach no.
SEYHOUR, T. J.	A79-25313	0.8 [SAE PAPER 780997]	A79-25881
Evaluation of the Ryan Stormscope as a sev	vere	• · · · · · · · · · · · · · · · · · · ·	
weather avoidance system for aircraft			

N79-18229

SHITH, S. H. The prediction of fatigue crack growth us flight-by-flight leading	nder	STRINNING, P. Comparison between flows in cascades and r	otors in
flight-by-flight loading	A79-25482	the transonic range. 3: Comparison of experimental and theoretical results of	
SHYTH, C. C. Internal cockpit reflections of external light sources for the model YAH-64 adv		studies on blade-to-blade surfaces in an compressor rotor	N79-1900
attack belicopter	N79-19643	STROUB, R. H. Constant life rotor for a heavier than air	
SNYDER, R. G. Occupant injury mechanisms in civil helicaccidents	copter	[NASA-CASE-ARC-11045-1] STROUT, P. G. Flight effects on noise generated by the J	N79-1784 T8D
SOBIESZCZANSKI-SOBIESKI, J.	N79-19653	engine with inverted primary/fan flow as measured in the NASA-Ames 40- by 80-foot	
Accuracy of an approximate static struct analysis technique based on stiffness eigenmodes		tunnel [AIAA PAPER 79-0614] STUART, T. A.	A79-2693
[AIAA 79-0748] SOHEL, M. S. RCS reduction of installed aircraft ante	A79-28263	Pilter weight minimization for rectified superconducting alternator power supplie	s 179-2696
Res reduction of installed affectate ante-	A79-24716	STURONIS, H.	R/3-2030
SPEARMAN, M. L. Wind-tunnel studies of the effects of size damage on the aerodynamic characterist.	mulated	Causes for the deterioration of splined connections in aircraft engines during s	er v ice 179-2524
airplanes and missiles	A79-27424	STUMP, C. W. Apparatus for measuring an aircraft's spee	d and
SPEER, I. B. Small fan-jet engines	.70 04534	height [NASA-CASE-LAR-12275-1]	N79-1829
Small fan-jet engines	A79-26531 N79-18891	SULLIVAN, B. U. A commercial airport noise environment: Measurement, prediction and control	
SREENIVASAN, S. Design specifications for the capped ball		[NASA-CR-3107] SUN, K.	N79-1981
special reference to their survival in equatorial tropopause	the	Laser aircraft	A79-2659
[AIAA 79-0426] SRIDHAR, B.	A79-26635	SZEWCZYK, V. H. Coaxial jet noise in flight	
Configuration management and automatic co an augmentor wing aircraft with vector	ed thrust	[AIAA PAPER 79-0636]	A79-26919
[NASA-TP-1222] ST. HILAIRE, A. O.	N79-17872	T	
The influence of sweep on aerodynamic los an oscillating NACA0012 airfoil. Volum Data report		TAILLET, J. Alrcraft static charging testing [ONERA, TP NO. 1978-110]	A79-26130
[NASA-CR-145350] STAHL, W.	N79-17802	TANKA, H. K. Effects of simulated forward flight on jet	
Wings	N79-18921	shock noise and internal noise [ATAN PAPER 79-0615]	A79-26936
STARKEN, H. Comparison between flows in cascades and the transonic range. 1: Basic conside		TEGRADEN, F. W. Life Cycle Cost in advanced technology eng. development	ıne
STARKS, D. W.	N79-19000	[SAE PAPER 781029] TEICHMAN, H.	A79-25901
GASP IV simulation model for the composit	es and	Crashworthiness tests on model aircraft fus	selage
bonding production facility	170 27207		170 2725
STASZEK, J.	A79-27297	[AIAA 79-0688] TEKRONY, K. L.	
	at high	TEKRONY, K. L. Development and testing of a shipboard laughter balloon system	nched
STASZEK, J. Characteristic aerodynamic coefficients a	at high A79-25247 of an	TERRONY, R. L. Development and testing of a shipboard law balloon system {AIAA 79-0420} TENNISON, R. C.	nched A79-26631
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520]	at high A79-25247 of an	TERRONY, R. L. Development and testing of a shipboard law balloon system farm 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft fustructures [AIM 79-0688]	nched A79-26631 selage
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration {BLL-RTS-11520} STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per	at high A79-25247 of an ation and N79-17794	TEKRONY, R. L. Development and testing of a shipboard law balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft fustructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet	nched A79-2663 selage A79-2735
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083]	at high A79-25247 of an ation and N79-17794	TERRONY, R. L. Development and testing of a shipboard law balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft fustructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615]	A79-26631 selage A79-27354
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des	at high A79-25247 of an ation and N79-17794 rformance N79-17811	TEKRONY, R. L. Development and testing of a shipboard laur balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft furstructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615] THIRIET, Y. New airborne armament systems	nched A79-26631 selage A79-27354 noise, A79-26936
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configure with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des minimum operating cost [NIAA 79-0690]	at high A79-25247 of an ation and N79-17794 rformance N79-17811	TEKRONY, R. L. Development and testing of a shipboard laur balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft for structures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615] THIRIET, Y. New airborne armament systems [AIAA 79-0697] THOMAS, J. L.	nched A79-26631 selage A79-27354 noise, A79-26936
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration (BLL-RTS-11520) STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] STEWART, W. L. NASA research on general aviation power [AIAA PAPER 79-0561]	At high A79-25247 of an ation and N79-17794 rformance N79-17811 sign for A79-27356	TERRONY, R. L. Development and testing of a shipboard laur balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft furstructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPPER 79-0615] THIRIET, Y. New airborne armament systems [AIAA 79-0697] THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspect-highly swept arrow-wing configuration	A79-26635 selage A79-27355 noise, A79-26936 A79-27362 of ratio
Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] STEWART, W. L. NASA research on general aviation power p [AIAA PAPER 79-0561] STONE, H. Damage-tolerance practices applied to tra	At high A79-25247 of an ation and N79-17794 rformance N79-17811 sign for A79-27356 plants A79-25870	TERRONY, R. L. Development and testing of a shipboard law balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft fustructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615] THIRIET, Y. New airborne armament systems [AIAA 79-0697] THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspect-1 highly swept arrow-wing configuration [NASA-TM-80041] THURBOW, J. W.	A79-2663* selage A79-27354 noise, A79-26936 A79-27362 of ratio
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration (BLL-RTS-11520) STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Perprediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft desminimum operating cost [AIAA 79-0690] STEWART, W. L. NASA research on general aviation power paina AIAA PAPER 79-0561] STONE, M. Damage-tolerance practices applied to trail aircraft structures [SAZ PAPER 781021]	A79-25247 of an ation and N79-17794 rformance N79-17811 sign for A79-27356 plants A79-25870 ansport A79-25896	TEKRONY, R. L. Development and testing of a shipboard law balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft furstructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615] THIRIET, V. New airborne armament systems [AIAA 79-0697] THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspectingly swept arrow-wing configuration [NASA-TM-80041]	A79-26631 selage A79-27354 noise, A79-26936 A79-27362 of ratio N79-17871 system
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des minimum operating cost [NIAM 79-0690] STEWART, W. L. NASA research on general aviation power p [AIAM PAPER 79-0561] STONE, M. Damage-tolerance practices applied to tra aircraft structures [SAZ PAPER 781021]	At high A79-25247 of an ation and N79-17794 rformance N79-17811 sign for A79-27356 plants A79-25870 ansport A79-25896 ary missions	TEKRONY, R. L. Development and testing of a shipboard laur balloon system [AIAA 79-0420] TENNISON, R. C. Crashworthiness tests on model aircraft furstructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPPER 79-0615] THIRIET, Y. New airborne armament systems [AIAA 79-0697] THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspect-highly swept arrow-wing configuration [NASA-TH-80041] THURBOW, J. W. A method for selecting a crashworthy fuel sesign	A79-26631 selage A79-27354 noise, A79-26936 A79-27362 of ratio N79-17871 system
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configura with the conventional configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Per prediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft des minimum operating cost [AIAA 79-0690] STEWART, W. L. NASA research on general aviation power [AIAA PAPER 79-0561] STONE, M. Damage-tolerance practices applied to tra aircraft structures [SAZ PAPER 781021] STOTZ, W. Rescue helicopters in primary and seconda STOWELL, W. K. Air Force applications for optical rotatic	A79-25247 of an ation and N79-17794 efformance N79-17811 sign for A79-27356 plants A79-25870 ansport A79-25896 ary missions N79-19606	TERRONY, R. L. Development and testing of a shipboard laur balloon system [AIAA 79-0420] TENNYSON, R. C. Crashworthiness tests on model aircraft furstructures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise [AIAA PAPER 79-0615] THIRIET, Y. New airborne armament systems [AIAA 79-0697] THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspectingly swept arrow-wing configuration [NASA-TH-80041] THURBOW, J. W. A method for selecting a crashworthy fuel selecting. TING, L. Radiation of an acoustic source near the transport of a wing in forward motion [AIAA PAPER 79-0605]	A79-26631 selage A79-27354 noise, A79-26936 A79-27362 of ratio N79-17871 system N79-19661
STASZEK, J. Characteristic aerodynamic coefficients a Reynolds numbers Comparison of the aerodynamic properties aeroplane with the tail-first configuration [BLL-RTS-11520] STEPHNIEWSKI, W. Z. Rotary-wing aerodynamics. Volume 2: Perprediction of helicopters [NASA-CR-3083] STEWART, D. J. New technology in commercial aircraft desminimum operating cost [AIAA 79-0690] STEWART, W. L. NASA research on general aviation power painamy appears of AIAA PAPER 79-0561] STONE, M. Damage-tolerance practices applied to trailing arrivant structures [SAZ PAPER 781021] STOTZ, W. Rescue helicopters in primary and secondary structures in primary and secondary structures are secondary structures.	A79-25247 of an ation and N79-17794 efformance N79-17811 sign for A79-27356 plants A79-25870 ansport A79-25896 ary missions N79-19606	TERRONY, R. L. Development and testing of a shipboard laur balloon system {AIAA 79-0420} TENNISON, R. C. Crashworthiness tests on model aircraft for structures [AIAA 79-0688] TESTER, B. J. Effects of simulated forward flight on jet shock noise and internal noise {AIAA PAPER 79-0615} THIRIET, Y. New airborne armament systems {AIAA 79-0697} THOMAS, J. L. Theoretical and experimental investigation ground induced effects for a low-aspect-ingly swept arrow-wing configuration [NASA-TM-80041] THURBOW, J. W. A method for selecting a crashworthy fuel selecting. L. Radiation of an acoustic source near the tredge of a wing in forward motion	A79-26631 selage A79-27354 noise, A79-26936 A79-27362 of ratio N79-17871 system N79-19661 railing

PERSONAL AUTHOR INDEX WALSE, B.

TRIPP, M. W.		VAICAITIS, B.	
Pilter weight minimization for rectified		Noise transmission - Turboprop problem	.70 0/033
superconducting alternator power suppli	.es A79-26966	[AIAA PAPER 79-0645] VALERY, H. A.	A79-26933
TROMP, P. J.	20100	Validation of MIL-P-9490D: General specific	cation
Environmental effects on crack growth in	70 7 5 m/	for flight control system for prioted mil	
flight-simulation tests on 2024-T3 and material	/0/5-T6	aircraft. Volume 1: Summary of YP-17 and validations	d C-5A
[NLR-TR-76104-U]	พ79-18012		N79-19008
TROTTER, B. L.		VAN KEUK, G.	
Design considerations for the NOAA airbor	ne	Problems of computer-aided tracking, giving	
meteorological radar and data system	A79-25689	particular attention to radar which can be electronically turned	E
TRUJILLO, E.		- i	A79-26761
Multimode radar processor	170.10059	VAN REUTH, E. C.	
TRONIN, I. I.	A79-28058	Potential uses of rapidly solidified alloys turbine engines	in gas
Prediction of gas-turbine alloy creep			A79-27313
characteristics	*70 00014	VANDENBRARNBUSSCHE, R.	
TSAI, B. S.	A79-26841	Outlet air angle prediction for subsonic flo cascades	DW
Propagation of buzz-saw noise in a nonuni	form medium		N79-18997
[AIAA PAPER 79-0639]	A79-26896	Plow modelling and aerodynamic design technic	ıques
TURANSKYJ, L. Design of multistage compressors with		for centrifugal compressors	N79-19386
consideration of the real behavior of g	as and	VANDERPLAATS, G. N.	175-15500
gas mixtures		Approximation concepts for numerical airfoil	1
Mannager D C	N79-19390	optimization	N79-18915
TURBBULL, R. C. Recent General Electric engine developmen	t testina	[NASA-TP-1370] VANDERVAART, J. C.	179-10915
for improved service life		Worst case time-histories causing largest	
[SAE PAPER 780990]	A79-25876	deviations from a desired flight path: A	n
TURNER, B. A. An acoustic problem in anechoic chambers	arisınd	analytical approach [VTH-LR-267]	N79-17839
from exhaust noise testing	arrorny	VANGOOL, M. P. C.	
[AIAA PAPER 79-0649]	A79-26929	The need of stick force stability for	
TURNER, B. H. A proposed integrated ECM system using th		attitude-stabilized aircraft, Part 2 [NLR-TR-77027-H]	N79-17875
constant index lens antenna		VAUGBAN, W. H.	17075
	A79-24726	Failure studies of a third stage fan disk fi	гот а
TURNER, J. A. Aviation wide angle visual system /AWAVS/	' - Wacnal	TT-30 turbine engine [AD-A061801]	N79-19004
system performance	- VISUAI	VEDIH, A. N.	.,, 1,004
-	A79-28161	Operational experience with linked-blade	
TURRIZIANI, R. V.	=0	high-output gas-turbine	A79-26830
Evaluation of a long-endurance-surveillan remotely-piloted vehicle with and without		VERNON, J.	A73-20030
laminar flow control		Life cycle cost in preliminary engine design	
[NASA-CR-159006] TUSTIN, B. A.	N79-17852	[SAE PAPER 781032] VICKERY, E. D.	A79-25904
Development of fire test methods for airp	lane	A new life saving application for the parach	hute
interior materials		[AIAA 79-0456]	A79-26659
[NASA-CR-160119] FUTTLE, R. P.	N79-19112	VIGNERON, Y. C. Calculation of supersonic viscous flow over	dolta
Cargo/Logistics Airlift System Study (CLA	SS) .	wings with sharp subsonic leading edges	delta
volume 1		· · · · · · · · · · · · · · · · · · ·	N79-18909
[NASA-CR-158915]	N79-17822	VILMOS, E. Objectives related to an enhancement of the	
Cargo/Logistics Airlift System Study (CLA volume 2	33),	effectivity of MALEV. I	
[NASA-CR-158916]	N79-17823		79-25368
Cargo/Logistics Airlift System Study (CLA	SS),	VOLMIR, A. S.	
executive summary [NASA-CR-158959]	N79-17824	Behavior of elastic systems in separated flo	A79-25618
rye, w.		VULIS, L. A.	
Safety of air transport	170 DECUD	Aerodynamics of flame jets	70-26255
	A79-25542	•	179-26355
11		W	
		VV	
U		DAGEDD D	
UKBOV, B. V.	tions in	WAGNER, B. Theoretical investigations of real gas effective.	ets in
•	eld of view	Theoretical investigations of real gas effect cryogenic wind tunnels	
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi		Theoretical investigations of real gas effect cryogenic wind tunnels [DS-PB-76/50B]	cts in N79-17820
UKHOV, B. V. Ellmination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F.	eld of view	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L.	N79-17820
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi	eld of View A79-27416	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in	N79-17820
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fiungument. J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585]	eld of View A79-27416	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines	N79-17820 : fields
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H.	eld of view A79-27416 ion A79-26882	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001]	N79-17820
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fiungument. J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585]	eld of view A79-27416 ion A79-26882 ct rapid	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow fin turbomachines [SAE PAPER 781001] WALKEWHORST, W. Aerodynamic behavior of fibres and sampling	N79-17820 E Elelds A79-25884
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Full-scale fire modeling tests of a comparesponse foam and dry chemical powder d system	eld of view A79-27416 ion A79-26882 ct rapid ispensing	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEHORST, W. Aerodynamic behavior of fibres and sampling respirable dust	N79-17820 E fields N79-25884 of
UKBOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Pull-scale fire modeling tests of a comparesponse foam and dry chemical powder d	eld of view A79-27416 ion A79-26882 ct rapid	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEMHORST, W. Aerodynamic behavior of fibres and sampling respirable dust [BLL-RTS-11267]	N79-17820 E Elelds A79-25884
UKBOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Full-scale fire modeling tests of a compa response foam and dry chemical powder d system [PAA-NA-78-24]	eld of view A79-27416 ion A79-26882 ct rapid ispensing	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEMBORST, W. Aerodynamic behavior of fibres and sampling respirable dust [BLI-RTS-11267] WALKO, L. C. Recent advances in indirect lightning effect	n79-17820 fields A79-25884 of
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Full-scale fire modeling tests of a compa response foam and dry chemical powder d system [PAA-NA-78-24]	eld of view A79-27416 ion A79-26882 ct rapid ispensing	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEWHORST, W. Aerodynamic behavior of fibres and sampling respirable dust [BLL-RTS-11267] WALKO, L. C. Recent advances in indirect lightning effect research	179-17820 Efields 179-25884 of 179-18470
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Full-scale fire modeling tests of a compa response foam and dry chemical powder d system [PAA-NA-78-24] VACHON, L.	eld of view A79-27416 ion A79-26882 ct rapid ispensing	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEWHORST, W. Aerodynamic behavior of fibres and sampling respirable dust [BLL-RTS-11267] WALKO, L. C. Recent advances in indirect lightning effect research	n79-17820 fields A79-25884 of
UKHOV, B. V. Elimination of scale and luminance distor thermal imaging systems with a large fi UNRUH, J. F. A finite element subvolume technique for structural-borne interior noise predict [AIAA PAPER 79-0585] URBAN, C. H. Full-scale fire modeling tests of a compa response foam and dry chemical powder d system [PAA-NA-78-24]	eld of view A79-27416 ion A79-26882 ct rapid ispensing	Theoretical investigations of real gas effective cryogenic wind tunnels [DS-PB-76/50B] WALITT, L. An alternating direction explicit method for computing three-dimensional viscous flow in turbomachines [SAE PAPER 781001] WALKEMHORST, W. Aerodynamic behavior of fibres and sampling respirable dust [BLL-RTS-11267] WALKO, L. C. Recent advances in indirect lightning effect research WALSH, B. Engine technology for production turbofan en	779-17820 fields 779-25884 of 779-18470 ts

Future avionics - Keeping capability u	p, costs down A79-27093	WILBY, J. F.	
WALZ, A.	R13-27033	Characteristics of propeller noise on an aircraf fuselage related to interior noise transmissio	
Contribution to the development of the		[AIAA PAPER 79-0646] A79-2	
calculations for the design and opti lifting bodies. (Solution of three-	mization of	WILHEM, D. P. Factors affecting residual strength prediction o	æ
basic thermo fluid dynamics equation		a cracked aircraft structure	1
strong interacting attached and sepa		A79-2	8380
fields)	N70-17016	WILLIAMS, C. B.	
[BMVG-FBWT-78-4] WAN, C. H.	N79-17816	Aircraft fire protection and rescue procedures /2nd edition/	
Investigation of torsion free wing tre	nd flutter	A79-2	5750
models	W70 40057	WILLIAMS, P. W.	
[AD-A061942] WANG, S. T.	N79-18957	New agents for the extinguishment of magnesium f [AD-A061664] N79-1	
Stable boundary layer wind shear model	for	WILLIAMSON, G.	
aircraft flight hazard definition	.20 02575	Gust load estimation using a simplified power	
WARREN, R. E.	A79-27575	spectral technique [ARAP-362] N79-1	7870
Reduction of rotor-turbulence interact	ion noise in	WILLIS, B. A.	
static fan noise testing	170 26025	NASA research on general aviation power plants	E 020
[AIAA PAPER 79-0656] WASHBURN, S. F.	A79-26925	[AIAA PAPER 79-0561] A79-2 WILTSE, D. B.	5870
Evaluation of a long-endurance-surveil		Applying design-to-life cycle cost methods during	ıg
remotely-puloted vehicle with and wi	thout	engine advanced development	
laminar flow control [NASA-CR-159006]	N79-17852	[SAE PAPER 781030] A79-2 WINTER, A. B.	.5902
WASSELL, A. B.		The search and rescue satellite (SARSAT) system	
 The design and development of high per 	formance	project	
combustors	N79-19380	WOLTER, W. A.	8115
WAY, D. J.		Environmental models for moisture absorption by	
An experimental study of the influence		aircraft composites	7577
flight-stream turbulence on jet mixi [AIAA PAPER 79-0617]	A79-26935	WORSHAM, R. H.	.1312
WEBB, D. B.		Integrated Thermal Avionics Design (ITAD)	
Development and initial test results of		[AD-A061227] N79-1	7855
with automatic inflation modulation [AIAA 79-0467]	A79-26673	WU, Y. T. Thermoelastic and dynamic phenomena in seals	
WEBER, R. J.		[AD-A061754] N79-1	9396
NASA research on general aviation powe FAIAA PAPER 79-0561]		WYSONG, R. R.	
WEINSTOCK, C. B.	A79-25870	TDS - A preliminary design system for turbines [SAE PAPER 780999] A79-2	5882
SIFT - Design and analysis of a fault-	tolerant	•	
	COLCLUNC		
computer for aircraft control		Y	
	A79-25718	YANG, H. T. Y.	
computer for aircraft control	A79-25718	Investigation of torsion free wing trend flutter	
computer for aircraft control WEIR, K. W. The U-2 story		Investigation of torsion free wing trend flutter models	
computer for aircraft control WEIR, K. W.	A79-25718	Investigation of torsion free wing trend flutter	
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. P. Laser propulsion	A79-25718	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for	
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V.	A79-25718 A79-26537 A79-26598	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures	8957
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. P. Laser propulsion WEISS, V. Application of fracture mechanics to d	A79-25718 A79-26537 A79-26598	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R.	8957 8275
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A.	A79-25718 A79-26537 A79-26598 esign A79-26980	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [ATAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains	8957 8275
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite	A79-25718 A79-26537 A79-26598 esign A79-26980 wings	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System	8957 8275 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [ATAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains	8957 8275 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeiler slipstream wing interactions	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system	8957 8275 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [ATAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains the microwave landing system N79-1	8957 8275 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WEWSLEY, J. H.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and	8957 8275 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WEWSLEY, J. H. SIFT - Design and analysis of a fault-	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height	8957 8275 t 6534 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WEWSLEY, J. H.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AINA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains the microwave landing system N79-1 YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [WASA-CASE-LAR-12275-1] N79-1	8957 8275 t 6534 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [ATAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains the microwave landing system N79-1 YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1 YU, J. C. On sound radiation from the trailing edge of an	8957 8275 t 6534 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains the microwave landing system N79-1 YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1 YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow	8957 8275 et 6534 et 8894
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [ATAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains the microwave landing system N79-1 YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1 YU, J. C. On sound radiation from the trailing edge of an	8957 8275 4 6534 8894 8296
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TM-75377] WERNICKE, K. G.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [WASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction through mean flow modification	8957 88275 86534 8894 8296
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeiler slipstream wing interactions 0.8 [SAF PAPER 780997] WEWSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. XV-15 Tilt Rotor Research Aircraft - P	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction	8957 88275 86534 8894 8296
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TM-75377] WERNICKE, K. G. XV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2 Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1 YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1 YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-26	8957 88275 86534 8894 8296
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA)	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-26	8957 88275 86534 8894 8296
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAE PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TM-75377] WERNICKE, K. G. XV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H.	8957 tt 66534 8894 8296 6907 6908
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA- project WESTERMAN, C. W.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YAMG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YEMMI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-26 ZATYKA, H. Introduction of electron beam welding in aircraft production	8957 8275 tt 66534 8894 8296 6907 6908
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TM-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA- project WESTERMAN, C. W. An IFF antenna with superior sidelobe	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains the Microwave Landing System Plying NASA's terminal configured vehicle agains the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production	8957 8275 tt 66534 8894 8296 6907 6908
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA- project WESTERMAN, C. W.	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YAMG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YEMMI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-26 ZATYKA, H. Introduction of electron beam welding in aircraft production	8957 18275 18894 18894 18894 18996 16908 15248
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAR, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. XV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA) project WESTERMAN, C. W. An IFF antenna with superior sidelobe suppression characteristics	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115 and backlobe A79-24718	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production A79-2: ZELLWEGER, A. G. FAA air traffic control automation - Programs and trends	8957 tt. 66534 8894 8296 6907 6908 t
weir, K. W. The U-2 story Weirs, R. F. Laser propulsion Weiss, V. Application of fracture mechanics to d Weisshar, T. A. Divergence of forward swept composite [AIAA 79-0722] Weice, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] Wensley, J. H. SIFT - Design and analysis of a fault- computer for aircraft control Werle, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] Wennicke, K. G. IV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] Wenstiuk, H. L. The search and rescue satellite (SARSA- project Westerman, C. W. An IFF antenna with superior sidelobe suppression characteristics	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115 and backlobe A79-24718 ffic	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production ZELLWEGER, A. G. FAA air traffic control automation - Programs and trends A79-2:	8957 tt. 66534 8894 8296 6907 6908 t
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P. [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA) project WESTERMAN, C. W. An IFF antenna with superior sidelobe suppression characteristics WESTPHAL, G. Selective calling procedure in air tra	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115 and backlobe A79-24718 ffic A79-25369	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production A79-2: ZELLWEGER, A. G. FAA air traffic control automation - Programs and trends	8957 tt. 66534 8894 8296 6907 6908 t
Computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAMB, T. A. Divergence of forward swept composite [AIAA 79-0722] WEIGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. XV-15 Tilt Rotor Research Aircraft - P [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA project WESTPHAN, C. W. An IFF antenna with superior sidelobe suppression characteristics WESTPHAL, G. Selective calling procedure in air tra WHITELAW, J. H. The influence of geometric asymmetry o	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115 and backlobe A79-24718 ffic A79-25369 n the flow	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. B. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System A79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production ZELLWEGER, A. G. FAA air traffic control automation - Programs and trends A79-2: ZHUIKOV, V. V. Method for digital computer calculation of unsteady temperature fields in turbomachine dis-	8957 18275 106534 18894 8296 6907 106908 t 5248 d 6871 scs
computer for aircraft control WEIR, K. W. The U-2 story WEISS, R. F. Laser propulsion WEISS, V. Application of fracture mechanics to d WEISSHAAB, T. A. Divergence of forward swept composite [AIAA 79-0722] WELGE, H. R. Propeller slipstream wing interactions 0.8 [SAF PAPER 780997] WENSLEY, J. H. SIFT - Design and analysis of a fault- computer for aircraft control WERLE, H. Vortex pattern development on the uppe a swept wing at high angle of attack [NASA-TH-75377] WERNICKE, K. G. IV-15 Tilt Rotor Research Aircraft - P. [AIAA 79-0704] WERSTIUK, H. L. The search and rescue satellite (SARSA) project WESTERMAN, C. W. An IFF antenna with superior sidelobe suppression characteristics WESTPHAL, G. Selective calling procedure in air tra	A79-25718 A79-26537 A79-26598 esign A79-26980 wings A79-28255 at Mach no. A79-25881 tolerant A79-25718 r surface of N79-18914 rogram report A79-27371 T) system N79-18115 and backlobe A79-24718 ffic A79-25369 n the flow	Investigation of torsion free wing trend flutter models [AD-A061942] N79-1 YANG, J. N. Statistical estimation of economic life for aircraft structures [AIAA 79-0761] A79-2 YENNI, K. R. Flying NASA's Terminal Configured Vehicle agains: the Microwave Landing System N79-2: Flying NASA's terminal configured vehicle agains: the microwave landing system N79-1: YOUNG, W. R. Apparatus for measuring an aircraft's speed and height [NASA-CASE-LAR-12275-1] N79-1: YU, J. C. On sound radiation from the trailing edge of an isolated airfoil in a uniform flow [AIAA PAPER 79-0603] A79-2: An experimental study of USB flap noise reduction through mean flow modification [AIAA PAPER 79-0607] A79-2: ZATYKA, H. Introduction of electron beam welding in aircraft production ZELLWEGER, A. G. FAA air traffic control automation - Programs and trends A79-2: ZHUIKOY, V. V. Method for digital computer calculation of	8957 18275 106534 18894 8296 6907 106908 t 5248 d 6871 scs

PERSONAL AUTHOR INDEX ZUERW, J.

ZIERBICKI, R.
Air Force applications for optical rotation rate sensors
A79-28

A79-28122

ZIHH, B. T.
Wave propagation in ducts using the finite element method
[AIAA PAPER 79-0659] A79-2687

A79-26879

TOURN, J.

Hardware and software structure of a coordination system for air traffic control on the basis of flight plan data

A79-26

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Suppl 110)

JUNE 1979

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number Under each contract number the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF PROJ. 2307	EC-77-A-31-1011
N79-18957 AF PROJ. 2402	N79-17859 PAN PROJ. 023-241
N79-18971	N79-18156
AF PROJECT 649E	FAA PROJ. 081-431-100
A79-25323	N79-17825
AF-AFOSR-76-2997	FAA PROJ. 181-521-000
A79-26966	N79-17966
AF-AFOSR-76-3021	FAA PROJ. 216-103-100
A79-26545 AF-AFOSE-77-3413	N79-17877
A79-26966	P19628-78-C-0006
AF-AFOSR-77-3423	F33615-72-C-1796
A79-28255	A79-28380
AF-AFOSR-3265-77	F33615-75-C-2073
N79-18957	A79-25882
ARPA ORDER 3152	P33615-75-C-5224
A79-27313	N79-19418
AT (29-1) -789 A79-26636	F33615-76-C-0528
CTDA-01SU,T8200-7-7536	N79-19010
A79-27354	F33615-76-C-3034
DA PROJ. 1L2-62209-AH-76	N79-19008
N79-18958	N79-19009
N79-18959	F33615-76-C-3037
DAAG-76-G-0318	N79-19007
A79-25869	F33615-76-C-3104
DAAG29-C-027 A79-26938	N79-18969
DAAG29-77-G-0111	F33615-77-C-1070
A79-24715	A79-24721
DAAH01-76-C-0583	F33615-77-C-2074
A79-24718 DAAJ02-74-C-0028	N79-17855
A79-25907	F33615-77-C-2102 N79-18971
DAAJ02-74-C-0040	F33615-77-C-3123
A79-28287	A79-28275
DAAJ02-77-C-0020	F33615-77-C-5169
N79-18956	A79-25321
ท79-18958	N79-18242
N79-18959	F33657-76-C-0215
DAAK70-78-C-0001	N79-19149
A79-25899	F33657-77-C-0425
DOT TASK 3 A79-26912	A79-25903
DOT-FA70WA-2448	P49620-78-C-0023
A79-27129	A79-28139
DOT-FA71WAI-223 N79-18475	MIPR-FY8952-76-65017 N79-19122
DOT-FA72WA-3098	NASA ORDER C-41581-B
N79-17841	N79-18977
DOT-FA74NA-1100	NASW-3199 N79-18914
N79-17860	NAS1-4007 N79-17849
N79-17863	NAS1-13034 N79-17812
N79-17864	NAS1-13500 N79-17852
N79-17865	NAS1-13792 A79-25718
N79-17866	NAS1-13986 N79-17798
N79-17867	NAS1-14162 N79-17807
N79-17868	NAS1-14193 N79-17803
N79-17869	NAS1-14404 N79-19814
DOT-FA76-WAI-620	NAS1-14630 N79-17799
A79-27575	NAS1-14698 N79-18057
DOT-FA76WAI-612	NAS1-14873 N79-17802
A79-25323	NAS1-14967 N79-17822
DOT-FA78WAI-847	N79-17823
N79-17876	N79-17824
DOT-OS-30034 A79-26912 E(49-26)-1028	NAS1-15075 N79-17850 NAS1-15083 N79-19815
N79-19414	NAS1-15083 N79-19815 NAS1-15185 N79-17848
817-13414	04011=C14 C01C1=1Can

NAS1-15186 NAS1-15380	N79-17848
W151-15380	N79-18074
NAS2-7007	275 10074
NAS2-/00/	N79-17811
NAS2-8558	170_20200
	A79-17801 A79-26925 A79-26923 A79-26936 N79-17858 N79-18976
NAS2-8612 NAS3-17853 NAS3-17863 NAS3-20050 NAS3-20091 NAS3-20298 NAS3-21015 NAS4-2526 NAS7-100	M/9-1/601
NAS3-17853	A79-26925
VACT-17967	170-26022
NR33-17003	A73-20923
NAS3-20050	A79-26936
N1 C2-20001	N70-170E0
NESS-20091	M/3-1/030
NAS3-20298	N79-19314
NAS3-21015	N79-18976
NR55-21015	
NAS4-2526	N79-18286
NAS7-100	A79-26941
WAS7 100	273 20341
NAS8-31377	A79-27576
NAS9-15168	N79-19112
NGL-49-002-0	
NGL-49-002-0	
	A79-26597
NGR-09-010-0	
1-010-co-usu	
	A79-26885
NGR-39-009-2	
いらいーンフーリリブー	
	A79-26945
NTVR-1725	N79-18012
NIVR-1725 NIVR-1745	
NIVR-1745	N79-17875
NRC A-9185	N79-17875 A79-27354)3406-A02 A79-27576 A79-24771 N79-18917 N79-17800 N79-17805 A79-26931 A79-26943 A79-25863
NOD 300 70 7	3000 300
NSP ATM-74-(J34U6→AU 2
	A79-27576
NCC-1000	170 20771
NSG-1098 NSG-1139 NSG-1143 NSG-1174 NSG-1253	A/9-24//I
NSG-1139	N79-18917
NCC-1103	#70-17900
N3G-1143	M/9-1/000
NSG-1174	N79-17805
WCC-1252	170-26021
N3G-1233	A75-20551
	A79-26943
NSG-1419 NSG-1450	A79-25863
NSG 1413	270 25003
NSG-1450	A79-26933
NSG-1469	A79-26940
NOG 1405	170 20070
NSG-1474	A79-26876
NSG-2238	N79-18973
NSG-2298	170 OCE 0E
	A79-26545
NSG-3012	A79-25861
	A79-26544
	A/3-20344
NSG-3036	179-26879
NSG-3082	N79-19#1#
NSG-3082 NSG-7192	1000 00000
NSG-/192	A79-26879 N79-19414 A79-26893
N00014-75-C-	-0761
	¥70 10306
	N79-19396
N00140-77-C-	-1345
	A79-25899
	A13"43033
RB-RLD-1976-	-1.3.1 N79-17875
	N79-17875
BCDD ** ^/ -	
USBR-14-06-1	7699
	A79-25681
505-03-13-17	N70-18686
505 05 05	#7.5-10000
505-06-21	N79-17796
505-07-11	N79-17872
EAE AO 43 44	T70 1000
202-09-13-11	M/9-1868/
505-03-13-17 505-06-21 505-07-11 505-09-13-11 505-10-41 505-11-13-01 505-11-23-03	N79-17804
505-11-12-01	N70-17006
202-11-13-01	m/9-1/800
505-11-23-03	N79-17808
•	N79-17800
	D-7699 A79-25681 7 N79-18686 N79-17796 N79-17872 N79-18687 N79-17804 N79-17808 N79-17809
505-11-31-02	N79-17807
506-17-22-01	N79-18284
EAC- 47 02 00	W70 47040
506-17-23-02	N79-17812
516-50-11-02	-00
	170_1004E
	N79-18915 N79-17851 N79-17852
516-50-23-01	N79-17851
	N70-17053
	013-11032
516-58-11	N/9-18960
518-51-01	N70-19916
510 51 01 517 51 61 61	10010 170 47074
537-53-43-02	: m/9-17871
750-03-30-01	79-17871 179-17854 179-17801
791-40-03	W70-17801
191-40-03	M / 3 - 1 / 60 1

		 			
1 Report No NASA SP-7037 (110)	2 Government Access	sion No.	3. Recipient's Catalog	No.	
4 Title and Subtitle AERONAUTICAL ENGINEERING			5 Report Date June 1979		
A Continuing Bibliography	/ (Supplement	110)	6. Performing Organia	ration Code	
7 Author(s)			8. Performing Organiz	ation Report No	
9 Performing Organization Name and Address			10. Work Unit No.		
National Aeronautics and Washington, D. C. 20546	Space Adminis	tration	11. Contract or Grant		
12 Sponsoring Agency Name and Address			Type of Report ar	d Period Covered	
			14 Sponsoring Agency	Code	
15 Supplementary Notes					
16. Abstract					
This bibliography lists introduced into the NASA in May 1979.					
ı					
17 Key Words (Suggested by Author(s))		18 Distribution Statement			
Aerodynamics					
Aeronautical Engineering Aeronautics Bibliographies		Unclassifie	d - Unlimited		
19 Security Classif (of this report) Unclassified	20 Security Classif (o Unclassifi	of this page) ed	21. No. of Pages 150	22. Price* E02 \$4.75 HC	2
L	<u> </u>			L	

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA distributes its technical documents and bibliographic tools to ten special libraries located in the organizations listed below. Each library is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

PENNSYLVANIA

Carnegie Library of Pittsburgh

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library

MISSOURI

Kansas City Public Library

St. Louis Public Library

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati Public Library

Cleveland Public Library

Dayton Public Library

Toledo Public Library

OKLAHOMA

Oklahoma County Libraries, Oklahoma City

TENNESSEE

Memphis Public Library

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 750 Third Avenue, New York, New York, 10017.

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England. By virtue of arrangements other than with NASA, the British Library Lending Division also has available many of the non-NASA publications cited in *STAR*. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "#" and "*", from: ESRO/ELDO Space Documentation Service, European Space Research Organization, 114, av. Charles de Gaulle, 92-Neuilly-sur-Seine, France.

National Aeronautics and Space Administration

Washington, D.C. 20546

Penalty for Private Use, \$300

THIRD-CLASS BULK RATE

Postage and Fees Paid National Aeronautics and Space Administration NASA-451



NASA

POSTMASTER:

If Undeliverable (Section 158 Postal Manual) Do Not Return

NASA CONTINUING BIBLIOGRAPHY SERIES

FREQUENCY	TITLE	NUMBER
Monthly	AEROSPACE MEDICINE AND BIOLOGY	NASA SP-7011
	Aviation medicine, space medicine, and space biology	
Monthly	AERONAUTICAL ENGINEERING	NASA SP-7037
	Engineering, design, and operation of aircraft and aircraft components	
Semiannually	NASA PATENT ABSTRACTS BIBLIOGRAPHY	NASA SP-7039
	NASA patents and applications for patent	
Quarterly	EARTH RESOURCES	NASA SP-7041
	Remote sensing of earth resources by aircraft and spacecraft	
Quarterly	ENERGY	NASA SP-7043
	Energy sources, solar energy, energy conversion, transport, and storage	
Annually	MANAGEMENT	NASA SP-7500
	Program, contract, and personnel management, and management techniques	

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Washington, D.C. 20546